
**Hydrodynamic plain journal bearings
under steady-state conditions —
Circular cylindrical bearings —**

**Part 3:
Permissible operational parameters**

*Paliers lisses hydrodynamiques radiaux fonctionnant en régime
stabilisé — Paliers circulaires cylindriques —*

Partie 3: Paramètres opérationnels admissibles



This document is a preview generated by EKO



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and units	1
5 Operational parameters to avoid wear	2
5.1 Minimum permissible lubrication film thickness	2
5.2 Effective waviness and maximum permissible effective waviness	2
6 Operational parameters to avoid excessive mechanical loading	6
7 Operational parameters to avoid excessive thermal loading	7
8 Operational parameters for the bearing clearance	8
Bibliography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 8, *Calculation methods for plain bearings and their applications*.

This second edition cancels and replaces the first edition (ISO 7902-3:1998), of which it constitutes a minor revision. The changes compared to the previous edition are as follows:

- adjustment to ISO/IEC Directives, Part 2:2018;
- correction of typographical errors.

A list of all parts in the ISO 7902 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In order to attain sufficient operational reliability of circular cylindrical plain journal bearings when calculated in accordance with ISO 7902-1, it is essential that the calculated operational parameters h_{\min} , T_B or T_{ex} and \bar{p} do not lie above or below the permissible operational parameters h_{lim} , T_{lim} and \bar{p}_{lim} . The permissible parameters represent geometrically and technologically dependent operational limits within the plain bearing tribological system. They are empirical values which still enable sufficient operational reliability even for minor influences (see ISO 7902-1).

Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings —

Part 3: Permissible operational parameters

1 Scope

This document specifies empirical permissible values for h_{lim} , T_{lim} and \bar{p}_{lim} .

The empirical values stated can be modified for certain applications, for example if information supplied by the manufacturer is to be taken into account. The descriptions of the symbols and calculation examples are given in ISO 7902-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7902-1, *Hydrodynamic plain journal bearings under steady-state conditions Circular cylindrical bearings — Part 1: Calculation procedure*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Symbols and units

Symbols and units are defined in [Table 1](#). ISO 7902-1:2020, Table 1 shall be referenced to identify the meaning of symbols not listed in [Table 1](#).

Table 1 — Symbols and their designations

B	Nominal bearing width	m
C	Nominal bearing clearance	m
D	Nominal bearing diameter (inside diameter)	m
E	Dimensionless modulus of elasticity	1
G	Dimensionless shear modulus	1
h_{wav}	Waviness of sliding surface (from Figure 3)	m
$h_{\text{wav,eff}}$	Effective waviness of sliding surface	m
$h_{\text{wav,eff,lim}}$	Maximum permissible effective waviness	m
$h_{\text{wav,lim}}$	Maximum permissible waviness	m