
**Road vehicles — Environmental
conditions and testing for electrical
and electronic equipment for
drive system of electric propulsion
vehicles —**

**Part 6:
Traction battery packs and systems**

*Véhicules routiers — Spécifications d'environnement et essais
de l'équipement électrique et électronique pour les véhicules à
propulsion électrique —*

Partie 6: Packs et systèmes de batterie de traction



This document is a preview generated by EKO



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	3
4.1 Symbols	3
4.2 Abbreviated terms	4
5 Operating modes	4
5.1 General	4
5.2 Operating mode 5	5
5.3 Operating mode 6	5
5.4 Operating mode 7	6
6 Functional status classification	6
7 Functional status checks	6
7.1 Electrical requirements check	6
7.1.1 General	6
7.1.2 Equipotential bonding	6
7.1.3 Insulation resistance	7
7.1.4 Withstand voltage test	7
7.2 Mechanical requirements check	7
7.2.1 Technical tightness check of battery pack or system enclosure	7
7.2.2 Leak tightness check of internal temperature control system	7
8 Tests and requirements	8
8.1 Mechanical categories of battery packs or systems	8
8.1.1 Category 1	8
8.1.2 Category 2	9
8.1.3 Category 3	9
8.2 Pre-conditioning	9
8.2.1 General	9
8.2.2 Thermo-mechanical pre-conditioning	10
8.3 Thermal cycling tests	10
8.3.1 General	10
8.3.2 Thermal cycling for DUT without internal temperature control system	10
8.3.3 Thermal cycling for DUT with internal temperature control system	12
8.3.4 Thermal cycling with electric operation	14
8.4 Structural durability and strength tests	16
8.4.1 General	16
8.4.2 Fixture	16
8.4.3 Pre-conditioning for mechanical tests	17
8.4.4 Durability test	17
8.4.5 Mechanical shock	24
8.4.6 Requirements	25
8.5 Water protection	25
8.5.1 Test	25
8.5.2 Requirements	25
8.6 Dust protection	26
8.6.1 Test	26
8.6.2 Requirements	26
8.7 Humid heat condensation test	26
8.7.1 Purpose	26

8.7.2	Test.....	26
8.7.3	Requirements	28
8.8	Damp heat, steady state test.....	28
8.8.1	Purpose.....	28
8.8.2	Test.....	28
8.8.3	Requirement.....	29
8.9	Corrosion	29
8.9.1	General.....	29
8.9.2	Mixed gas corrosion	29
8.9.3	Salt-spray test for external mounting location	30
8.9.4	Salt corrosion test for internal mounting location	31
8.10	Chemical resistance	34
Annex A (informative) Example of leak tightness check.....		35
Annex B (informative) Test concept for additional mechanical loads on a battery pack or system.....		36
Annex C (informative) Example of electrical and thermal profile for the mechanical durability test		39
Annex D (informative) Example of electrical profile for heat dissipation.....		41
Annex E (informative) Example of acceptance criterion for corrosion infiltration.....		42
Bibliography		44

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

A list of all parts in the ISO 19453 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

For over fifty years, traction batteries for electric vehicles have been developed to achieve high energy density and high power output. Specifically, lead-acid battery, Ni-Cd battery and Ni-MH battery with aqueous electrolyte were most applied to electric vehicles in the early days. Thermal activated batteries, such as molten salt batteries like sodium sulphur battery and Zebra battery were also examined. Lithium ion battery penetrated the consumer market in portable battery application from 1991. Currently, it is the most promising candidate of traction battery for electric vehicles. ISO 6469-1 specifies safety requirement of RESS (Rechargeable Energy Storage System) and the ISO 12405 series has been published to specify performance and reliability tests. This document focuses on environmental and endurance tests of lithium ion battery systems.

The ISO 19453 series specifies the test conditions on environment and reliability for electrical and electric equipment for the drive system of electric propulsion vehicles. The battery pack or system is the electric system which charges and discharges electricity through the converter. The test condition for mechanical load in ISO 19453-3 is too severe to apply to the battery pack or system from the standpoint of frequency range and amplitude of vibration in the test input spectrum. The test conditions for climatic load in ISO 19453-4 is also excessive to apply to the battery pack or system, because lithium ion battery pack is designed to control temperature within adequate operational range. That is the reason why appropriate conditions for the lithium ion battery are specified in this document.

The purpose of this document is to assist its user in systematically defining and/or applying a set of internationally accepted environmental conditions, tests and operating requirements, which are based on the anticipated actual environment in which the equipment will be operated and exposed to during its life cycle. This document has been developed based on fundamental investigations and vehicle measurements on voltage class A and B battery pack/system. The following environmental factors have been considered in the development of the ISO 19453 series.

- World geography and climate

Electric propulsion vehicles are operated in nearly all terrestrial regions of the earth. Significant variation in environmental conditions due to climatic environment, including diurnal and seasonal cycles, can therefore be expected. Consideration has been given to worldwide ranges in the temperature, humidity, precipitation and atmospheric conditions including dust, pollution and altitude.

- Type of electric propulsion vehicle

Operating environment in an electric propulsion vehicle can depend on its electric powertrain architecture as well as its mass, size, supply voltage and so on. Consideration has been given to typical types of series production electric propulsion vehicle architectures such as hybrid electric vehicles, battery electric vehicles, range extender hybrid electric vehicles and fuel cell vehicles, but not including equipment specific for fuel cell system.

- Vehicle use conditions and operating modes

Environmental conditions in and on the vehicle vary significantly with vehicle use (e.g. driving, charging during parking, etc.). Operating modes, such as starting, driving, braking, stopping and so on, have been considered, in particular, for traction battery system.

- Battery durability

For battery system, it is necessary to be resistant to environmental conditions experienced during manufacture, shipping, handling, storage, vehicle assembly, vehicle usage and vehicle maintenance and repair.

- Component mass and volume

The mass of battery pack is generally in the range of around 20 kg up to 60 kg for HEV, 80 kg to 150 kg for PHEV, more than 200 kg for BEV (weight assumptions from year 2020). The battery pack has generally

a large volume and thermal capacity. It is necessary not only to prepare a large chamber but it will also take a long time to keep the thermal equivalent when performing a thermal shock test.

— Mounting location in the vehicle

HEV battery packs are generally installed inside the vehicle, PHEV battery packs are installed both outside and inside, and BEV battery packs are generally installed outside. The environmental condition such as water splashing, dust, salt spray, humidity or corrosion for battery packs installed outside vehicle interior is more severe than for battery packs installed inside. In this document, test conditions are specified according to mounting location.

a) Applicability to manufacturers' responsibility

Due to technology limitations or variations in vehicle design, the vehicle manufacturer may be required to place a component in a location where it cannot withstand the environmental conditions described in the ISO 19453 series. Under these circumstances, it is the responsibility of the vehicle manufacturer to provide the necessary environmental protection.

b) Applicability to wiring harnesses, cables and electrical connectors

Although some environmental conditions and tests in the ISO 19453 series may be relevant to vehicle wiring harnesses, cables and connectors, its scope is not sufficient to be used as a complete standard. It is therefore not recommended that the ISO 19453 series is directly applied to such devices and equipment.

c) Applicability to parts or assemblies inside equipment

The ISO 19453 series describes environmental conditions and tests to be applied to electrical and electronic equipment directly mounted in or on the vehicle. It is not intended for direct application to parts or assemblies that are part of the equipment. For example, the ISO 19453 series should not be directly applied to integrated circuits (ICs) and discrete components, electrical connectors, printed circuit boards (PCBs), gauges, etc. that are attached in or on the equipment. Electrical, mechanical, climatic and chemical loads for such parts and assemblies can be quite different from those described in the ISO 19453 series. Therefore, for those sub-components applying test conditions of the ISO 16750 series can be considered as a reference.

On the other hand, it is desirable to use the ISO 19453 series to help derive environmental conditions and test requirements for parts and assemblies that are intended for use in road vehicle equipment.

d) Applicability relative to system integration and validation

The user of the ISO 19453 series is cautioned to understand that its scope is limited to conditions and testing at the equipment level and therefore does not represent all conditions and testing necessary for complete verification and validation of the vehicle system, for example cold water shock tests were omitted from this document. Environmental and reliability testing of equipment parts and vehicle systems may be required. For example, the ISO 19453 series does not necessarily ensure that environmental and reliability requirements for solder joints, solderless connections, integrated circuits and so on are met. Such items are assured at the part, material or assembly level. Additionally, vehicle and system level testing might be required to validate the equipment in the vehicle application.

Road vehicles — Environmental conditions and testing for electrical and electronic equipment for drive system of electric propulsion vehicles —

Part 6: Traction battery packs and systems

1 Scope

This document specifies requirements for lithium-ion traction battery packs or systems used in battery electric, hybrid electric and fuel cell electric road vehicles. This document describes the most relevant environmental stresses and specifies tests and test boundary conditions. This document establishes a classification of battery packs or systems and defines different stress levels for testing when a classification is applicable and required. The objective of this document is to specify standard test procedures and conditions to enable the observation of the reliability of the lithium-ion traction battery in the vehicle.

This document specifies tests for a battery pack or system of voltage class A and B.

This document provides the necessary information to set up a dedicated test plan for a battery pack or system subject to agreement between the customer and supplier. If required, the relevant test procedures and/or test conditions can also be selected from this document.

NOTE This document only covers requirements and test conditions for a traction battery pack or system used in passenger cars.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6469-3, *Electrically propelled road vehicles — Safety specifications — Part 3: Electrical safety*

ISO 6469-3:2018/Amd 1, *Electrically propelled road vehicles — Safety specifications — Part 3: Electrical safety — Amendment 1: Withstand voltage test for electric power sources*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 19453-1, *Road vehicles — Environmental conditions and testing for electrical and electronic equipment for drive system of electric propulsion vehicles — Part 1: General*

ISO 19453-4, *Road vehicles — Environmental conditions and testing for electrical and electronic equipment for drive system of electric propulsion vehicles — Part 4: Climatic loads*

ISO 19453-5, *Road vehicles — Environmental conditions and testing for electrical and electronic equipment for drive system of electric propulsion vehicles — Part 5: Chemical loads*

ISO 20653, *Road vehicles — Degrees of protection (IP code) — Protection of electrical equipment against foreign objects, water and access*

IEC 60068-2-14, *Environmental testing — Part 2-14: Tests — Test N: Change of temperature*

IEC 60068-2-27, *Environmental testing — Part 2-27: Tests — Test Ea and guidance: Shock*

IEC 60068-2-38, *Environmental testing — Part 2-38: Tests — Test Z/AD: Composite temperature/humidity cyclic test*

IEC 60068-2-60, *Environmental testing — Part 2-60: Tests — Test Ke: Flowing mixed gas corrosion test*

IEC 60068-2-64, *Environmental testing — Part 2-64: Tests — Test Fh: Vibration, broad-band random and guidance*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19453-1, ISO 20653 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

BMS

battery management system

electronic system that controls, manages, detects or calculates electric and thermal functions of the battery pack or system and that provides communication between the battery pack or system and other vehicle controllers

3.2

electric chassis

conductive parts of a vehicle that are electrically connected and whose potential is taken as reference

3.3

ITCS

internal temperature control system

internal thermal management system of a battery pack or system that can heat or cool the battery pack or system to a target temperature determined by the *BMS* (3.1)

EXAMPLE Liquid based heating/cooling system.

3.4

main contactor

electronic or mechanic switching/disconnect device for the battery pack or system *main power supply live part* (3.5)

3.5

main power supply live part

conductor or conductive part intended to be energized in normal use, but by convention not *the electric chassis* (3.2) or the class A auxiliary voltage supply

3.6

MAST

multiaxial simulation table

multiaxial system to induce vibrations or shocks in all three axial dimensions to the DUT

3.7

PSD

power spectral density

measure of signal's power content versus frequency

Note 1 to entry: A PSD is typically used to characterize broadband random signals. The amplitude of the PSD is normalized by the spectral resolution employed to digitize the signal.