# TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

**CLC/TS 50238-2** 

July 2020

ICS 29.280; 45.060.10

Supersedes CLC/TS 50238-2:2015

#### **English Version**

# Railway applications - Compatibility between rolling stock and train detection systems - Part 2: Compatibility with track circuits

Applications ferroviaires - Compatibilité entre le matériel roulant et les systèmes de détection des trains - Partie 2 - Compatibilité avec les circuits de voie

Bahnanwendungen - Kompatibilität zwischen Fahrzeugen und Gleisfreimeldesystemen - Teil 2: Kompatibilität mit Gleisstromkreisen

This Technical Specification was approved by CENELEC on 2020-06-15.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

| Con | tents  | Page |
|-----|--|------|
| Ει  | ıropéan foreword   | 4    |
| In  | troduction   | 5    |
| 1   | Scope  | 6    |
| 2   | Normative references   | 6    |
| 3   | Terms, definitions and abbreviations                             | 7    |
|     | 3.1 Terms and definitions  |      |
|     | 3.2 Abbreviations  | 9    |
| 4   | General aspects of interference current limits for RST           | 9    |
|     | 4.1 Derivation of interference current limits for RST            | 9    |
|     | 4.2 Application of Interference current limits to RST design     | 10   |
|     | 4.3 System definition  | 10   |
| Ar  | nnex A (normative) Interference current limits for RST           |      |
| A.  | 1 Definitions  | 13   |
| A.  | 2 Preferred track circuits for DC traction                       | 13   |
| A.  | 3 Preferred track circuits for RST for 16,7 Hz traction          | 14   |
| Α.  | 4 Preferred track circuits for RST for 50 Hz traction            | 14   |
| Α.  | 5 UGSK3  | 15   |
| A.  | 6 UGSK95   | 15   |
| Α.  | 7 FTGS 46 / FTGS 917/TCM100                                      | 15   |
| Α.  |  |      |
| Α.  | 9 Jade   | 17   |
| Α.  | 10 Coded track circuits for DC traction                          | 18   |
| Α.  | 11 Digicode  | 18   |
| Α.  | 12 CoRTo   | 19   |
| Α.  | 13 CBDAC   | 19   |
|     | 14 Preferred track circuit in Czech Republic                     |      |
|     | 15 All kind of UM71 equipped with RENUM receptor and UC 9500     |      |
|     | 16 DC track circuits in UK                                       |      |
| Δ.  | 17 EBI Track 200 (TI21)  | 21   |
| Δ.  | 18 EBI Track 400   | 22   |
|     | 19 FS3000  |      |
|     | 20 FS2000 / FS 2500 / FS 2550 / FS 5000                          |      |
|     | 21 Track circuits of 95 Hz and 105 Hz in Norway                  |      |
|     | 22 JRK 10470   |      |
|     |  |      |
|     | nnex B (normative) Rolling Stock Interference Evaluation methods |      |
| В.  |  |      |
| В.  |  |      |
| В.  | 3 Derivation of the interference current limits for RST          | 26   |

| B.5 Defined interference current limits for RST   | B.4   | Criteria for compatibility   | 26 |
|---|-------|--|----|
| B.7 Test equipment requirements (hardware)  | B.5   | Defined interference current limits for RST                            | 27 |
| B.8       Train interference analysis and evaluation methods       31         B.8.1 Evaluation method       31         B.9       Requirements for on-train interference monitoring and control       33         B.10       Documentation       33         Annex C (informative) Infrastructure data       35         C.1       Supply frequency       35         C.2       Infrastructure characterization       35         C.3       Power supply impedance       36         C.4       Approximate calculation of the lowest power supply resonance frequency       36         C.5       Simplified method to handle resonance effects with roof cables       38         C.6       Return current transfer function       39         Annex D (informative) Typical voltage resonance graphs       40         D.1       General       40         D.2       Interface voltage/current measurement       40         D.3       Voltage resonance graphs for 15 kV 16,7 Hz network       40         D.4       Voltage resonance graphs for 25 kV, 50 Hz network       41         D.5       Voltage resonance graphs for 1 500 V DC network       41         D.6       Voltage resonance graphs for 3 000 V DC network       42         Bibliography       43 <td>B.6</td> <td>Test specifications for RST interference measurements</td> <td> 27</td> | B.6   | Test specifications for RST interference measurements                  | 27 |
| B.8.1 Evaluation method       31         B.9 Requirements for on-train interference monitoring and control       33         B.10 Documentation       33         Annex C (informative) Infrastructure data       35         C.1 Supply frequency       35         C.2 Infrastructure characterization       35         C.3 Power supply impedance       36         C.4 Approximate calculation of the lowest power supply resonance frequency       36         C.5 Simplified method to handle resonance effects with roof cables       38         C.6 Return current transfer function       39         Annex D (informative) Typical voltage resonance graphs       40         D.1 General       40         D.2 Interface voltage/current measurement       40         D.3 Voltage resonance graphs for 15 kV 16,7 Hz network       40         D.4 Voltage resonance graphs for 25 kV, 50 Hz network       41         D.5 Voltage resonance graphs for 1 500 V DC network       41         D.6 Voltage resonance graphs for 3 000 V DC network       42         Bibliography       43  | B.7   | Test equipment requirements (hardware)                                 | 30 |
| B.9 Requirements for on-train interference monitoring and control   | B.8   | Train interference analysis and evaluation methods                     | 31 |
| B.10 Documentation       33         Annex C (informative) Infrastructure data       35         C.1 Supply frequency       35         C.2 Infrastructure characterization       35         C.3 Power supply impedance       36         C.4 Approximate calculation of the lowest power supply resonance frequency       36         C.5 Simplified method to handle resonance effects with roof cables       38         C.6 Return current transfer function       39         Annex D (informative) Typical voltage resonance graphs       40         D.1 General       40         D.2 Interface voltage/current measurement       40         D.3 Voltage resonance graphs for 15 kV 16,7 Hz network       40         D.4 Voltage resonance graphs for 25 kV, 50 Hz network       41         D.5 Voltage resonance graphs for 1 500 V DC network       41         D.6 Voltage resonance graphs for 3 000 V DC network       42         Bibliography       43  | B.8.1 | Evaluation method  | 31 |
| Annex C (informative) Infrastructure data   | B.9   | Requirements for on-train interference monitoring and control          | 33 |
| C.1 Supply frequency  | B.10  | Documentation  | 33 |
| C.2 Infrastructure characterization   | Anne  | ex C (informative) Infrastructure data                                 | 35 |
| C.3 Power supply impedance  | C.1   | Supply frequency   | 35 |
| C.4 Approximate calculation of the lowest power supply resonance frequency  | C.2   | Infrastructure characterization  | 35 |
| C.5 Simplified method to handle resonance effects with roof cables  | C.3   | Power supply impedance   | 36 |
| C.6 Return current transfer function  | C.4   | Approximate calculation of the lowest power supply resonance frequency | 36 |
| Annex D (informative) Typical voltage resonance graphs  | C.5   | Simplified method to handle resonance effects with roof cables         | 38 |
| D.1 General   | C.6   | Return current transfer function                                       | 39 |
| D.2 Interface voltage/current measurement   | Anne  | ex D (informative) Typical voltage resonance graphs                    | 40 |
| D.3 Voltage resonance graphs for 15 kV 16,7 Hz network  | D.1   | General  | 40 |
| D.4 Voltage resonance graphs for 25 kV, 50 Hz network   | D.2   | Interface voltage/current measurement                                  | 40 |
| D.5 Voltage resonance graphs for 1 500 V DC network   | D.3   | Voltage resonance graphs for 15 kV 16,7 Hz network                     | 40 |
| D.6 Voltage resonance graphs for 3 000 V DC network   | D.4   | Voltage resonance graphs for 25 kV, 50 Hz network                      | 41 |
| Bibliography43  | D.5   | Voltage resonance graphs for 1 500 V DC network                        | 41 |
|   | D.6   | Voltage resonance graphs for 3 000 V DC network                        | 42 |
|   |       |  |    |
|   |       |  |    |
|   |       |  |    |
|   |       |  |    |

# **European foreword**

This document (CLC/TS 50238-2:2020) has been prepared by CLC/SC 9XA "Communication, signalling and processing systems" of Technical Committee CLC/TC 9X, "Electrical and electronic applications for railways".

This document supersedes CLC/TS 50238-2:2015 and its corrigendum of July 2016.

CLC/TS 50238-2:2020 includes the following significant technical changes with respect to CLC/TS 50238-2:2015:

The interference current limits for RST have been updated in the normative Annex A.

This Technical Specification is Part 2 of the EN 50238 series published under the title Railway applications — Compatibility between rolling stock and train detection systems. The series consists of:

- Part 1: General:
- Part 2: Compatibility with track circuits [this document]; As a contain of the containing of the containing
- Part 3: Compatibility with axle counters.

# Introduction

This Technical Specification defines the interference limits and evaluation criteria for electromagnetic compatibility between rolling stock and track circuits.

The limits have been defined on the basis of national specifications described in NTRs.

This Part 2 of the series defines:

- a set of interference current limits for rolling stock based on defined track circuits,
- ath y with silliy require. measurement and evaluation methods to verify rolling stock interference current emissions and demonstrate compatibility with the track circuits;
- traceability of compatibility requirements (types of track circuit and associated limits).

## 1 Scope

This document defines, for the purpose of ensuring compatibility between rolling stock and track circuits, the limits for interference current emissions from rolling stock. The measurement and evaluation methods for verifying conformity of rolling stock to these limits are presented in a dedicated annex.

The interference limits are only applicable to rolling stock that is intended to run on lines exclusively equipped with preferred track circuits listed in this document. The rolling stock test methodology (infrastructure conditions, test configurations, operational conditions, etc.) presented in this document is applicable to establish compatibility with any track circuits.

This document gives guidance on the derivation of interference current limits specified for rolling stock and defines measurement methods and evaluation criteria in a dedicated annex.

This document defines:

- a) a set of interference current limits for RST (Rolling Stock) applicable for each of the following types of traction system:
  - 1) DC (750 V, 1,5 kV and 3 kV);
  - 16,7 Hz AC;
  - 3) 50 Hz AC;
- b) methodology for the demonstration of compatibility between rolling stock and track circuits;
- c) measurement method to verify interference current limits and evaluation criteria.
- NOTE 1 The basic parameters of track circuits associated with the interference current limits for RST are not in the scope of this document.
- NOTE 2 Any phenomena linked to traction power supply and associated protection (over voltage, short-circuit current, under- and over-voltage if regenerative brakes are used) is part of the track circuit design and outside the scope of this document.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50126 (all parts), Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)

EN 50128, Railway applications - Communication, signalling and processing systems - Software for railway control and protection systems

EN 50129, Railway applications — Communication, signalling and processing systems — Safety related electronic systems for signalling

EN 50238-1, Railway applications — Compatibility between rolling stock and train detection systems — Part 1: General

CLC/TS 50238-3, Railway applications — Compatibility between rolling stock and train detection systems — Part 3: Compatibility with axle counters

EN 50388, Railway Applications - Power supply and rolling stock - Technical criteria for the coordination between power supply (substation) and rolling stock to achieve interoperability

CLC/TR 50507, Railway applications - Interference limits of existing track circuits used on European railways