INTERNATIONAL STANDARD

ISO 17871

Second edition 2020-07

Gas cylinders — Quick-release cylinder valves — Specification and type testing

ceilles ecificatio. Bouteilles à gaz — Robinets de bouteilles à ouverture rapide —



Reference number ISO 17871:2020(E)



© ISO 2020

nentation, no part c'
vical, including p'
vuested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org

Website: www.iso.org Published in Switzerland

Contents			Page
Fore	word		iv
Intr	oductio	on	v
1	Scop	ıe	1
2	Norn	native references	1
3	Tern	ns and definitions	2
4 5 Ann	4.1 4.2 4.3 Marl	irements General requirements Differing/additional requirements 4.2.1 Valve connections 4.2.2 Resistance to mechanical impact 4.2.3 Valve operating mechanism 4.2.4 Valve operating device 4.2.5 Leakage 4.2.6 Documentation 4.2.7 Valve burst test pressure 4.2.8 Valve test pressure 4.2.9 Leak tightness tests 4.2.10 Endurance test 4.2.11 Securing arrangements Manufacturing tests and examinations king Dormative) Manufacturing tests and examinations National Control of the	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 23, *Transportable gas cylinders*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 17871:2015), which has been technically revised. It also incorporates the Amendment ISO 17871:2015/Amd 1:2018.

The main changes compared to the previous edition are as follows:

- extension of the scope to valves for pressure drums and tubes;
- addition of the valve burst test pressure;
- deletion of the flame impingement test;
- deletion of internal leak tightness test at -40 °C for quick-release cylinder valves only used for fixed fire-fighting systems installed in buildings;
- complete revision of $\underline{4.2.11}$ and $\underline{\text{Annex A}}$.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document covers the function of a quick-release cylinder valve as a closure (defined by the UN Model Regulations). Additional features of a quick-release cylinder valve (e.g. pressure regulators, residual pressure-retaining devices, non-return devices and pressure-relief devices) can be covered by other standards and/or regulations.

Quick-release cylinder valves complying with this document can be expected to perform satisfactorily under normal service conditions.

This document pays particular attention to:

- a) suitability of materials;
- b) safety (mechanical strength, impact strength, endurance, leak tightness);
- c) testing;
- d) marking.

This document has been written so that it is suitable to be referenced in the UN Model Regulations [1].

In this document, the unit bar is used due to its universal use in the field of technical gases. However, it is noted that bar is not an SI unit, and that the corresponding SI unit for pressure is Pa $(1 \text{ bar} = 10^5 \text{ Pa} = 10^5 \text{ N/m}^2)$.

Pressure values given in this document are given as gauge pressure (pressure exceeding atmospheric pressure) unless noted otherwise.

Charging of agents with a compressed gas is in some areas, e.g. fire-fighting, referred to as superpressurization.

This document is a previous generated by tills

Gas cylinders — Quick-release cylinder valves — Specification and type testing

1 Scope

This document, in conjunction with ISO 10297 and ISO 14246, specifies design, type testing, marking and manufacturing tests, and examinations requirements for quick-release cylinder valves intended to be fitted to refillable transportable gas cylinders, pressure drums and tubes which convey:

- non-toxic;
- non-oxidizing;
- non-flammable; and
- non-corrosive;

compressed or liquefied gases or extinguishing agents charged with compressed gases to be used for fire-extinguishing, explosion protection, and rescue applications.

NOTE 1 The main application of such quick-release cylinder valves is in the fire-fighting industry. However, there are other applications such as avalanche airbags, life raft inflation and similar applications.

NOTE 2 Where there is no risk of ambiguity, gas cylinders, pressure drums and tubes are addressed with the collective term "cylinders" within this document.

This document covers the function of a quick-release cylinder valve as a closure.

This document does not apply to quick-release cylinder valves for cryogenic equipment and for liquefied petroleum gas (LPG).

This document does not apply to quick-release cylinder valves if used as the main closure of portable fire extinguishers because portable fire extinguishers are not covered by transport regulation.

Quick-release cylinder valves of auxiliary refillable propellant gas cylinders used within or as part of portable fire extinguishers are covered by this document, if these cylinders are transported separately, e.g. for filling (see UN Model Regulations, Chapter 3.3, Special Provision 225, second note^[1]).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10286, Gas cylinders — Terminology

ISO 10297:2014+Amd.1:2017, Gas cylinders — Cylinder valves — Specification and type testing

ISO 14246, Gas cylinders — Cylinder valves — Manufacturing tests and examinations

ISO 22435, Gas cylinders — Cylinder valves with integrated pressure regulators — Specification and type testing