

IEC TS 62910

Edition 2.0 2020-07

TECHNICAL SPECIFICATION







THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



IEC TS 62910

Edition 2.0 2020-07

TECHNICAL SPECIFICATION

UNE

07.15



Utility-interconnected photovoltaic inverters – Test procedure for under voltage ver Ver ride-through measurements

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 27.160

ISBN 978-2-8322-8383-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD		4	
1 Scope		7	
2 Normative references		7	
50	mbols and abbreviated terms		
3.1 Terms, definition	ns and symbols	7	
	ns		
4 Test circuit and equip	ment		
4.1 General			
4.2 Test circuit			
4.3 Test equipment.			
4.3.1 Measuring i	nstruments	10	
4.3.2 DC source		11	
	t emulator		
	based grid simulator		
•	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		
	t		
	cuit faults and voltage drops		
• •			
	e short-circuit fault		
	short-circuit fault with ground		
	short-circuit fault with ground		
	se short-circuit fault with ground		
	ermination of critical performance values in UVRT te		
· · · · ·		•	
B.3 Ride-through time			
B.5 Active power			
Annex C (informative) Red	quirements of the UVRT curve		
C.1 General			
C.2 UVRT curve	C.2 UVRT curve		
C.3 Test points			
Bibliography		29	
Figure 1 – Testing circuit diagram10			
Figure 2 – Short-circuit emulator			

Figure 3 – Converter device example	14
Figure 4 – UVRT curve example	16
Figure 5 – Tolerance of voltage drop	17
Figure A.1 – Grid fault diagram	21
Figure A.2 – Diagram of voltage vector for three-phase short-circuit fault	22
Figure A.3 – Diagram of voltage vector of two-phase (BC) short-circuit fault with ground	23
Figure A.4 – Diagram of voltage vector of two-phase (BC) short-circuit fault	24
Figure A.5 – Diagram of voltage vector of single-phase (A) short-circuit fault with ground	25
Figure B.1 – Determination of reactive current output	27
Figure B.2 – Determination of active power recovery	27
Figure C.1 – The typical curve of UVRT	
Table 1 – Accuracy of measurements	11
Table 2 – Fault type and switch status	13
Table 3 – Test specification for UVRT (Indicative)	15
Table A.1 – Short-circuit paths for different fault types	
Table A.2 – Amplitude and phase changes in three-phase short-circuit fault	22
Table A.3 – Amplitude and phase changes in two-phase (BC)	23
Table A.4 – Amplitude and phase changes in two-phase (BC) short-circuit fault	24
Table A.5 – Amplitude and phase changes in single-phase (A)	25

hase (BC, phase (BC) s. .ngle-phase (A)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UTILITY-INTERCONNECTED PHOTOVOLTAIC INVERTERS – TEST PROCEDURE FOR UNDER VOLTAGE RIDE-THROUGH MEASUREMENTS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62910, which is a technical specification, has been prepared by IEC technical committee 82: Solar photovoltaic energy systems.

This second edition cancels and replaces the first edition issued in 2015, and constitutes a technical revision.

It remains a TS because it is limited to providing recommended practices for UVRT testing in the context of non-uniform grid-codes lacking international consensus, and the rapid development of test technology in recent years.

Clause	Previous edition	Present edition
3.1.12	the voltage support of EUT in accordance with the voltage drops. The K-factor is to be specified by the EUT manufacturer	the K-factor is to be supplied by the EUT manufacturer meeting additional requirements imposed by national standards and/or local codes
Figure 2	Back to Back circuit	Back to Back circuit
4.3.4	The test circuit essentially comprises a voltage source with a low internal resistance combined with broadband amplifiers	The test circuit essentially comprises a voltage source with a low internal resistance combined optionally with broadband amplifiers
Table 3	d The test should be carried out under specified K-factor provided by local manufacture.	d The test should be carried out under specified K-factor provided by manufacture meeting additional requirements imposed by national standards and/or local codes.
Figure 4	VIT cure VIT cu	12 14 15 15 15 15 15 15 15 15 15 15
5.2	NOTE The example shows two types of points on the UVRT curve: the lowest point and the inflection point. Tests must be carried out at both types of points	The example shows three types of points on the UVRT curve: the highest point, the lowest point and the inflection point. Tests shall be carried out at above types of points.
5.3.1	Prior to the fault simulation tests, the EUT should run in normal operating mode. The selected UVRT curve should be used to identify voltage drop points, including the lowest point and the inflection point,	Prior to the fault simulation tests, the EUT should run in normal operating mode. The selected UVRT curve should be used to identify voltage drop points, including the highest point, the lowest point and the inflection point,
		- S

The main technical changes with regard to the previous edition are as follows:

The text of this Technical Specificationis based on the following documents:

Draft TS	Report on voting	
82/1607/DTS	82/1640A/RVDTS	

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

UTILITY-INTERCONNECTED PHOTOVOLTAIC INVERTERS – TEST PROCEDURE FOR UNDER VOLTAGE RIDE-THROUGH MEASUREMENTS

1 Scope

This document provides a test procedure for evaluating the performance of Under Voltage Ride-Through (UVRT) functions in inverters used in utility-interconnected Photovoltaic (PV) systems.

This document is most applicable to large systems where PV inverters are connected to utility high voltage (HV) distribution systems. However, the applicable procedures may also be used for low voltage (LV) installations in locations where evolving UVRT requirements include such installations, e.g. single-phase or 3-phase systems.

The assessed UVRT performance is valid only for the specific configuration and operational mode of the inverter under test. Separate assessment is required for the inverter in other factory or user-settable configurations, as these may cause the inverter UVRT response to behave differently.

The measurement procedures are designed to be as non-site-specific as possible, so that UVRT characteristics measured at one test site, for example, can also be considered valid at other sites.

This document is for testing of PV inverters, though it contains information that may also be useful for testing of a complete PV power plant consisting of multiple inverters connected at a single point to the utility grid. It further provides a basis for utility-interconnected PV inverter numerical simulation and model validation.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61836, Solar photovoltaic energy systems – Terms, definitions and symbols

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms, definitions and symbols

For the purposes of this document, the terms and definitions in IEC TS 61836 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp