

IEC 62899-402-2

Edition 1.0 2020-08

INTERNATIONAL



Printed electronics – Part 402-2: Printability – Measurement of qualities – Edge waviness



THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and definitions clause of IEC publications issued between 2002 and 2015. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.





Edition 1.0 2020-08

INTERNATIONAL STANDARD - Changer S



Printed electronics of q Concernence of the second s Part 402-2: Printability – Measurement of qualities – Edge waviness

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 31.180

ISBN 978-2-8322-8769-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

	KEWC	עאר						
INT	RODI	JCTION	5					
1	Scop	pe	6					
2 Normative references								
3	3 Terms and definitions6							
4	4 Atmospheric conditions for evaluation and conditioning							
5	Mea	suring methods and instruments	8					
F	5 1	Image acquisition	8					
Ę	5.2	Measuring instrument	8					
Ę	5.3	Analysis software	8					
Ę	5.4	Preparation of image (specimen)	9					
Ę	5.5	Data collection and analysis	9					
5	5.6	Obtaining edge waviness and related attributes	12					
6	Repo	ort of results	12					
e	5. 1	Test identification information	12					
e	6.2	Instrument specification	12					
6	6.3	Results	12					
Bibl	iogra	phy	13					
Figı	ure 1 -	– ROI image of the specimen, and inner edge and test line selection	9					
Figu	ure 2 -	 Distribution graph of pattern edge waviness 	10					
Figu	ıre 3 -	- Distribution graph of pattern edge waviness of the sample with a spike on						
the	edge		11					
the Figu	edge ure 4 - edae	 Distribution graph of pattern edge waviness of the sample with a groove on 	11					
the Figu the	edge ure 4 - edge	 Distribution graph of pattern edge waviness of the sample with a groove on 	11 11					
the Figu the	edge ure 4 - edge	- Distribution graph of pattern edge waviness of the sample with a groove on	11 11					
Tab	edge ure 4 - edge le 1 –	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
Tigu Figu the Tab	edge ure 4 - edge le 1 –	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
Tab	edge ure 4 - edge le 1 –	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
Tab	edge ure 4 - edge le 1 -	– Distribution graph of pattern edge waviness of the sample with a groove on - Reporting items (example)	11 11 12					
Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example)	11 11 12					
Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	– Distribution graph of pattern edge waviness of the sample with a groove on - Reporting items (example)	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	– Distribution graph of pattern edge waviness of the sample with a groove on - Reporting items (example)	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example)	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	 Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example) 	11 12					
the Figu the Tab	edge ure 4 - edge le 1 -	- Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example)	11 12					
Tab	edge ure 4 - edge le 1 -	- Distribution graph of pattern edge waviness of the sample with a groove on Reporting items (example)	11 12					

Table 1 – Reporti	ng items (exa	mple)				12
-------------------	---------------	-------	--	--	--	----

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRINTED ELECTRONICS –

Part 402-2: Printability – Measurement of qualities – Edge waviness

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and nongovernmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62899-402-2 has been prepared by IEC technical committee 119: Printed Electronics.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
119/310/FDIS	119/317/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62899 series, published under the general title *Printed electronics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

BORONIEW OGNORATED DE LE COMPANY

INTRODUCTION

This part of IEC 62899-402 describes the measurement methods of printed patterns to evaluate their printability in the field of printed electronics. Printability is defined as both the qualities of printed patterns and the reproducibility of printing designs as the interaction result of printing media, inks and substrates. The qualities of printed patterns are satisfied by accurate measuring of the printed patterns two- and/or three-dimensionally with mechanical, physical and optical apparatus. The reproducibility of printing designs is achieved by estimating the reproducibility of replica. In terms of the business background, the requests from the industry applying the printing technology to the electronics manufacturing concern the guarantees of both the quality and reproducibility of printed patterns and printing designs to facilitate international trade and enhance user value in the field of printed electronics.

This document provides fundamental information on the measurement of printed pattern edge waviness to evaluate the printability in the field of printed electronics. An assurance of printability enhances user value of printed electronics and facilitates international trade. This document includes the measurement procedure, as well as the definition of edge waviness and related attributes such as average edge, touch edge and distribution edge of edge waviness, which are quite different from those that appear in the printing of graphic arts or from etching processes.

This document excludes the standardization of any kind of measurement equipment or system. It focuses on specifying the properties related to edge waviness of the printed patterns obtained by an optical measurement system.

PRINTED ELECTRONICS -

- 6 -

Part 402-2: Printability – Measurement of qualities – Edge waviness

1 Scope

This part of IEC 62899 describes the measurement methods of the edge waviness of printed patterns in printed electronics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 291, Plastics – Standard atmospheres for conditioning and testing

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

inner edge

line drawn in a tangent to the innermost edge point and parallel to the pattern's centre line

3.2

test line

selected line on a sample pattern edge (parallel to the inner edge) to test the edge waviness

3.3

background gray value

gray value of the line which is in the area without any printed patterns and parallel to the inner edge

Note 1 to entry: A centre line between two adjacent printed patterns is recommended.

3.4

average edge

1σ edge

distance to the inner edge of a gray ratio of more than 0,68 (single standard deviation in Gaussian distribution)