

This document is a review generated by EVS

Space engineerning - SpaceFibre - Very high-speed serial link

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 16603-50-11:2020 sisaldb Euroopa standardi EN 16603-50-11:2020 ingliskeelset teksti.	This Estonian standard EVS-EN 16603-50-11:2020 consists of the English text of the European standard EN 16603-50-11:2020.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 16.09.2020.	Date of Availability of the European standard is 16.09.2020.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 49.140

Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN 16603-50-11

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2020

ICS 49.140

English version

Space engineering - SpaceFibre - Very high-speed serial link

Ingénierie spatiale - SpaceFibre - Liaison série très haut débit

Raumfahrttechnik - SpaceFibre - Sehr schnelle serielle Schnittstelle

This European Standard was approved by CEN on 3 May 2020.

CEN and CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN and CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN and CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels

Table of contents

European Foreword.....	9
1 Scope.....	10
2 Normative references	11
3 Terms, definitions and abbreviated terms.....	13
3.1 Terms defined in other standards	13
3.2 Terms specific to the present standard	13
3.3 Abbreviated terms.....	26
3.4 Conventions.....	29
3.4.1 Numbers	29
3.4.2 Multiplication	29
3.4.3 Differential signals.....	29
3.4.4 Order of sending bits in symbols	29
3.4.5 Graphical representation of packets.....	30
3.4.6 State diagram notation	30
3.4.7 UML diagram notation.....	31
3.4.8 D/K notation for 8B/10B characters	32
3.5 Nomenclature	32
4 Principles	34
4.1 SpaceFibre purpose	34
4.2 SpaceFibre overview	35
5 Requirements.....	37
5.1 Overview	37
5.2 Protocol stack and interface architecture	37
5.2.1 General	37
5.2.2 Network layer	39
5.2.3 Data Link layer	39
5.2.4 Multi-Lane layer	40
5.2.5 Lane layer	40
5.2.6 Physical layer.....	41

5.2.7	Management Information Base	41
5.3	Formats	41
5.3.1	Control words and encoding/decoding	41
5.3.2	8B/10B encode/decode	42
5.3.3	Lane control words.....	44
5.3.4	Multi-Lane control words	51
5.3.5	Data Link control words.....	53
5.3.6	Receive error indication control word (RXERR).....	62
5.3.7	Characters	63
5.3.8	Frames.....	66
5.3.9	Packets	70
5.3.10	Control word and frame precedence	70
5.3.11	K-code summary.....	73
5.3.12	Control word symbol summary	73
5.4	Physical layer	74
5.4.1	Physical layer responsibilities.....	74
5.4.2	Serialisation	75
5.4.3	Electrical physical layer.....	77
5.4.4	Electrical medium.....	88
5.4.5	Fibre optic physical layer.....	97
5.4.6	Fibre optic medium.....	103
5.5	Lane layer.....	112
5.5.1	Lane layer responsibilities	112
5.5.2	Lane initialisation and standby management.....	114
5.5.3	Data signalling rate compensation	126
5.5.4	IDLE words	126
5.5.5	Parallel loopback.....	127
5.5.6	Symbol synchronisation	127
5.5.7	Word synchronisation.....	127
5.5.8	Receive synchronisation state machine	129
5.6	Multi-Lane layer	131
5.6.1	Multi-Lane layer responsibilities	131
5.6.2	Multi-Lane link	132
5.6.3	Multi-Lane bypass	133
5.6.4	Multi-Lane distribution	133
5.6.5	Multi-Lane concentration	137
5.6.6	Lane Alignment	137

5.6.7	Alignment state diagram	141
5.6.8	Asymmetric links	144
5.6.9	Initialisation of unidirectional lanes	145
5.6.10	Hot redundant lanes.....	146
5.7	Data Link layer.....	149
5.7.1	Data Link layer responsibilities	149
5.7.2	Virtual channels	151
5.7.3	Flow control.....	153
5.7.4	Medium access controller.....	155
5.7.5	Broadcast flow control	163
5.7.6	Framing.....	164
5.7.7	Error recovery	177
5.7.8	Data word identification state machine	184
5.7.9	Link Reset state machine	189
5.7.10	Link reset	192
5.8	Network layer.....	194
5.8.1	Network layer responsibilities	194
5.8.2	SpaceFibre network	195
5.8.3	Virtual networks	196
5.8.4	Links	199
5.8.5	Packet format.....	199
5.8.6	Sending a packet	200
5.8.7	Receiving a packet.....	200
5.8.8	Routing switch.....	201
5.8.9	Packet addressing.....	207
5.8.10	Group adaptive routing.....	209
5.8.11	Packet multicast.....	209
5.8.12	Broadcast messages.....	210
5.8.13	SpaceFibre nodes	212
5.8.14	SpaceFibre units	213
5.9	Management Information Base	214
5.9.1	Management Information Base responsibilities	214
5.9.2	Network management	214
5.9.3	Configuration parameters.....	215
5.9.4	Status parameters.....	219
6	Service interfaces	221
6.1	Overview	221

6.2	Network layer service interface	221
6.2.1	Network layer services	221
6.2.2	Packet Transfer service	221
6.2.3	Broadcast message service	223
6.3	Data Link layer service interface	224
6.3.1	Data Link layer services	224
6.3.2	Virtual Channel service	224
6.3.3	Broadcast message service	225
6.3.4	Schedule synchronisation service	226
6.4	Physical layer service interfaces	227
6.4.1	Physical layer services	227
6.4.2	Transfer symbols service	227
6.4.3	Control service	228
6.5	Management Information Base service interface	230
6.5.1	Management Information Base services	230
6.5.2	Link Management service	230
	Bibliography.....	232

Figures

Figure 3-1:	Convention for first bit to be sent	29
Figure 3-2:	Graphical packet notation	30
Figure 3-3:	State diagram style	30
Figure 3-4:	UML notation	31
Figure 3-5:	D/K notation for 8B/10B characters	32
Figure 4-1:	Overview of SpaceFibre protocol stack	35
Figure 5-1:	SpaceFibre protocol stack - single-lane	38
Figure 5-2:	SpaceFibre protocol stack - multi-lane	39
Figure 5-3:	Fills at the end of packets	65
Figure 5-4:	Fills at the start and end of a packet	66
Figure 5-5:	Data frame format for a single lane	66
Figure 5-6:	Idle frame format	67
Figure 5-7:	Broadcast frame format	68
Figure 5-8:	Interfaces to the Physical layer	75
Figure 5-9:	One direction of electrical Physical layer, showing series capacitors, discharge resistors, and different grounds	77
Figure 5-10:	Serial output signals	79
Figure 5-11:	Serial output test circuit	80

Figure 5-12: Serial eye pattern mask	80
Figure 5-13: Serial input signals	86
Figure 5-14: Type-A electrical flight cable assembly	89
Figure 5-15: Type-A electrical flight connector saver	90
Figure 5-16: Type-C electrical EGSE cable assembly	93
Figure 5-17: Type-C electrical EGSE to flight adaptor cable assembly	94
Figure 5-18: One direction of fibre optic Physical layer, showing fibre optic transmitter, receiver, connectors and cable.....	97
Figure 5-19: One direction of active optical cable type of fibre optic Physical layer.....	97
Figure 5-20: Electro-optical eye pattern for 1 Gbit/s to 5 Gbit/s transmitters	99
Figure 5-21: Electro-optical eye pattern for 1 Gbit/s to 10 Gbit/s transmitters	100
Figure 5-22: SpaceFibre lane comprising two Type-A fibre optic flight cable assemblies, one for each direction.....	105
Figure 5-23: Type-B fibre optic flight cable assembly with one lane.....	107
Figure 5-24: Type-B fibre optic flight cable assembly with several lanes	108
Figure 5-25: Type-B fibre optic flight cable assembly for an asymmetric link	108
Figure 5-26: Type-C flight active optical cable assembly	111
Figure 5-27: Interfaces to the Lane layer for a single lane link	113
Figure 5-28: Interfaces to the Lane layer for a multi-lane link.....	114
Figure 5-29: Lane initialisation state machine	115
Figure 5-30: Receive synchronisation state machine.....	129
Figure 5-31: Interfaces to Multi-Lane layer	132
Figure 5-32: Multi-Lane link with different number of lanes at each end	133
Figure 5-33: Words forming a row across a multi-lane link	134
Figure 5-34: Spreading data across a multi-lane link	135
Figure 5-35: PAD control words in a multi-lane link	135
Figure 5-36: Row alignment across a multi-lane link.....	140
Figure 5-37: Alignment state machine	141
Figure 5-38: Multi-Lane link incorporating some unidirectional lanes	144
Figure 5-39: Interfaces to the Data Link layer for a single lane link	150
Figure 5-40: Interfaces to the Data Link layer for a multi-lane link	150
Figure 5-41: Scrambler / de-scrambler	165
Figure 5-42: Example of scrambling of a short data frame.....	166
Figure 5-43: Effect of scrambling on an idle frame.....	167
Figure 5-44: Examples of CRC calculation for a short data frame	172
Figure 5-45: Illustration of bit ordering during 16-bit CRC calculation	172
Figure 5-46: Examples of CRC calculation for a broadcast frame and FCT	175
Figure 5-47: Illustration of bit ordering during 8-bit CRC calculation	176

Figure 5-48: Receive Error state machine	182
Figure 5-49: Data Word Identification state machine	185
Figure 5-50: Link Reset state machine	190
Figure 5-51: Interfaces to the Network layer	194
Figure 5-52: Components of a SpaceFibre network.....	195
Figure 5-53: Relationships of a SpaceFibre virtual network	197
Figure 5-54: SpaceFibre packet format	199
Figure 5-55: Components of a SpaceFibre routing switch	202
Figure 5-56: Components and specialisations of a SpaceFibre node	212
Figure 5-57: Components and specialisations of a SpaceFibre unit	214

Tables

Table 5-1: 5B/6B encoding	43
Table 5-2: 3B/4B encoding	44
Table 5-3: Lane control words	44
Table 5-4: Multi-Lane control words.....	51
Table 5-5: Data framing control words.....	53
Table 5-6: Flow control word	58
Table 5-7: Error recovery control words.....	60
Table 5-8: Receive error indication control word	63
Table 5-9: SpaceFibre N-Char Symbols	64
Table 5-10: Fill control character symbol	64
Table 5-11: Meaning of K-codes.....	73
Table 5-12: Meaning of control word symbols	73
Table 5-13: Serial output interface.....	77
Table 5-14: Serial eye pattern mask intervals 1 Gbit/s to 3,125 Gbit/s.....	81
Table 5-15: Serial eye pattern mask intervals above 3,125 Gbit/s to 6,25 Gbit/s	81
Table 5-16: Coefficient α for different values of BER	82
Table 5-17: Driver and receiver characteristics 1 Gbit/s to 3,125 Gbit/s.....	83
Table 5-18: Driver and receiver characteristics above 3,125 Gbit/s to 6,25 Gbit/s	84
Table 5-19: Serial input interface.....	85
Table 5-20: Type-A electrical flight cable assembly connector contact terminations	89
Table 5-21: Type-A electrical flight connector saver connector contact terminations	89
Table 5-22: Type-B electrical flight cable assembly connector contact terminations	92
Table 5-23: Type-C electrical EGSE cable assembly connector contact terminations	93
Table 5-24: Type-C electrical EGSE to flight adaptor cable assembly connector contact terminations	94
Table 5-25: Type-D electrical EGSE cable assembly connector contact terminations	96

Table 5-26: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s transmitters	100
Table 5-27: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s transmitters	101
Table 5-28: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s receivers.....	102
Table 5-29: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s receivers.....	103
Table 5-30: Connection of SpaceFibre lane using Type-A flight fibre optic cable assemblies	105
Table 5-31: Type-B flight fibre optic cable assembly connector contact terminations for each SpaceFibre lane	107
Table 5-32: Type-C flight active optical cable connector terminations for each SpaceFibre lane	109
Table 5-33: Type-C flight active optical cable assembly connector contact terminations for each SpaceFibre lane	110
Table 5-34: Precedence for different qualities of service	158
Table 5-35: Routing switch addresses.....	204
Table 5-36: SpaceFibre configuration parameters	216
Table 5-37: SpaceFibre status parameters.....	219

European Foreword

This document (EN 16603-50-11:2020) has been prepared by Technical Committee CEN-CENELEC/TC 5 "Space", the secretariat of which is held by DIN.

This document (EN 16603-50-11:2020) originates from ECSS-E-ST-50-11C.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2021, and conflicting national standards shall be withdrawn at the latest by March 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a standardization request given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any EN covering the same scope but with a wider domain of applicability (e.g. : aerospace).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1**Scope**

SpaceFibre is a very high-speed serial link and network technology, designed specifically for use on board spacecraft. SpaceFibre is able to operate over fibre-optic and electrical cable and supports data rates of up to 5 Gbit/s (6,25 Gbit/s data signalling rate). It complements the capabilities of the widely used SpaceWire on-board networking standard: improving the data rate by a factor of 10, reducing the cable mass and providing galvanic isolation. Multi-laning improves the data rate further to well over 20 Gbit/s.

SpaceFibre provides a coherent quality of service mechanism able to support bandwidth reserved, scheduled and priority-based qualities of service. It substantially improves the fault detection, isolation and recovery (FDIR) capability compared to SpaceWire.

SpaceFibre aims to support high data-rate payloads, for example synthetic aperture radar and hyper-spectral optical instruments. It provides robust, long distance communications for launcher applications and supports avionics applications with deterministic delivery constraints through the use of virtual channels. SpaceFibre enables a common on-board infrastructure to be used across many different mission applications resulting in cost reduction and design reusability. SpaceFibre uses a packet format which is the same as SpaceWire enabling simple connection between existing SpaceWire equipment and high-speed SpaceFibre links and networks. Applications developed for SpaceWire can be readily transferred to SpaceFibre.

The SpaceFibre standard specifies the interfaces to the user application and to the physical medium. Intermediate interfaces between protocol layers are also specified. The functions that a SpaceFibre interface has to implement are specified. Connector and cable characteristics for SpaceFibre optical and copper implementations are also specified.

This standard may be tailored for the specific characteristics and constraints of a space project in conformance with ECSS-S-ST-00.

2**Normative references**

The following normative documents contain provisions which, through reference in this text, constitute provisions of this ECSS Standard. For dated references, subsequent amendments to, or revision of any of these publications do not apply. However, parties to agreements based on this ECSS Standard are encouraged to investigate the possibility of applying the more recent editions of the normative documents indicated below. For undated references, the latest edition of the publication referred to applies.

EN reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system - Glossary of terms
EN 16603-50-52	ECSS-E-ST-50-52	Space engineering - SpaceWire – Remote memory access protocol
EN 16602-70-02	ECSS-Q-ST-70-02	Space product assurance - Thermal vacuum outgassing test for the screening of space materials
EN 16602-70-21	ECSS-Q-ST-70-21	Space product assurance - Flammability testing for the screening of space materials
EN 16602-70-29	ECSS-Q-ST-70-29	Space product assurance - Determination of offgassing products from materials and assembled articles to be used in a manned space vehicle crew compartment
	ESCC 2263420:2017	Evaluation Test programme for optical fibre cable assemblies, ESCC Basic Specification, issue 1, June 2017
	ESCC 3401/090:2018	High Data Rate Connectors Savers, Plugs based on type AxoMach, ESCC Detail Specification, issue 1, 2018
	ESCC 3409:2018	High Data Rate Cable Assemblies, ESCC Generic Specification, issue 1, 2018
	ESCC 3409/001:2018	High Data Rate Harnesses based on type AxoMach, ESCC Detail Specification, issue 1, 2018
	ESCC 3420:2017	Optical Fibre Cable Assemblies with Single Fibre Ferrules, ESCC Generic Specification, issue 1, June 2017
	ESCC 3420/001:2017	Optical Fibre Cable Assemblies with Single Fibre Ferrules, ESCC Detail Specification, issue 1, June 2017

EN reference	Reference in text	Title
	IEC 60793-2-10:2015	Optical fibres - Part 2-10: Product specifications - Sectional specification for category A1 multimode fibres, IEC, 2015
	IEC 61754-5:2005	Fibre optic connector interfaces - Part 5: Type MT connector family, IEC, 2005
	IEC 61755-3-31:2015	Fibre optic interconnecting devices and passive components - Connector optical interfaces - Part 3-31: Connector parameters of non-dispersion shifted single mode physically contacting fibres - Angled polyphenylene sulphide rectangular ferrules
	IEC 61755-3-32:2015	Fibre optic interconnecting devices and passive components - Connector optical interfaces - Part 3-32: Connector parameters of non-dispersion shifted single mode physically contacting fibres - Angled thermoset epoxy rectangular ferrules
	IEEE 802.3:2012	IEEE Standard for Ethernet, IEEE Standards Association, 28 December 2012
	MIL-PRF-49291, Revision D, Amendment 1, 20 November 2014	Performance Specification, Fiber, Optical, (Metric) General Specification
	Serial ATA Revision 3.0:2009	Serial ATA Revision 3.0, clause 6.6.1, Serial ATA International Organization, June 2, 2009, Gold Revision