

ICS 35.240.60; 03.220.01

English Version

Cooperative intelligent transport systems (C-ITS) -
Position, velocity and time functionality in the ITS station
(ISO/TS 21176:2020)

Systèmes de transport intelligents coopératifs (C-ITS) -
Fonctionnalité de position, de vitesse et de temps dans
la Station ITS (ISO/TS 21176:2020)

Intelligente Verkehrssysteme - Kooperative ITS -
Position, Geschwindigkeit und Zeitfunktionen in einer
ITS-Station (ISO/TS 21176:2020)

This Technical Specification (CEN/TS) was approved by CEN on 24 August 2020 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

This document (CEN ISO/TS 21176:2020) has been prepared by Technical Committee ISO/TC 204 "Intelligent transport systems" in collaboration with Technical Committee CEN/TC 278 "Intelligent transport systems" the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO/TS 21176:2020 has been approved by CEN as CEN ISO/TS 21176:2020 without any modification.

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Abbreviated terms.....	4
5 Conformance.....	5
6 PVT service in the ITS station and communication architecture.....	5
6.1 ITS station and communication architecture.....	5
6.2 ITS-S application processes (ITS-S-APs).....	6
6.3 ITS-S facilities layer services.....	6
6.4 PVT service provided by the ITS-S facilities layer.....	8
6.5 Access to the PVT service.....	8
6.6 PVT-augmented ADUs.....	9
7 PVT service.....	9
7.1 PVT service reference model.....	9
7.2 PVT-related input parameters.....	10
7.3 PVT output parameters.....	11
7.3.1 General.....	11
7.3.2 PvtInfoEcdd.....	12
7.3.3 PvtInfoEcdd-PosVelocityTime.....	16
7.3.4 PvtInfoEcdd-PosTime.....	16
7.3.5 PvtInfoEcdd-VelocityAccelerationTime.....	16
7.3.6 PvtInfoEcdd-VelocityTime.....	16
7.3.7 PvtInfoEcdd-SpeedTime.....	16
7.3.8 PvtInfoNmeaData.....	17
8 PVT-SAP service primitives.....	17
8.1 General.....	17
8.1.1 Overview.....	17
8.1.2 PVTinit.....	18
8.1.3 Return codes.....	18
8.2 Get-PVT.....	18
8.3 Subscribe-PVT-related service primitives.....	19
8.3.1 Subscribe-PVT.....	19
8.3.2 Notify-PVT.....	20
8.3.3 Cancel-PVT.....	20
9 PVT capability.....	20
Annex A (normative) PVT data type specifications.....	22
Annex B (normative) Implementation conformance statement proforma.....	23
Bibliography.....	27

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 278, *Intelligent transport systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Context of C-ITS

This document is part of a family of deliverables from Standard Development Organizations (SDOs) for Cooperative Intelligent Transport Systems (C-ITS), a subset of standards for Intelligent Transport Systems (ITS).

ITS aims at improving surface transportation in terms of:

- **safety**, e.g. crash avoidance, obstacle detection, emergency call, dangerous goods;
- **efficiency**, e.g. navigation, green wave, priority, lane access control, contextual speed limits, car sharing;
- **comfort**, e.g. telematics, parking, electric vehicle charging, infotainment;

by applying information and communication technologies (ICT).

To support interoperability, C-ITS specifications are developed to exchange and share information within a given ITS application domain, or between ITS application domains.

C-ITS services are based on the exchange of data between vehicles of any category, the roadside and urban infrastructure (e.g. traffic lights, road tolls, variable message signs), control and services centres (e.g. traffic control centre, map providers), and other road users (e.g. pedestrians, cyclists).

Many ITS services require the cooperation of vehicles with their surrounding environment (e.g. other vehicles, other road users, roadside and urban infrastructure), whilst other services require connectivity to remote service platforms (e.g. road traffic control centres, map providers, service providers, fleet managers, equipment manufacturers).

In order to support:

- a large variety of C-ITS services with diverging requirements, and
- efficient sharing of information maintained by individual service applications,

it is necessary to combine multiple access technologies and communication protocols with distinct performance characteristics (communication range, available bandwidth, end-to-end transmission delay, quality of service, security, etc.).

Combining multiple access technologies and communication protocols requires a common approach to the way communications and data are managed in a secure way. A functional architecture (the ITS station architecture) has therefore been specified to manage security, communications and data related to C-ITS services.

For more detail on C-ITS, see the ITS station and communication architecture specified in ISO 21217, and the multi-part technical report CEN/TR 21186 providing guidelines on the usage of C-ITS; see also <https://www.itsstandards.eu/cits>.

Need for position, velocity and time (PVT) information in C-ITS

Many ITS services, particularly those where vehicles or other mobile devices such as smartphones are involved, require position, velocity and time (PVT) information. Such PVT information is needed for various purposes. It is notably used by navigation systems, any related ITS service where position is needed (e.g. car-sharing, taxi ride booking, fleet management), advanced driver assistance or automated driving systems. The information transmitted between ITS stations or between components of an ITS station can be required to be marked with position or time information (geo- or time stamping).

PVT-related information can originate from various sources, such as a global navigation satellite system or systems (GNSSs). Accuracy and reliability can be improved by usage of several sources, such as anti-spoofing flags used for GNSS signal authentication, inertial measurement units (IMUs), light detection

and ranging (LIDAR)-based sensors, video camera-based sensors, digital maps and differential correction systems. Input from the various sources needs to be properly merged and the output be associated with a defined accuracy.

The provision of PVT information in a standardized form that can be used by all types of C-ITS services (e.g. road safety, traffic efficiency, public transport, freight and logistics, emergency call and other value-added services) is urgently needed, particularly in pilots and pre-deployment of C-ITS standards in Europe (e.g. ITS Corridor, ECo-AT, SCOOP@F, C-Roads), North America (e.g. Connected Vehicle Pilot Deployments) and Asia (e.g. Anting Project). In addition, PVT information is applicable to forthcoming deployments of the European emergency call (eCall) service. Further, high resolution and accurate PVT information is essential for automated driving.

High availability, precision and integrity of PVT information is essential for some C-ITS services, notably for advanced driver assistance or automated driving (e.g. lane keeping, platooning).

A major challenge in defining and assessing the (GNSS) positioning performance, is that it is highly influenced by the environment and the operational scenario. Research projects, standardization activities and pilot projects are on-going to address open issues and to define a common and broadly adopted framework, including the definition of relevant quality parameters and associated test procedures for conformance assessment.

SaPPART, an Action under the European Cooperation in Science and Technology programme, brought together experts in GNSSs, ITS and mobility to address the open issues. SaPPART defined a framework for the assessment of the performances of GNSS-based positioning terminals^{[22][23][24]}, whose concepts have been integrated in leading ongoing research projects (e.g. inLANE and ESCAPE).

Context of use of this document

This document aims to define a functionality providing the PVT information and the interface between this new functionality and other existing functionalities of the ITS station so that it can be used in a uniform, flexible and future-proof extensible way by ITS-S application processes complying with the ITS station and communication architecture and related standards.

This document makes provision for any kind of quality parameter definitions, for example, the accuracy levels for predefined confidence levels, associated with PVT information.

It is outside the scope of this document to define the associated conformance evaluation test procedures.

The EN 16803 series^[11] defines a framework for assessing the performance of ITS GNSS-based terminals. It defines so-called protection levels of position and velocity (i.e. error bounds around the estimated position and velocity provided by the positioning module), of which each is associated with an integrity risk (i.e. probability that the actual error for a given position or velocity exceeds the associated protection level). EN 16803-2^[11] defines a test methodology based on replay in the laboratory of real data sets recorded during field tests. It may be used to assess the accuracy of the position and velocity of the positioning terminal and underpin the confidence levels of the position and the velocity as defined in this document.

Cooperative intelligent transport systems (C-ITS) — Position, velocity and time functionality in the ITS station

1 Scope

This document specifies a generic position, velocity and time (PVT) service. It further specifies the PVT service within the ITS station (ITS-S) facilities layer (ISO 21217) and its interface to other functionalities in an ITS-S such as:

- ITS-S application processes (ITS-S-APs), defined in ISO 21217;
- the generic facilities service handler (FSH) functionality of the ITS station facilities layer, defined in ISO/TS 17429.

This document specifies:

- a PVT service which, dependent on a specific implementation, uses a variety of positioning-related sources such as global navigation satellite systems (GNSSs, e.g. GALILEO, GLONASS and GPS), roadside infrastructure, cellular infrastructure, kinematic state sensors, vision sensors;
- a PVT service which merges data from the above-mentioned positioning-related sources and provides the PVT output parameters (carrying the PVT information) including the associated quality (e.g. accuracy);
- how the PVT service is integrated as an ITS-S capability of the ITS station facilities layer;
- the interface function calls and responses (Service Access Point – service primitives) between the PVT ITS-S capability and other functionalities of the ITS station architecture;
- optionally, the PVT service as a capability of the ITS-S facilities layer; see ISO 24102-6;
- an ASN.1 module C-itsPvt, providing ASN.1 type and value definitions (in [Annex A](#));
- an implementation conformance statement proforma (in [Annex B](#)), as a basis for assessment of conformity to this document.

NOTE It is outside the scope of this document to define the associated conformance evaluation test procedures.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 8824-1, *Information technology — Abstract Syntax Notation One (ASN.1): Specification of basic notation*

ISO 17423, *Intelligent transport systems — Cooperative systems — Application requirements and objectives*

ISO/TS 17429, *Intelligent transport systems — Cooperative ITS — ITS station facilities for the transfer of information between ITS stations*

ISO 17575-1:2016, *Electronic fee collection — Application interface definition for autonomous systems — Part 1: Charging*

ISO 21217, *Intelligent Transport Systems — Communications access for land mobiles (CALM — Architecture*

ISO 24102-6:2018, *Intelligent Transport Systems — Communications access for land mobiles (CALM) — ITS station management — Part 6: Path and flow management*

EN 16803-1, *Space — Use of GNSS-based positioning for road Intelligent Transport Systems (ITS) — Part 1: Definitions and system engineering procedures for the establishment and assessment of performances*

ETSI TS 102 894-2 V1.3.1 (2018-08), *Intelligent Transport Systems (ITS) — Users and applications requirements — Part 2: Applications and facilities layer common data dictionary*

ETSI prEN 302 890-2¹⁾, *Intelligent Transport Systems (ITS); Facilities Layer function Part 2: Facility Position and Time management (POTI)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

3.1 acceleration

rate of change of *velocity* (3.19) of an object with respect to time

Note 1 to entry: Acceleration is a physical vector quantity; both magnitude and direction are needed to define it. The unit of the scalar absolute value (magnitude) of acceleration is measured in the international system of units as metres per second squared (m/s^2).

3.2 confidence level

probability that the actual *PVT information* (3.15) is within the error bounds of the estimated PVT information

Note 1 to entry: Confidence level represents the confidence that the estimated position does not exceed the error bounds, referred to as *protection level* (3.13) in EN 16803-1.

Note 2 to entry: Confidence level, the term used in ETSI TS 102 894-2 V1.3.1 (2018-08), is the complementary probability of the *integrity risk* (3.3) (i.e. $\text{confidence level} = 1 - \text{integrity risk}$).

3.3 integrity risk

probability that, for positioning terminals providing a *protection level* (3.13) as integrity-related quantity, the actual error on a given output component exceeds its associated *protection level*

Note 1 to entry: *Integrity risk* is the complementary probability of the *confidence level* (3.2) (i.e. $\text{integrity risk} = 1 - \text{confidence level}$).

[SOURCE: EN 16803-1:2020, 3.2.8]

3.4 ITS-S application

ITS-S application process (3.5) residing in the ITS-S application entity

[SOURCE: ISO 21217:2014, 3.18]

1) Under preparation.