INTERNATIONAL STANDARD

ISO 23130

> First edition 2020-09

Milking and cooling machine installations — Monitoring device for bulk milk cooling tanks — Requirements

lations a arveillance a Installations de machines de traite et de refroidissement — Dispositif



Reference number ISO 23130:2020(E)



© ISO 2020

Tentation, no part of vical, including pluested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

COI	ntent	ts	Page
Fore	word		iv
Intr	oductio	on	v
1	Scop	pe	1
2	Nori	mative references	1
3	Tern	ns and definitions	1
4	4.1 4.2 4.3 4.4	General 4.1.1 Functionality and suitability 4.1.2 Design Technical requirements of the monitoring device 4.2.1 Functional requirements Alarms for monitoring milk cooling, storage and agitation 4.3.1 Monitoring milk cooling and storage temperature 4.3.2 Monitoring agitation Monitoring cleaning of bulk milk tank	
5	4.5	Record information	
6		Operator's manual Instructions for tanker driver Instructions for installation	6 6 6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

As milk is a sensitive product, the cooling and storage conditions are of special importance. Monitoring devices for cooling tanks support the control of the cooling and storage conditions and indicate if actual conditions do not comply with the specified conditions.

As the monitoring device is part of the milking and cooling installation, it is essential that its design am, catio.

Aliments the and installation are compatible with the complete installation and comply with the installation manufacturer's specifications.

This document compliments the other standards for milking and cooling equipment provided by TC 23.

This document is a previous general ded by tills

Milking and cooling machine installations — Monitoring device for bulk milk cooling tanks — Requirements

1 Scope

This document specifies minimum performance and information requirements for monitoring devices of bulk milk cooling tanks as part of milking and milk cooling machinery installations in agricultural operations. It also specifies the minimum requirements for materials, design and installation.

The purpose of this document is to contribute to a high-quality milk production by monitoring, collecting data and providing alarms with respect to defined parameters of the milk cooling, storage and cleaning processes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3918, Milking machine installations — Vocabulary

ISO 5708, Refrigerated bulk milk tanks

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3918 and ISO 5708 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

monitoring device

means allowing to measure, to record and to evaluate specified technical or operational parameters of the bulk milk tank

3.2

first batch of milk

quantity of milk that is filled to the tank between T0 and T1

Note 1 to entry: See Table 2 and Figure 1.

3.3

blended batch

comprises the quantity of milk stored between T1 and T2

Note 1 to entry: See <u>Table 2</u> and <u>Figure 1</u>.

10 m