
**Small craft — Hull construction and
scantlings —**

Part 7:
**Determination of loads for multihulls
and of their local scantlings using
ISO 12215-5**

Petits navires — Construction de la coque et échantillonnage —

*Partie 7: Détermination des charges des multicoques et de leur
échantillonnage local en utilisant l'ISO 12215-5*



This document is a preview generated by EKO



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Symbols.....	4
5 Application of this document.....	6
5.1 Materials.....	6
5.2 Limitations.....	6
5.3 Overall procedure for the application of this document.....	7
6 Main dimensions, data and areas.....	7
6.1 Dimensions and data.....	7
6.1.1 General.....	7
6.1.2 Bottom deadrise of the hulls β_x and chine beam B_{Cx} of planing multihulls.....	7
6.1.3 Wet deck bottom.....	8
6.1.4 Crossbeams.....	8
6.2 Areas.....	11
7 Dimensions and pressure for panels and stiffeners under local loads.....	14
7.1 General.....	14
7.2 Example of application on multihulls.....	14
7.2.1 Sections.....	14
7.2.2 Details on panel assessment and dimensions.....	16
7.2.3 The constant averaged pressure method.....	16
7.2.4 Other assessment and dimensioning methods.....	17
7.2.5 Panels acting as "natural" stiffeners.....	17
7.3 Other topics on panel or stiffener dimensions.....	17
8 Local pressure-adjusting factors.....	17
9 Local design pressures.....	24
9.1 General.....	24
9.2 Limits of areas.....	24
9.3 Tables defining the local design pressures for multihulls.....	24
9.4 Design pressure for trimaran floats P_{TRFx}	27
9.4.1 Pressure reduction factors.....	27
9.4.2 Pressure.....	27
9.5 Design pressure on watertight bulkheads and integral tanks.....	27
10 Further treatment of structural elements subject to local loads.....	27
11 Assessment of multihulls rudders, appendages and their wells.....	28
12 Multihull global loads.....	28
12.1 General.....	28
12.2 Typical structural arrangements.....	28
12.3 Global load assessment.....	30
12.3.1 General.....	30
12.3.2 The simplified method.....	30
12.3.3 The enhanced method.....	31
12.4 Design stresses under global loads.....	32
12.5 Global load case GLC1: Diagonal load in quartering sea.....	32
12.6 Global load case GLC 2: Rig loads.....	33
12.7 Combination of diagonal load GLC 1 and rig load GLC 2 for sailing multihulls.....	33
12.8 Global load case GLC 3: Asymmetric broaching loads in sailing multihulls.....	33

12.9	Global load case GLC 4: Longitudinal broaching/pitchpoling.....	34
12.9.1	General.....	34
12.9.2	Full method of analysis of the buoyancy load when the craft pitchpoles.....	35
12.10	Global load case GLC 5: Longitudinal force on one hull.....	36
12.10.1	General.....	36
12.10.2	Longitudinal force.....	36
12.11	Global load case GLC 6: Bending of crossbeams connecting hulls for motor catamarans..	37
13	Structural arrangement for supporting global loads.....	38
14	Multihulls used as commercial craft and workboats.....	38
15	Information to be included in the owner's manual.....	38
15.1	General.....	38
15.2	Respect of maximum loaded displacement.....	38
15.3	Operational guidance.....	38
15.4	Information to take care of sandwich plating.....	38
15.5	Information required by Annex J of ISO 12215-5:2019 - for commercial craft and workboat.....	38
Annex A (informative)	Application sheet of ISO 12215-7.....	39
Annex B (informative)	"Established practice" recommendations for global loads assessment using FEM methods and reporting.....	41
Annex C (informative)	"Established practice" details.....	43
Annex D (informative)	Technical background and example of torsional moment analysis with differential deflection of crossbeams.....	51
Bibliography		58

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 188, *Small craft*.

A list of all parts in the ISO 12215 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The reason underlying the preparation of this document is that standards and recommended practices for loads on the hull and the dimensioning of small craft differ considerably, thus limiting the general worldwide acceptability of boat scantlings. This document has been set towards the minimal requirements of the current practice.

The dimensioning according to this document is regarded as reflecting current practice, provided the craft is correctly handled in the sense of good seamanship and operated at a speed appropriate to the prevailing sea state in a safe and responsible manner, having due cognisance of the prevailing conditions.

Implementation of this document allows to achieve an overall structural strength that ensures the watertight and weathertight integrity of the craft. This document is intended to be a tool to determine the scantlings of a craft as per minimal requirements. It is not intended to be a structural design procedure.

The mechanical property data supplied as default values in this document make no explicit allowance for deterioration in service nor provide any guarantee that these values can be obtained for any particular craft.

Like the other parts of ISO 12215, this document was developed to assess the structure of recreational craft up to 24 m L_H , but it can also be used, where relevant, for non-recreational craft, workboats or yachts with an IMO load line length of up to 24 m, with the necessary critical mind.

Small craft — Hull construction and scantlings —

Part 7:

Determination of loads for multihulls and of their local scantlings using ISO 12215-5

1 Scope

This document defines the dimensions, local design pressures and global loads acting on multihull craft with a hull length (L_H) or load line length of up to 24 m (see Note). It considers all parts of the craft that are assumed watertight or weathertight when assessing stability, freeboard and buoyancy in accordance with ISO 12217 (all parts). Scantlings corresponding to the local design pressures are then assessed using ISO 12215-5.

NOTE The load line length is defined in the OMI "International Load Lines Convention 1966/2005", it can be smaller than L_H for craft with overhangs. This length also sets up at 24 m the lower limit of several IMO conventions.

This document is applicable to multihulls built from the same materials as in ISO 12215-5, in intact condition, and of the two following types:

- recreational craft, including recreational charter vessels;
- commercial craft and workboats.

It is not applicable to multihull racing craft designed only for professional racing.

This document is applicable to the structures supporting windows, portlights, hatches, deadlights and doors.

For the complete scantlings of the craft, this document is intended to be used in conjunction with ISO 12215-8 for rudders, ISO 12215-9 for appendages of sailing craft and ISO 12215-10 for rig loads and rig attachment in sailing craft. ISO 12215-6 can be used for additional details.

Throughout this document, unless otherwise specified, dimensions are in (m), areas in (m^2), masses in (kg), forces in (N), moments in (Nm), Pressures in (kN/m^2) ($1 kN/m^2 = 1 kPa$), stresses and elastic modulus in (N/mm^2) ($1 N/mm^2 = 1 MPa$).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8666:2020, *Small craft — Principal data*

ISO 12215-5:2019, *Small craft — Hull construction and scantlings — Part 5: Design pressures for monohulls, design stress, scantlings determination*

ISO 12215-8:2009, *Small craft — Hull construction and scantlings — Part 8: Rudders*

ISO 12215-9:2012, *Small craft — Hull construction and scantlings — Part 9: Sailing craft appendages*

ISO 12215-10:2020, *Small craft — Hull construction and scantlings — Part 10: Rig loads and rig attachments in sailing craft*

ISO 12217-1:2015, *Small craft — Stability and buoyancy assessment and categorization — Part 1: Non-sailing boats of hull length greater than or equal to 6 m*

ISO 12217-2:2015, *Small craft — Stability and buoyancy assessment and categorization — Part 2: Sailing boats of hull length greater than or equal to 6 m*

ISO 12217-3:2015, *Small craft — Stability and buoyancy assessment and categorization — Part 3: Boats of hull length less than 6 m*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 multihull

craft with two or more hulls with a connecting *wet deck* (3.8)/crossbeams above the loaded waterline, as opposed to a tunnel boat or scow

Note 1 to entry: See Clause 6 and [Figure 2](#) for the main dimensions of a multihull.

3.2 design categories

description of the sea and wind conditions for which a craft is assessed to be suitable

Note 1 to entry: The design categories are defined in ISO 12217 (all parts).

Note 2 to entry: The definitions of the design categories are in line with the European Recreational Craft Directive 2013/53/EU.

[SOURCE: ISO 12215-5:2019, 3.1.]

3.3 loaded displacement

m_{LDC}

mass of water displaced by the craft, including all appendages, when in fully loaded ready for use condition

Note 1 to entry: The fully loaded ready for use condition is further defined in ISO 8666.

[SOURCE: ISO 12215-5:2019, 3.2.]

3.4 mass in minimum operating conditions

m_{OC}

mass of the craft in minimum operating condition

Note 1 to entry: The minimum operating condition is further defined in ISO 8666.

3.5 sailing craft

craft for which the primary means of propulsion is wind power

Note 1 to entry: It is further defined in ISO 8666.

Note 2 to entry: In this document, non-sailing craft are considered as motor craft.