INTERNATIONAL STANDARD

ISO 717-2

Fourth edition 2020-12

Acoustics — Rating of sound insulation in buildings and of building elements —

Part 2: Impact sound insulation

Acoustique — Évaluation de l'isolement acoustique des immeubles et .ction contr des éléments de construction —

Partie 2: Protection contre le bruit de choc





© ISO 2020

nentation, no part of vical, including provested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	tents		Page
Forew	ord		iv
Introd	uction	n	v
1	Scope	е	1
2	Norm	native references	1
3	Term	s and definitions	2
4	4.1 4.2 4.3	Reference values Method of comparison 4.3.1 Measurements in one-third-octave bands 4.3.2 Measurements in octave bands	3 4 4 5
	4.4 4.5	Statement of resultsImpact sound insulation measured with heavy and soft impact sources	
5		Calculation Statement of results	7 7 8
6	6.1 6.2 6.3 6.4	General Reference curves for the reference lightweight floors used to calculate $\Delta L_{\rm t,w}$ Statement of results	9 9 10
		formative) Additional weighting procedure	11
Annex	B (inf impa	formative) Procedure for evaluating the equivalent weighted normalized ct sound pressure level of bare heavy floors	14
Annex	C (inf	formative) Examples of the evaluation of a single-number quantity	16
	D (no	ormative) Rating method for impact sound insulation measured with a heavy soft impact source	20
Biblio	graph	y	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 126, *Acoustic properties of building elements and of buildings*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fourth edition cancels and replaces the third edition (ISO 717-2:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

— A new <u>Annex D</u> with a method for rating heavy/soft impact sound insulation using an A-weighted maximum impact sound pressure level.

A list of all parts in the ISO 717 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

2

Introduction

Methods of measurement of impact sound insulation in buildings and of building elements have ed 1
th are 1
requency
acterizing th. been standardized in ISO 10140-3 and ISO 16283-2. These methods give values for the impact sound insulation which are frequency dependent. The purpose of this document is to standardize a method whereby the frequency-dependent values of impact sound insulation can be converted into a single number characterizing the acoustical performance.

This document is a preview general ded by tills

Acoustics — Rating of sound insulation in buildings and of building elements —

Part 2:

Impact sound insulation

1 Scope

This document

- a) defines single-number quantities for impact sound insulation in buildings and of floors,
- b) gives rules for determining these quantities from the results of measurements carried out in one-third-octave bands in accordance with ISO 10140-3 and ISO 16283-2, and in octave bands in accordance with that option in ISO 16283-2 for field measurements only.
- c) defines single-number quantities for the impact sound reduction of floor coverings and floating floors calculated from the results of measurements carried out in accordance with ISO 10140-3, and
- d) specifies a procedure for evaluating the weighted reduction in impact sound pressure level by floor coverings on lightweight floors.

The single-number quantities in accordance with this document are intended for rating impact sound insulation and for simplifying the formulation of acoustical requirements in building codes. An additional single-number evaluation in steps of 0,1 dB is indicated where it is needed for the expression of uncertainty (except for spectrum adaptation terms). Numerical values of the single-number quantities are specified where required for calculations.

The rating of measurements over an enlarged frequency range is given in Annex A.

A method for obtaining single-number quantities for bare heavy floors according to their performance in combination with floor coverings is given in <u>Annex B</u>.

Example calculations of single-number quantities are given in Annex C.

The rating of measurements with a heavy and soft impact source (rubber ball) is given in Annex D.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10140-1, Acoustics — Laboratory measurement of sound insulation of building elements — Part 1: Application rules for specific products

ISO 10140-3:2010, Acoustics — Laboratory measurement of sound insulation of building elements — Part 3: Measurement of impact sound insulation

ISO 10140-5, Acoustics — Laboratory measurement of sound insulation of building elements — Part 5: Requirements for test facilities and equipment

ISO 12999-1, Acoustics — Determination and application of measurement uncertainties in building acoustics — Part 1: Sound insulation

ISO 16283-2:2018, Acoustics — Field measurement of sound insulation in buildings and of building elements — Part 2: Impact sound insulation

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

single-number quantity for impact sound insulation rating

value of the relevant reference curve at 500 Hz after shifting it in accordance with the method specified in 4.3.1 or the value of the relevant reference curve at 500 Hz after shifting it in accordance with the method specified in 4.3.2, reduced by 5 dB

Note 1 to entry: Terms and symbols for the single-number quantity used depend on the type of measurement. Examples are listed in <u>Table 1</u> for impact sound insulation properties of building elements and in <u>Table 2</u> for impact sound insulation in buildings. In general, new single-number quantities are derived in a similar way.

Note 2 to entry: This quantity is expressed in decibels.

3.2

spectrum adaptation term

 $C_{\mathbf{I}}$

value to be added to the single-number quantity (e.g. $L_{\rm n}$) to take account of the unweighted impact sound level, thereby representing the characteristics of typical walking noise spectra

Note 1 to entry: This quantity is expressed in decibels.

3.3

weighted reduction in impact sound pressure level

difference between the weighted normalized impact sound pressure levels derived with a bare heavy reference floor or a lightweight reference floor, without and with a floor covering

Note 1 to entry: The quantity derived with a bare heavy reference floor is denoted by $\Delta L_{\rm W}$ and is expressed in decibels.

Note 2 to entry: The quantity derived with a lightweight reference floor is denoted by $\Delta L_{\rm t,w}$ and is expressed in decibels. According to the type of reference floor it is denoted as $\Delta L_{\rm t1,w}$, $\Delta L_{\rm t2,w}$, $\Delta L_{\rm t2,w}$, $\Delta L_{\rm t3,w}$.

3.4

equivalent weighted normalized impact sound pressure level of a bare heavy floor

 $L_{\text{n.eq.0.w}}$

sum of the weighted normalized impact sound pressure level of the bare floor under test with the reference floor covering and the weighted reduction in impact sound pressure level of the reference floor covering

Note 1 to entry: This quantity is calculated in accordance with the method specified in this document.

Note 2 to entry: This quantity is expressed in decibels.

3 5

A-weighted maximum impact sound pressure level

 $L'_{iA,Fmax}$

A-weighted maximum impact sound pressure level determined with Fast time-weighting when measured with a heavy and soft impact source, the rubber ball

Note 1 to entry: This quantity is expressed in decibels.