
Hydrometry — Calibration of current- meters in straight open tanks

*Hydrométrie — Étalonnage des moulinets en bassins découverts
rectilignes*



This document is a preview generated by EUS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle of calibration	1
4.1 Statement of the principle	1
4.2 Accuracy of the method	2
4.2.1 Overall uncertainty on the velocity measurement	2
4.2.2 Requirements for accurate measurements	2
5 Infrastructure	2
5.1 Dimensions of the towing tank	2
5.1.1 General	2
5.1.2 Length	2
5.1.3 Depth and width	2
5.2 Towing cart	3
5.2.1 General	3
5.2.2 Cart track system	3
5.2.3 Types of towing carts	3
5.2.4 Cart operation	3
5.2.5 Cart control	4
5.3 Measuring equipment	4
5.3.1 General	4
5.3.2 Distance measurement	4
5.3.3 Time measurement	4
5.3.4 Current-meter velocity measurement	4
5.3.5 Sources of error related to infrastructure	5
5.4 Data acquisition	6
5.5 Data processing	6
5.6 Other requirements	6
6 Calculation of uncertainty	6
7 Calibration procedure	7
7.1 Calibration of rotating element current-meters	7
7.1.1 Suspension of the current-meter	7
7.1.2 Performance of calibration	7
7.1.3 Data analysis	8
7.1.4 Presentation of results	9
7.2 Calibration of electromagnetic current-meters	10
7.2.1 Instructions for calibration	10
7.2.2 Mounting the electromagnetic current-meter	10
7.2.3 Number of calibration points	10
7.2.4 Performance of calibration	11
7.2.5 Data analysis	11
7.2.6 Presentation of results	11
7.3 Calibration of acoustic current-meters for point velocity measurement	11
7.3.1 Instructions for calibration	11
7.3.2 Mounting the acoustic current-meter	12
7.3.3 Performance of calibration	12
7.3.4 Data analysis	12
7.3.5 Presentation of results	12
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 5, *Instruments, equipment and data management*.

This third edition cancels and replaces the second edition (ISO 3455:2007), which has been technically revised.

The main changes compared to the previous editions are as follows:

- a subclause for calibration of acoustic current-meters for point velocity measurement has been added;
- clauses referring to outdated tracking systems like track systems using tooth belts have been removed;
- clauses referring to outdated technique for data acquisition like strip chart recorder or magnetic tapes have been removed;
- the clause for computerized data acquisition and processing system has been removed;
- the clause discussing the Epper effect has been removed.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Hydrometry — Calibration of current-meters in straight open tanks

1 Scope

This document specifies a calibration method for mechanical type, electromagnetic type and acoustic type hydrometric current-meters used for point velocity measurement of flowing water. The method requires towing the instrument through still water in a straight open tank. It includes measuring apparatus, the calibration procedure, the method of presenting the results and the uncertainties associated with the method.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

ISO 2537, *Hydrometry — Rotating-element current-meters*

ISO/IEC Guide 98-3 *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle of calibration

4.1 Statement of the principle

Calibration of a current-meter means experimental determination of the relationship between water velocity and either the rate of revolution of the rotating element or the velocity directly indicated by the current-meter. For this purpose, the current-meter is mounted on a towing cart and drawn through still water contained in a straight tank with a uniform cross section at a number of steady speeds of the towing cart. Simultaneous measurements of the speed of the towing cart and the rate of revolution of the rotating element or the velocity indicated by the current-meter are made. In the case of rotating-element current-meters, the two parameters are related by one or more formula(e), the limits of validity of which are stated. In the case of stationary-sensor type current-meters, containing no rotating elements, the velocity indicated by its display unit is compared with the corresponding cart speed to know the error in measurement.