EESTI STANDARD

Timber structures - Cross laminated timber is la. Requirements



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

	This Estonian standard EVS-EN 16351:2021 consists of the English text of the European standard EN 16351:2021.		
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.		
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 03.03.2021.	Date of Availability of the European standard is 03.03.2021.		
Standard on kättesaadav Eesti Standardimis-ja Akrediteerimiskeskusest.	The standard is available from the Estonian Centre for Standardisation and Accreditation.		
Fagasisidat standardi sisu kahta an võimalik ada	stada kasutadas EVS i vashilahal asuvat tagasisid		

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

ICS 79.060.10

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis-ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis-ja Akrediteerimiskeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 16351

March 2021

ICS 79.060.10

Supersedes EN 16351:2015

English Version

Timber structures - Cross laminated timber -Requirements

Structures en bois - Bois lamellé croisé - Exigences

Holzbauwerke - Brettsperrholz - Anforderungen

This European Standard was approved by CEN on 4 January 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Europ	ean foreword	4
Introd	luction	
1	Scope	7
2	Normative references	8
3	Terms, definitions and symbols	10
3.1	Terms and definitions	10
3.2	Symbols	
3.2.1	Main symbols	
3.2.2	Subscripts	17
4	Characteristics	19
4.1	Modulus of elasticity, bending strength, compressive strength, tensile streng	th and
	shear strength	19
4.1.1	General	19
4.1.2	Geometrical data of cross laminated timber	21
4.1.3	Strength, stiffness and density properties of layers	
4.1.4	Bending strength of large finger joints	
4.1.5	Rolling shear strength, compression strength perpendicular to grain and der	
	cross laminated timber	
4.2	Bonding strength	
4.2.1	General	
4.2.2	Bonding strength of glue lines between layers	
4.2.3	Bonding strength of structural edge bonds	
4.2.4	Bonding strength of large finger joints	
4.3	Resistance to fire	
4.4	Reaction to fire	
4.4.1	General	
4.4.2	Classification without further testing	27
4.4.3	Classification based on testing	29
4.5	Dimensional stability	
4.6	Emission of formaldehyde	
4.7	Durability	
4.7.1	Durability of bonding strength	31
4.7.2	Durability of other characteristics	32
5	Assessment and Verification of Constancy of Performance (AVCP)	
5.1	General	
5.2	Type testing	
5.2.1	General	
5.2.2	Test samples, testing and compliance criteria	
5.2.3	Test reports	
5.3	Factory production control (FPC)	
5.3.1	General	
5.3.2	Provisions	
5.3.3	Initial inspection of factory and of FPC	
5.3.4	Continuous surveillance of FPC	
5.3.5	Procedure for modifications	51

Annex A (normative)	Delamination test of glue lines between layers	52
Annex B (normative)	Tests with laminations with or without finger joints	56
cross laminate	Determination of strength, stiffness and density characteristics of ed timber	
Annex D (normative)	Measurement of moisture content	76
	Adhesive application for finger joints in laminations	
Annex F (normative)	Minimum production provisions	78
Annex G (normative)	Shear tests	92
Annex H (normative) FJ for use in st	Additional test methods and requirements for adhesives of subclass ructural edge bonds	95
Bibliography		96
	ructural edge bonds	

European foreword

This document (EN 16351:2021) has been prepared by Technical Committee CEN/TC 124 "Timber structures", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2021, and conflicting national standards shall be withdrawn at the latest by December 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.


This document supersedes EN 16351:2015.

The following changes have been made:

- the standard has been adjusted to the latest versions of standards for adhesives;
- the provisions for reaction and resistance to fire have been modified;
- the provisions for gap widths and ratios of lamination width by thickness have been modified;
- missing provisions for factory production control have been added;
- the provisions for determination of strength, stiffness and density characteristics of cross laminated timber have been modified;
- the standard has been adjusted to the latest templates;
- Annex ZA has been deleted.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction






Figure 1 — Relation of some European Standards on structural timber products

Cross laminated timber in accordance with this document and multilayer solid wood panels in accordance with EN 13353 may have the same layup, but for cross laminated timber the timber is strength graded according to EN 14081-1 and the adhesives are tested according to the provisions of this document.

<text> The following standards mentioned in Clause 2, EN 13986, EN 14080, EN 14081-1, EN 14374 and EN 15497, are harmonized product standards. The applicable version cited in the Official Journal of the EU are not necessarily the latest published by CEN.

1 Scope

This document sets out provisions regarding the performance of characteristics of the following Types of cross laminated timber for use in buildings and bridges:

- Type 1: Straight or curved cross laminated timber comprising only timber layers but no large finger joints;
- Type 2: Straight cross laminated timber comprising only timber layers and large finger joints;
- Type 3: Straight cross laminated timber comprising timber and wood-based panel layers but no large finger joints.

This document covers cross laminated timber of all three Types of cross laminated timber:

- manufactured according to this document, which sets up provisions for:
 - boundary conditions during manufacture of cross laminated timber;
 - moisture content and temperature of timber to be bonded;
 - production of finger joints and bonds between layers;
- to be used in service class 1 or 2 according to EN 1995-1-1;
- made of coniferous species and poplar listed in this document;
- which may be made of layers made of different species;
- bonded with phenolic or aminoplastic or moisture curing one-component polyurethane or emulsion polymer isocyanate adhesives of adhesive Type I according to the respective standard;
- made of timber laminations having a nominal width between 40 mm (including) and 300 mm (including);
- built up of at least three orthogonally bonded layers (at least two of them timber layers);
- which may have, depending on the number of layers, adjacent layers bonded parallel to the grain;
- made of timber layers which are made of strength graded timber according to EN 14081-1;
- made of timber layers having nominal thicknesses between 6 mm (including) and 47 mm (including);
- made of timber layers which may comprise edge bonds;
- having nominal overall thicknesses up to 500 mm.

Additional provisions of this document apply for straight cross laminated timber comprising only timber layers and comprising large finger joints (Type 2):

- made from cross laminated timber pieces having the same cross-section and layup; \checkmark
- made from cross laminated timber pieces having nominal cross-sectional thicknesses from 51 mm (including) up to 345 mm (including) and nominal minimum thicknesses of the outer layers not less than 17 mm (including);

- made from cross laminated timber pieces solely comprising timber layers;
- made from plane cross laminated timber pieces;
- with parallel x-axes of the jointed components;
- with large finger joints having a finger length of at least 45 mm and fingers which are visible at the two narrow sides of the components;
- having large finger joints bonded with phenolic or aminoplastic or moisture curing one-component polyurethane adhesives of adhesive Type I according to the respective standard.

Additional provisions of this document apply for straight cross laminated timber comprising timber and wood-based panel layers but no large finger joints (Type 3):

- made of structural wood-based panels specified in this document;
- made of one panel per layer and;
- having thicknesses between 6 mm (including) and 45 mm (including).

This document applies to cross laminated timber untreated or treated against biological attack.

This document does not cover:

- cross laminated timber treated with fire retardants;
- cross laminated timber which is produced from re-used timber or wood-based panels comprising reused timber.

It also lays down procedures for assessment and verification of constancy of performance (AVPC) of cross laminated timber.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 301:2017, Adhesives, phenolic and aminoplastic, for load-bearing timber structures - Classification and performance requirements

EN 302-1, Adhesives for load-bearing timber structures - Test methods - Part 1: Determination of longitudinal tensile shear strength

EN 302-2, Adhesives for load-bearing timber structures - Test methods - Part 2: Determination of resistance to delamination

EN 338, Structural timber - Strength classes

EN 335, Durability of wood and wood-based products - Use classes: definitions, application to solid wood and wood-based products

EN 350, Durability of wood and wood-based products - Testing and classification of the durability to biological agents of wood and wood-based materials

EN 351-1, Durability of wood and wood-based products - Preservative-treated solid wood - Part 1: Classification of preservative penetration and retention

EN 408:2010+A1:2012, Timber structures - Structural timber and glued laminated timber - Determination of some physical and mechanical properties

EN 717-1, Wood-based panels - Determination of formaldehyde release - Part 1: Formaldehyde emission by the chamber method

EN 789, Timber structures - Test methods - Determination of mechanical properties of wood based panels

EN 1995-1-1, Eurocode 5: Design of timber structures - Part 1-1: General - Common rules and rules for buildings

EN 1995-1-2, Eurocode 5: Design of timber structures - Part 1-2: General - Structural fire design

EN 12369-2, Wood-based panels - Characteristic values for structural design - Part 2: Plywood

EN 12369-3, Wood-based panels - Characteristic values for structural design - Part 3: Solid-wood panels

EN 13183-1, Moisture content of a piece of sawn timber - Part 1: Determination by oven dry method

EN 13183-2, Moisture content of a piece of sawn timber - Part 2: Estimation by electrical resistance method

EN 13183-3, Moisture content of a piece of sawn timber - Part 3: Estimation by by capacitance method

EN 13238, Reaction to fire tests for building products - Conditioning procedures and general rules for selection of substrates

EN 13501-1, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 13501-2, Fire classification of construction products and building elements - Part 2: Classification using data from fire resistance tests, excluding ventilation services

EN 13823, Reaction to fire tests for building products - Building products excluding floorings exposed to the thermal attack by a single burning item

EN 13986, Wood-based panels for use in construction - Characteristics, evaluation of conformity and marking

EN 14081-1, Timber structures - Strength graded structural timber with rectangular cross-section - Part 1: General requirements

EN 14358, Timber structures - Calculation and verification of characteristic values

EN 14374, Timber structures - Structural laminated veneer lumber - Requirements

EN 15228:2009, Structural timber - Structural timber preservative treated against biological attack

EN 15425:2017, Adhesives - One component polyurethane (PUR) for load-bearing timber structures - Classification and performance requirements

EN 16254:2013+A1:2016, Adhesives - Emulsion polymerized isocyanate (EPI) for load bearing timber structures - Classification and performance requirements

EN ISO 9239-1, Reaction to fire tests for floorings - Part 1: Determination of the burning behaviour using a radiant heat source (ISO 9239-1)

EN ISO 11925-2:2020, Reaction to fire tests - Ignitability of products subjected to direct impingement of flame - Part 2: Single-flame source test (ISO 11925-2)

3 Terms, definitions and symbols

For the purposes of this document, the following terms, definitions and symbols apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at <u>http://www.electropedia.org/</u>

3.1 Terms and definitions

3.1.1

actual size

measured size of a cross laminated timber at a given moisture content

[SOURCE: EN 14080:2013, 3.1 - modified]

3.1.2

bonding strength

structural effectiveness of adhesives between timber pieces when subjected to stresses

[SOURCE: EN 14080:2013, 3.2]

3.1.3

contact-free application

application without contact between timber and application unit

3.1.4

corrected size

size of a cross laminated timber corrected by calculation from its actual size to its size at the reference moisture content

[SOURCE: EN 14080:2013, 3.6 - modified]

3.1.5

cross laminated timber

structural timber member composed by at least three face-bonded layers which comprise solid timber laminations and may comprise wood-based panels, at least one layer orthogonally oriented to the two adjacent layers

Note 1 to entry: See also Figure 2.