

# TECHNICAL SPECIFICATION



**Rotating electrical machines –  
Part 27-5: Off-line measurement of partial discharge inception voltage on  
winding insulation under repetitive impulse voltage**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC online collection - [oc.iec.ch](http://oc.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Preview generated by EVS

# TECHNICAL SPECIFICATION



**Rotating electrical machines –  
Part 27-5: Off-line measurement of partial discharge inception voltage on  
winding insulation under repetitive impulse voltage**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 29.160.01

ISBN 978-2-8322-9648-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions, symbols and abbreviated terms .....	8
4 Repetitive impulse voltages for PD measurement .....	11
4.1 General.....	11
4.2 Waveform of single impulse voltage .....	12
4.2.1 Waveform at impulse generator terminal without test object.....	12
4.2.2 Typical distortions of impulse waveform at the terminals of test object.....	14
4.3 Train of single impulse voltage.....	17
4.4 Step-by-step voltage increase and decrease using trains of single impulse voltage.....	18
4.5 Impulse voltage distribution inside rotating machines .....	22
5 PD measurement methods with impulse voltage .....	23
5.1 General.....	23
5.2 Electrical PD measurements .....	23
5.2.1 General .....	23
5.2.2 Coupling capacitor with higher order analogue filter.....	23
5.2.3 HFCT with higher order analogue filter .....	24
5.2.4 Electromagnetic couplers.....	25
5.3 Threshold level of PD detection .....	26
5.4 Measuring system with impulse generator and computer.....	27
5.5 Calculation and interpretation of RPDIV and RPDEV .....	27
6 Impulse PD test procedure .....	28
6.1 Test object.....	28
6.1.1 Twisted-pair or equivalent.....	28
6.1.2 Motorette or formette .....	29
6.1.3 Complete winding and connection.....	29
6.2 Safety and environment during PD test .....	31
6.2.1 Grounding and floating of test objects during tests.....	31
6.2.2 Environment during test.....	31
6.3 Test procedure and reports .....	32
Annex A (informative) Typical PD measurements on a complete winding .....	33
Annex B (informative) Example of PD data analysis using phase angle.....	35
Annex C (informative) Example of connection of complete windings .....	37
C.1 General.....	37
C.2 Connections for three-terminal machines .....	37
C.3 Connections for four-terminal machines .....	40
Annex D (informative) Example of SBS voltage increase pattern of repetitive impulse .....	41
Bibliography.....	42
Figure 1 – Block representation of measurement circuit for RPDIV and RPDEV .....	11
Figure 2 – Simplified impulse generator (IG) circuit with a single switch S .....	12
Figure 3 – Output voltage at open terminal of IG with single switch.....	13

Figure 4 – Two impulses at open terminal of IG with single switch .....	13
Figure 5 – Simplified IG circuit with four-arm (switch) bridge circuit.....	13
Figure 6 – Output voltages at open terminal of four-arm bridge circuit.....	14
Figure 7 – Increase of rise time and decrease of peak voltage of triangular impulse .....	15
Figure 8 – Increase of rise time and decrease of peak voltage of rectangular impulse.....	15
Figure 9 – Overshoot of peak and following fast oscillation of triangular impulse .....	15
Figure 10 – Overshoot of peak and following fast oscillation of rectangular impulse .....	16
Figure 11 – Typical "ringing" observed during bipolar rectangular voltage test .....	16
Figure 12 – Slow oscillating decay of triangular impulse .....	17
Figure 13 – Slow oscillating decay of rectangular impulse.....	17
Figure 14 – Schematic representation of train parameters of positive unipolar impulses .....	18
Figure 15 – Schematic representation of train parameters of bipolar impulses .....	18
Figure 16 – SBS parameters of positive unipolar impulses .....	19
Figure 17 – SBS voltage pattern of positive unipolar impulses for RPDIV and RPDEV .....	19
Figure 18 – SBS voltage pattern of bipolarly distorted positive unipolar impulse .....	20
Figure 19 – SBS voltage increase of bipolar impulses .....	20
Figure 20 – Representative scheme of conditioning procedure before RPDIV measurement.....	21
Figure 21 – Schematic representation of phase/phase, phase/ground and turn/turn voltages of the winding of a rotating machine fed from a two-level converter [2] .....	23
Figure 22 – Coupling capacitor with higher order analogue filter .....	24
Figure 23 – Example of voltage impulse and PD pulse frequency spectra before (left) and after (right) filtering .....	24
Figure 24 – HFCT between supply and test object with higher order analogue filter .....	25
Figure 25 – HFCT between test object and earth with higher order analogue filter .....	25
Figure 26 – Circuit using an electromagnetic coupler (for example an antenna) to suppress impulses from the test supply.....	25
Figure 27 – Circuit using an electromagnetic UHF antenna .....	26
Figure 28 – Schematic representation of noise, disturbance and threshold values .....	26
Figure 29 – Example diagram of PD measurements with PC .....	27
Figure 30 – Example of RPDIV and RPDEV calculation using a 50 % PD probability against repetitive impulse voltage (Figure 12 of IEC TS 61934:2011, modified).....	28
Figure 31 – Representative scheme of voltage terminals for three-terminal machine and four-terminal machine .....	30
Figure A.1 – Block diagram of PD measurement system used in RRT .....	33
Figure A.2 – Impulse pattern used in RRT and PD inception .....	33
Figure B.1 – Example of PD phase angle pattern of sinusoidal voltage .....	35
Figure B.2 – Example of PD phase angle pattern of PWM voltage on the phase angle of a sinusoidal one.....	36
Figure B.3 – Example of PD phase angle pattern of PWM voltage on rectangular voltage angle (PRPD pattern) .....	36
Figure C.1 – Connection of six-terminal machines.....	37
Figure C.2 – Connection of three- or four-terminal machines (with N terminal) .....	37
Figure C.3 – Three-terminal machine connection, Type A (Table 2) .....	38
Figure C.4 – Three-terminal machine connection, Type B (Table 2) .....	38
Figure C.5 – Three-terminal machine connection, Type C (Table 2) .....	38

Figure C.6 – Three-terminal machine connection, Type D (Table 2) .....	39
Figure C.7 – Three-terminal machine connection, Type E (Table 2) .....	39
Figure C.8 – Three-terminal machine connection, Type F (Table 2) .....	39
Figure C.9 – Four-terminal machine with earthed N terminal – Connection types (Table 3) .....	40
Figure D.1 – SBS voltage increase of alternating train of unipolar impulses .....	41
Table 1 – Typical ranges of impulse voltage parameters at terminal of test object to be reported .....	21
Table 2 – Connection of complete winding of three-terminal machine .....	30
Table 3 – Connection of complete winding of four-terminal machine .....	31
Table A.1 – Parameters used in RRT .....	33

This document is a preview generated by EVS

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## ROTATING ELECTRICAL MACHINES –

**Part 27-5: Off-line measurement of partial discharge inception voltage on winding insulation under repetitive impulse voltage**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 60034-27-5, which is a Technical Specification, has been prepared by IEC technical committee 2: Rotating machinery.

The text of this Technical Specification is based on the following documents:

Draft TS	Report on voting
2/1955/DTS	2/1962A/RVDTS

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

NOTE A table of cross-references of all IEC TC 2 publications can be found on the IEC TC 2 dashboard on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**



## INTRODUCTION

The recent development of power electronics technology has led to various power drive systems (PDS) of variable-speed rotating electrical machines. The new influences of PDS on rotating machines are introduced in IEC TS 60034-25 [1]<sup>1</sup>. This document points out that electrical insulation of machine winding is exposed to numerous voltage impulses due to the repetitive fast switching of power devices in PDS. The severity of the impulses depends on ratings of converter and machines, converter topology, length of cable between machine and converter, filtering equipment and so on.

IEC 60034-18-41 [2], published in 2014, is the first International Standard which describes design qualification and type tests for Type I (partial discharge free) insulation systems used in converter-fed rotating electrical machines. In this document, both tests require partial discharge (PD) tests with power frequency voltage or impulse excitation. As for PD measurements with impulse excitation, IEC 60034-18-41 cites IEC TS 61934, which provides a technical explanation and several PD measuring methods, in general. For practical test guidance specific to winding insulation of rotating machines, this document was prepared as an off-line measurement of PD inception and extinction voltages during repetitive impulse condition, RPDIV and RPDEV.

---

<sup>1</sup> Numbers in square brackets refer to the Bibliography

## ROTATING ELECTRICAL MACHINES –

### Part 27-5: Off-line measurement of partial discharge inception voltage on winding insulation under repetitive impulse voltage

#### 1 Scope

This document provides an off-line measurement method of the partial discharge inception and extinction voltage on winding insulation under repetitive impulse voltage. This document is relevant to rotating machines supplied by a voltage source converter.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-27-1, *Rotating electrical machines – Part 27-1: Off-line partial discharge measurements on the winding insulation*

IEC TS 61934:2011, *Electrical insulating materials and systems – Electrical measurement of partial discharges (PD) under short rise time and repetitive voltage impulses*

IEC TS 62478, *High voltage test techniques – Measurement of partial discharges by electromagnetic and acoustic methods*

#### 3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms, definitions, symbols and abbreviated terms given in IEC 60034-27-1, IEC TS 61934, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

##### 3.1

##### partial discharge

##### PD

localized electrical discharge that only partially bridges the insulation between conductors and which can or cannot occur adjacent to a conductor

##### 3.2

##### repetitive partial discharge inception voltage

##### RPDIV

minimum peak-to-peak impulse voltage at which more than five PD pulses occur on ten voltage impulses of the same peak-to-peak values when the impulse voltage applied to the test object is increased with step-by-step method

Note 1 to entry: This is a mean value for the specified test time and a test arrangement where the voltage applied to the test object is increased with the step-by-step method. Details are mentioned in 5.5.