

TECHNICAL SPECIFICATION



**Fire hazard testing –
Part 2-20: Glowing/hot wire based test methods – Hot-wire coil test method –
Apparatus, verification, test method and guidance**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Preview generated by EVS

TECHNICAL SPECIFICATION



**Fire hazard testing –
Part 2-20: Glowing/hot wire based test methods – Hot-wire coil test method –
Apparatus, verification, test method and guidance**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 13.220.40, 29.020

ISBN 978-2-8322-9707-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	9
4 Principle.....	11
5 Apparatus.....	12
5.1 Test chamber.....	12
5.2 Heater wire	12
5.3 Power supply and test circuit	13
5.4 Test specimen fixture.....	13
5.5 Test specimen winding and pressing.....	13
5.6 Conditioning chamber	14
5.7 Timing device	15
5.8 Micrometer.....	15
5.9 Measuring scale.....	15
6 Test specimens	15
6.1 Test specimen preparation.....	15
6.2 Test specimen dimensions.....	15
7 Conditioning	16
7.1 Requirements	16
7.2 Test specimen conditioning.....	16
7.3 Heater wire conditioning	16
7.4 Test conditions	16
8 Test procedure	17
8.1 General.....	17
8.2 Apparatus	17
8.3 Determination of the test current, I_c	17
8.4 Calculation of test current, I_c	18
8.5 Determination of time to ignite, IT and/or time to drip, DT	18
9 Observations and measurement	20
10 Evaluation of test results	21
10.1 Assigning a HWCT PLC classification	21
10.2 Precision data.....	21
11 Test report.....	21
Annex A (informative) Guidance on how to effectively wind the heater wire on to the test specimen	22
Annex B (normative) Hot wire coil test (HWCT) – Performance level category (PLC) classes	23
B.1 General.....	23
B.2 Reporting a classification.....	23
Annex C (informative) Calibration curve to determine test current (I_c) in a spreadsheet program.....	24
Annex D (informative) Precision data	25
D.1 General.....	25

D.2	Results of preliminary inter-laboratory round robin	25
D.3	Evaluation of test results	28
	Bibliography	30
Figure 1	– Test fixture arrangement (example)	11
Figure 2	– Test specimen winding pattern	12
Figure 3	– Test specimen fixture (example)	13
Figure 4	– Heater wire winding device (Example)	14
Figure 5	– Test circuit arrangement for heater wire calibration	17
Figure 6	– Calibration curve	18
Figure 7	– Decision tree	20
Figure A.1	– Illustration of type a) behaviour	22
Figure A.2	– Illustration of type b) behaviour	22
Figure C.1	– Calibration curve in a spreadsheet program used to determine I_C	24
Table 1	– Nominal thickness tolerances	16
Table B.1	– Hot wire coil test (HWCT) – Performance level category (PLC) classes	23
Table D.1	– Results for material 1A	26
Table D.2	– Results for material 1B	26
Table D.3	– Results for material 2A	26
Table D.4	– Results for material 2B	27
Table D.5	– Results for material 3	27
Table D.6	– Results for material 4	28
Table D.7	– Occurrence of PLC classes in the round robin	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIRE HAZARD TESTING –**Part 2-20: Glowing/hot wire based test methods –
Hot-wire coil test method –
Apparatus, verification, test method and guidance**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 60695-2-20 has been prepared by IEC technical committee 89: Fire hazard testing. It is a Technical Specification.

This third edition of IEC TS 60695-2-20 replaces the second edition of IEC TS 60695-2-20 published in 2004. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- Contents page added
- Updated Scope (Clause 1)
- Updated Terms and Definitions, added new relevant terms (Clause 3)
- Updated Principle (Clause 4)

- Updated Apparatus (Clause 5; recommendation to change the power source from a.c. to d.c. with a constant current output. Reason for this recommendation: D.c. technology is easier to obtain and to handle, which has been found to improve the Repeatability and Reproducibility of the test.
- Updated Test specimen dimensions (6.2)
- Revised Test procedure (Clause 8)
- Revised Observations and measurements (Clause 9)
- Revised Evaluation of test results (Clause 10)
- Revised Test report (Clause 11)
- Revised Annex A: Deletion of conformational test; Guidance on verification of the heater wire winding before testing
- Addition of normative Annex B: HWCT PLC Classes
- Addition of informative Annex C: Calibration curve to determine test current (I_c) in a spreadsheet program
- Addition of informative Annex D: Precision data

The text of this Technical Specification is based on the following documents:

DTS	Report on voting
89/1465/DTS	89/1488/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

It has the status of a basic safety publication in accordance with IEC Guide 104 and ISO/IEC Guide 51.

Part 2 of IEC 60695 consists of the following parts:

- Part 2-10: *Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*
- Part 2-11: *Glowing/hot-wire based test methods – Glow-wire flammability test method for end products*
- Part 2-12: *Glowing/hot-wire based test methods – Glow-wire flammability index (GWFI) test method for materials*
- Part 2-13: *Glowing/hot-wire based test methods – Glow-wire ignition temperature (GWIT) test method for materials*
- Part 2-20: *Glowing/hot-wire based test methods – Hot-wire coil test method – Apparatus, verification, test method and guidance*

A list of all parts in the IEC 60695 series, published under the general title *Fire hazard testing*, can be found on the IEC website.

Words **in bold** in the text are defined in Clause 3.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

In the design of any electrotechnical product, the risk of **abnormal heat** and the potential hazards associated with **abnormal heat** need to be considered. In this respect the objective of component, circuit, and product design, as well as the choice of materials, is to reduce to acceptable levels the potential risks during normal operating conditions, reasonably foreseeable abnormal use, malfunction and/or failure. IEC/TC 89 has developed IEC 60695-1-10 [1]¹, together with its companion IEC 60695-1-11 [2], to provide guidance on how this is to be accomplished.

The primary aims of IEC 60695-1-10 [1] and IEC 60695-1-11 [2] are to provide guidance on how:

- a) to prevent **ignition** caused by an electrically energized component part, and
- b) to confine any resulting fire within the bounds of the enclosure of the electro technical product in the event of **ignition**.

Secondary aims of IEC 60695-1-10 [1] and IEC 60695-1-11 [2] include the minimization of any flame spread beyond the product's enclosure and the minimization of the harmful effects of **fire effluents** such as heat, smoke, toxicity and/or corrosivity.

This test method applies to solid electrical insulating materials which can provide test specimens. It applies to materials for which the test specimen does not deform during preparation, especially during the winding of the test specimen with the heater wire as described in 5.5.

Examples of deformation that render this test method inapplicable include:

- a) bowing, in either a transverse or a longitudinal direction, or twisting of the test specimen during the winding of the test specimen with the heater wire, to a degree visible to the eye, or
- b) visible indentation of the test specimen by the heater wire.

An informative classification system described in Annex B can be used for the **preselection** of materials.

¹ Numbers in square brackets refer to the bibliography.

FIRE HAZARD TESTING –

Part 2-20: Glowing/hot wire based test methods – Hot-wire coil test method – Apparatus, verification, test method and guidance

1 Scope

This part of IEC 60695, which is a technical specification, describes a test method that applies to solid electrical insulating materials of which test specimens can be provided. The test measures the time required to ignite a test specimen when it is affected by heat from an electrically heated wire wound around the test specimen. If the test specimen drips, the time at which this occurs is also recorded.

The test method can be used to provide classifications which can be used for quality assurance, the **preselection** of materials of products as described in IEC 60695-1-30, or to verify the required minimum classification of materials used in **end products**.

This basic safety publication is intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications. The requirements, test methods or test conditions of this basic safety publication will not apply unless specifically referred to or included in the relevant publications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60695-1-30, *Fire hazard testing - Part 1-30: Guidance for assessing the fire hazard of electrotechnical products - Preselection testing process - General guidelines*

IEC 60695-4:2012, *Fire hazard testing - Part 4: Terminology concerning fire tests for electrotechnical products*

IEC GUIDE 104:2019, *The preparation of safety publications and the use of basic safety publications and group safety publications*

ISO/IEC Guide 51:2014, *Safety aspects – Guidelines for their inclusion in standards*

ISO 291:2008, *Plastics – Standard atmospheres for conditioning and testing*

ISO 293, *Plastics – Compression moulding test specimens of thermoplastic materials*

ISO 294 (all parts), *Plastics – Injection moulding of test specimens of thermoplastic materials*

ISO 295, *Plastics – Compression moulding of test specimens of thermosetting materials*

ISO 13943:2008, *Fire safety - Vocabulary*

ISO 16012:2004, *Plastics – Determination of linear dimensions of test specimens*

JIS C 2520:1999, *Wires and rolled wires for electrical heating*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13943:2017, some of which are reproduced below for the user's convenience, as well as the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

abnormal heat

<electrotechnical> heat that is additional to that resulting from use under normal conditions, up to and including that which causes a fire

[SOURCE: ISO 13943:2017, definition 3.1]

3.2

classification time, t_A

arithmetic mean of relevant **times to ignite, IT** and **times to drip, DT** , used for the purpose of classification

3.3

combustion

exothermic reaction of a substance with an oxidizing agent

Note 1 to entry: Combustion generally emits fire effluent accompanied by flames and/or glowing.

[SOURCE: ISO 13943:2017, definition 3.55]

3.4

draught-free environment

space in which the results of experiments are not significantly affected by the local air speed

Note 1 to entry: A qualitative example is a space in which a wax candle flame remains essentially undisturbed. Quantitative examples are small-scale fire tests in which a maximum air speed of $0,1 \text{ m}\cdot\text{s}^{-1}$ or $0,2 \text{ m}\cdot\text{s}^{-1}$ is sometimes specified

[SOURCE: ISO 13943:2017, definition 3.83]

3.5

end product

product which is ready for use

Note 1 to entry: An **end product** can be a component of another **end product**.

[SOURCE: IEC 60695-4:2012, definition 3.2.7]