IEC TR 62977-1-31

Edition 1.0 2021-04

TECHNICAL REPORT

colour inside

Electronic displays –
Part 1-31: Generic – Practical information on the use of light measuring devices

IEC TR 62977-1-31:2021-04(en)

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC TR 62977-1-31

Edition 1.0 2021-04

TECHNICAL REPORT

colour inside

Electronic displays –
Part 1-31: Generic – Practical information on the use of light measuring devices

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-9716-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms, definitions, and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 10
4 General information on LMDs for photometry and colorimetry 10
4.1 General 10
4.2 Photometry and colorimetry for electronic displays 10
4.3 LMDs for luminance and chromaticity measurements 11
4.3.1 Configuration of LMDs 11
4.3.2 Input optics of LMDs 13
4.3.3 Electronic system of LMDs 13
4.3.4 Calibration of LMDs 14
4.3.5 Maintenance of LMDs 14
4.4 Setup conditions for measurement 14
4.4.1 LMDs 14
4.4.2 DUTs 14
4.4.3 Environment 14
5 Influence of LMD properties on luminance and chromaticity measurements 14
5.1 General 14
5.2 Repeatability 15
5.2.1 General 15
5.2.2 Example of the repeatability of an LMD 15
5.3 Accuracy 16
5.3.1 General 16
5.3.2 Example of the accuracy of an LMD 16
5.3.3 Linearity 16
5.3.4 Range change 17
5.4 Luminance range 17
5.5 Spectral properties of the spectroradiometer 17
5.5.1 General 17
5.5.2 Wavelength accuracy and spectral bandwidth 17
5.6 Spectral properties of the filter-type luminance meter and colorimeter 23
5.6.1 General 23
5.6.2 Spectral responsivity 23
5.6.3 Methods to reduce the measurement difference 25
5.7 Angular response of LMDs 26
5.7.1 General 26
5.7.2 Subtended angles 26
5.7.3 Consideration of the input optics 27
5.8 Measurement field 28
5.8.1 General 28
5.8.2 Number of pixels within the measurement field 29
5.9 Polarization 29

5.9.1 General 29
5.9.2 Polarization dependence of LMDs 30
5.10 Temporal synchronization 31
5.10.1 General 31
5.10.2 Temporal synchronization of the LMD and DUT 31
6 Influence of LMD properties on measurements of the optical characteristics of electronic displays 32
6.1 General 32
6.2 Contrast ratio 32
6.2.1 General 32
6.2.2 Calculated influence of LMD properties on the contrast ratio measurements 32
6.3 Electro-optical transfer function (EOTF) 35
6.3.1 General 35
6.3.2 Calculated influence of the LMD properties on the EOTF measurements 35
6.4 Chromaticity gamut area 36
6.4.1 General 36
6.4.2 Calculated influence of LMD properties on the chromaticity gamut area measurements 36
6.5 Viewing direction characteristics 38
6.5.1 General 38
6.5.2 Calculated influence of the LMD properties on the viewing direction characteristics measurements 38
6.5.3 Measurement field at an oblique direction 40
6.6 Spatial uniformity 41
6.6.1 General 41
6.6.2 Calculated influence of LMD properties on uniformity and non-uniformity measurements 41
6.7 Response time 43
6.7.1 General 43
6.7.2 Measurement of the response time 43
6.8 Flicker 46
6.8.1 General 46
6.8.2 Measurement method of the flicker 46
6.8.3 Low-pass filter of LMDs 47
Annex A (informative) Photometry and colorimetry 49
A.1 General 49
A.2 Photometry 49
A.3 Colorimetry 49
A.3.1 General 49
A.3.2 Standard colorimetric observer 50
A.3.3 Tristimulus values 50
A.3.4 Chromaticity diagram and colour space 50
Annex B (informative) Method for reducing the measurement difference of colorimeters 53
B.1 General 53
B.2 Matrix calibration methods for colorimeters 53
B.2.1 Matrix calibration process 1: RGB calibration 53
B.2.2 Matrix calibration process 2: RGBW calibration 54

Annex C (informative) Input data in Clause 5 and Clause 6, and calculation methods in 5.8 and 6.5 56
C.1 General 56
C.2 Characteristics of DUTs 56
C.2.1 Spectral radiances of the DUTs 56
C.2.2 Directional characteristic of the DUT 57
C.2.3 Temporal modulation characteristics of the DUT 57
C.2.4 EOTF characteristics of the DUTs 57
C.2.5 Uniformity characteristics of the DUTs 58
C.3 Characteristics of the filter-type LMDs 59
C.3.1 Spectral responsivities of the filter-type LMDs 59
C.3.2 Specifications of filter-type LMDs 61
C.4 Influence of the number of pixels within the measurement field 63
C.5 Validity of the viewing direction dependence obtained by a simplified method 64
Annex D (informative) Instabilities of DUTs in measurement 66
D.1 General 66
D.2 DUT instabilities 66
Bibliography 68

Figure 1 – Block diagrams of three types of LMDs 12
Figure 2 – Example of configurations for the input optics and detector 12
Figure 3 – Example of input optics for the luminance meters 13
Figure 4 – Block diagram of a typical electronic system 13
Figure 5 – Examples of the repeatability of an LMD as a function of luminance 15
Figure 6 – Examples of the accuracy of an LMD as a function of luminance 16
Figure 7 – Calculated relative luminance difference as a function of wavelength error 19
Figure 8 – Calculated relative luminance difference as a function of spectral bandwidth 20
Figure 9 – Calculated chromaticity differences as a function of wavelength error 21
Figure 10 – Calculated chromaticity differences as a function of spectral bandwidth 22
Figure 11 – Calculated relative luminance difference as a function of f_1' 24
Figure 12 – Calculated chromaticity differences as a function of f_1', xyz 25
Figure 13 – Angular aperture and measurement field angle 27
Figure 14 – Calculated relative luminance difference and chromaticity difference as a function of the angular aperture 27
Figure 15 – Diagram of light rays in object space telecentric and non-telecentric optical design 28
Figure 16 – Calculated chromaticity difference as a function of the number of pixels 29
Figure 17 – Measured luminance variation as a function of the rotation angle of the polarizer 30
Figure 18 – Calculated relative luminance differences as a function of sampling period 32
Figure 19 – Total measurement times for 0,3 % repeatability (2σ) in three LMDs 36
Figure 20 – Calculated relative difference, ΔGA_{xy}, by spectroradiometers 37
Figure 21 – Calculated relative difference, ΔGA_{xy}, by colorimeters 38
Figure 22 – Cone of light rays for calculating the tristimulus values measured by an LMD with the angular aperture, α, and an optical axis at an inclination angle, θ_{LMD} 39

Figure 23 – Calculated luminance and chromaticity dependence as a function of the inclination angle for the 2°, 6°, and 10° angular apertures 40
Figure 24 – Measurement field and test pattern 41
Figure 25 – Calculated non-uniformity difference by the filter-type colorimeters 43
Figure 26 – Measurement setups for response time measurements 44
Figure 27 – Response curves measured at different sampling rates 44
Figure 28 – Measured response subjected to various low-pass filterings 45
Figure 29 – Measured response curves switched from the 10 % to 90 % level 46
Figure 30 – Schematic measured temporal luminance modulation of the LCD with a common voltage offset 47
Figure 31 – Conceptual pseudo-temporal luminance modulation 48
Figure 32 – Simulated luminance modulations with and without high frequency noise 48
Figure C.1 – Spectral radiances 56
Figure C.2 – Inclination angle dependence 57
Figure C.3 – Temporal modulation of the luminance 57
Figure C.4 – EOTF characteristics 58
Figure C.5 – Spectral responsivity of the colorimeter 61
Figure C.6 – Repeatability of three LMD models 62
Figure C.7 – Three positions of a circular measurement field relative to the RGB stripes 63
Figure C.8 – Configuration to measure DUT emission by the LMD at the inclination angle, θ_{LMD} 64
Figure C.9 – Inclination angle dependence calculated by two methods using an LMD with an angular aperture of 10° 65
Figure D.1 – Changes of luminance and chromaticity after switching the grey levels 66
Figure D.2 – Changes of luminance after switching from the black to grey level 67

Table 1 – DUT characteristics for the calculations 33
Table 2 – Calculated results of the contrast ratio by three LMDs 34
Table 3 – Calculated durations of the EOTF measurements 36
Table 4 – Chromaticity gamut area of three DUTs 37
Table 5 – Non-uniformity of DUTs 42
Table 6 – Rise times calculated from a measured response subjected to various low-pass filterings 45
Table 7 – Rise times measured by LMDs of various $V(\lambda)$ fidelities 46
Table C.1 – Measured luminance and chromaticity at the nine positions of DUT-1 58
Table C.2 – Measured luminance and chromaticity at the nine positions of DUT-2 59
Table C.3 – Specifications of filter-type LMDs 62
Table D.1 – Luminance and chromaticity transition 66
Table D.2 – Luminance changes in two measurements 67

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 62977-1-31 has been prepared by IEC technical committee 110: Electronic displays. It is a Technical Report.

The text of this Technical Report is based on the following documents:

DTR	Report on voting
110/1258/DTR	110/1281A/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62977 series, published under the general title *Electronic displays*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Measurements of the optical characteristics of electronic displays are primarily affected by three factors: measuring procedures, displays (devices under test: DUTs), and light measuring devices (LMDs), for which there are many international standards supporting consistent and comparable measurements. Most of them, however, provide only limited information on LMDs, making it difficult to appropriately select and use the LMD for the measurement objective. The purpose of this document is to provide best practices and suggestions which are missing in the standards.

This document addresses how the major properties of a typical LMD affect the measurement results. It is often impractical and unnecessary to consider the influences of all properties of LMDs and all characteristics of DUTs as well as their interactions and influences on the measurement results. Therefore, the multiple interaction effects that exist are beyond the scope of this document. Due to the rapid innovation and abundance of LMDs, covering all types of LMDs is also outside the objectives of this document.

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

1 Scope

This part of IEC 62977 provides practical information on light measuring devices (luminance meters, colorimeters, and spectroradiometers) with luminance measuring optics for the characterization of electronic displays.

2 Normative references

There are no normative references in this document.

3 Terms, definitions, and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at http://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

NOTE CIE Electronic international lighting vocabulary (e-ILV) is also available at http://cie.co.at/e-ilv.

3.1.1
repeatability
<of an LMD> closeness of agreement between indications or measured quantity values obtained by replicated measurements over a short period of time using a specific LMD under conditions specified by the LMD manufacturer

Note 1 to entry: Repeatability of an LMD is usually expressed numerically by statistical quantities, such as standard deviation, variance, or coefficient of variation (relative standard deviation) under the specified conditions of measurement.

Note 2 to entry: The influence on measurement repeatability caused by fluctuations of the measured light source and by the measurement procedure is assumed to be negligible when the manufacturer specifies the repeatability of an LMD. Manufacturers often specify the type of light source and measurement conditions used for determining the repeatability of an LMD.

Note 3 to entry: Measurement precision is the closeness of agreement between indications or measured quantity values obtained by replicate measurements on the same or similar objects under specified conditions. Measurement repeatability is measurement precision under a set of repeatability conditions of measurement that includes the same measurement procedures, same operators, same measuring system, same operating conditions, same location, and replicate measurements on the same or similar objects over a short period of time. Measurement reproducibility is measurement precision under a set of reproducibility conditions of measurement that includes different locations, operators, measuring systems, and replicate measurements on the same or similar objects [1], [2][1].

---

[1] Numbers in square brackets refer to the Bibliography.