## INTERNATIONAL STANDARD

## ISO 21806-11

First edition 2021-05

## Road vehicles — Media Oriented Systems Transport (MOST) —

Part 11:

# 150-Mbit/s coaxial physical layer conformance test plan

Véhicules routiers — Système de transport axé sur les médias — Partie 11: Plan d'essais de conformité de la couche coaxiale physique à 150 Mbit/s





© ISO 2021

mentation, no part of rical, including processed from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

<b>Contents</b>				
Fore	word		<b>v</b>	
Intro	oduction	n	vi	
1	Scop	e	1	
2	Norm	native references	1	
3	Term	ns and definitions	1	
4	Symbols and abbreviated terms			
	4.1	Symbols	2	
	4.2	Abbreviated terms	2	
5	Conv	rentions	3	
6		rating conditions and measurement tools, requested accuracy	4	
	6.1 6.2	Operating conditions		
7		trical characteristics		
,	7.1	Test according to LVDS		
	7.2	Test according to LVTTL		
8	Coaxial characteristics			
	8.1	High/low detection at SP2		
	8.2 8.3	Transition times at SP2 Steady state amplitude at SP2		
	8.4	Attenuation of coaxial interconnect		
	0.1	8.4.1 General		
		8.4.2 Coefficient values based on attenuation measurements	7	
		8.4.3 Fitting of corridor		
		8.4.4 Attenuation test set-up		
	8.5	8.4.5 Test procedure RL of connectors and couplers	8	
	8.6 Ch 8.7 RL 8.8 RL 8.9 Sti 8.9	Characteristic impedance of coaxial cable		
		RL of coaxial interconnect		
		RL of PCB interfaces		
		Stimulus creation for SP3		
		8.9.1 General		
		8.9.2 Pattern generator	16	
		8.9.3 Arbitrary signal generator	17	
		8.9.5 Cable or analogue representation	17	
		8.9.6 Noise generator		
		8.9.7 Creating a stimulus for SP3 for simplex applications	18	
		8.9.8 Creating a stimulus for SP3 for duplex applications	20	
9	Meas	surement of phase variation	23	
	9.1	General	23	
	9.2	Measuring alignment jitter	25	
	9.3	Measuring transferred jitter		
10		set-ups		
	10.1 10.2	General Craphical symbols and descriptions		
		Graphical symbols and descriptions		
		10.2.2 SP3 stimulus		
		10.2.3 Standalone simplex ECport under test	31	
		10.2.4 Integrated simplex ECport under test		
		10.2.5 Standalone simplex CEport under test	32	

### ISO 21806-11:2021(E)

		10.2.6 Integrated simplex CEport under test		
		10.2.7 Duplex ECport under test		
	10.2	10.2.8 Duplex CEport under test		
	10.5	10.3.1 General		
		10.3.2 SP2 signal quality measurement for simplex		
		10.3.3 SP4 jitter measurement (AJ and TJ) for simplex		
	10.4	Set-ups for duplex		
		10.4.1 General		
		10.4.2 Directional couplers		
		10.4.3 SP2 signal quality measurement for duplex		
		10.4.4 SP4 jitter measurement (AJ and TJ) for duplex	42	
11	Power-on and power-off			
	11.1	General		
	11.2	Measuring ECC parameters	45	
		11.2.1 Measuring ECC parameters – Test set-up	45	
		11.2.2 Measuring ECC parameters – Signal charts		
		11.2.3 Measuring ECC parameters – Test sequences	47	
	11.3	Measuring CEC parameters		
		11.3.1 Measuring CEC parameters – Test set-up		
		11.3.2 Measuring CEC parameters – Signal charts	53	
		11.3.3 Measuring CEC parameters – Test sequences		
<b>12</b>	Detec	cting bit rate (frequency reference)	57	
13	Syste	m performance	57	
	13.1	General	57	
	13.2			
	13.3	TimingMaster delay tolerance	58	
14	Conformance tests of 150-Mbit/s coaxial physical layer			
• •	14.1		61	
	14.2	Control signals	64	
	14.3	Control signals Limited access to specification points	65	
	14.4	Parameter overview	66	
15	Limit	ted physical layer conformance	66	
13	15.1		66	
	15.2			
	15.3	Generating test signals for the IUT input section SP3		
	15.4	Analysis of test results	69	
	15.5	Test flow overview	69	
	15.6	Measurement of SP3 input signal of the IUT	70	
	15.7	Measurement of SP2 output signal of the IUT	71	
	15.8	Measurement of RL		
	15.9	Functional test of wake-up and shutdown		
16	Direc	t physical measuring accuracy	72	
17		surement of Port1 delay drift		
		formative) Limited physical layer conformance for development tools		
		rmative) SP3 stress conditions		
		rmative) Compensation set-up for MOST150 cPHY duplex		
		formative) <b>Test procedure for 2-port nodes</b>		
		y		

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 21806 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

#### Introduction

The Media Oriented Systems Transport (MOST) communication technology was initially developed at the end of the 1990s in order to support complex audio applications in cars. The MOST Cooperation was founded in 1998 with the goal to develop and enable the technology for the automotive industry. Today, MOST<sup>1)</sup> enables the transport of high Quality of Service (QoS) audio and video together with packet data and real-time control to support modern automotive multimedia and similar applications. MOST is a function-oriented communication technology to network a variety of multimedia devices comprising one or more MOST nodes.

Figure 1 shows a MOST network example.




Figure 1 — MOST network example

The MOST communication technology provides:

- synchronous and isochronous streaming,
- small overhead for administrative communication control,
- a functional and hierarchical system model,
- API standardization through a function block (FBlock) framework,
- free partitioning of functionality to real devices,
- service discovery and notification, and
- flexibly scalable automotive-ready Ethernet communication according to ISO/IEC/IEEE 8802-3[2].

MOST is a synchronous time-division-multiplexing (TDM) network that transports different data types on separate channels at low latency. MOST supports different bit rates and physical layers. The network clock is provided with a continuous data signal.

<sup>1)</sup> MOST® is the registered trademark of Microchip Technology Inc. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO.

Within the synchronous base data signal, the content of multiple streaming connections and control data is transported. For streaming data connections, bandwidth is reserved to avoid interruptions, collisions, or delays in the transport of the data stream.

MOST specifies mechanisms for sending an isochronous, packet-based data in addition to control data and streaming data. The transmission of packet-based data is separated from the transmission of control data and streaming data. None of them interfere with each other.

A MOST network consists of devices that are connected to one common control channel and packet channel.

In summary, MOST is a network that has mechanisms to transport the various signals and data streams that occur in multimedia and infotainment systems.

The ISO Standards Maintenance Portal (<a href="https://standards.iso.org/iso/">https://standards.iso.org/iso/</a>) provides references to MOST specifications implemented in today's road vehicles because easy access via hyperlinks to these specifications is necessary. It references documents that are normative or informative for the MOST versions 4V0, 3V1, 3V0, and 2V5.

The ISO 21806 series has been established in order to specify requirements and recommendations for implementing the MOST communication technology into multimedia devices and to provide conformance test plans for implementing related test tools and test procedures.

To achieve this, the ISO 21806 series is based on the open systems interconnection (OSI) basic reference model in accordance with ISO/IEC 7498-1 and ISO/IEC 10731, which structures communication yer. systems into seven layers as shown in Figure 2. Stream transmission applications use a direct stream data interface (transparent) to the data link layer.




Figure 2 — The ISO 21806 series reference according to the OSI model

The International Organization for Standardization (ISO) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO. Information may be obtained from the patent database available at <a href="https://www.iso.org/patents">www.iso.org/patents</a>.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. ISO shall not be held responsible for identifying any or all such patent rights.

## Road vehicles — Media Oriented Systems Transport (MOST) —

#### Part 11:

### 150-Mbit/s coaxial physical layer conformance test plan

#### 1 Scope

This document specifies the conformance test plan for the 150-Mbit/s coaxial physical layer for MOST (MOST150 cPHY), a synchronous time-division-multiplexing network.

This document specifies the basic conformance test measurement methods, relevant for verifying compatibility of networks, nodes, and MOST components with the requirements specified in ISO 21806-10.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 21806-1, Road vehicles — Media Oriented Systems Transport (MOST) — Part 1: General information and definitions

ISO 21806-10, Road vehicles — Media Oriented Systems Transport (MOST) — Part 10: 150-Mbit/s coaxial physical layer

ISO 20860-2, Road vehicles — 50 ohms impedance radio frequency connection system interface — Part 2: Test procedures

EN 50289-1-8, Communication cables — Specifications for test methods — Part 1-8: Electrical test methods — Attenuation

EN 50289-1-11, Communication cables — Specifications for test methods — Part 1-11: Electrical test methods — Characteristic impedance, input impedance, return loss

No JEDEC JESD8C.01,<sup>2)</sup> interface Standard for Nominal 3 V/3.3 V Supply Digital Integrated Circuits

TIA/EIA-644-A-2001,<sup>3)</sup>Electrical Characteristics of Low-Voltage Differential Signaling (LVDS) interface Circuits

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 21806-1, ISO 21806-10 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>

<sup>2)</sup> Available at <a href="https://www.jedec.org/">https://www.jedec.org/</a>.

<sup>3)</sup> Available at <a href="https://www.tiaonline.org/standards/">https://www.tiaonline.org/standards/</a>.