
**Road vehicles — Media Oriented
Systems Transport (MOST) —**

**Part 10:
150-Mbit/s coaxial physical layer**

*Véhicules routiers — Système de transport axé sur les médias —
Partie 10: Couche coaxiale physique à 150-Mbit/s*



This document is a preview generated by EKO



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
4.1 Symbols	2
4.2 Abbreviated terms	2
5 Conventions	3
6 Physical layer service interface to OSI data link layer	3
6.1 Overview	3
6.2 Data type definitions	3
6.3 Event indications and action requests	3
6.3.1 P_EVENT.INDICATE	3
6.3.2 P_ACTION.REQUEST	4
6.4 Parameters	4
6.4.1 PHY_Event	4
6.4.2 PHY_Request	4
7 Basic physical layer requirements	5
7.1 Logic terminology	5
7.1.1 Single-ended low-voltage digital signals	5
7.1.2 Differential LVDS signals	5
7.2 Specification points (SPs)	5
7.3 Phase variation	6
7.3.1 General	6
7.3.2 Wander	6
7.3.3 Jitter	6
7.3.4 Clock recovery and reference clock	7
7.3.5 Link quality	8
7.3.6 MOST network quality	10
8 MOST150 cPHY requirements	13
8.1 General MOST network parameters	13
8.1.1 MOST network coding	13
8.1.2 Link and interconnect type	14
8.1.3 SP details	15
8.1.4 Analogue frontend	16
8.1.5 Integration of coaxial transceiver	17
8.2 Models and measurement methods	19
8.2.1 Golden PLL	19
8.2.2 Jitter filter	20
8.2.3 Retimed bypass mode and stress pattern	21
9 Link specifications	21
9.1 General	21
9.2 SP1	21
9.3 SP2	22
9.4 Coaxial link requirements	23
9.4.1 Coaxial interconnect, length and attenuation	23
9.4.2 Characteristic impedance and return loss (L_{RL})	26
9.5 SP3	30
9.6 SP4	30

10	Power-on and power-off	31
10.1	Frequency reference and power supply	31
10.2	Power supply monitoring circuitry	32
10.3	Coaxial transceiver ECC and CEC	32
10.3.1	General	32
10.3.2	CTR requirements	32
10.3.3	ECC requirements	32
10.3.4	ECC power-on and power-off sequence	35
10.3.5	CEC requirements	35
10.3.6	CEC power-on and power-off sequence	37
11	MOST network requirements	38
11.1	SP4 receiver tolerance	38
11.2	TimingMaster delay tolerance	39
11.3	Environmental requirements and considerations	39
12	Electrical interfaces	39
12.1	LVDS	39
12.2	Bit rate and frequency tolerance	40
13	MOST150 cPHY topologies	40
13.1	Daisy chain topologies	40
13.2	Daisy chain structure	42
13.3	2-port nodes	42
13.4	Port1 delay drift	43
14	Device connectors	46
15	SPs for cable extensions	46
16	Coaxial interconnect attenuation	47
	Bibliography	49

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 21806 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The Media Oriented Systems Transport (MOST) communication technology was initially developed at the end of the 1990s in order to support complex audio applications in cars. The MOST Cooperation was founded in 1998 with the goal to develop and enable the technology for the automotive industry. Today, MOST¹⁾ enables the transport of high quality of service (QoS) audio and video together with packet data and real-time control to support modern automotive multimedia and similar applications. MOST is a function-oriented communication technology to network a variety of multimedia devices comprising one or more MOST nodes.

Figure 1 shows a MOST network example.




Figure 1 — MOST network example

The MOST communication technology provides:

- synchronous and isochronous streaming,
- small overhead for administrative communication control,
- a functional and hierarchical system model,
- API standardization through a function block (FBlock) framework,
- free partitioning of functionality to real devices,
- service discovery and notification, and
- flexibly scalable automotive-ready Ethernet communication according to ISO/IEC/IEEE 8802-3^[2].

MOST is a synchronous time-division-multiplexing (TDM) network that transports different data types on separate channels at low latency. MOST supports different bit rates and physical layers. The network clock is provided with a continuous data signal.

1) MOST® is the registered trademark of Microchip Technology Inc. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO.

Within the synchronous base data signal, the content of multiple streaming connections and control data is transported. For streaming data connections, bandwidth is reserved to avoid interruptions, collisions, or delays in the transport of the data stream.

MOST specifies mechanisms for sending anisochronous, packet-based data in addition to control data and streaming data. The transmission of packet-based data is separated from the transmission of control data and streaming data. None of them interfere with each other.

A MOST network consists of devices that are connected to one common control channel and packet channel.

In summary, MOST is a network that has mechanisms to transport the various signals and data streams that occur in multimedia and infotainment systems.

The ISO Standards Maintenance Portal (<https://standards.iso.org/iso/>) provides references to MOST specifications implemented in today's road vehicles because easy access via hyperlinks to these specifications is necessary. It references documents that are normative or informative for the MOST versions 4V0, 3V1, 3V0, and 2V5.

The ISO 21806 series has been established in order to specify requirements and recommendations for implementing the MOST communication technology into multimedia devices and to provide conformance test plans for implementing related test tools and test procedures.

To achieve this, the ISO 21806 series is based on the open systems interconnection (OSI) basic reference model in accordance with ISO/IEC 7498-1^[1] and ISO/IEC 10731^[3] which structures communication systems into seven layers as shown in [Figure 2](#). Stream transmission applications use a direct stream data interface (transparent) to the data link layer.




Figure 2 — The ISO 21806 series reference according to the OSI model

The International Organization for Standardization (ISO) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO. Information may be obtained from the patent database available at www.iso.org/patents.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. ISO shall not be held responsible for identifying any or all such patent rights.

Road vehicles — Media Oriented Systems Transport (MOST) —

Part 10: 150-Mbit/s coaxial physical layer

1 Scope

This document specifies the 150-Mbit/s coaxial physical layer for MOST (MOST150 cPHY), a synchronous time-division-multiplexing network.

This document specifies the applicable constraints and defines interfaces and parameters, suitable for the development of products based on MOST150 cPHY. Such products include coaxial links, coaxial receivers, coaxial transmitters, electrical to coaxial converters, and coaxial to electrical converters.

This document also establishes basic measurement techniques and actual parameter values for MOST150 cPHY.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 21806-1, *Road vehicles — Media Oriented Systems Transport (MOST) — Part 1: General information and definitions*

No JEDEC JESD8C.01,²⁾ *Interface Standard for Nominal 3 V/3,3 V Supply Digital Integrated Circuits*

TIA/EIA-644-A-2001,³⁾ *Electrical Characteristics of Low Voltage Differential Signaling (LVDS) Interface Circuits*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 21806-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 ECC

electrical to coaxial converter

MOST component that converts an electrical signal into a coaxial signal

2) Available at <http://www.jedec.org/>.

3) Available at <https://www.ti.com/lit/wh/wh689>.