
**Information technology — Radio
frequency identification for item
management —**

**Part 1:
Interference rejection performance
test method between a tag as
defined in ISO/IEC 18000-63 and a
heterogeneous wireless system**

This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier; Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	1
5 Conditions applicable to the test methods	2
5.1 Test environment	2
5.2 Radio frequency (FR) environment	2
5.3 Pre-conditioning	2
5.4 Default tolerance	2
5.5 Total measurement uncertainty	3
5.6 Test result reporting	3
5.7 Test mounting material	3
5.8 Test communication parameters	3
6 Test set-up	3
6.1 DUT placement	3
6.2 Test setup for tag's R_X sensitivity power measurement under non-interference environment	3
6.2.1 Test apparatus and test circuits	3
6.2.2 Setup of the devices	4
6.2.3 Antenna polarization and requirements	4
6.3 Test setup for tag's R_X sensitivity power measurement under interference environment	5
6.3.1 Sub-1GHz wireless communications technologies	5
6.3.2 Setup of the devices	5
6.3.3 Antenna polarization and requirements	6
7 Test procedure	7
7.1 General description	7
7.2 Tag's R_X sensitivity power measurement under non-interference environment	7
7.2.1 Purpose	7
7.2.2 Test procedure	7
7.3 Tag's R_X sensitivity power measurement under interference environment	8
7.3.1 Purpose	8
7.3.2 Test procedure	8
7.4 Test report	9
Bibliography	13

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives) or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

A list of all parts in the ISO/IEC 23200 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

This document provides test procedures and method to evaluate the impact on tag as defined in ISO/IEC 18000-63 of interference generated by other wireless systems. The interference rejection test method of this document is different to ISO/IEC 18046-3:2012, 8.8. This document covers interference effect between the tags and heterogeneous wireless system, while ISO/IEC 18046-3 covers interference effect between tags and homogeneous wireless systems.

Ultra-high-frequency (UHF) radio frequency identification (RFID) is a wireless technology that connects billions of everyday items to the Internet of Things (IoT), enabling consumers and businesses to identify, locate, authenticate, and engage each item. IoT applications require a data connection between the physical and digital world, and UHF RFID is the ideal technology to bridge these realms with the ability to bring low cost, unique identification to everyday items. Low-power wide-area networks (LPWAN) operate at long read ranges of 2 km to 3 km. While LoRaWan devices have a very slow data-transfer rate, they are useful for transmitting sensor data. For example, LoRaWAN, WiFi-Halow (802.11ah), Sigfox, NB-IoT, WB-IoT, and LTE-M are representative technologies.

The frequencies used by LoRaWAN systems differ by region and country, as do the frequency bands designated for UHF RFID systems. In particular, LoRaWAN and RFID systems use different power levels and heterogeneous protocols in shared frequency bands. They are susceptible to interference generated by other wireless systems. This harsh signal propagation environment combined with interference from coexisting wireless technologies can lead to a degradation of the performance or even application failures. To evaluate possible interference on UHF RFID systems, industrial stakeholders make a constructive discussion on how to overcome interference problems.

Information technology — Radio frequency identification for item management —

Part 1:

Interference rejection performance test method between a tag as defined in ISO/IEC 18000-63 and a heterogeneous wireless system

1 Scope

This document defines a test method to evaluate the interference rejection performance of tags covered by ISO/IEC 18000-63 and a heterogeneous wireless system using different access technologies, e.g. radio frequency identification and cell phone network.

It specifies the general requirements and test requirements.

The test method in this document makes it possible to compare the relative interference rejection performance among tags under a single wireless interference environment. In addition, this document can be used in a benchmarking test according to requirements in a given application or service.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 19762, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions provided in ISO/IEC 19762 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Symbols and abbreviated terms

ANT _{TX}	T _X interrogator antenna in the bistatic test set-up
ANT _{RX}	R _X interrogator antenna in the bistatic test set-up
ANT _{TRX}	interrogator antenna in the monostatic test set-up
ANT _{INT}	antenna connected to the radio frequency interference source
CW	continuous wave