

TECHNICAL SPECIFICATION

**Direct current (DC) appliance couplers for information and communication technology (ICT) equipment installed in data centres and telecom central offices –
Part 2: 5,2 kW system**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Preview generated by EVS

TECHNICAL SPECIFICATION

Direct current (DC) appliance couplers for information and communication technology (ICT) equipment installed in data centres and telecom central offices –
Part 2: 5,2 kW system

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.120.01, 29.120.30

ISBN 978-2-8322-9928-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	7
3 Terms and definitions	7
4 General requirements	7
5 General notes on tests	7
6 Standard ratings	7
7 Classification of appliance coupler.....	7
8 Marking	8
9 Dimensions and compatibility	8
10 Protection against electric shock	8
11 Provision for earthing	8
12 Terminals and terminations.....	8
13 Construction	8
14 Insulation resistance and electric strength	9
15 Forces necessary to insert and to withdraw the connector	9
15.1 General.....	9
16 Operation of contact	9
17 Resistance to heating of appliance coupler.....	9
18 Breaking capacity	10
19 Normal operation	10
20 Temperature rise	10
21 Cords and their connection	11
21.1 Cords for non-rewirable connectors	11
21.2 Cable anchorage.....	11
22 Mechanical strength	12
23 Resistance to heat and ageing.....	12
24 Screws, current-carrying parts and connections.....	12
24.1 General.....	12
25 Creepage distances, clearances and distances through sealing compound.....	12
26 Resistance of insulating material to heat, fire and tracking	12
27 Resistance to rusting	13
28 Electromagnetic compatibility (EMC) requirements	13
101 0 (zero) current operated appliance inlet systems.....	13
Annex A (xxx) Safety-related routine tests for factory-wired accessories (protection against electric shock and correct polarity)	14
Annex B (xxx) Test schedule.....	15
Annex C (xxx) Alternative gripping tests.....	16
Annex D (xxx) Standard sheets and gauges.....	17
D.1 Standard sheets.....	17
D.2 Gauges.....	22
D.2.1 Distance to the point of first contact.....	22

D.2.2	"GO" gauges for appliance inlets according to standard sheet 1 (Figure D.1)	23
D.2.3	"GO" gauge for connectors according to standard sheet 2 (Figure D.2).....	25
D.2.4	Gauge for checking the maximum withdrawal force (see 15.2)	26
D.2.5	Gauges for checking the minimum withdrawal force (see 15.3)	26
D.2.6	Position of switch cam of optional micro switches	27
Bibliography		28
Figure D.1 – Appliance inlet		19
Figure D.2 – Connector		21
Figure D.3 – Positioning of the "+" and "-" pins/connector-contacts		22
Figure D.4 – Gauges for checking point of first contact		23
Figure D.5 – "GO" gauges for appliance inlets according to standard sheet 1 (Figure D.1)		24
Figure D.6 – "GO" gauges for connector according to standard sheet 2 (Figure D.2).....		25
Figure D.7 – Gauge representing the counterpart inlet designed to accept DC only for checking the maximum withdrawal force, for breaking capacity test and for normal operation test.....		26
Figure D.8 – Gauge for checking the minimum withdrawal force for "+" and "-" connector-contact		26
Figure D.9 – Gauge for checking the minimum withdrawal force for "+", "-" and "PE" socket-contact		27
Table 1 – Relationship between rated power and connectable nominal cross-sectional areas or American Wire Gauges (AWG) size of copper conductors		8
Table 2 – Maximum diameters of the cords		9
Table 3 – Maximum and minimum withdrawal forces		9
Table 4 – Cords and conductors for the tests of Clause 21		11
Table 5 – Type and nominal cross-sectional area of cords		11
Table 6 – Types of cable for the rewirable connector test.....		11
Table 7 – Value for the lateral pulls applied		12
Table 8 – Values for straight and lateral pull forces.....		12
Table D.1 – Dimension of contact gauge		23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIRECT CURRENT (DC) APPLIANCE COUPLERS FOR INFORMATION AND COMMUNICATION TECHNOLOGY (ICT) EQUIPMENT INSTALLED IN DATA CENTRES AND TELECOM CENTRAL OFFICES –

Part 2: 5,2 kW system

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 63236-2 has been prepared by IEC technical committee 23: Electrical accessories. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

DTS	Report on voting
23/916/DTS	23/958A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

This Part 2 is to be used in conjunction with IEC TS 63236-1:2021.

The clauses of this document supplement or modify the corresponding clauses in IEC 63236-1. When a particular subclause or annex of Part 1 is not mentioned in this Part 2, the subclause or annex of IEC 63236-1 applies as far as is reasonable. Where this document states “addition”, “amendment” or “replacement”, the relevant requirement, test specification or explanatory matter in IEC 63236-1 is to be adapted accordingly.

Clauses or subclauses which are additional to those in Part 1 are numbered starting from 101.

A list of all parts in the IEC 63236 series, published under the general title *Direct current (DC) appliance couplers for information and communication technology (ICT) equipment installed in data centres and telecom central offices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

DIRECT CURRENT (DC) APPLIANCE COUPLERS FOR INFORMATION AND COMMUNICATION TECHNOLOGY (ICT) EQUIPMENT INSTALLED IN DATA CENTRES AND TELECOM CENTRAL OFFICES –

Part 2: 5,2 kW system

1 Scope

This part of IEC 63236, which is a Technical Specification, applies to DC appliance couplers for class I equipment with two active contacts plus an earthing contact, a rated power of 5,2 kW and a rated voltage range from 294 V to 400 V DC. They are intended to power DC information and communication technology equipment only, as specified in IEC 62368-1.

The accessories according to this document are intended to be used by ordinary persons in data centres only where the value of the DC voltage distribution system is defined as follows:

- 380 V with a tolerance of ± 20 V for installations with no backup battery or with a voltage regulation system;
- 380 V with a voltage range of 294 V to 400 V for installations with a backup battery where voltage regulation is not guaranteed;
- the voltage value between each live conductor and earth does not exceed 200 V DC during normal operation;
- there are two abnormal voltage ranges (duration below 10 min):
 - 260 V up to 294 V, and
 - above 400 V to 410 V.

The maximum current of the appliance couplers is

- 13 A when the voltage between live contacts is 400 V DC,
- 17,6 A when the voltage between live contacts is 294 V DC,

and can rise up to 20 A when the voltage between live contacts decreases to 260 V DC for 10 min maximum.

The voltage between live conductors can fall down to 260 V DC when the voltage discharge value of the battery reaches the disconnecting level. The consequence is that the current increases accordingly.

The accessories according to this document do not require maintenance.

The accessories according to this document are intended for use in circuits where

- basic protection,
- an overcurrent protection (of 17,6 A or less for each socket-outlet or multiple socket-outlet),
- the fault protection (indirect contact protection), and
- additional protection

are already assured.

Appliance couplers complying with this document are suitable for normal use at ambient air temperatures not normally exceeding +60 °C, with a lower limit of the ambient air temperature of -5 °C.

Appliance couplers are not suitable for use in place of plug and socket-outlet systems according to the IEC TS 62735 series

The 2,6 kW system complying with IEC TS 63236-1 is not compatible with the system complying with IEC TS 63236-2 as it is impossible to mate the 2,6 kW connector in the 5,2 kW appliance inlet and it is also impossible to mate the 5,2 kW connector into the 2,6 kW appliance inlet.

2 Normative references

This clause of IEC TS 63236-1:2021 applies.

3 Terms and definitions

This clause of IEC TS 63236-1:2021 applies except as follows:

Addition:

Add the following new definition:

3.101

0 (zero) current operated appliance coupler system

system, either electrical or electronic or mechanical or a combination of these, that prevents current flow while making and breaking

4 General requirements

This clause of IEC TS 63236-1:2021 applies.

5 General notes on tests

This clause of IEC TS 63236-1:2021 applies.

6 Standard ratings

This clause of IEC TS 63236-1:2021 is replaced as follows:

Replacement:

Accessories shall have a rated power of 5,2 kW at any voltage within the rated voltage range of 294 V to 400 V.

7 Classification of appliance coupler

This clause of IEC TS 63236-1:2021 applies.