INTERNATIONAL STANDARD

ISO 24281

First edition 2021-07

Textiles — Biaxial tensile properties of woven fabric — Determination of maximum force and elongation at maximum force using the grab method

Textile- Propriétés biaxiales des tissus- Détermination de la force maximale et de l'élongation par la méthode d'arrachement





© ISO 2021

Tentation, no part of vical, including pluested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

COI	itents	Page
Fore	word	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	3
5	Sampling	3
6	Apparatus — Biaxial test machine	4
7	Atmosphere for conditioning and testing	4
8	Preparation of test specimens 8.1 General 8.2 Dimensions 8.3 Preparation of test specimens	4 5
9	Procedure 9.1 Gauge length 9.2 Rate of extension 9.3 Mounting of test specimens 9.4 Operation	5 5 5
10	Calculation and expression of results	
11	Test report	6
Bibli	iography	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT),see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 38, *Textiles*, Subcommittee SC 24, *Conditioning atmospheres and physical tests for textile fabrics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Textiles — Biaxial tensile properties of woven fabric — Determination of maximum force and elongation at maximum force using the grab method

1 Scope

This document specifies a procedure to determine the maximum force and elongation at maximum force of textiles woven fabrics using a grab method in the biaxial testing machine.

The method is mainly applicable to woven textile fabrics, including fabrics which exhibit stretch characteristics imparted by the presence of an elastomeric fibre, mechanical, or chemical treatment. It can be applicable to fabrics produced by other techniques. It is not applicable to geotextiles^[4], nonwovens^[3], coated fabrics^[5], textile-glass woven fabrics^[2], and fabrics made from carbon fibres or polyolefin tape yarns.

The method is restricted to the use of constant rate of extension (CRE) testing machines to the same axis.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 139, Textiles — Standard atmospheres for conditioning and testing

ISO 7500-1, Metallic materials — Calibration and verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Calibration and verification of the force-measuring system

 ${\tt ISO\,10012}$, Measurement management systems — Requirements for measurement processes and measuring equipment

ISO 13934-1, Textiles — Tensile properties of fabrics — Part 1: Determination of maximum force and elongation at maximum force using the strip method

ISO 13934-2, Textiles — Tensile properties of fabrics — Part 2: Determination of maximum force using the grab method

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13934-1, ISO 13934-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1

biaxial

related to measurement or application along two axes simultaneously