
**Acoustics — Experimental method
for transposition of dynamic forces
generated by an active component
from a test bench to a receiving
structure**

*Acoustique — Méthode expérimentale de transposition des forces
dynamiques générées par un composant actif d'un banc d'essai vers
une structure réceptrice*



This document is a preview generated by EKO



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle of the method of transposition of the dynamic force	5
4.1 General matters	5
4.2 General formulae	6
4.3 Geometrical considerations	6
5 Operating mode	7
5.1 General	7
5.2 Synopsis of procedure	7
5.3 Tasks and preliminary operations	7
5.4 Transfer matrices determination	9
5.4.1 General	9
5.4.2 Final receiving structure transfer matrix determination Y_{RS}	9
5.4.3 Test bench transfer matrix determination, Y_{TB}	9
5.4.4 Connecting device spring-like matrix properties determination, S_I	9
5.4.5 Active Component transfer matrix determination, Y_{AC}	9
5.5 Measured dynamic forces transmitted to the test bench	10
5.6 Predicted dynamic forces transmitted to the final structure	10
5.6.1 General	10
5.6.2 Strong decoupling	10
5.6.3 Very similar bench and receiving structure	11
5.6.4 Case of a rigid receiving structure	11
5.6.5 Case of a non-rigid receiving structure	12
6 Requirements for data in test report	14
6.1 Specification of the integrator to the supplier	14
6.2 Data sent by the supplier to the integrator	14
Annex A (informative) Theoretical developments	16
Annex B (informative) Frequency response functions measurement	19
Annex C (informative) Dynamic forces measurement	22
Annex D (informative) Data processing	28
Annex E (informative) Study of a wiper system	31
Annex F (informative) Equivalent force torsor and block-sensor method	47
Bibliography	58

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The vibroacoustic behaviour of products has become a major challenge not only in terms of user health protection through regulations, but also in terms of sound quality for safety, quality perception, and attractiveness.

At the same time, requirements on products development cycles are more and more stringent, reaching the point where component suppliers and integrators should work independently, without physical prototypes.

To master the transmission of dynamic forces (also called structure-borne noise), one needs to adapt the components to the receiving structure, and hence exchange information prior to manufacturing prototypes. This information will only be valuable for the integrator if it is clearly defined and intrinsic to the component.

This document, issued from a French experimental standard, addresses this issue. It is a user guidance to characterize an active source on a test bench and predict the effects of its integration on a passive structure. The component is characterized on its own, which makes the document complementary to the ISO 20270 that describes the measurement of “in-situ” characteristics (blocked forces), where the component is connected to its receiving structure.

The intrinsic characterization of an active source requires measuring two quantities (expressed as a function of the frequency): the first one characterizing the dynamic aspect, blocked forces, and the second one describing “static” behaviour, such as the impedance or the mobility.

The objective of this document is to help the user predict the component behaviour in a particular assembly. The theoretical background is laid in [Annex A](#). The user is then guided (see [5.2](#)) all along the experimental procedure enabling to reach this objective:

- Static characterization of the component, the test bench and the receiving structure.
- Force measurement: the standard proposes here direct and indirect methods. Indirect methods are generally easier to implement, but they need a particular focus on the measurement quality and matrix inversion.
- Interface integration (connecting device).
- Prediction of the behaviour of the component/receiving structure assembly.

This whole procedure is based on a general formula expressing the dynamic forces in the assembly as a function of blocked forces and static characteristics. Depending on these static characteristics, simplifications are proposed (see [5.6](#)).

[Annex B](#) and [C](#) guide the user to measure both transfer functions and dynamic forces. It should be noted that, in general, these quantities are expressed in the 3 directions and 3 rotations, but the procedure can be applied on a number of degrees of freedom chosen by the user.

The [Annex D](#) informs about data processing. The [Annex E](#) contains a test example and the [Annex F](#) describes the method using a particular test bench (block sensor).

The data obtained and assessed in this document can be used:

- as part of a specification between suppliers and integrators;
- as input data of numerical vibroacoustic simulation models;
- to drive the modification of the physical structure or the interface in order to improve the vibroacoustic behaviour.

Acoustics — Experimental method for transposition of dynamic forces generated by an active component from a test bench to a receiving structure

1 Scope

This document specifies a method to predict the dynamic forces generated by an active component on a receiving structure from measurement on a test bench.

It sets out the requirements applicable to test benches and setup measurement conditions of dynamic forces: a criterion of validity of transfer functions measurements can be established for example.

The objective is to evaluate noise and vibrations generated by active components mounted on receiving structures, including the possibility to optimise vibration isolators.

It can be applied to different systems connected to a building, such as a compressor or a power generator, or to systems connected to a vehicle body, such as an engine powertrain or an electrical actuator, for example.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

active component

active substructure which generates dynamic forces

Note 1 to entry: See [Figure 1](#).

3.2

connecting device

mechanical interface with a specific “spring like” matrix structure which allows connecting the *active component* ([3.1](#)) to the receiving structure

Note 1 to entry: See [Figure 1](#), Key 2.

Note 2 to entry: Insulators at fixation points are typical “spring like” connecting devices.

Note 3 to entry: A “spring like” connecting device is a structure with no internal degrees of freedom and internal mass, see [3.10](#).

Note 4 to entry: In the case of a connecting point, active component and receiving structure share the same location.