
**Telecommunications and exchange
between information technology
systems — Requirements for local and
metropolitan area networks —**

**Part 1AX:
Link aggregation**

*Télécommunications et échange entre systèmes informatiques —
Exigences pour les réseaux locaux et métropolitains —*

Partie 1AX: Agrégation de lien



This document is a preview generated by ELS



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-1AX was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802.1AX-2020) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

This second edition cancels and replaces the first edition (ISO/IEC/IEEE 8802-1AX:2016), which has been technically revised. It also incorporates the Technical Corrigendum ISO/IEC/IEEE 8802-1AX:2016/Cor 1:2018.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

IEEE Std 802.1AX™-2020
(Revision of IEEE Std 802.1AX-2014)

IEEE Standard for Local and Metropolitan Area Networks— Link Aggregation

Developed by the
**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 30 January 2020
IEEE SA Standards Board

Abstract: Link Aggregation allows parallel point-to-point links to be used as if they were a single link and also supports the use of multiple links as a resilient load-sharing interconnect between multiple nodes in two separately administered networks. This standard defines a MAC-independent Link Aggregation capability and provides general information relevant to specific MAC types.

Keywords: Aggregated Link, Aggregator, Distributed Resilient Network Interconnect, DRNI, interconnect, Link Aggregation, Link Aggregation Group, local area network, management, Network-Network Interface, NNI

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 29 May 2020. Printed in the United States of America.

IEEE and IEEE 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF:	ISBN 978-1-5044-6428-4	STD24045
Print:	ISBN 978-1-5044-6429-1	STDPD24045

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <https://www.ieee.org/about/corporate/governance/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <https://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit IEEE Xplore at <https://ieeexplore.ieee.org/> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <https://standards.ieee.org>.

Errata

Errata, if any, for IEEE standards can be accessed via <https://standards.ieee.org/standard/index.html>. Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore: <https://ieeexplore.ieee.org/browse/standards/collection/ieee/>. Users are encouraged to periodically check for errata.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this revision was submitted to the IEEE SA for approval, the IEEE P802.1 Working Group had the following membership:

Glenn Parsons, *Chair*
John Messenger, *Vice Chair*
János Farkas, *Chair, Time-Sensitive Networking Task Group*
Stephen Haddock and Jessy Rouyer, *Co-Editors*

Astrit Ademaj	Yoshihiro Ito	Maximilian Riegel
Ralf Assmann	Michael Karl	Atsushi Sato
Jens Bierschenk	Stephan Kehrer	Frank Schewe
Christian Boiger	Randy Kelsey	Michael Seaman
Paul Bottorff	Hajime Koto	Maik Seewald
Radhakrishna Canchi	James Lawlis	Johannes Specht
Feng Chen	Christophe Mangin	Marius Stanica
Weiyang Cheng	Scott Mansfield	Gunter Steindl
Paul Congdon	Kenichi Maruhashi	Karim Traore
Rodney Cummings	David McCall	Hao Wang
Josef Dorr	Larry McMillan	Tongtong Wang
Hesham Elbakoury	Tero Mustala	Xinyuan Wang
Thomas Enzinger	Roy Myers	Karl Weber
Donald Fedyk	Hiroki Nakano	Brian Weis
Norman Finn	Bob Noseworthy	Ludwig Winkel
Geoffrey Garner	Tomoki Ohsawa	Jordon Woods
Craig Gunther	Hiroshi Ohue	Takahiro Yamaura
Marina Gutierrez	Donald R. Pannell	Nader Zein
Mark Hantel	Michael Potts	William Zhao
Marc Holness	Dieter Proell	Helge Zinner
Satoko Itaya	Wei Qiu	Harald Zweck
	Karen Randall	

The following members of the balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Raj Jain	Bansi Patel
Richard Alfvén	Sangkwon Jeong	Brian Petry
Butch Anton	Pranav Jha	David Piehler
Stefan Aust	Lokesh Kabra	Walter Pienciak
Harry Bims	Srinivas Kandala	Rick Pimpinella
Kenneth Bow	Piotr Karocki	Clinton Powell
Rich Boyer	Stuart Kerry	R. K. Rannow
Nancy Bravin	Evgeny Khorov	Maximilian Riegel
Vern Brethour	Yongbum Kim	Robert Robinson
Demetrio Bucaneg	Robert Landman	Jessy Rouyer
William Byrd	Hyeong Ho Lee	John Sargent
Radhakrishna Canchi	John Lemon	Frank Schewe
Paul Cardinal	James Lepp	Michael Seaman
Juan Carreon	Michael Lynch	Thomas Starai
Pin Chang	John Mackay	Walter Struppler
János Farkas	Roger Marks	Michael Thompson
John Fletcher	Arthur Marris	Mark-Rene Uchida
Avraham Freedman	Jeffery Masters	James Van De Ligt
Devon Gayle	Brett McClellan	Dmitri Varsanofiev
Zhigang Gong	Richard Mellitz	George Vlantis
Randall Groves	Jose Morales	Stephen Webb
Stephen Haddock	Ronald Murias	Karl Weber
Marek Hajduczenia	Bruce Muschlitz	Hung-Yu Wei
Marco Hernandez	Nick S. A. Nikjoo	Scott Willy
Werner Hoelzl	Satoshi Obara	Peter Wu
Yasuhiro Hyakutake	Carlos Pardo	Oren Yuen
Satoko Itaya		Nader Zein

When the IEEE-SA Standards Board approved this standard on 30 January 2020, it had the following membership:

Gary Hoffman, Chair
Vacant Position, Vice Chair
Jean-Philippe Faure, Past Chair
Konstantinos Karachalios, Secretary

Ted Burse	Howard Li	Dorothy Stanley
J. Travis Griffith	Dong Liu	Mehmet Ulema
Grace Gu	Kevin Lu	Lei Wang
Guido R. Hiertz	Paul Nikolich	Sha Wei
Joseph L. Koepfinger*	Damir Novosel	Philip B. Winston
John D. Kulick	Jon Walter Rosdahl	Daidi Zhong
David J. Law		Jingyi Zhou

*Member Emeritus

Introduction

(This introduction is not part of IEEE Std 802.1AX-2020, IEEE Standard for Local and Metropolitan Area Networks—Link Aggregation.)

Link Aggregation allows one or more links to be aggregated together to form a Link Aggregation Group (LAG) so that the Link Aggregation Client can treat the LAG as if it were a single link. Link Aggregation was originally published as IEEE Std 802.3ad™-2000 and subsequently incorporated into the IEEE Std 802.3™, 2000 Edition. In 2008 Link Aggregation was removed from IEEE Std 802.3 and published as IEEE Std 802.1AX-2008. These standards specified the aggregation of full-duplex point-to-point links using IEEE Std 802.3 media of the same speed.

An amendment, IEEE Std 802.1AXbk™-2012, specified changes to the addressing used by the link aggregation control and marker protocols to allow a LAG to span Two-Port Media Access Control (MAC) Relays (TPMRs) and to span Provider Bridged Networks and Provider Backbone Bridge Networks.

A revision, IEEE Std 802.1AX-2014, extended Link Aggregation in three areas. First, it explicitly allowed the aggregation of point-to-point links of any speed using any physical media or logical connection capable of supporting the Internal Sublayer Service specified in IEEE Std 802.1AC™. Second, it specified Conversation-Sensitive Collection and Distribution (CSCD) that provides a mechanism to identify the distribution algorithm in use to map data frames to individual links in the LAG and to convey that information to the Link Aggregation Partner via Link Aggregation Control Protocol Data Units (LACPDU)s containing version 2 type/length/values (TLVs). Third, it specified Distributed Resilient Network Interconnect (DRNI) that allows a LAG to terminate at two or three cooperating Systems so that the LAG provides resiliency to System-level failures as well as link level failures. A corrigendum, IEEE Std 802.1AX-2014/Cor 1-2017, provided technical and editorial corrections to CSCD.

This revision, IEEE Std 802.1AX-2020, makes significant refinements and simplifications to the Link Aggregation Control Protocol (LACP) as well as to CSCD and DRNI. In LACP, the Periodic state machine and Transmit state machine are combined to a single machine, and the Mux machine is optimized to reduce the likelihood of excessive Link Aggregation Control Protocol Data Unit (LACPDU) transmissions. CSCD is refined to eliminate the TLVs that led to LACPDU)s greater than 128 bytes in length. DRNI is significantly revised and simplified to support a LAG terminating at just two (not three) cooperating Systems.

Every effort has been made to maintain interoperability, without prior configuration, with LACP implementations conforming to IEEE Std 802.3ad-2000, IEEE Std 802.1AX-2008, or IEEE Std 802.1AX-2014 and with CSCD implementations conforming to IEEE Std 802.1AX-2014. The changes to DRNI, and in particular the Distributed Relay Control Protocol (DRCP), are such that an implementation conforming to this standard will not interoperate with a DRCP implementation conforming to IEEE Std 802.1AX-2014. The DRCP version number in this standard has been changed to version 2, and care has been taken so that a DRCP implementation conformant to IEEE Std 802.1AX-2014 will discard version 2 DRCPDU)s as invalid and that implementations of this standard will discard version 1 DRCPDU)s.

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material. Information on the current revision state of this and other IEEE 802 standards may be obtained from

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Contents

1.	Overview.....	18
1.1	Scope.....	18
1.2	Purpose.....	18
1.3	State diagram conventions	19
2.	Normative references	20
3.	Definitions	21
4.	Acronyms and abbreviations	24
5.	Conformance.....	25
5.1	Requirements terminology	25
5.2	Protocol implementation conformance statement.....	25
5.3	Link Aggregation.....	25
5.3.2	Link Aggregation options	26
5.4	Distributed Resilient Network Interconnect (DRNI).....	26
5.4.2	DRNI options.....	27
6.	Link Aggregation.....	28
6.1	Overview.....	28
6.1.1	Goals and objectives	28
6.1.2	Positioning of Link Aggregation within the IEEE 802 architecture.....	29
6.1.3	Protocol Parser/Multiplexer	29
6.1.3.1	Protocol Parser state diagram	30
6.2	Link Aggregation operation.....	31
6.2.1	Principles of Link Aggregation.....	33
6.2.2	Service interfaces	34
6.2.3	Frame Collector	34
6.2.3.1	Frame Collector state diagram.....	35
6.2.4	Frame Distributor.....	36
6.2.4.1	Frame Distributor state diagram	36
6.2.5	Marker Generator/Receiver (optional).....	37
6.2.6	Marker Responder.....	38
6.2.7	Aggregator Parser/Multiplexer	38
6.2.7.1	Aggregator Parser/Multiplexer state diagrams	38
6.2.8	Aggregator	42
6.2.9	LACP Parser/Multiplexer	43
6.2.10	Addressing	43
6.2.10.1	Source address (SA).....	43
6.2.10.2	Destination address (DA).....	43
6.3	Link Aggregation Control.....	44
6.3.1	Characteristics of Link Aggregation Control.....	45
6.3.2	System identification	46
6.3.3	Aggregator identification.....	46
6.3.4	Port identification	46
6.3.5	Capability identification	47
6.3.6	Link Aggregation Group identification	48

6.3.6.1	Construction of the Link Aggregation Group Identifier	48
6.3.6.2	Representation of the Link Aggregation Group Identifier	48
6.3.7	Selecting a Link Aggregation Group	49
6.3.8	Agreeing on a Link Aggregation Group	49
6.3.9	Attaching a link to an Aggregator	50
6.3.10	Signaling readiness to transfer user data	50
6.3.11	Enabling the Frame Collector and Frame Distributor	50
6.3.12	MAC_Operational status	51
6.3.13	Monitoring the membership of a Link Aggregation Group	51
6.3.14	Detaching a link from an Aggregator	51
6.3.15	Configuration and administrative control of Link Aggregation	52
6.3.16	Link Aggregation Control state information	52
6.4	Link Aggregation Control Protocol	52
6.4.1	LACP design elements	52
6.4.2	LACPDU structure and encoding	53
6.4.2.1	Transmission and representation of octets	53
6.4.2.2	Encapsulation of LACPDU in frames	53
6.4.2.3	LACPDU structure	54
6.4.2.4	Version 2 TLVs	57
6.4.3	LACP state machine overview	59
6.4.4	Constants	60
6.4.5	Variables associated with each Aggregator	61
6.4.6	Variables associated with each Aggregation Port	63
6.4.7	Variables used for managing the operation of the state machines	68
6.4.8	Functions	69
6.4.9	Timers	72
6.4.10	Messages	72
6.4.11	LACP Receive machine	72
6.4.12	Selection Logic	74
6.4.12.1	Selection Logic—Requirements	75
6.4.12.2	Selection Logic—Recommended default operation	77
6.4.13	Mux machine	78
6.4.14	LACP Transmit machine	81
6.5	Marker protocol	82
6.5.1	Introduction	82
6.5.2	Sequence of operations	83
6.5.3	Marker and Marker Response PDU structure and encoding	83
6.5.3.1	Transmission and representation of octets	83
6.5.3.2	Encapsulation of Marker and Marker Response PDU in frames	83
6.5.3.3	Marker and Marker Response PDU structure	84
6.5.4	Protocol definition	85
6.5.4.1	Operation of the marker protocol	85
6.5.4.2	Marker Responder state diagram	86
6.6	Conversation-Sensitive Collection and Distribution	87
6.6.1	Port Algorithms and Port Conversation IDs	89
6.6.2	Link numbers and link selection	89
6.6.3	Conversation-sensitive LACP	90
6.6.3.1	Per-Aggregator variables	91
6.6.3.2	Variables associated with each Aggregation Port	94
6.6.3.3	Variables used for managing the operation of the state diagrams	95
6.6.3.4	Functions	96
6.6.3.5	Update Mask machine	100
6.7	Configuration capabilities and restrictions	102
6.7.1	Use of system and port priorities	102

6.7.2	Dynamic allocation of operational Keys	103
6.7.3	Link Aggregation on shared-medium links	103
6.7.4	Selection Logic variants.....	104
6.7.4.1	Reduced reconfiguration.....	104
6.7.4.2	Limited Aggregator availability.....	104
6.7.5	LACP configuration for dual-homed Systems.....	104
7.	Management.....	106
7.1	Overview.....	106
7.1.1	Systems management overview.....	106
7.1.2	Management model.....	107
7.2	Managed objects	107
7.2.1	Introduction.....	107
7.2.2	Overview of managed objects.....	108
7.2.2.1	Text description of managed objects	108
7.2.3	Containment.....	108
7.2.4	Naming.....	109
7.2.5	Capabilities	109
7.3	Management for Link Aggregation	114
7.3.1	Aggregator managed object class	114
7.3.1.1	Aggregator attributes	115
7.3.1.2	Aggregator Notifications	125
7.3.2	Aggregation Port managed object class.....	125
7.3.2.1	Aggregation Port Attributes.....	125
7.3.2.2	Aggregation Port Extension Attributes.....	132
7.3.3	Aggregation Port Statistics managed object class	133
7.3.3.1	Aggregation Port Statistics attributes	133
7.3.4	Aggregation Port Debug Information managed object class	134
7.3.4.1	Aggregation Port Debug Information attributes	135
7.4	Management for Distributed Resilient Network Interconnect.....	137
7.4.1	DRNI Managed Object Class	137
7.4.1.1	DRNI Attributes.....	137
8.	Distribution algorithms	148
8.1	Distribution algorithm identification	148
8.2	Per-Service Frame Distribution	149
8.2.1	Distribution based on C-VLAN Identifier (C-VID)	149
8.2.2	Distribution based on S-VLAN Identifier (S-VID).....	150
8.2.3	Distribution based on Backbone Service Instance Identifier (I-SID).....	150
8.2.4	Distribution based on Traffic Engineering Service Instance Identifier (TE-SID).....	150
8.2.5	Distribution based on Flow Hash.....	150
9.	Distributed Resilient Network Interconnect	151
9.1	Goals	151
9.2	Distributed Relay operation	152
9.3	Intra-Relay Connection.....	154
9.4	Using DRNI	155
9.4.1	DRNI connectivity.....	155
9.4.2	DRNI fault recovery	157
9.4.3	DRNI configuration	158

9.5	DRNI Gateway	159
9.5.1	DRCP Parser/Multiplexer	160
9.5.2	DRNI Gateway Relay	160
9.5.2.1	Service interfaces	160
9.5.2.2	variables	161
9.5.2.3	Functions	162
9.5.2.4	Messages	162
9.5.2.5	DR_Gateway Collector/Distributor	162
9.5.2.6	DR_Aggregator Parser/Multiplexer	163
9.5.2.7	DR_IRP Parser/Multiplexer	164
9.5.3	DRNI Gateway Control	165
9.5.3.1	DRNI Gateway and DRNI Identification	165
9.5.3.2	Forming the DRNI	166
9.5.3.3	Partner Selection and Forming a LAG	166
9.5.3.4	Port Algorithm and Aggregator Port Selection	166
9.5.3.5	Gateway Algorithm and DRNI Gateway Port selection	167
9.6	Distributed Relay Control Protocol	168
9.6.1	DRCPDU transmission, addressing, and protocol identification	169
9.6.1.1	Destination MAC Address	169
9.6.1.2	Source MAC Address	170
9.6.1.3	Priority	170
9.6.1.4	Protocol Identification	170
9.6.1.5	Encapsulation of DRCPDUs in frames	170
9.6.2	DRCPDU structure and encoding	170
9.6.2.1	Transmission and representation of octets	170
9.6.2.2	DRCP TLV structure	171
9.6.2.3	DRCPDU structure	172
9.6.2.4	Aggregator State TLV	174
9.6.2.5	Gateway State TLV	176
9.6.2.6	Gateway Preference TLV	176
9.6.2.7	Organization-Specific TLV	177
9.6.3	DRCP state machine overview	178
9.6.4	Constants	179
9.6.5	Variables associated with the DRNI Gateway	179
9.6.6	Variables used for managing the operation of the state machines	185
9.6.7	Functions	187
9.6.8	Timers	194
9.6.9	Messages	194
9.6.10	DRCP Receive machine	195
9.6.11	Distributed Relay machine	197
9.6.12	DRNI Gateway and Aggregator machine	198
9.6.13	DRCP Transmit machine	199
Annex A	(normative) Protocol implementation conformance statement (PICS) proforma	200
A.1	Introduction	200
A.1.1	Abbreviations and special symbols	200
A.1.2	Instructions for completing the PICS proforma	201
A.1.3	Additional information	201
A.1.4	Exceptional information	201
A.1.5	Conditional items	202
A.1.6	Identification	202
A.1.6.1	Implementation identification	202
A.1.6.2	Protocol summary	202

A.2	PICS proforma for Clause 6.....	203
A.2.1	Major capabilities/options	203
A.2.3	Protocol Parser/Multiplexer support	204
A.2.4	Frame Collector.....	204
A.2.5	Frame Distributor	204
A.2.2	LLDP Port connectivity	204
A.2.7	Aggregator Parser/Multiplexer.....	205
A.2.8	LACP Parser/Multiplexer.....	205
A.2.6	Marker protocol.....	205
A.2.10	Aggregator identification	206
A.2.11	Port identification.....	206
A.2.12	Capability identification.....	206
A.2.9	System identification.....	206
A.2.14	Detaching a link from an Aggregator.....	207
A.2.15	LACPDU structure.....	207
A.2.16	Receive machine	207
A.2.13	Link Aggregation Group identification.....	207
A.2.18	Mux machine.....	208
A.2.17	Selection Logic.....	208
A.2.20	Marker protocol.....	209
A.2.19	Transmit machine.....	209
A.2.21	Management	210
A.2.23	Conversation-sensitive frame collection and distribution.....	211
A.2.22	Per-Service Frame Distribution.....	211
A.2.25	Link Aggregation on shared-medium links.....	212
A.2.24	Configuration capabilities and restrictions.....	212
A.2.27	DRCPDU structure.....	213
A.2.26	Distributed Resilient Network Interconnect.....	213
Annex B	(informative) Collection and distribution algorithms.....	214
B.1	Introduction.....	214
B.2	Port selection.....	215
B.3	Dynamic reallocation of conversations to different Aggregation Ports	215
B.4	Topology considerations in the choice of distribution algorithm.....	216
Annex C	(informative) LACP standby link selection and dynamic Key management	218
C.1	Introduction.....	218
C.2	Goals	218
C.3	Standby link selection.....	219
C.4	Dynamic Key management.....	219
C.5	A dynamic Key management algorithm	219
C.6	Example 1	221
C.7	Example 2	221
Annex D	(normative) SMIPv2 MIB definitions for Link Aggregation	223
D.1	Introduction.....	223
D.2	SNMP Management Framework	223
D.3	Security considerations	223
D.4	Structure of the MIB module	224
D.4.1	Relationship to the managed objects defined in Clause 7	225
D.4.2	MIB Subtrees.....	232
D.4.2.1	The dot3adAgg Subtree.....	232
D.4.2.2	The dot3adAggPort Subtree.....	232

D.4.2.3	The dot3adAggNotifications Subtree.....	232
D.4.2.4	The dot3adDrni Subtree	232
D.5	Relationship to other MIBs.....	233
D.5.1	Relationship to the Interfaces MIB	233
D.5.2	Layering model	233
D.5.3	ifStackTable	234
D.5.4	ifRcvAddressTable.....	234
D.6	Definitions for Link Aggregation MIB.....	234
Annex E (informative)	DRNI on Bridges.....	325
E.1	DRNI on VLAN Bridges	325
E.2	DRNI on Provider Bridges and Provider Edge Bridges	326
E.3	DRNI on Backbone Edge Bridges	327
Annex F (normative)	Link Aggregation and Link Layer Discovery Protocol.....	328
F.1	Positioning Link Layer Discovery Protocol (LLDP) relative to Link Aggregation	328
F.1.1	LLDP Parser/Multiplexer	328
F.2	Link Aggregation TLV	328
F.2.1	aggregation status.....	329
F.2.2	aggregated Port ID	329
F.2.3	Link Aggregation TLV usage rules.....	329
F.2.4	Use of other TLVs on an Aggregator or Aggregation Link	330
Annex G (informative)	Bibliography	331

Figures

Figure 6-1	Architectural positioning of Link Aggregation sublayer	29
Figure 6-2	Protocol Parser state diagram.....	31
Figure 6-3	Link Aggregation sublayer block diagram.....	32
Figure 6-4	Frame Collector state diagram	36
Figure 6-5	Frame Distributor state diagram	37
Figure 6-6	Aggregator Parser state diagram	41
Figure 6-7	Aggregator Multiplexer state diagram	42
Figure 6-8	LACPDU structure.....	54
Figure 6-9	Bit encoding of the Actor_State and Partner_State fields.....	55
Figure 6-10	Port Algorithm TLV.....	57
Figure 6-11	Port Conversation Link Digest TLV	58
Figure 6-12	Port Conversation Service Digest TLV	58
Figure 6-13	LACP state machine overview.....	59
Figure 6-14	LACP Receive state diagram	73
Figure 6-15	Selection of Aggregators.....	78
Figure 6-16	Mux state diagram.....	79
Figure 6-17	LACP Transmit state diagram.....	81
Figure 6-18	Marker protocol time sequence diagram.....	83
Figure 6-19	Marker PDU and Marker Response PDU structure	84
Figure 6-20	Marker Responder state diagram	86
Figure 6-21	Conversation-Sensitive Collection and Distribution overview.....	88
Figure 6-22	Distribution algorithm information flow.....	91
Figure 6-23	Update Mask state diagram.....	101
Figure 6-24	Dual-homed System examples.....	105
Figure 7-1	Link aggregation entity relationship diagram	109
Figure 8-1	Distribution algorithm identifiers.....	148
Figure 9-1	A DRNI	153
Figure 9-2	Transmission and reception via the IRC.....	154
Figure 9-3	DRNI with dedicated IRC Link	155
Figure 9-4	DRNI with dedicated IRC LAG.....	155
Figure 9-5	DRNI end station attach.....	156
Figure 9-6	DRNI network attach	156
Figure 9-7	DRNI Gateway block diagram.....	159
Figure 9-8	DR_Gateway state machine	163
Figure 9-9	DR_Aggregator state machine.....	164
Figure 9-10	DR_IRP state machine.....	165
Figure 9-11	Basic TLV format	171
Figure 9-12	DRCPDU structure	172
Figure 9-13	Bit encoding of the Home_IRP_State and Neighbor_IRP_State fields.....	173
Figure 9-14	Aggregator State TLV.....	174
Figure 9-15	Bit encoding of the Aggregator_CSCD_State fields	175
Figure 9-16	Gateway State TLV.....	176
Figure 9-17	Gateway Preference TLV.....	176
Figure 9-18	Organization-Specific TLV.....	177
Figure 9-19	DRCP state machine overview	178
Figure 9-20	DRCP Receive machine state diagram	195
Figure 9-21	Distributed Relay machine state diagram	197
Figure 9-22	DRNI Gateway and Aggregator machine state diagram.....	198
Figure 9-23	DRCP Transmit state diagram	199
Figure B-1	Link aggregation topology examples.....	217
Figure C-1	Example 1	221

Figure C-2	Example 2a.....	222
Figure C-3	Example 2b	222
Figure E-1	DRNI on VLAN Bridges	325
Figure E-2	DRNI on Provider Edge Bridges	326
Figure E-3	DRNI on Backbone Edge Bridges	327
Figure F-1	Link Aggregation TLV format.....	328

Tables

Table 6-1	Link Aggregation protocol destination addresses.....	44
Table 6-2	Example Partner parameters	49
Table 6-3	Slow Protocols EtherType Assignment	53
Table 6-4	Type field values of Version 2 TLVs	57
Table 7-1	Link Aggregation capabilities.....	110
Table 8-1	IEEE per-service distribution algorithms	149
Table 9-1	Distributed Relay Control Protocol destination addresses	169
Table 9-2	DRNI EtherType Assignment.....	170
Table 9-3	DRNI Protocol subtypes	170
Table 9-4	Type field values of DRCP TLVs.....	171
Table F.1	Link aggregation capability/status	329

IEEE Standard for Local and Metropolitan Area Networks— Link Aggregation

1. Overview

1.1 Scope

Link Aggregation provides protocols, procedures, and managed objects that allow the following:

- One or more parallel instances of point-to-point links to be aggregated together to form a Link Aggregation Group (LAG) so that a Link Aggregation Client can treat the LAG as if it were a single link.
- Conversation-Sensitive Collection and Distribution (CSCD) that specifies a means to identify the distribution algorithm in use to assign frames to individual links in a LAG and to convey that information to the System at the other end of the LAG.
- Distributed Resilient Network Interface (DRNI) that enables a LAG to terminate at a pair of cooperating Systems in order to provide system-level as well as link-level resiliency.

1.2 Purpose

Link Aggregation allows the establishment of point-to-point links that have a higher aggregate bandwidth than the individual links that form the aggregation and the use of multiple systems at each end of the aggregation. This allows improved utilization of available links in Bridged local area network (LAN) environments, along with improved resilience in the face of failure of individual links or systems. In applications connecting separately administered networks, the networks are isolated from each other's fault recovery events.

1.3 State diagram conventions

This standard uses the state diagram conventions in Annex E of IEEE Std 802.1Q™-2018.¹

When implementation of a state diagram is required for conformance, all states and transitions shown with solid lines shall be implemented. States and transitions shown with dashed lines may be implemented.

If a conflict exists between a state diagram and either the corresponding global transition tables or the textual description associated with the state machine, the state diagram takes precedence.

¹ Information on references can be found in Clause 2.

2. Normative references

The following referenced documents are indispensable for the application of this standard (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this standard is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

IEEE Std 802[®], IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture.^{2, 3}

IEEE Std 802.1AC[™], IEEE Standard for Local and metropolitan area networks—Media Access Control (MAC) Service Definition.

IEEE Std 802.1Q[™], IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks.

IEEE Std 802.3[™], IEEE Standard for Ethernet.

IETF RFC 1213 (IETF STD 17), Management Information Base for Network Management of TCP/IP-based internets: MIB-II, McCloghrie, K., and M. Rose, editors, Mar. 1991.⁴

IETF RFC 1321, The MD5 Message-Digest Algorithm, R. Rivest, Apr. 1992.

IETF RFC 2578 (STD 58), Structure of Management Information Version 2 (SMIv2), McCloghrie, K., D. Perkins, and J. Schoenwaelder, Apr. 1999.

IETF RFC 2579 (STD 58), Textual Conventions for SMIv2, McCloghrie, K., D. Perkins, J. Schoenwaelder, J. Case, M. Rose, and S. Waldbusser, Apr. 1999.

IETF RFC 2580 (STD 58), Conformance Statements for SMIv2, McCloghrie, K., D. Perkins, J. Schoenwaelder, J. Case, M. Rose, and S. Waldbusser, Apr. 1999.

IETF RFC 2863, The Interfaces Group MIB, McCloghrie, K., and F. Kastenholz, June 2000.

IETF RFC 3410, Introduction and Applicability Statements for Internet-Standard Management Framework, Case, J., R. Mundy, D. Partain, and B. Stewart, Dec. 2002.

IETF RFC 3414 (STD 62), User-based Security Model (USM) for Version 3 of the Simple Network Management Protocol (SNMPv3), Blumenthal, U., and B. Wijnen, Dec. 2002.

IETF RFC 3415 (STD 62), View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP), Wijnen, B., R. Presuhn, and K. McCloghrie, Dec. 2002.

ISO/IEC 10165-4:1992, Information technology—Open Systems Interconnection—Structure of management information—Part 4: Guidelines for the definition of managed objects.⁵

² IEEE publications are available from The Institute of Electrical and Electronics Engineers (<https://standards.ieee.org/>).

³ The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.

⁴ IETF documents (i.e., RFCs) are available from the Internet Engineering Task Force (<https://www.rfc-archive.org/>).

⁵ ISO/IEC publications are available from the International Organization for Standardization (<https://www.iso.org/>), the International Electrotechnical Commission (<https://www.iec.ch>), and the American National Standards Institute (<https://www.ansi.org/>).