

English Version

Petroleum and natural gas industries - Formulae and calculations for the properties of casing, tubing, drill pipe and line pipe used as casing or tubing (ISO/TR 10400:2018)

Industries du pétrole et du gaz naturel - Formules et calculs relatifs aux propriétés des tubes de cuvelage, des tubes de production, des tiges de forage et des tubes de conduites utilisés comme tubes de cuvelage et tubes de production (ISO/TR 10400:2018)

Erdöl- und Erdgasindustrie - Formeln und Berechnungen der Eigenschaften von Futterrohren, Steigrohren, Bohrgestängen und Leitungsrohren (ISO/TR 10400:2018)

This Technical Report was approved by CEN on 20 September 2021. It has been drawn up by the Technical Committee CEN/TC 12.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of ISO/TR 10400:2018 has been prepared by Technical Committee ISO/TC 67 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries" of the International Organization for Standardization (ISO) and has been taken over as CEN ISO/TR 10400:2021 by Technical Committee CEN/TC 12 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries" the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN ISO/TR 10400:2011.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

Endorsement notice

The text of ISO/TR 10400:2018 has been approved by CEN as CEN ISO/TR 10400:2021 without any modification.

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Symbols	4
5 Conformance	13
5.1 References	13
5.2 Units of measurement	13
6 Triaxial yield of pipe body	13
6.1 General	13
6.2 Assumptions and limitations	13
6.2.1 General	13
6.2.2 Concentric, circular cross-sectional geometry	14
6.2.3 Isotropic yield	14
6.2.4 No residual stress	14
6.2.5 Cross-sectional instability (collapse) and axial instability (column buckling)	14
6.3 Data requirements	14
6.4 Design formula for triaxial yield of pipe body	14
6.5 Application of design formula for triaxial yield of pipe body to line pipe	16
6.6 Example calculations	16
6.6.1 Initial yield of pipe body, Lamé formula for pipe when external pressure, bending and torsion are zero	16
6.6.2 Yield design formula, special case for thin wall pipe with internal pressure only and zero axial load	18
6.6.3 Pipe body yield strength	18
6.6.4 Yield in the absence of bending and torsion	19
7 Ductile rupture of the pipe body	20
7.1 General	20
7.2 Assumptions and limitations	20
7.3 Data requirements	21
7.3.1 General	21
7.3.2 Determination of the hardening index	21
7.3.3 Determination of the burst strength factor, k_a	22
7.4 Design formula for capped-end ductile rupture	23
7.5 Adjustment for the effect of axial force and external pressure	24
7.5.1 General	24
7.5.2 Design formula for ductile rupture under combined loads	25
7.5.3 Design formula for ductile necking under combined loads	26
7.5.4 Boundary between rupture and necking	27
7.5.5 Axisymmetric wrinkling under combined loads	27
7.6 Example calculations	28
7.6.1 Ductile rupture of an end-capped pipe	28
7.6.2 Ductile rupture for a given true axial load	28
8 External pressure resistance	29
8.1 General	29
8.2 Assumptions and limitations	29
8.3 Data requirements	29
8.4 Design formula for collapse of pipe body	30
8.4.1 General	30
8.4.2 Yield strength collapse pressure formula	30

8.4.3	Plastic collapse pressure formula	31
8.4.4	Transition collapse pressure formula	33
8.4.5	Elastic collapse pressure formula	34
8.4.6	Collapse pressure under axial tensile stress	35
8.4.7	Collapse pressure under axial stress and internal pressure	35
8.5	Formulae for empirical constants	35
8.5.1	General	35
8.5.2	SI units	36
8.5.3	USC units	36
8.6	Application of collapse pressure formulae to line pipe	37
8.7	Example calculations	37
9	Joint strength	37
9.1	General	37
9.2	API casing connection tensile joint strength	37
9.2.1	General	37
9.2.2	Round thread casing joint strength	38
9.2.3	Buttress thread casing joint strength	40
9.3	API tubing connection tensile joint strength	42
9.3.1	General	42
9.3.2	Non-upset tubing joint strength	42
9.3.3	Upset tubing joint strength	43
9.4	Line pipe connection joint strength	44
10	Pressure performance for couplings	44
10.1	General	44
10.2	Internal yield pressure of round thread and buttress couplings	44
10.3	Internal pressure leak resistance of round thread or buttress couplings	45
11	Calculated masses	48
11.1	General	48
11.2	Nominal linear masses	48
11.3	Calculated plain-end mass	48
11.4	Calculated finished-end mass	49
11.5	Calculated threaded and coupled mass	49
11.5.1	General	49
11.5.2	Direct calculation of e_m , threaded and coupled pipe	50
11.6	Calculated upset and threaded mass for integral joint tubing	50
11.6.1	General	50
11.6.2	Direct calculation of e_m , upset and threaded pipe	51
11.7	Calculated upset mass	51
11.7.1	General	51
11.7.2	Direct calculation of e_m , upset pipe	52
11.8	Calculated coupling mass	52
11.8.1	General	52
11.8.2	Calculated coupling mass for line pipe and round thread casing and tubing	52
11.8.3	Calculated coupling mass for buttress thread casing	55
11.9	Calculated mass removed during threading	56
11.9.1	General	56
11.9.2	Calculated mass removed during threading pipe or pin ends	56
11.9.3	Calculated mass removed during threading integral joint tubing box ends	58
11.10	Calculated mass of upsets	59
11.10.1	General	59
11.10.2	Calculated mass of external upsets	59
11.10.3	Calculated mass of internal upsets	60
11.10.4	Calculated mass of external-internal upsets	61
12	Elongation	61
13	Flattening tests	62
13.1	Flattening tests for casing and tubing	62

13.2	Flattening tests for line pipe.....	62
14	Hydrostatic test pressures	63
14.1	Hydrostatic test pressures for plain-end pipe and integral joint tubing.....	63
14.2	Hydrostatic test pressure for threaded and coupled pipe.....	64
15	Make-up torque for round thread casing and tubing.....	64
16	Guided bend tests for submerged arc-welded line pipe.....	65
16.1	General.....	65
16.2	Background.....	67
16.2.1	Values of ϵ_{eng}	67
16.2.2	Values of A_{gbtj}	67
17	Determination of minimum impact specimen size for API couplings and pipe	67
17.1	Critical thickness.....	67
17.2	Calculated coupling blank thickness.....	68
17.3	Calculated wall thickness for transverse specimens.....	71
17.4	Calculated wall thickness for longitudinal specimens.....	71
17.5	Minimum specimen size for API couplings	71
17.6	Impact specimen size for pipe.....	73
17.7	Larger size specimens.....	73
17.8	Reference information.....	74
Annex A (informative)	Discussion of formulae for triaxial yield of pipe body.....	75
Annex B (informative)	Discussion of formulae for ductile rupture	88
Annex C (informative)	Rupture test procedure.....	126
Annex D (informative)	Discussion of formulae for fracture.....	128
Annex E (informative)	Discussion of historical collapse formulae.....	135
Annex F (informative)	Development of probabilistic collapse performance properties.....	149
Annex G (informative)	Calculation of design collapse strength from collapse test data.....	188
Annex H (informative)	Calculation of design collapse strengths from production quality data....	191
Annex I (informative)	Collapse test procedure.....	205
Annex J (informative)	Discussion of formulae for joint strength.....	211
Annex K (informative)	Tables of calculated performance properties in SI units.....	219
Annex L (informative)	Tables of calculated performance properties in USC units	221
Bibliography		223

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 5, *Casing, tubing and drill pipe*.

This second edition cancels and replaces the first edition (ISO/TR 10400:2007), which has been technically revised.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Performance design of tubulars for the petroleum and natural gas industries, whether it is formulated by deterministic or probabilistic calculations, compares anticipated loads to which the tubular can be subjected to the anticipated resistance of the tubular to each load. Either or both of the load and resistance can be modified by a design factor.

Both deterministic and probabilistic approaches to performance properties are addressed in this document. The deterministic approach uses specific geometric and material property values to calculate a single performance property value. The probabilistic method treats the same variables as random and thus arrives at a statistical distribution of a performance property. A performance distribution in combination with a defined lower percentile determines the final design formula.

Both the well design process itself and the definition of anticipated loads are currently outside the scope of standardization for the petroleum and natural gas industries. Neither of these aspects is addressed in this document. Rather, it serves to identify useful formulae for obtaining the resistance of a tubular to specified loads, independent of their origin. It provides limit state formulae (see annexes) which are useful for determining the resistance of an individual sample whose geometric and material properties are given, and design formulae which are useful for well design based on conservative geometric and material parameters.

Whenever possible, decisions on specific constants to use in a design formula are left to the discretion of the reader.

Petroleum and natural gas industries — Formulae and calculations for the properties of casing, tubing, drill pipe and line pipe used as casing or tubing

1 Scope

This document illustrates the formulae and templates necessary to calculate the various pipe properties given in International Standards, including

- pipe performance properties, such as axial strength, internal pressure resistance and collapse resistance,
- minimum physical properties,
- product assembly force (torque),
- product test pressures,
- critical product dimensions related to testing criteria,
- critical dimensions of testing equipment, and
- critical dimensions of test samples.

For formulae related to performance properties, extensive background information is also provided regarding their development and use.

Formulae presented here are intended for use with pipe manufactured in accordance with ISO 11960 or API 5CT, ISO 11961 or API 5D, and ISO 3183 or API 5L, as applicable. These formulae and templates can be extended to other pipe with due caution. Pipe cold-worked during production is included in the scope of this document (e.g. cold rotary straightened pipe). Pipe modified by cold working after production, such as expandable tubulars and coiled tubing, is beyond the scope of this document.

Application of performance property formulae in this document to line pipe and other pipe is restricted to their use as casing/tubing in a well or laboratory test, and requires due caution to match the heat-treat process, straightening process, yield strength, etc., with the closest appropriate casing/tubing product. Similar caution is exercised when using the performance formulae for drill pipe.

This document and the formulae contained herein relate the input pipe manufacturing parameters in ISO 11960 or API 5CT, ISO 11961 or API 5D, and ISO 3183 or API 5L to expected pipe performance. The design formulae in this document are not to be understood as a manufacturing warranty. Manufacturers are typically licensed to produce tubular products in accordance with manufacturing specifications which control the dimensions and physical properties of their product. Design formulae, on the other hand, are a reference point for users to characterize tubular performance and begin their own well design or research of pipe input properties.

This document is not a design code. It only provides formulae and templates for calculating the properties of tubulars intended for use in downhole applications. This document does not provide any guidance about loads that can be encountered by tubulars or about safety margins needed for acceptable design. Users are responsible for defining appropriate design loads and selecting adequate safety factors to develop safe and efficient designs. The design loads and safety factors will likely be selected based on historical practice, local regulatory requirements, and specific well conditions.

All formulae and listed values for performance properties in this document assume a benign environment and material properties conforming to ISO 11960 or API 5CT, ISO 11961 or API 5D and

ISO 3183 or API 5L. Other environments can require additional analyses, such as that outlined in [Annex D](#).

Pipe performance properties under dynamic loads and pipe connection sealing resistance are excluded from the scope of this document.

Throughout this document tensile stresses are positive.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

Cauchy stress true stress

force applied to the surface of a body divided by the current area of that surface

3.2

coefficient of variance

dimensionless measure of the dispersion of a random variable, calculated by dividing the standard deviation by the mean

3.3

design formula

formula which, based on production measurements or specifications, provides a performance property useful in design calculations

Note 1 to entry: A design formula can be defined by applying reasonable extremes to the variables in a limit state formula to arrive at a conservative value of expected performance. When statistically derived, the design formula corresponds to a defined lower percentile of the resistance probability distribution curve.

3.4

deterministic

approach which assumes all variables controlling a performance property are known with certainty

Note 1 to entry: Pipe performance properties generally depend on one or more controlling parameters. A deterministic formula uses specific geometric and material property values to calculate a single performance property value. For design formulations, this value is the expected minimum.

3.5

ductile rupture

failure of a tube due to internal pressure and/or axial force in the plastic deformation range

3.6

e

Euler's constant

2,718 281 828