

RAUDTEEALASED RAKENDUSED. RATTARÖÖPA
ÜHILDUVUSE GEOMEETRILISED PARAMEETRID.
MÄÄRATLUSED JA HINDAMISE MEETODID

Railway Applications - Wheel-rail contact geometry
parameters - Definitions and methods for evaluation

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 15302:2021 sisaldab Euroopa standardi EN 15302:2021 ingliskeelset teksti.	This Estonian standard EVS-EN 15302:2021 consists of the English text of the European standard EN 15302:2021.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 06.10.2021.	Date of Availability of the European standard is 06.10.2021.
Standard on kättesaadav Eesti Standardimis- ja Akrediteerimiskeskusest.	The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 17.040.20, 45.060.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autoriõiguse kaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about standards copyright protection, please contact the Estonian Centre for Standardisation and Accreditation: Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Railway applications - Wheel-rail contact geometry parameters - Definitions and methods for evaluation

Applications ferroviaires - Paramètres géométriques
du contact roue-rail - Définitions et méthodes de
détermination

Bahnanwendungen - Parameter der Rad-Schiene
Kontaktgeometrie - Definitionen und
Berechnungsmethoden

This European Standard was approved by CEN on 2 August 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	7
Introduction	8
1 Scope	9
2 Normative references	9
3 Terms and definitions	10
4 Symbols and abbreviations	11
5 Overview of the process for determining contact parameters	12
6 Description of wheel and rail profiles	12
6.1 General.....	12
6.2 Uncertainty of the measuring systems.....	14
7 Plausibility check and processing of measured wheel and rail profiles	15
8 Determining the wheel-rail contact positions and contact functions	16
8.1 General.....	16
8.2 Determining the rolling radius difference function	16
8.3 Other wheel-rail contact geometry functions.....	17
9 Determining the equivalent conicity and the related nonlinearity parameter	17
9.1 Background to equivalent conicity.....	17
9.1.1 Mathematical description of the kinematic lateral wheelset motion	17
9.1.2 Determining the wavelength of a coned wheelset	18
9.2 Determining the equivalent conicity	19
9.3 Determining the nonlinearity parameter	19
10 Determining the rolling radii coefficient	20
10.1 Background and definition	20
10.2 Determining point E for the calculation of the rolling radii coefficient.....	22
11 Other wheel-rail contact parameters	23
12 Testing of calculation software for contact geometry parameters	24
12.1 Overview	24
12.2 Validation of the calculation algorithms	24
12.3 Assessment of the smoothing process.....	24
13 Assessment of the complete process for determination of wheel-rail contact parameters	28
13.1 General.....	28
13.2 Reproducibility of contact parameter determination based on rail profile measurement.....	28
13.2.1 Manual rail profile measuring devices.....	28
13.2.2 Vehicle based rail profile measuring systems	29
13.3 Reproducibility of contact parameter determination based on wheel profile measurement.....	30
13.3.1 Manual wheel profile measuring devices.....	30
13.3.2 Ground based wheel profile measuring systems.....	30
Annex A (informative) Example of presentation of contact geometry functions	32

Annex B (informative) Derivation of the kinematic equation of wheelset motion.....	33
Annex C (informative) Determination of the lateral peak displacements	36
Annex D (informative) Method for determining the wavelength of the wheelset motion by two-step integration of the nonlinear differential equation	38
D.1 General	38
D.2 Step 1.....	38
D.3 Step 2.....	38
Annex E (informative) Method for determining the wavelength of the wheelset motion by direct integration of the nonlinear differential equation.....	40
Annex F (informative) Method for determining the equivalent conicity by linear regression of the Δr function	41
F.1 General	41
F.2 Concerns regarding the method.....	41
Annex G (informative) Method for determining linearization parameters by harmonic linearization	43
G.1 General	43
G.2 Concerns regarding the method.....	44
Annex H (informative) Handling of special cases of the Δr function.....	45
Annex I (normative) Reference profiles for testing	48
I.1 General	48
I.2 Wheel A.....	49
I.2.1 Drawing.....	49
I.2.2 Analytic definition.....	49
I.2.3 Cartesian coordinates	50
I.3 Wheel B.....	52
I.3.1 Drawing.....	52
I.3.2 Analytic definition.....	52
I.3.3 Cartesian coordinates	53
I.4 Wheel C.....	55
I.4.1 Drawing.....	55
I.4.2 Analytic definition.....	55
I.4.3 Cartesian coordinates	56
I.5 Wheel H	58
I.5.1 Drawing.....	58
I.5.2 Analytic definition.....	58
I.5.3 Cartesian coordinates	59
I.6 Wheel I.....	61
I.6.1 Drawing.....	61

I.6.2	Analytic definition	61
I.6.3	Cartesian coordinates.....	62
I.7	Rail A.....	64
I.7.1	Drawing	64
I.7.2	Analytic definition	64
I.7.3	Cartesian coordinates.....	65
Annex J (normative)	Calculation results with reference profiles.....	67
J.1	General.....	67
J.2	Wheel A/Rail A	68
J.2.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	68
J.2.2	Numerical values for Δr function	69
J.2.3	Numerical values for $\tan \gamma_e$ function.....	70
J.3	Wheel B/Rail A	72
J.3.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	72
J.3.2	Numerical values for Δr function	73
J.3.3	Numerical values for $\tan \gamma_e$ function.....	74
J.4	Wheel C/Rail A	76
J.4.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	76
J.4.2	Numerical values for Δr function	77
J.4.3	Numerical values for $\tan \gamma_e$ function.....	79
J.5	Wheel H/Rail A.....	81
J.5.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	81
J.5.2	Numerical values for Δr function	82
J.5.3	Numerical values for $\tan \gamma_e$ function.....	83
J.6	Wheel I/Rail A	85
J.6.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	85
J.6.2	Numerical values for Δr function	86
J.6.3	Numerical values for $\tan \gamma_e$ function.....	87
J.7	Modified Wheel A (-2 mm on left wheel diameter)/Rail A.....	89
J.7.1	Representation of contact points, diagrams of Δr, $\Delta \tan \gamma$, $\tan \gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track.....	89
J.7.2	Numerical values for Δr function	90

J.7.3	Numerical values for $\tan\gamma_e$ function	91
J.8	Modified Wheel B (–2 mm on left wheel diameter)/Rail A	93
J.8.1	Representation of contact points, diagrams of Δr , $\Delta\tan\gamma$, $\tan\gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track	93
J.8.2	Numerical values for Δr function	94
J.8.3	Numerical values for $\tan\gamma_e$ function	95
J.9	Modified Wheel H (–2 mm on left wheel diameter)/Rail A	97
J.9.1	Representation of contact points, diagrams of Δr , $\Delta\tan\gamma$, $\tan\gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track	97
J.9.2	Numerical values for Δr function	98
J.9.3	Numerical values for $\tan\gamma_e$ function	99
J.10	Modified Wheel I (–2 mm on left wheel diameter)/Rail A	101
J.10.1	Representation of contact points, diagrams of Δr , $\Delta\tan\gamma$, $\tan\gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track	101
J.10.2	Numerical values for Δr function	102
J.10.3	Numerical values for $\tan\gamma_e$ function	103
J.11	(Right Wheel A – Left Wheel B)/Rail A	105
J.11.1	Representation of contact points, diagrams of Δr , $\Delta\tan\gamma$, $\tan\gamma_e$ functions and representation of kinematic rolling movement of the wheelset on track	105
J.11.2	Numerical values for Δr function	106
J.11.3	Numerical values for $\tan\gamma_e$ function	107
Annex K (normative)	Tolerances on equivalent conicity for testing calculations	109
K.1	General	109
K.2	Wheel A/Rail A	110
K.2.1	Diagram	110
K.2.2	Numerical values	111
K.3	Wheel B/Rail A	113
K.3.1	Diagram	113
K.3.2	Numerical values	114
K.4	Wheel C/Rail A	116
K.4.1	Diagram	116
K.4.2	Numerical values	117
K.5	Wheel H/Rail A	119
K.5.1	Diagram	119
K.5.2	Numerical values	120
K.6	Wheel I/Rail A	122
K.6.1	Diagram	122

K.6.2	Numerical values.....	123
K.7	Modified Wheel A (-2 mm on left wheel diameter)/Rail A.....	125
K.7.1	Diagram	125
K.7.2	Numerical values.....	126
K.8	Modified Wheel B (-2 mm on left wheel diameter)/Rail A.....	128
K.8.1	Diagram	128
K.8.2	Numerical values.....	129
K.9	Modified Wheel H (-2 mm on left wheel diameter)/Rail A	131
K.9.1	Diagram	131
K.9.2	Numerical values.....	132
K.10	Modified Wheel I (-2 mm on left wheel diameter)/Rail A.....	134
K.10.1	Diagram	134
K.10.2	Numerical values.....	135
K.11	(Right Wheel A - Left Wheel B)/Rail A	137
K.11.1	Diagram	137
K.11.2	Numerical values.....	138
	Bibliography.....	140

European foreword

This document (EN 15302:2021) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2022, and conflicting national standards shall be withdrawn at the latest by April 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15302:2008+A1:2010.

The main changes with respect to the previous edition are listed below:

- Extension of the Scope;
- Introduction of new wheel-rail contact geometry parameters (rolling radii coefficient, nonlinearity parameter);
- Additional methods for evaluation of equivalent conicity;
- Improvement of the description of the reference profiles;
- Additional reference wheel profile C;
- Reference results based on analytical solutions;
- Hints for plausibility checking of measured profiles;
- Revised assessment of the smoothing process;
- New assessment of the complete process.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This document is based on the UIC Code 519 OR submitted to CEN by the International Union of Railways (UIC) and which has been revised by CEN/TC 256/WG 10 "Vehicle/Track Interaction".

The wheel-rail contact geometry is fundamental for explaining the dynamic running behaviour of a railway vehicle, as well as the quasi-static behaviour in curves. Among the parameters which influence the dynamic behaviour of a rail vehicle, the equivalent conicity plays an essential role since it allows for the satisfactory characterization of the wheel-rail contact geometry on tangent track and on very large-radius curves. A wheelset describes a waveform while running on a track. Klingel's theory, valid for massless wheelsets with conical profiles, states that the waveform is sinusoidal and its wavelength depends on the cone angle of the wheel profile.

Real wheel profiles are not pure cones, but have changing cone angles across the tread, leading to a nonlinear dependency of the rolling radius difference on the lateral movement of the wheelset on the track. The wavelength of the wheelset movement according to the nonlinear kinematic equations of motion may be calculated by solving numerically this formula or by specific methods for linearization of the rolling radius difference function. Equivalent conicity is evaluated by comparison of this wavelength with the equivalent wavelength of a conical wheelset according to Klingel's formula or by calculating the conicity from the linearized rolling radius difference function.

It is important to have a clear specification for the evaluation of wheel-rail contact geometry parameters, which are used in European and national standards and documents (legal and technical).

The objective is to ensure that the results for the determined parameters are consistent. However, it is possible to use different evaluation procedures to those given in this document, provided that the procedure used leads to the determination of wheel-rail contact parameters in accordance with the calculation results using the reference profiles specified in Annex I. A validation process is given in this document to be used in order to determine whether or not an evaluation procedure can achieve the specified reference results.

Technical background will be given in a Technical Report published after the publication of this document.

1 Scope

This document establishes definitions and evaluation methods for wheel-rail contact geometry parameters influencing the vehicle running dynamic behaviour:

- the rolling radius difference between the two wheels of a wheelset (Δr -function) which serves as a basis for all further calculations;
- the equivalent conicity function from which are derived:
 - a single equivalent conicity value for a specified amplitude which is relevant for the assessment of vehicle running stability on straight track and in very large radius curves according to EN 14363;
 - the nonlinearity parameter which characterizes the shape of this function and is related to the vehicle behaviour particularly in the speed range close to the running stability limit;
- the rolling radii coefficient which is used to describe the theoretical radial steering capability of a wheelset in a curved track.

Additional information is given about the relationship between the contact angles of the two wheels of a wheelset ($\Delta \alpha$ -function) and about the roll angle parameter.

NOTE Out of the presented parameters only those related to the contact angle are relevant for independently rotating wheels of wheel pairs.

Descriptions of possible calculation methods are included in this document. Test case calculations are provided to achieve comparable results and to check the proper implementation of the described algorithms.

To validate alternative methods not described in this document acceptance criteria are given for the equivalent conicity function. This includes reference profiles, profile combinations, tolerances and reference results with tolerance limits.

This document also includes minimum requirements for the measurement of wheel and rail profiles as well as of the parameters needed for the transformation into a common coordinate system of right- and left-hand profiles.

This document does not define limits for the wheel-rail contact geometry parameters and gives no tolerances for the rail profile and the wheel profile to achieve acceptable results.

For the application of this document some general recommendations are given.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13231-2:2020, *Railway applications — Track — Acceptance of works — Part 2: Acceptance of reprofiling rails in plain line, switches, crossings and expansion devices*