

TECHNICAL

REPORT

# IEC TR 60286-3-4

Edition 1.0 2021-10



Packaging of components for automatic handling – Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder



## THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

**IEC Central Office** 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



**TECHNICAL** 

- Montis

REPORT

# IEC TR 60286-3-4

Edition 1.0 2021-10



Packaging of components for automatic handling – Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder

> iez 920

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ISBN 978-2-8322-1041-4

ICS 31.020; 31.240

Warning! Make sure that you obtained this publication from an authorized distributor.

# CONTENTS

FOREWORD					
INTRODUCTION					
1	Scop	e	7		
2	Normative references				
3	$O_{i}$				
	3.1	Terms and definitions	7		
	3.2	Symbols			
4	Over	view of Auto Loading Feeder	8		
	4.1	Overview and features of Auto Loading Feeder	8		
	4.2	Methods and mechanisms of automatically exposing the pockets in using Auto Loading Feeder			
5	Discu	ussion items for requirements for emboss taping for Auto Loading Feeder	10		
	5.1	General	10		
	5.2	Required dimensions for the cover tape sealed positions	10		
	5.3	Required dimensions for the distance between the upper side of the carrier tape and the top surface of a component in using Auto Loading Feeder	11		
	5.4	Necessity of $M_1$ and $M_2$ as the cover tape sealed positions	11		
	5.5	Necessity of $K_1$ as the distance between the upper side of the carrier tape and the top surface of a component	12		
	5.6	Necessity of $K_2$ as the recessed part in a cross-bar section	13		
	5.7	Necessity of $K_3$ as the distance between the upper side of the recessed part			
		in a cross-bar section and the top surface of a component			
	5.8	Sealing method for the cover tape			
	5.9	Dent of the cover tape over the pockets			
	5.10	Lower limit of peel-off strength of the cover tape			
	5.11	Adhesion of components on the cover tape			
	5.12	Bottom hole of pockets of the carrier tape			
	5.13 5.14	Maximum trailer length Fixing the tail end of the carrier tape			
6			17		
0	Summary of the discussions: considered requirements and dimensions for emboss taping for Auto Loading Feeder17				
	6.1	General	17		
	6.2	Required dimensions for the cover tape sealed positions			
	6.3	Required dimensions for the distance between the upper side of the carrier tape and the top surface of a component	18		
	6.4	Required specifications for the sealing method of the cover tape	18		
	6.5	Required specifications for maximum trailer length			
7	Poss	ible problems for emboss taping for Auto Loading Feeder	18		
	7.1	General			
	7.2	Relationship between sealed positions of the cover tape and openings of the pockets			
	7.3	Recessed part in a cross-bar section			
	7.4	Dot seals	19		
	7.5	Thickness of embossed carrier tape	20		
	7.6	Relationship between Auto Loading Feeder and tape camber specified in IEC 60286-3	21		

Annex A (informative) Methods and mechanisms of automatically exposing pockets in using Auto Loading Feeder	. 22
A.1 General	.22
A.2 Single-door method	.22
A.3 Double-door method	
Annex B (informative) Glossary	
Bibliography	.26
Figure 1 – Specified dimensions for emboss taping for Auto Loading Feeder	8
Figure 2 – Operation and features when another tape is re-supplied automatically by the Auto Loading Feeder	9
Figure 3 – Example of a part of embossed carrier tape with a recessed part in a cross- bar section	. 13
Figure 4 – Relationship between the cover tape and the exposure processing mechanism of the pocket	. 13
Figure 5 – Relationship between the exposure processing mechanism of the pocket and convex of carrier tape	. 14
Figure 6 – Example dent of the cover tape over the pocket	. 15
Figure 7 – Leader part and trailer part	. 18
Figure 8 – Dimension <i>B</i> <sub>1</sub> and sealed positions	. 19
Figure 9 – Example of dot seal	. 20
Figure 10 – Relationship between embossed carrier tape thickness and component exposure process	
Figure 11 – Tape camber (top view)	.21
Figure A.1 – Overview of the single-door method	.22
Figure A.2 – Overview of the double-door method	
Table 1 – Symbols used in figures and tables	8
Table 2 – The cover tape sealed positions required for emboss taping for Auto   Loading Feeder	.11
Table 3 – Distance between the upper side of the carrier tape and the top surface of acomponent required for emboss taping for Auto Loading Feeder	.11
Table B.1 – Glossary of mounter and feeder related terms	.24
Table B.1 – Glossary of mounter and feeder related terms	
(	2

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING -

# Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 60286-3-4 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
40/2844/DTR	40/2866/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available

IEC TR 60286-3-4:2021 © IEC 2021 - 5 -

at www.iec.ch/members\_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60286 series, published under the general title *Packaging of components for automatic handling*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding TO CHARACTER OF THE OF of its contents. Users should therefore print this document using a colour printer.

#### INTRODUCTION

This Technical Report was developed by the technical committee 40 working group 36 on components packaging, in which the members, such as mounter manufacturers, component manufacturers and packaging material manufacturers, had proposed, considered and discussed the possible standardization of the application of Auto Loading Feeder to enable automatically exchange SMD continuous tapes, using paper carrier tape during mounter operation, aiming to support IEC 60286-3, Edition 6, issued in 2019.

This document includes data expressed in the form of provisions, such as requirements or recommendations. These data, however, do not claim to be provisions and are just suggested as the results of the discussion.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a trademark concerning Auto Loading Feeder given in 3.1.1.

- Trademark ... AUTO LOADING FEEDER™
- Trademark registration number ... No.5983611 (Japan)

IEC takes no position concerning the evidence, validity and scope of this trademark right.

The holder of this trademark right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this trademark right is registered with IEC. Information may be obtained from:

• Name of holder of trademark right ... Yamaha Motor Co., Ltd.

Address ... 2500 Shingai, Iwata, Shizuoka, Japan

- Name of holder of trademark right ... FUJI CORPORATION Address ... 19 Chausuyama., Yamamachi, Chiryu, Aichi, Japan
- Name of holder of trademark right ... Panasonic Corporation

Address ... 2-7, Matsuba-cho, Kadoma, Osaka, Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of trademark rights other than those identified above. IEC shall not be held responsible for identifying any or all such trademark rights.

## PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING -

# Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder

## 1 Scope

This part of IEC 60286 considers the proposed requirements for emboss taping for the Auto Loading Feeder mechanism to mount electric components without leads or with stump type leads used for electric circuits. This document is applicable to the embossed carrier tape, with single round sprocket holes, with tape pitches of 2 mm or more (nominal tape width: 8 mm only) among the tapes of Type 2a in IEC 60286-3.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes the statement of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60286-3:2019, Packaging of components for automatic handling – Part 3: Packaging of surface mount components on continuous tapes

#### 3 Terms, definitions and symbols

#### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

NOTE Annex B features a Glossary of mounter and feeder related terms.

#### 3.1.1 Auto Loading Feeder AUTO LOADING FEEDER™

tape feeder that can keep supplying components by automatically carrying a tape of re-supplied SMD at the filling-in position into the components supply position, just after the components in the tape of previously supplied SMD are fed up during the assembly production

Note 1 to entry: Auto Loading Feeder has the mechanism that the cover tape of a SMD tape is automatically cut or peeled off to expose the pockets during the operation to supply components.

# 3.1.2

seal

bonding of a part of the top cover tape and a part of the carrier tape

Note 1 to entry: The top cover tapes are classified as heat welding type and adhesive type by the way to bond itself on the carrier tape.