

Unbound and hydraulically bound mixtures - Part 41:  
Test method for the determination of the compressive  
strength of hydraulically bound mixtures

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN 13286-41:2021 sisaldab Euroopa standardi EN 13286-41:2021 ingliskeelset teksti.	This Estonian standard EVS-EN 13286-41:2021 consists of the English text of the European standard EN 13286-41:2021.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 03.11.2021.	Date of Availability of the European standard is 03.11.2021.
Standard on kättesaadav Eesti Standardimis- ja Akrediteerimiskeskusest.	The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 93.080.20

**Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele**

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autoriõiguse kaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

**The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation**

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about standards copyright protection, please contact the Estonian Centre for Standardisation and Accreditation: Homepage [www.evs.ee](http://www.evs.ee); phone +372 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

English Version

Unbound and hydraulically bound mixtures - Part 41: Test  
method for the determination of the compressive strength  
of hydraulically bound mixtures

Mélanges traités et mélanges non traités aux liants  
hydrauliques - Partie 41: Méthode d'essai pour la  
détermination de la résistance à la compression des  
mélanges traités aux liants hydrauliques

Ungebundene und hydraulisch gebundene Gemische -  
Teil 41: Prüfverfahren zur Bestimmung der  
Druckfestigkeit hydraulisch gebundener Gemische

This European Standard was approved by CEN on 5 July 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

<b>Contents</b>	<b>Page</b>
<b>European foreword .....</b>	<b>3</b>
<b>1 Scope.....</b>	<b>5</b>
<b>2 Normative references.....</b>	<b>5</b>
<b>3 Terms and definitions.....</b>	<b>5</b>
<b>4 Principle .....</b>	<b>5</b>
<b>5 Apparatus .....</b>	<b>6</b>
<b>5.1 Compression testing machine .....</b>	<b>6</b>
<b>6 Test specimen .....</b>	<b>6</b>
<b>7 Test procedure.....</b>	<b>6</b>
<b>7.1 Dimensions.....</b>	<b>6</b>
<b>7.2 Mass .....</b>	<b>6</b>
<b>7.3 Adjustment of the test specimen.....</b>	<b>6</b>
<b>7.4 Defective specimens .....</b>	<b>6</b>
<b>7.5 Specimen positioning.....</b>	<b>7</b>
<b>7.6 Loading .....</b>	<b>7</b>
<b>7.7 Assessment of type of failure.....</b>	<b>7</b>
<b>8 Expression of result .....</b>	<b>8</b>
<b>9 Test report.....</b>	<b>8</b>
<b>9.1 Compulsory information.....</b>	<b>8</b>
<b>9.2 Optional information.....</b>	<b>9</b>

## European foreword

This document (EN 13286-41:2021) has been prepared by Technical Committee CEN/TC 227 “Road materials”, the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2022, and conflicting national standards shall be withdrawn at the latest by May 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13286-41:2003.

The following changes have been made in comparison with EN 13286-41:2003:

- editorial changes;
- to cater for the wide range of strengths possible for hydraulically bound mixtures – from < 1 MPa to 50 MPa or more - an increase in the permitted ‘time window’ for rupture of the specimen.

This document is one of a series of standards as listed below.

- EN 13286-1, Unbound and hydraulically bound mixtures — Part 1: Test methods for laboratory reference density and water content — Introduction, general requirements and sampling
- EN 13286-2, Unbound and hydraulically bound mixtures — Part 2: Test methods for laboratory reference density and water content — Proctor compaction
- EN 13286-3, Unbound and hydraulically bound mixtures — Part 3: Test methods for laboratory reference density and water content — Vibrocompression with controlled parameters
- EN 13286-4, Unbound and hydraulically bound mixtures — Part 4: Test methods for laboratory reference density and water content — Vibrating hammer
- EN 13286-5, Unbound and hydraulically bound mixtures — Part 5: Test methods for laboratory reference density and water content — Vibrating table
- EN 13286-7, Unbound and hydraulically bound mixtures — Part 7: Cyclic load triaxial test for unbound mixtures
- EN 13286-40, Unbound and hydraulically bound mixtures — Part 40: Test method for the determination of the direct tensile strength of hydraulically bound mixtures
- EN 13286-41, Unbound and hydraulically bound mixtures — Part 41: Test method for the determination of the compressive strength of hydraulically bound mixtures
- EN 13286-42, Unbound and hydraulically bound mixtures — Part 42: Test method for the determination of the indirect tensile strength of hydraulically bound mixtures
- EN 13286-43, Unbound and hydraulically bound mixtures — Part 43: Test method for the determination of the modulus of elasticity of hydraulically bound mixtures

- EN 13286-44, Unbound and hydraulically bound mixtures — Part 44: Test method for the determination of the alpha coefficient of vitrified blastfurnace slag
- EN 13286-45, Unbound and hydraulically bound mixtures — Test methods — Part 45: Test method for the determination of the workability period of hydraulically bound mixtures
- EN 13286-46, Unbound and hydraulically bound mixtures — Part 46: Test method for the determination of the moisture condition value
- EN 13286-47, Unbound and hydraulically bound mixtures — Part 47: Test methods for the determination of California bearing ratio, immediate bearing index and linear swelling
- EN 13286-48, Unbound and hydraulically bound mixtures — Part 48: Test method for the determination of the degree of pulverisation
- EN 13286-49, Unbound and hydraulically bound mixtures — Part 49: Test method for the determination of the accelerated swelling of soil treated by lime and/or hydraulic binder
- EN 13286-50, Unbound and hydraulically bound mixtures — Part 50: Method for the manufacture of test specimens of hydraulically bound mixtures using Proctor equipment or vibrating table compaction
- EN 13286-51, Unbound and hydraulically bound mixtures — Part 51: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrating hammer compaction
- EN 13286-52, Unbound and hydraulically bound mixtures — Part 52: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrocompression
- EN 13286-53, Unbound and hydraulically bound mixtures — Part 53: Method for the manufacture of test specimens of hydraulically bound mixtures using axial compression
- CEN/TS 13286-54, Unbound and hydraulically bound mixtures — Part 54: Test method for the determination of frost susceptibility — Resistance to freezing and thawing of hydraulically bound mixtures

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## 1 Scope

This document describes a test method for the determination of the compressive strength of specimens of hydraulically bound mixtures. This document applies to specimens manufactured in the laboratory or prepared from cores.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12390-3:2019, *Testing hardened concrete - Part 3: Compressive strength of test specimens*

EN 13286-50, *Unbound and hydraulically bound mixtures - Part 50: Method for the manufacture of test specimens of hydraulically bound mixtures using Proctor equipment or vibrating table compaction*

EN 13286-51, *Unbound and hydraulically bound mixtures - Part 51: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrating hammer compaction*

EN 13286-52, *Unbound and hydraulically bound mixtures - Part 52: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrocompression*

EN 13286-53, *Unbound and hydraulically bound mixtures - Part 53: Methods for the manufacture of test specimens of hydraulically bound mixtures using axial compression*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### **hydraulically bound mixture**

mixture that hardens by hydraulic and/or pozzolanic and/or sulfatic and/or carbonatic reaction, which usually has a workability to suit compaction by rolling and which is generally used in bases, sub-bases and capping layers

### 3.2

#### **compressive strength**

stress at failure of a specimen when tested in uniaxial unconfined compression

### 3.3

#### **slenderness ratio**

ratio of the length to the diameter of a cylindrical specimen

## 4 Principle

A specimen is subjected to a compressive force until failure. The maximum load sustained by the specimen is recorded and the compressive strength is calculated.