

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



BASIC EMC PUBLICATION

PUBLICATION FONDAMENTALE EN CEM

**Electromagnetic compatibility (EMC) –  
Part 4-20: Testing and measurement techniques – Emission and immunity  
testing in transverse electromagnetic (TEM) waveguides**

**Compatibilité électromagnétique (CEM) –  
Partie 4-20: Techniques d'essai et de mesure – Essais d'émission et d'immunité  
dans les guides d'onde TEM**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



BASIC EMC PUBLICATION

PUBLICATION FONDAMENTALE EN CEM

**Electromagnetic compatibility (EMC) –  
Part 4-20: Testing and measurement techniques – Emission and immunity  
testing in transverse electromagnetic (TEM) waveguides**

**Compatibilité électromagnétique (CEM) –  
Partie 4-20: Techniques d'essai et de mesure – Essais d'émission et d'immunité  
dans les guides d'onde TEM**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-1083-0

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

|                                                                                       |    |
|---------------------------------------------------------------------------------------|----|
| FOREWORD.....                                                                         | 7  |
| INTRODUCTION.....                                                                     | 9  |
| 1 Scope.....                                                                          | 10 |
| 2 Normative references .....                                                          | 11 |
| 3 Terms, definitions and abbreviated terms .....                                      | 11 |
| 3.1 Terms and definitions.....                                                        | 11 |
| 3.2 Abbreviated terms.....                                                            | 14 |
| 4 General .....                                                                       | 15 |
| 5 TEM waveguide requirements.....                                                     | 15 |
| 5.1 General.....                                                                      | 15 |
| 5.2 General requirements for the use of TEM waveguides .....                          | 16 |
| 5.2.1 Test volume and maximum EUT size .....                                          | 16 |
| 5.2.2 Validation of usable test volume .....                                          | 16 |
| 5.3 Special requirements and recommendations for certain types of TEM waveguides..... | 23 |
| 5.3.1 Set-up of open TEM waveguides .....                                             | 23 |
| 5.3.2 Alternative TEM mode verification for a two-port TEM waveguide .....            | 23 |
| 5.3.3 TEM mode generation for a four-port TEM waveguide .....                         | 23 |
| 5.4 Figures for Clause 5 .....                                                        | 24 |
| 6 Overview of EUT types .....                                                         | 26 |
| 6.1 General.....                                                                      | 26 |
| 6.2 Small EUT .....                                                                   | 26 |
| 6.3 Large EUT .....                                                                   | 26 |
| 7 Laboratory test conditions.....                                                     | 26 |
| 7.1 General.....                                                                      | 26 |
| 7.2 Climatic conditions.....                                                          | 26 |
| 7.3 Electromagnetic conditions .....                                                  | 26 |
| 8 Evaluation and reporting of test results.....                                       | 27 |
| Annex A (normative) Emission measurements in TEM waveguides .....                     | 28 |
| A.1 Overview.....                                                                     | 28 |
| A.2 Test equipment .....                                                              | 28 |
| A.3 Correlating TEM waveguide voltages to electric field strength data .....          | 28 |
| A.3.1 General .....                                                                   | 28 |
| A.3.2 Correlation algorithms .....                                                    | 29 |
| A.4 Emission measurement correction factors .....                                     | 33 |
| A.4.1 Reference emission sources .....                                                | 33 |
| A.4.2 Arrangement of small EUTs .....                                                 | 34 |
| A.4.3 Calculation of the small EUT correction factor .....                            | 34 |
| A.5 Emission measurement procedures in TEM waveguides .....                           | 37 |
| A.5.1 EUT types.....                                                                  | 37 |
| A.5.2 EUT arrangement .....                                                           | 37 |
| A.6 Test report.....                                                                  | 38 |
| A.7 Figures for Annex A .....                                                         | 39 |
| Annex B (normative) Immunity testing in TEM waveguides.....                           | 44 |
| B.1 Overview.....                                                                     | 44 |
| B.2 Test equipment .....                                                              | 44 |

|                       |                                                                       |    |
|-----------------------|-----------------------------------------------------------------------|----|
| B.2.1                 | General .....                                                         | 44 |
| B.2.2                 | Description of the test facility .....                                | 44 |
| B.3                   | Field uniformity area calibration .....                               | 45 |
| B.4                   | Test levels .....                                                     | 45 |
| B.5                   | Test set-up .....                                                     | 45 |
| B.5.1                 | Arrangement of table-top equipment .....                              | 45 |
| B.5.2                 | Arrangement of floor-standing equipment .....                         | 46 |
| B.5.3                 | Arrangement of wiring .....                                           | 46 |
| B.6                   | Test procedures .....                                                 | 46 |
| B.7                   | Test results and test report .....                                    | 46 |
| B.8                   | Figures for Annex B .....                                             | 47 |
| Annex C (normative)   | HEMP transient testing in TEM waveguides .....                        | 49 |
| C.1                   | Overview .....                                                        | 49 |
| C.2                   | Immunity tests .....                                                  | 49 |
| C.2.1                 | General .....                                                         | 49 |
| C.2.2                 | Radiated test facilities .....                                        | 50 |
| C.2.3                 | Frequency domain spectrum requirements .....                          | 51 |
| C.3                   | Test equipment .....                                                  | 51 |
| C.4                   | Test set-up .....                                                     | 52 |
| C.5                   | Test procedure .....                                                  | 52 |
| C.5.1                 | General .....                                                         | 52 |
| C.5.2                 | Severity level and test exposures .....                               | 53 |
| C.5.3                 | Test procedure .....                                                  | 53 |
| C.5.4                 | Test execution .....                                                  | 54 |
| C.5.5                 | Execution of the radiated immunity test .....                         | 54 |
| C.6                   | Figure for Annex C .....                                              | 55 |
| Annex D (informative) | TEM waveguide characterization .....                                  | 56 |
| D.1                   | Overview .....                                                        | 56 |
| D.2                   | Distinction between wave impedance and characteristic impedance ..... | 56 |
| D.3                   | TEM wave .....                                                        | 57 |
| D.3.1                 | General .....                                                         | 57 |
| D.3.2                 | Free-space TEM mode .....                                             | 57 |
| D.3.3                 | Waveguides .....                                                      | 57 |
| D.4                   | Wave propagation .....                                                | 58 |
| D.4.1                 | General .....                                                         | 58 |
| D.4.2                 | Spherical propagation .....                                           | 58 |
| D.4.3                 | Plane wave propagation in free space .....                            | 58 |
| D.4.4                 | Velocity of propagation .....                                         | 58 |
| D.5                   | Polarization .....                                                    | 58 |
| D.6                   | Types of TEM waveguides .....                                         | 59 |
| D.6.1                 | General .....                                                         | 59 |
| D.6.2                 | Open TEM waveguides (striplines, etc.) .....                          | 60 |
| D.6.3                 | Closed TEM waveguides (TEM cells) .....                               | 60 |
| D.7                   | Frequency limitations .....                                           | 60 |
| D.8                   | Figures for Annex D .....                                             | 61 |
| Annex E (informative) | Calibration method for E-field probes in TEM waveguides .....         | 69 |
| E.1                   | Overview .....                                                        | 69 |
| E.2                   | Probe calibration requirements .....                                  | 69 |
| E.2.1                 | General .....                                                         | 69 |

|                       |                                                                                                                             |     |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------|-----|
| E.2.2                 | Calibration frequency range .....                                                                                           | 69  |
| E.2.3                 | Calibration volume .....                                                                                                    | 70  |
| E.2.4                 | Probe dimensions .....                                                                                                      | 70  |
| E.2.5                 | Perturbations of TEM waveguide fields due to the probe .....                                                                | 70  |
| E.2.6                 | Frequency steps .....                                                                                                       | 71  |
| E.2.7                 | Field strength .....                                                                                                        | 71  |
| E.3                   | Requirements for calibration instrumentation .....                                                                          | 71  |
| E.3.1                 | Specifications of TEM waveguide .....                                                                                       | 71  |
| E.3.2                 | Harmonics and spurious signals .....                                                                                        | 72  |
| E.3.3                 | Probe fixture .....                                                                                                         | 72  |
| E.3.4                 | Measuring net power to a transmitting device using directional couplers .....                                               | 72  |
| E.4                   | E-field probe calibration .....                                                                                             | 73  |
| E.4.1                 | Calibration methods .....                                                                                                   | 73  |
| E.4.2                 | Calibration procedure using a two-port TEM waveguide .....                                                                  | 73  |
| E.4.3                 | Calibration procedure using one-port TEM waveguide .....                                                                    | 74  |
| E.5                   | Figures for Annex E .....                                                                                                   | 77  |
| Annex F (informative) | Instrumentation uncertainty of emission measurement results .....                                                           | 79  |
| F.1                   | Radiated disturbance measurements using a TEM waveguide .....                                                               | 79  |
| F.1.1                 | Measurand for radiated disturbance measurements using a TEM waveguide .....                                                 | 79  |
| F.1.2                 | Symbols of input quantities common to all disturbance measurements .....                                                    | 79  |
| F.1.3                 | Symbols of input quantities specific to TEM waveguide measurements .....                                                    | 79  |
| F.2                   | Input quantities to be considered for radiated disturbance measurements using a TEM waveguide .....                         | 79  |
| F.3                   | Uncertainty budget and rationale for the input quantities for radiated disturbance measurements using a TEM waveguide ..... | 80  |
| F.3.1                 | Uncertainty budget for radiated disturbance measurements using a TEM waveguide .....                                        | 80  |
| F.3.2                 | Rationale for the estimates of input quantities for radiated disturbance measurements using a TEM waveguide .....           | 81  |
| F.4                   | Figures for Annex F .....                                                                                                   | 87  |
| Annex G (informative) | Measurement uncertainty of immunity testing due to test instrumentation .....                                               | 89  |
| G.1                   | General symbols .....                                                                                                       | 89  |
| G.2                   | Symbol and definition of the measurand .....                                                                                | 89  |
| G.3                   | Symbols for input quantities .....                                                                                          | 89  |
| G.4                   | Example: Uncertainty budget for immunity test .....                                                                         | 89  |
| G.5                   | Rationale for the estimates of input quantities .....                                                                       | 90  |
| Annex H (informative) | Correlation of emission and immunity limits between EMC test facilities .....                                               | 93  |
| H.1                   | Overview .....                                                                                                              | 93  |
| H.2                   | Dipole in free space (representing FAR set-up) .....                                                                        | 93  |
| H.3                   | Dipole in half space (representing OATS or SAC set-up) .....                                                                | 95  |
| H.4                   | Dipole in a TEM-mode transmission line .....                                                                                | 96  |
| H.5                   | Dipole in a reverberation chamber .....                                                                                     | 97  |
| H.6                   | Correlation .....                                                                                                           | 98  |
| H.7                   | Example of emission limits .....                                                                                            | 99  |
| H.8                   | Figures for Annex H .....                                                                                                   | 100 |
| Annex I (informative) | TEM waveguide transient characterization .....                                                                              | 103 |
| I.1                   | Overview .....                                                                                                              | 103 |

|     |                                                     |     |
|-----|-----------------------------------------------------|-----|
| I.2 | Test equipment .....                                | 103 |
| I.3 | Test set-up .....                                   | 103 |
| I.4 | TEM waveguide characterization by correlation ..... | 104 |
| I.5 | Quantification of the Pcc .....                     | 105 |
| I.6 | Performable transient test signals .....            | 105 |
| I.7 | Figures for Annex I .....                           | 106 |
|     | Bibliography .....                                  | 108 |

|                                                                                                                                                 |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 1 – Flowchart of TEM mode and field uniformity verification procedure with the “constant forward power” method (see 5.2.2.4.1) .....     | 24 |
| Figure 2 – Flowchart of TEM mode and field uniformity verification procedure with the “constant field strength” method (see 5.2.2.4.2) .....    | 25 |
| Figure A.1 – Routing the exit cable to the corner at the ortho-angle and the lower edge of the test volume in a TEM waveguide (see A.5.2) ..... | 39 |
| Figure A.2 – Basic ortho-axis EUT positioner or manipulator (see 3.1.13, A.4.2, A.5.1.2, A.5.2) .....                                           | 40 |
| Figure A.3 – Die pattern and axis alignment for an EUT [26] (see A.3.2.3.2) .....                                                               | 41 |
| Figure A.4 – Non-redundant twelve-face and axis orientations for a typical EUT [26] (see A.3.2.3.2) .....                                       | 42 |
| Figure A.5 – Open-area test site (OATS) emission measurements geometry (see A.3.2.4) .....                                                      | 43 |
| Figure B.1 – Example of test set-up for single-polarization TEM waveguide (see Clause B.5) .....                                                | 47 |
| Figure B.2 – Uniform area calibration points in a TEM waveguide (see Clause B.3) .....                                                          | 48 |
| Figure C.1 – Pulse waveform frequency domain spectral magnitude between 100 kHz and 300 MHz (see C.2.1) .....                                   | 55 |
| Figure D.1 – Simple waveguide (no TEM mode) (see D.3.3) .....                                                                                   | 61 |
| Figure D.2 – Example of waveguides supporting TEM-mode propagation (see D.3.3) .....                                                            | 61 |
| Figure D.3 – E-field polarization vector (see Clause D.5) .....                                                                                 | 61 |
| Figure D.4 – Simple transmission line model for TEM mode propagation (see D.6.1) .....                                                          | 62 |
| Figure D.5 – One- and two-port TEM waveguide concepts (see D.6.1) .....                                                                         | 62 |
| Figure D.6 – Operation of four-port TEM waveguides (see D.6.1) .....                                                                            | 62 |
| Figure D.7 – Two-port TEM cell (symmetric septum) (see D.6.1 and D.6.3) .....                                                                   | 63 |
| Figure D.8 – One-port TEM cell (asymmetric septum) (see D.6.1 and D.6.3) .....                                                                  | 64 |
| Figure D.9 – Stripline (two plates) (see D.6.1 and D.6.2) .....                                                                                 | 66 |
| Figure D.10 – Stripline (four plates, balanced feed) (see D.6.1) .....                                                                          | 67 |
| Figure D.11 – Four-port TEM waveguide (symmetric parallel septa) (see D.6.1 and D.6.3) .....                                                    | 68 |
| Figure E.1 – Example of test points for calibration volume validation (see E.2.3) .....                                                         | 77 |
| Figure E.2 – Set-up for validation of probe perturbation (see E.2.5) .....                                                                      | 77 |
| Figure E.3 – Set-up for measuring net power to a transmitting device (not to scale) (see E.3.4) .....                                           | 77 |
| Figure E.4 – Example set-up for E-field probe calibration with two-port TEM waveguide (see E.4.2) .....                                         | 78 |
| Figure E.5 – Example set-up for E-field probe calibration with one-port TEM waveguide and alternative method (see E.4.3.2) .....                | 78 |
| Figure E.6 – Equivalent circuit of monopole antenna and measuring apparatus (see E.4.3.3) .....                                                 | 78 |

|                                                                                                                                                                                                                  |     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure F.1 – Deviation of the QP detector level indication from the signal level at receiver input for two cases, a sine-wave signal and an impulsive signal with a pulse repetition frequency of 100 Hz .....   | 87  |
| Figure F.2 – Deviation of the peak detector level indication from the signal level at receiver input for two cases, a sine-wave signal and an impulsive signal with a pulse repetition frequency of 100 Hz ..... | 88  |
| Figure H.1 – Representation of a short centre-fed dipole and a more general source representing an EUT (see Clause H.2) .....                                                                                    | 100 |
| Figure H.2 – Vertical source and receiving dipoles located over a perfectly-conducting ground plane of infinite extent (see Clause H.3) .....                                                                    | 100 |
| Figure H.3 – Two types of TEM cells with a vertically polarized dipole source and the source to receive port geometry defined (see Clause H.4) .....                                                             | 101 |
| Figure H.4 – Reverberation chamber with a source dipole, a stirrer to randomize the fields, and a general receive antenna (see Clause H.5) .....                                                                 | 101 |
| Figure H.5 – TEM waveguide Class A and Class B emission limits correlated from CISPR 32 [68] (see Clause H.7) .....                                                                                              | 102 |
| Figure I.1 – Test set-up .....                                                                                                                                                                                   | 106 |
| Figure I.2 – Signal windowing .....                                                                                                                                                                              | 107 |
| Figure I.3 – Example of a heatmap – Pcc for a test point in the uniform area .....                                                                                                                               | 107 |
| Table 1 – Values $k$ for expanded uncertainty with normal distribution .....                                                                                                                                     | 18  |
| Table B.1 – Uniform area calibration points .....                                                                                                                                                                | 45  |
| Table B.2 – Test levels .....                                                                                                                                                                                    | 45  |
| Table C.1 – Radiated immunity test levels defined for this document .....                                                                                                                                        | 50  |
| Table E.1 – Calibration frequencies .....                                                                                                                                                                        | 71  |
| Table E.2 – Calibration field strength level .....                                                                                                                                                               | 71  |
| Table F.1 – Uncertainty budget for radiated disturbance measurement results using a TEM waveguide from 30 MHz to 1 000 MHz (example) .....                                                                       | 80  |
| Table F.2 – Uncertainty budget for radiated disturbance measurement results using a TEM waveguide from 1 GHz to 6 GHz (example) .....                                                                            | 81  |
| Table F.3 – Values of $S_{lim}$ for 30 MHz to 1 000 MHz .....                                                                                                                                                    | 83  |
| Table F.4 – Values of $S_{lim}$ for 1 GHz to 6 GHz .....                                                                                                                                                         | 84  |
| Table G.1 – Example uncertainty budget of the immunity test level .....                                                                                                                                          | 90  |
| Table H.1 – Summary of the emission correlation parameters .....                                                                                                                                                 | 99  |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTROMAGNETIC COMPATIBILITY (EMC) –****Part 4-20: Testing and measurement techniques –  
Emission and immunity testing in transverse  
electromagnetic (TEM) waveguides****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61000-4-20 has been prepared by subcommittee 77B: High frequency phenomena, of IEC technical committee 77: Electromagnetic compatibility, in cooperation with CISPR (International Special Committee on Radio Interference) subcommittee A: Radio-interference measurements and statistical methods.

It forms Part 4-20 of IEC 61000. It has the status of a basic EMC publication in accordance with IEC Guide 107.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) provide information on the testing of large EUTs (including cables);

- b) apply the work on measurement uncertainties by adapting the work completed in CISPR and TC 77 (for emissions and immunity);
- c) update the validation procedure for the test volume regarding field uniformity and TEM mode verification;
- d) provide information concerning two-port and four-port TEM waveguides;
- e) add a new informative annex (Annex I) dealing with transient TEM waveguide characterization; and
- f) add information dealing with dielectric test stands for EUTs.

The text of this International Standard is based on the following documents:

| Draft        | Report on voting |
|--------------|------------------|
| 77B/853/FDIS | 77B/855/RVD      |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

A list of all parts of the IEC 61000 series, published under the general title *Electromagnetic compatibility (EMC)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

### **Part 1: General**

General considerations (introduction, fundamental principles)

Definitions, terminology

### **Part 2: Environment**

Description of the environment

Classification of the environment

Compatibility levels

### **Part 3: Limits**

Emission limits

Immunity limits (in so far as they do not fall under the responsibility of the product committees)

### **Part 4: Testing and measurement techniques**

Measurement techniques

Testing techniques

### **Part 5: Installation and mitigation guidelines**

Installation guidelines

Mitigation methods and devices

### **Part 6: Generic standards**

### **Part 9: Miscellaneous**

Each part is further subdivided into several parts, published either as International Standards, Technical Specifications or Technical Reports, some of which have already been published as sections. Others are and will be published with the part number followed by a dash and a second number identifying the subdivision (example: IEC 61000-6-1).

This part is an International Standard which gives emission, immunity and HEMP and IEMI transient testing requirements.

## **ELECTROMAGNETIC COMPATIBILITY (EMC) –**

### **Part 4-20: Testing and measurement techniques – Emission and immunity testing in transverse electromagnetic (TEM) waveguides**

#### **1 Scope**

This part of IEC 61000 focuses on emission and immunity test methods for electrical and electronic equipment using various types of transverse electromagnetic (TEM) waveguides. These types include open structures (for example striplines and electromagnetic pulse simulators) and closed structures (for example TEM cells). These structures can be further classified as one-port, two-port, or multi-port TEM waveguides. The frequency range depends on the specific testing requirements and the specific TEM waveguide type.

The object of this document is to describe

- TEM waveguide characteristics, including typical frequency ranges and equipment-under-test (EUT) size limitations;
- TEM waveguide validation methods for electromagnetic compatibility (EMC) tests;
- the EUT (i.e. EUT cabinet and cabling) definition;
- test set-ups, procedures, and requirements for radiated emission measurements in TEM waveguides; and
- test set-ups, procedures, and requirements for radiated immunity testing in TEM waveguides.

NOTE Test methods are defined in this document to measure the effects of electromagnetic radiation on equipment and the electromagnetic emissions from the equipment concerned. The simulation and measurement of electromagnetic radiation is not adequately exact for the quantitative determination of effects for all end-use installations. The test methods defined are structured for a primary objective of establishing adequate reproducibility of results at various test facilities for qualitative analysis of effects.

This document does not intend to specify the tests to be applied to any particular apparatus or system(s). The main intention of this document is to provide a general basic reference for all interested product committees of the IEC. For radiated emission measurements, product committees select emission limits and measurement methods in consultation with CISPR standards. For radiated immunity testing, product committees remain responsible for the appropriate choice of immunity tests and immunity test limits to be applied to equipment within their scope. This document describes test methods that are separate from those of IEC 61000-4-3 [34].<sup>1</sup>

---

<sup>1</sup> Numbers in square brackets refer to the Bibliography.

These other distinct test methods may be used when so specified by product committees, in consultation with CISPR and TC 77.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, *International Electrotechnical Vocabulary (IEV) – Part 161: Electromagnetic compatibility*

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-4, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements*

## 3 Terms, definitions and abbreviated terms

### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1.1

##### **anechoic material**

material that exhibits the property of absorbing, or otherwise reducing, the level of electromagnetic energy reflected from that material

#### 3.1.2

##### **broadband transmission-line termination**

termination which combines a low-frequency discrete-component load, to match the characteristic impedance of the TEM waveguides (typically 50  $\Omega$ ), and a volume of high-frequency anechoic material

#### 3.1.3

##### **characteristic impedance**

for any constant phase wave-front, magnitude of the ratio of the voltage between the inner conductor and the outer conductor to the current on either conductor and which is independent of the voltage/current magnitudes and depends only on the cross-sectional geometry of the transmission line

Note 1 to entry: TEM waveguides are typically designed to have a characteristic impedance of 50  $\Omega$ . TEM waveguides with a characteristic impedance of 100  $\Omega$  are often used for transient testing.

#### 3.1.4

##### **correlation algorithm**

mathematical routine for converting TEM waveguide voltage measurements to open-area test sites (OATS), semi-anechoic chamber (SAC), or free space field strength levels