MOOTORIKÜTUSED. VEDELGAAS. NÕUDED JA KATSEMEETODID

Automotive fuels - LPG - Requirements and test methods



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 589:2018+A1:2022 sisaldab Euroopa standardi EN 589:2018+A1:2022 ingliskeelset teksti.

This Estonian standard EVS-EN 589:2018+A1:2022 consists of the English text of the European standard EN 589:2018+A1:2022.

Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas

This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.

Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 23.02.2022.

Date of Availability of the European standard is 23.02.2022.

Standard on kättesaadav Eesti Standardimis-ja Akrediteerimiskeskusest.

The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

ICS 75.160.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis-ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis-ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 589:2018+A1

February 2022

ICS 75.160.20

Supersedes EN 589:2018

English Version

Automotive fuels - LPG - Requirements and test methods

Carburants pour automobiles - GPL - Exigences et méthodes d'essai

Kraftstoffe - Flüssiggas - Anforderungen und Prüfverfahren

This European Standard was approved by CEN on 19 October 2018 and includes Amendment 1 approved by CEN on 6 January 2022.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Con	itents	Page
Euro	pean foreword	3
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Sampling	6
5	Pump marking	6
6	Requirements and test methods	7
6.1	General	
6.2	Water content	
6.3	Odour	
6.4	Density	7
6.5	Precision and dispute	7
7	Remarks concerning vehicle application issues like residues in vaporizers or injectors	9
Anne	ex A (normative) Test method for odour of LPG	
A.1	Introduction	
A.2	Principle	10
A.3	Material	
A.4	Apparatus	10
A.5	Procedure	
A.6	Expression of results	12
Anne	ex B (normative) Method of calculation of the Motor Octane Number (MON) from compositional analysis of LPG	
B.1	Introduction	13
B.2	Principle	13
B.3	Determination	
B.4	Calculation and expression of results	13
B.5	Reporting	
Anne	ex C (normative) Absolute vapour pressure blending factors	15
Anne	ex D (informative) Seasonal gauge vapour pressure limits	16
Bibli	ography	17

European foreword

This document (EN 589:2018+A1:2022) has been prepared by Technical Committee CEN/TC 19 "Gaseous and liquid fuels, lubricants and related products of petroleum, synthetic and biological origin", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2022, and conflicting national standards shall be withdrawn at the latest by August 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes (A) EN 589:2018 (A).

This document includes Amendment 1 approved by CEN on 6 January 2022.

The start and finish of text introduced or altered by amendment is indicated in the text by tags $\boxed{\mathbb{A}}$.

This is the 7th edition of EN 589. The main technical changes include:

- a) reduction of the sulfur limit value to 30 mg/kg;
- b) removal of ASTM D 3246, sulfur determination by oxidative microcoulometry, as being incapable of measuring that level;
- c) addition of single limit value for propane in Table 1;
- d) addition of a single limit value for 1,3 butadiene in Table 1 due to CLP requirements [5];
- e) introduction of new test methods for the determination of 1,3 butadiene and hydrocarbon composition (DIN 51619), of low levels of sulfur content (EN 17178) and of evaporation residue (EN 16423) (A);
- f) addition of Clause 7 "Remarks concerning vehicle application issues like residues in vaporizers or injectors";
- g) permission to use alternative odour tests added to sub-clause 6.3. The odour test according to Annex A is not a precise test method with any given precision. Odour is subjectively perceived, not measured. For this reason it is hard to define a referee method;
- h) inclusion of reference to EN 16942 regarding pump marking in line with the requirements set by the new Directive 2014/94/EU [1].
- The following is a list of significant technical changes between this amendment EN 589:2018/A1:2022 and the actual European Standard, EN 589:2018:
- update of revised test method standards;
- adjustment of vapour pressure reporting format to the format required by the test methods EN ISO 8973 and Annex C;

- removal of the increase of the propane content by 2022-05-01;
- modification of the footnote to table g to Table 1 on the performance requirement. lacktriangle

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, iic, iia, Lu. a, Serbia, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This document specifies requirements and test methods for marketed and delivered automotive liquefied petroleum gas (LPG), with LPG defined as low pressure liquefied gas composed of one or more light hydrocarbons which are assigned to UN 1011, 1075, 1965, 1969 or 1978 only and which consists mainly of propane, propene, butane, butane isomers, butenes with traces of other hydrocarbon gases.

This standard is applicable to automotive LPG for use in LPG engine vehicles designed to run on automotive LPG.

NOTE For the purposes of this European Standard, the terms "(m/m)" and "(V/V)" are used to represent respectively the mass fraction, μ , and the volume fraction, φ .

WARNING — Attention is drawn to the risk of fire and explosion when handling LPG and to the hazard to health arising through inhalation of excessive amounts of LPG.

LPG is a highly volatile hydrocarbon liquid which is normally stored under pressure. If the pressure is released large volumes of gas will be produced which form flammable mixtures with air over the range of approximately 2 % (V/V) to 10 % (V/V). This European Standard involves the sampling, handling and testing of LPG. Naked flames, unprotected electrical equipment electrostatic hazards etc. are sources of ignition for LPG.

LPG in liquid form can cause cold burns to the skin. The national health and safety regulations apply.

LPG is heavier than air and accumulates in cavities. There is a danger of suffocation when inhaling high concentrations of LPG.

CAUTION — One of the tests described in this European Standard involves the operator inhaling a mixture of air and LPG vapour. Particular attention is drawn to the cautionary statement provided in A.1, where this method is referred to.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15469, Petroleum products - Test method for free water in liquefied petroleum gas by visual inspection

EN 15470, Liquefied petroleum gases - Determination of dissolved residues - High temperature Gas chromatographic method

EN 15471, Liquefied petroleum gases - Determination of dissolved residues - High-temperature gravimetric method

EN 16423, Liquefied petroleum gases - Determination of dissolved residue - Gas chromatographic method using liquid, on-column injection

EN 16942, Fuels - Identification of vehicle compatibility - Graphical expression for consumer information

A) EN 17178, Liquid petroleum products — Determination of the total volatile sulfur content in liquefied petroleum gases by ultraviolet fluorescence spectroscopy (A)

EN 27941, Commercial propane and butane - Analysis by gas chromatography (ISO 7941)

EN ISO 4256, Liquefied petroleum gases - Determination of gauge pressure - LPG method (ISO 4256)

EN ISO 4257, Liquefied petroleum gases - Method of sampling (ISO 4257)

EN ISO 4259-2, Petroleum and related products - Precision of measurement methods and results - Part 2: Interpretation and application of precision data in relation to methods of test (ISO 4259-2)

EN ISO 6251, Liquefied petroleum gases - Corrosiveness to copper - Copper strip test (ISO 6251)

EN ISO 8819, Liquefied petroleum gases - Detection of hydrogen sulfide - Lead acetate method (ISO 8819)

EN ISO 8973, Liquefied petroleum gases - Calculation method for density and vapour pressure (ISO 8973)

DIN 51619, Testing of mineral oil hydrocarbons — Determination of the composition of liquid petroleum gases — Gas chromatographic analysis under special consideration of 1,3-butadiene with mass fractions $\leq 0.1\%$ (m/m)

ASTM D6667-14, Standard Test Method for Determination of Total Volatile Sulfur in Gaseous Hydrocarbons and Liquefied Petroleum Gases by Ultraviolet Fluorescence

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1

liquefied petroleum gas

LPG

petroleum gas that can be stored and/or handled in the liquid phase under moderate conditions of pressure and at ambient temperature, consisting predominantly of propane and butanes, with small proportions of propene, butenes and pentanes/pentenes

4 Sampling

Samples shall be taken as described in EN ISO 4257 and/or in accordance with the requirements of national standards or regulations for the sampling of automotive LPG. The national requirements shall be set out in detail or shall be referred to by reference in a national annex to this European Standard.

In view of the sensitivity of some of the test methods referred to in this European Standard, particular attention shall be paid to compliance with any guidance on sampling containers which is included in the test method standard.

IMPORTANT — It is important that the sampling procedure is followed in detail in order to avoid evaporation losses.

Before sampling from the dispenser hose, 20 l of product should be pumped or recirculated, in order to obtain a representative sample.

5 Pump marking

Information to be marked on dispensing pumps and nozzles used for delivering automotive LPG, and the dimensions of the label shall be in accordance with EN 16942.