



Edition 2.0 2022-03

TECHNICAL REPORT



High-voltage direct current (HVDC) power transmission using voltage sourced converters (VSC)





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.





Edition 2.0 2022-03

TECHNICAL REPORT



High-voltage direct current (HVDC) power transmission using voltage sourced converters (VSC)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ISBN 978-2-8322-1090-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F(DREWO	RD	6
1	Scop	e	8
2	Norm	native references	8
3	Terms and definitions		
	3.1	General	8
	3.2	Letter symbols	
	3.3	VSC transmission	
	3.4	Power losses	
4	VSC	transmission overview	
	4.1	Basic operating principles of VSC transmission	11
	4.1.1		
	4.1.2		
	4.1.3		
	4.1.4		
	4.2	Design life	
	4.3	VSC transmission configurations	15
	4.3.1		
	4.3.2		
	4.3.3		
	4.3.4		
	4.3.5		
	4.3.6	Series connection of two converters	19
	4.3.7	Parallel and series connection of more than two converters	19
	4.4	Semiconductors for VSC transmission	
5	VSC	transmission converter topologies	21
	5.1	General	21
	5.2	Converter topologies with VSC valves of switch type	
	5.2.1		
	5.2.2		
	5.2.3		
	5.3	Converter topologies with VSC valves of the controllable voltage source type	
	5.3.1		
	5.3.2	MMC topology with VSC levels in half-bridge topology	26
	5.3.3		
	5.3.4		
	5.3.5		
	5.4	VSC valve design considerations	29
	5.4.1	Reliability and failure mode	29
	5.4.2	Current rating	29
	5.4.3	Transient current and voltage requirements	29
	5.4.4	Diode requirements	30
	5.4.5	Additional design details	30
	5.5	Other converter topologies	
	5.6	Other equipment for VSC transmission schemes	
	5.6.1	General	
	5.6.2	Power components of a VSC transmission scheme	31

	5.6.3	VSC substation circuit breaker	32
	5.6.4	AC system side harmonic filters	32
	5.6.5	Radio frequency interference filters	32
	5.6.6	Interface transformers and phase reactors	32
	5.6.7	Valve reactor	33
	5.6.8	DC capacitors	33
	5.6.9	DC reactor	35
	5.6.1	0 DC filter	36
	5.6.1	1 Dynamic braking system	36
6	Over	view of VSC controls	36
	6.1	General	36
	6.2	Operational modes and operational options	
	6.3	Power transfer	
	6.3.1		
	6.3.2		
	6.4	Reactive power and AC voltage control	
	6.4.1		
	6.4.2		
	6.5	Black start capability	
	6.6	Supply from a wind farm	
7		dy-state operation	
-	7.1	Steady-state capability	
	7.2	Converter power losses	
8		mic performance	42
		AC system disturbances	
	8.1		
	8.2	DC system disturbances	42
	8.2.1		
	8.2.2		
^	8.3	Internal faults	
9		C performance requirements	
			44
	9.2	Wave distortion	
	9.3	Fundamental and harmonics	
	9.3.1		45
	9.3.2		
	9.4	Harmonic voltages on power systems due to VSC operation	46
	9.5	Design considerations for harmonic filters (AC side)	46
	9.6	DC side filtering	
10		onmental impact	
	10.1	General	
	10.2	Audible noise	
	10.3	Electric and magnetic fields (EMF)	
	10.4	Electromagnetic compatibility (EMC)	
11	Testi	ng and commissioning	48
	11.1	General	48
	11.2	Factory tests	49
	11.2.	1 Component tests	49
	11.2.	2 Control system tests	49

11.3	Commissioning tests/system tests	49
11.3.	1 General	49
11.3.2	Precommissioning tests	50
11.3.3	3 Subsystem tests	50
11.3.4	,	50
	nformative) Functional specification requirements for VSC transmission	55
A.1	General	55
A.2	Purchaser and manufacturer information requirements	55
A.2.1	General	
A.2.2	General requirements	56
A.2.3	Detailed descriptions	57
Annex B (i	informative) Modulation strategies for 2-level converters	61
B.1	Carrier wave PWM	61
B.2	Selective harmonic elimination modulation	62
Bibliograp	hy	64
	/6	
Figure 1 –	Major components that can be found in a VSC substation	9
_	Diagram of a generic voltage source converter	
•	Principle of active power control	
•	Principle of reactive power control	
•	A point-to-point VSC transmission scheme	
_	VSC transmission with a symmetrical monopole	
•	VSC transmission with an asymmetrical monopole with metallic return	
•	VSC transmission with an asymmetrical monopole with earth return	
•	VSC transmission in bipolar configuration with earth return	
•	VSC transmission in bipolar configuration with dedicated metallic return	
•	– VSC transmission in rigid bipolar configuration	
-	– Parallel connection of two converter units	
Figure 13	Symbol of a turn-off semiconductor device and associated free-wheeling	
	– Symbol of an IGBT and associated free-wheeling diode	
_	Diagram of a three-phase 2-level converter and associated AC waveform	20
for one ph	ase	23
	Single-phase AC output for 2-level converter with PWM switching at 21 amental frequency	23
	Diagram of a three-phase 3-level NPC converter and associated AC for one phase	24
Figure 18 21 times fo	Single-phase AC output for 3-level NPC converter with PWM switching at undamental frequency	25
Figure 19	Electrical equivalent for a converter with VSC valves acting like a le voltage source	
Figure 20	VSC valve level arrangement and equivalent circuit in MMC topology in topology	
_	 Converter block arrangement with MMC topology in half-bridge topology 	
Figure 22	VSC valve level arrangement and equivalent circuit in MMC topology with	
	topology	28

Figure 23 – Typical SSOA for the IGBT								
Figure 24 – A 2-level VSC bridge with the IGBTs turned off	30							
Figure 25 – Representing a VSC unit as an AC voltage of magnitude U and phase angle δ behind reactance	36							
Figure 26 – Concept of vector control								
Figure 27 – VSC power controller								
Figure 28 – AC voltage controller								
							Figure 32 – Equivalent circuit at the PCC of the VSC	46
							Figure B.1 – Voltage harmonics spectra of a 2-level VSC with carrier frequency at 21st	
							Figure B.2 – Phase output voltage for selective harmonic elimination modulation	
(SHEM)	63							
4								
O .								
	4							

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION USING VOLTAGE SOURCED CONVERTERS (VSC)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 62543 has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment. It is a Technical Report.

This second edition cancels and replaces the first edition published in 2011, Amendment 1:2013 and Amendment 2:2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) in Clause 3, some redundant definitions which were identical to those listed in IEC 62747 have been deleted;
- b) in 4.3.4, description and diagrams have been added for the cases of a bipole with dedicated metallic return and a rigid bipole;
- c) in 4.4, mention is made of the bi-mode insulated gate transistor (BiGT) and injection enhanced gate transistor (IEGT) as possible alternatives to the IGBT;

d) in 5.6, the reference to common-mode blocking reactors has been deleted since these are very rarely used nowadays.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
22F/649/DTR	22F/669/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

HIGH-VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION USING VOLTAGE SOURCED CONVERTERS (VSC)

1 Scope

This document gives general guidance on the subject of voltage sourced converters (VSC) used for transmission of power by high voltage direct current (HVDC). It describes converters that are not only voltage sourced (containing a capacitive energy storage medium and where the polarity of DC voltage remains fixed) but also self-commutated, using semiconductor devices which can both be turned on and turned off by control action. The scope includes 2-level and 3-level converters with pulse-width modulation (PWM), along with multi-level converters, modular multi-level converters and cascaded two-level converters, but excludes 2-level and 3-level converters operated without PWM, in square-wave output mode.

HVDC power transmission using voltage sourced converters is known as "VSC transmission".

The various types of circuit that can be used for VSC transmission are described in this document, along with their principal operational characteristics and typical applications. The overall aim is to provide a guide for purchasers to assist with the task of specifying a VSC transmission scheme.

Line-commutated and current-sourced converters are specifically excluded from this document.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62501, Voltage sourced converter (VSC) valves for high-voltage direct current (HVDC) power transmission – Electrical testing

IEC 62747, Terminology for voltage-sourced converters (VSC) for high-voltage direct current (HVDC) systems

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62747, IEC 62501 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 General

Basic terms and definitions for voltage sourced converters used for HVDC transmission are given in IEC 62747. Terminology on electrical testing of VSC valves for HVDC transmission is given in IEC 62501.