
**Graphic technology — Image
quality evaluation methods for
printed matter —**

**Part 11:
Colour gamut analysis**

*Technologie graphique — Méthodes d'évaluation de la qualité
d'image pour les imprimés —*

Partie 11: Analyse de la gamme des couleurs



This document is a preview generated by ELS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Describing a colour gamut	2
4.1 General	2
4.2 Requirements of a gamut boundary description	2
4.3 Device gamut and usable gamut	3
4.4 Procedures for describing a colour gamut	3
4.4.1 General	3
4.4.2 Procedure for describing the colour gamut of a reproduction system based on its ICC profile	4
4.4.3 Procedure for describing the device gamut of a reproduction system based on its characterization model	5
4.4.4 Procedure for describing the device gamut of a reproduction system based on measurement of a printed gamut target	5
4.4.5 Procedure for describing the device gamut of a reproduction system based on characterization data	5
5 Computing the volume of a colour reproduction gamut	6
5.1 General	6
5.2 Volume of a single gamut	6
5.2.1 Volume calculation	6
5.2.2 Verifying the volume calculation	7
5.3 Volume of the intersection of two gamuts	8
5.3.1 General	8
5.3.2 Determining if a coordinate is inside or outside a gamut	8
6 Comparing colour gamuts	9
6.1 General	9
6.2 GCI	9
6.3 Gamut coverage	9
6.4 Out-of-gamut volume proportion	9
7 Encoding and communicating a colour gamut description	9
Annex A (informative) Images for use in determining the gamut boundary of RGB and CMYK printing processes	11
Annex B (informative) Gamut volumes for a set of reference profiles	12
Annex C (informative) Errors in triangulation	13
Annex D (normative) Media-relative colour gamuts	15
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

This second edition cancels and replaces the first edition (ISO/TS 18621-11:2019), which has been technically revised.

The main changes are as follows:

- [Formula \(1\)](#) has been corrected;
- requirements for conformance were clarified throughout;
- the list of example gamut volumes in [Table B.1](#) has been revised.

A list of all parts in the ISO 18621 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The colour gamut that can be achieved by a reproduction system is an important attribute. It enables users to compare the colour reproduction capabilities of different printing systems and to determine whether one system can simulate all the colours available in another. This document describes procedures to define and compare colour gamuts.

Given a set of coordinates known to lie on the surface of a colour gamut, the volume of the gamut can be determined by segmenting the gamut into a series of tetrahedra, computing the volume of each tetrahedron and summing the results. For a reproduction process with three colour components, a colour will lie on the surface if it satisfies the condition that at least one component has a value of 0 or 1, where 1 represents the maximum amount of the colour component. However, printing processes usually have four or more colour components (e.g. Cyan, Magenta, Yellow and Black in four-colour process printing), and determining which coordinates lie on the gamut boundary cannot be done solely from the relative amounts of the colour components. For CMYK processes, in almost all cases, the Black colorant extends the gamut below the gamut vertex at each hue angle. This makes it possible to identify a set of coordinates which are expected to lie on the gamut surface from the relative colorant amounts and the coordinates of the two- and three-colour overprints. For processes with more than four colour components, some knowledge of the colorimetry of a sample of colours from the colour data encoding is needed in order to determine which colours lie on the boundary.

For these reasons, coordinates on the surface of the gamut of RGB and CMYK printing processes can be determined by printing a test chart with suitable colorant combinations, and measuring the colours; while for other printing processes, it is necessary to model the colorant-to-colorimetry relationship in order to identify colours on the gamut boundary. (RGB here refers to the input signal and supports the common situation where the printer driver accepts RGB instead of CMYK.)

Graphic technology — Image quality evaluation methods for printed matter —

Part 11: Colour gamut analysis

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This document defines procedures to measure and compare the colour gamuts of RGB and CMYK printing processes.

It is not applicable to other printing processes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 15076-1, *Image technology colour management — Architecture, profile format and data structure — Part 1: Based on ICC.1:2010*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

colour gamut

range of colours that can be reproduced by an output device on a given medium, represented in a CIE-based colour space

Note 1 to entry: The CIE colour space for representation of colour gamuts is normally CIELAB.

3.2

gamut vertex

coordinate in a CIE-based colour space which represents a point on a *colour gamut* (3.1) surface and which is used in defining the surface of the gamut