
Design using geosynthetics —

**Part 9:
Barriers**

*Design pour géosynthétiques —
Partie 9: Barrières*



This document is a preview generated by EUS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Pictograms	2
4.1 Product and function	2
4.2 Applications	2
4.2.1 Containment application, non-landfill (CA)	2
4.2.2 Chemical containment, non-landfill (CC)	2
4.2.3 Construction waterproofing (CW)	3
4.2.4 Landfill base lining (LBL)	3
4.2.5 Landfills caps (LC)	3
4.2.6 Secondary containment (SC)	4
4.2.7 Transport infrastructure applications (TIA)	4
4.2.8 Tunnels (Tu)	5
4.2.9 Water retaining structure (WRS-e), e.g. balancing ponds, dams, dykes and canals (usually empty)	5
4.2.10 Water retaining structure (WRS-f), e.g. reservoirs, canals (usually full)	5
5 Design Criteria	6
6 Materials	7
6.1 General	7
6.2 HDPE	7
6.3 LLDPE	7
6.4 fPP	7
6.5 PVC	7
6.6 EPDM	7
6.7 Bitumen	7
6.8 EIA (ethylene interpolymers alloy)	7
6.9 Bentonite	7
6.10 Sodium bentonite	8
6.11 Calcium bentonite	8
7 Properties relevant to design	8
7.1 General	8
7.2 Chemical resistance	9
7.3 Physical properties	9
7.4 Durability/weathering	10
7.4.1 General	10
7.4.2 Mechanisms of degradation of the GBR	10
7.4.3 Mechanisms of degradation of the joints	10
8 Principles of design	11
8.1 General	11
8.2 Subgrade preparation	11
8.3 Slope stability	11
8.4 Climate conditions	12
8.5 Temperature effects (thermal expansion and stiffness)	12
8.6 Protection and testing	12
8.6.1 Puncture protection	12
8.6.2 Installation issues, excluding jointing	12
8.6.3 QC on site	13
8.6.4 Hydraulic uplift	14

9	Example design chart	14
	Bibliography	16

This document is a preview generated by EVS

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 221, *Geosynthetics*.

A list of all parts in the ISO 18228 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 18228 series provides guidance for designs using geosynthetics for soils and below ground structures in contact with natural soils, fills and asphalt. The series contains 10 parts which cover designs using geosynthetics, including guidance for characterization of the materials to be used and other factors affecting the design and performance of the systems which are particular to each part, with ISO/TR 18228-1 providing general guidance relevant to the subsequent parts of the series.

The series is generally written in a limit state format and guidelines are provided in terms of partial material factors and load factors for various applications and design lives, where appropriate.

For each of the design considerations, the characteristics of the geosynthetics and the test methods normally used to quantify the properties of the geosynthetics are described. Some regional specific rules and regulations that normally apply to designs using geosynthetics in these regions are also mentioned.

This document contains recommendations and guidance for the design of geosynthetic barriers in geotechnical applications. The standard provides design guidance over various applications, design lives, material types, parameters and site-specific conditions. Professional judgement is needed in all designs. Be aware that national regulations might apply. This document is intended to assist in the process, by identifying parameters which are relevant.

Design using geosynthetic barriers (GBRs) takes into account the nature of the material in contact with the GBR, both underneath (the substrate), alongside and on top (the contained substances). As the primary function of a GBR is to retain or exclude fluids, primary issues in design relate to its ability to perform this function. Often, but not always, GBR materials are incorporated into structures with an extensive life expectancy and therefore the material's durability (its ability to continue to perform its primary function over time) is critical.

Balancing the combination of often conflicting performance criteria and different GBR materials to the proposed installation is always a complex matter. This inevitably comes down to professional judgement. This document does not set out to and cannot solve this potential conflict but seeks to assist the designer in identifying and clarifying the various components of the decision-making process by identifying existing standards for comparisons of individual parameters and giving some direction on prioritization in various applications as well as conflicting performance characteristics which may be encountered.

Design using geosynthetics —

Part 9: Barriers

1 Scope

This document considers the guidance for geotechnical and civil engineers involved in the design of the barrier function.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10318-1, *Geosynthetics — Part 1: Terms and definitions*

3 Terms and definitions

For the purposes of this document, the terms and definitions in ISO 10318-1:2015 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

barrier

use of a geosynthetic to prevent or limit the migration of fluids

3.2

geosynthetic barrier

GBR

low-permeability geosynthetic material, used in geotechnical and civil engineering applications with the purpose of reducing or preventing the flow of fluid through the construction

3.3

geomembrane

GBR-P

polymeric geosynthetic barrier

factory-assembled structure of geosynthetic materials in the form of a sheet in which the *barrier* (3.1) function is essentially fulfilled by polymers

3.4

clay geosynthetic barrier

GBR-C

geosynthetic clay liner

factory-assembled structure of geosynthetic materials in the form of a sheet in which the *barrier* (3.1) function is essentially fulfilled by clay