Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 1: General principles and requirements (ISO 5167-1:2022)



#### EESTI STANDARDI EESSÕNA

#### NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 5167-1:2022 sisaldab Euroopa standardi EN ISO 5167-1:2022 ingliskeelset teksti.

This Estonian standard EVS-EN ISO 5167-1:2022 consists of the English text of the European standard EN ISO 5167-1:2022.

Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas

This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.

Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 29.06.2022.

Date of Availability of the European standard is 29.06.2022.

Standard on kättesaadav Eesti Standardimis-ja Akrediteerimiskeskusest.

The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

#### ICS 17.120.10

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis-ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis-ja Akrediteerimiskeskusega: Koduleht <a href="https://www.evs.ee">www.evs.ee</a>; telefon 605 5050; e-post <a href="mailto:info@evs.ee">info@evs.ee</a>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

# EUROPEAN STANDARD

## **EN ISO 5167-1**

# NORME EUROPÉENNE

**EUROPÄISCHE NORM** 

June 2022

ICS 17.120.10

Supersedes EN ISO 5167-1:2003

#### **English Version**

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 1: General principles and requirements (ISO 5167-1:2022)

Mesurage de débit des fluides au moyen d'appareils déprimogènes insérés dans des conduites en charge de section circulaire - Partie 1: Principes généraux et exigences générales (ISO 5167-1:2022) Durchflussmessung von Fluiden mit Drosselgeräten in voll durchströmten Leitungen mit Kreisquerschnitt -Teil 1: Allgemeine Grundlagen und Anforderungen (ISO 5167-1:2022)

This European Standard was approved by CEN on 14 June 2022.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

#### **European foreword**

This document (EN ISO 5167-1:2022) has been prepared by Technical Committee ISO/TC 30 "Measurement of fluid flow in closed conduits" in collaboration with Technical Committee CEN/SS F05 "Measuring Instruments" the secretariat of which is held by CCMC.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2022, and conflicting national standards shall be withdrawn at the latest by December 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 5167-1:2003.

Any feedback and questions on this document should be directed to the users' national standards body/national committee. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

#### **Endorsement notice**

The text of ISO 5167-1:2022 has been approved by CEN as EN ISO 5167-1:2022 without any modification.

Co	ntent	ts	Page
Fore	eword		<b>v</b>
Intr	oductio	on	vi
1	Scor	De	1
		mative references	
2			
3		ns and definitions	
	3.1 3.2	Pressure measurement Primary devices	
	3.3	Flow	
4	<b>Sym</b> 4.1	bols and subscripts Symbols	<b>b</b>
_			
5	Prin	ciple of the method of measurement and computation	7
	5.1 5.2	Principle of the method of measurement	/
	5.2	primary device	8
	5.3	Computation of flow rate	
	5.4	Determination of density, pressure and temperature	
		5.4.1 General	
		5.4.2 Density	
		5.4.3 Static pressure 5.4.4 Temperature	
	5.5	Differential pressure flow measurement system	
	5.5	5.5.1 General	10
		5.5.2 Primary device	
		5.5.3 Impulse lines and transmitters	12
		5.5.4 Impulse line isolation valves and valve manifolds	12
	<b>F</b> 6	5.5.5 Flow computer	
	5.6	Differential pressure flow measurement system design considerations	
		5.6.2 Meter calibration	
		5.6.3 Permanent pressure loss	13
		5.6.4 Diagnostics and meter verification	14
		5.6.5 Overall uncertainty of differential pressure metering system	14
6	Gen	eral requirements for the measurements	14
	6.1	Primary device	14
	6.2	Nature of the fluid	15
	6.3	Flow conditions	
7	Inst	allation requirements	15
	7.1	General	14 15 15 15
	7.2	Minimum upstream and downstream straight lengths	17
	7.3	General requirement for flow conditions at the primary device	17
		7.3.1 Requirement	
		7.3.3 Good velocity profile conditions	
	7.4	Flow conditioners	
		7.4.1 Compliance testing	
		7.4.2 Specific test	
8	Unc	ertainties on the measurement of flow rate	20
	8.1	General	20
	8.2	Definition of uncertainty	
	8.3	Practical computation of the uncertainty	
		8.3.1 Component uncertainties	21

mex B (informative) Iterative computations 24  mex B (informative) Examples of values of the pipe wall uniform equivalent roughness, k <sub>a</sub> 26  mex C (informative) Flow conditioners and flow straighteners 27  mex D (informative) Example of uncertainty calculation for a differential pressure device 36  mex F (informative) Permanent pressure loss example 40  ibliography 42	8.3.2 Practical working formula	21
nnex B (informative) Examples of values of the pipe wall uniform equivalent roughness, k <sub>o</sub> = 26 nnex C (informative) Flow conditioners and flow straighteners = 27 nnex D (informative) Differential pressure transmitters, flow range and turndown = 29 nnex E (informative) Example of uncertainty calculation for a differential pressure device = 36 nnex F (informative) Permanent pressure loss example = 40 ibliography = 42	nnex A (informative) Iterative computations	24
nnex D (informative) Differential pressure transmitters, flow range and turndown 29 nnex E (informative) Example of uncertainty calculation for a differential pressure device 36 nnex F (informative) Permanent pressure loss example 40 ibliography 42		
nnex E (informative) Example of uncertainty calculation for a differential pressure device 36 nnex F (informative) Permanent pressure loss example 40 ibliography 42	nnex C (informative) Flow conditioners and flow straighteners	27
nnex F (informative) Permanent pressure loss example 40 ibliography 42	nnex D (informative) Differential pressure transmitters, flow range and turndown	29
	nnex E (informative) Example of uncertainty calculation for a differential pressure device	36
	nnex F (informative) Permanent pressure loss example	40
	ibliography	42
© 100 2022 All #-l-l	Coment is a previous seneral party of the company o	5
	© ISO 2022 – All rights rese	ruod

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

ISO 5167-1 was prepared by Technical Committee ISO/TC 30, Measurement of fluid flow in closed conduits, Subcommittee SC 2, Pressure differential devices, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/SS F05, Measuring instruments, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 5167-1:2003), which has been technically revised

The main changes are as follows:

- improved consistency between ISO 5167-1 to ISO 5167-6 (some items that were new in ISO 5167-5 and ISO 5167-6 have been moved to this document);
- a primary element has been set as part of a differential pressure metering system;
- a short section on diagnostics and CBM (Condition Based Monitoring) has been included;
- a limitation on the use of the 5 % 2° rule for an acceptable profile has been noted;
- improved text about uncertainty calculation and an example in Annex E has been provided;
- annexes on turndown and permanent pressure loss have been included.

A list of all parts in the ISO 5167 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

#### Introduction

ISO 5167, consisting of six parts, covers the geometry and method of use (installation and operating conditions) of orifice plates, nozzles, Venturi tubes, cone meters and wedge meters when they are inserted in a conduit running full to determine the flow rate of the fluid flowing in the conduit. It also gives necessary information for calculating the flow rate and its associated uncertainty.

ISO 5167 (all parts) is applicable only to pressure differential devices in which the flow remains subsonic throughout the measuring section and where the fluid can be considered as single-phase, but is not applicable to the measurement of pulsating flow. Furthermore, each of these devices can only be used uncalibrated within specified limits of pipe size and Reynolds number, or alternatively they can be used across their calibrated range.

ISO 5167 (all parts) deals with devices for which direct calibration experiments have been made, sufficient in number, spread and quality to enable coherent systems of application to be based on their results and coefficients to be given with certain predictable limits of uncertainty. ISO 5167 also provides methodology for bespoke calibration of differential pressure meters.

The devices introduced into the pipe are called primary devices. The term primary device also includes the pressure tappings. All other instruments or devices required to facilitate the instrument readings are known as secondary devices, and the flow computer that receives these readings and performs the algorithms is known as a tertiary device. ISO 5167 covers primary devices; secondary devices (see ISO 2186) and tertiary devices will be mentioned only occasionally.

Aspects of safety are not dealt with in ISO 5167-1 to ISO 5167-6. It is the responsibility of the user to ensure that the system meets applicable safety regulations.

e: Additional documents that may provide assistance include:

- ISO/TR 3313;
- ISO/TR 9464;
- ISO/TR 12767;
- ISO/TR 15377.

# Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full —

## Part 1:

# General principles and requirements

#### 1 Scope

This document defines terms and symbols and establishes the general principles for methods of measurement and computation of the flow rate of fluid flowing in a conduit by means of pressure differential devices (orifice plates, nozzles, Venturi tubes, cone meters, and wedge meters) when they are inserted into a circular cross-section conduit running full. This document also specifies the general requirements for methods of measurement, installation and determination of the uncertainty of the measurement of flow rate.

ISO 5167 (all parts) is applicable only to flow that remains subsonic throughout the measuring section and where the fluid can be considered as single-phase. It is not applicable to the measurement of pulsating flow.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4006, Measurement of fluid flow in closed conduits — Vocabulary and symbols

ISO 5167 (all parts), Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full

ISO 5168, Measurement of fluid flow — Procedures for the evaluation of uncertainties

ISO/IEC Guide 98-3, Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)

#### 3 Terms and definitions

For the purposes of this document, the terms, definitions and symbols given in ISO 4006 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>