

RÖÖBASTEL LIIKUVAD VIRNASTAJAD. VIRNASTAJATE
OHUTUSNÕUDED

Rail dependent storage and retrieval equipment -
Safety requirements for S/R machines

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 528:2021+A1:2022 sisaldab Euroopa standardi EN 528:2021+A1:2022 ingliskeelset teksti.	This Estonian standard EVS-EN 528:2021+A1:2022 consists of the English text of the European standard EN 528:2021+A1:2022.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 13.07.2022.	Date of Availability of the European standard is 13.07.2022.
Standard on kättesaadav Eesti Standardimis-ja Akrediteerimiskeskusest.	The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 53.080

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN 528:2021+A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

July 2022

ICS 53.080

Supersedes EN 528:2021

English Version

Rail dependent storage and retrieval equipment - Safety requirements for S/R machines

Transtockeurs - Prescriptions de sécurité

Regalbediengeräte - Sicherheitsanforderungen

This European Standard was approved by CEN on 4 January 2021 and includes Amendment 1 approved by CEN on 4 May 2022.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword.....	5
Introduction.....	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	10
4 Safety requirements and/or protective/risk reduction measures	13
4.1 General	13
4.2 Control position	13
4.2.1 General	13
4.2.2 Access to and egress from the permanent on-board control position	13
4.2.3 Floor of the on-board control position	13
4.2.4 Design and dimensioning of permanent on-board control position	13
4.2.5 Emergency call device on permanent on-board control positions	14
4.2.6 Lighting on permanent on-board control position	14
4.3 Control equipment	15
4.3.1 General	15
4.3.2 Safeguard of the operator on a permanent on-board control position	15
4.3.3 Prevention of unauthorised operation (equipment switch)	15
4.3.4 Changing mode of operation (mode switch)	15
4.3.5 Key dependence	16
4.3.6 Control devices for powered movements	16
4.3.7 Control device identification	16
4.3.8 Stop function	16
4.3.9 Emergency stop function	17
4.3.10 Safety requirements related to EMC	17
4.4 Hoist unit	17
4.4.1 Hoist unit brake	17
4.4.2 Limitation of the lifting and lowering movement	18
4.4.3 Overload and slack condition protection	18
4.4.4 Safety gear and overspeed governor	19
4.4.5 Suspension elements	20
4.4.6 Hydraulic drives	23
4.4.7 Lead-screw drive	23
4.4.8 Rack and pinion drives	24
4.5 Travel unit of the S/R machine	24
4.5.1 Travel unit braking system	24
4.5.2 Speed reducing system	25
4.5.3 Limitation of travel	25
4.5.4 Anti-derailment devices	26
4.5.5 Stability	26
4.6 Load handling devices	27
4.6.1 Load stability	27
4.6.2 Determination of possible impacts on the rack	27
4.6.3 Rotating devices	27
4.6.4 Interlocking functions	27
4.6.5 Auxiliary handling equipment	27
4.6.6 Load position monitoring	28

4.6.7	Satellites	28
4.7	Electrical equipment	28
4.7.1	General	28
4.7.2	Electrical supply conditions	28
4.7.3	Environment	28
4.7.4	Supply disconnecting (isolating) device	28
4.7.5	Protection against electric shock	29
4.7.6	Suspension of safeguarding	29
4.7.7	Overriding of safety functions	29
4.8	Transfer device	29
4.8.1	General	29
4.8.2	Retention of position	30
4.8.3	Movement	30
4.8.4	Interlocking functions	30
4.8.5	Stability	30
4.9	Maintenance repair and fault clearance	30
4.9.1	General	30
4.9.2	Maintenance position	30
4.9.3	Emergency control position	31
4.9.4	Speed limitation	31
4.9.5	Communication	32
4.9.6	Protection from operating machines (S/R machines and its transfer equipment)	32
4.9.7	Access along the mast	32
4.10	Machine environment	34
4.10.1	General	34
4.10.2	Communication of force information	34
4.10.3	Safety clearances	34
4.10.4	Safeguarding of persons (Limiting access)	34
4.10.5	Load entry / exit points	35
4.10.6	Escape from dangerous areas	36
4.10.7	Protection against unintentional load movement	37
4.10.8	Protection against falling	38
5	Verification of safety requirements and/or measures	38
5.1	Examination	38
5.1.1	General	38
5.1.2	Movements to be done	38
5.1.3	Test of the safety gear	38
5.1.4	Verification of the mechanical limits of travel	39
5.1.5	Test of the lowering control valve	39
5.1.6	Written record	39
5.2	EMC	39
5.3	Noise	39
5.3.1	General	39
5.3.2	Noise measurement	39
5.3.3	Declaration	40
5.4	Load tests	41
5.4.1	Test load	41
5.4.2	Static load test	41
5.4.3	Dynamic load test	41
5.4.4	Load test record	41
6	Information for use	41
6.1	General	41
6.2	Erection on site	41
6.3	Commissioning	41
6.3.1	Method statement	41

6.3.2	Instructions	42
6.3.3	Training	42
6.3.4	Safety devices	42
6.3.5	Individual elements of the machine	42
6.3.6	Integrated commissioning	42
6.4	Normal operation	42
6.4.1	General	42
6.4.2	Operation and use	42
6.4.3	Maintenance, repair and fault-clearing	42
6.4.4	Spare parts	42
6.4.5	Certification of suspension elements	42
6.4.6	Noise declaration	42
6.4.7	Test report	43
6.4.8	Minimum markings	43
6.4.9	Conditions for the safe operation of equipment	43
6.5	Fault finding/troubleshooting	46
6.5.1	General	46
6.5.2	Description of safe access and egress to trouble points on the S/R machine	46
6.5.3	Description of safe access and egress to trouble points at the interface between S/R machine and racking	46
6.5.4	Description of safe access and egress to trouble points at the interface between the S/R machine and the conveying system	46
6.5.5	Training	46
6.6	Rescue of persons	46
6.7	Maintenance, inspection, testing and training	46
6.7.1	General	46
6.7.2	Maintenance	46
6.7.3	Periodic maintenance and testing	47
6.7.4	Training	48
6.8	Dismantling	48
	Annex A (informative) Figures	49
	Annex B (normative) Performance levels according to EN ISO 13849-1:2015	57
	Annex C (normative) Preventing access to dangerous movements across the load entry/exit points	64
	Annex D (normative) Access to restricted areas	76
	Annex E (normative) Verification of safety requirements and/or measures	79
	Annex F (normative) List of significant and relevant hazards	86
	Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EU aimed to be covered	91
	Bibliography	99

European foreword

This document (EN 528:2021+A1:2022) has been prepared by Technical Committee CEN/TC 149 “Power-operated warehouse equipment”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2023, and conflicting national standards shall be withdrawn at the latest by January 2023.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association and supports essential requirements of EU Directive(s) / Regulation(s).

For relationship with EU Directive(s) / Regulation(s), see informative Annex ZA, which is an integral part of this document.

This document includes Amendment 1 approved by CEN on 4 May 2022.

This document supersedes A1 EN 528:2021 A1.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

The main changes compared to the previous edition EN 528:2008 are as follows:

- clearer / more understandable Annex C dealing with preventing access to dangerous movements across the load entry/exit points;
- Annex ZA has been updated by introducing the generic template for Annex ZA amended in accordance with decision of EU commission;
- revision and adaption of Annex B Performance level according to EN ISO 13849-1:2015;
- the scope has been stated more precisely;
- more readable and clearer text in standard due to avoidness of separate chapters for automatic and manual machines;
- amendment or rather change of the following definitions (3):
 - on-board control position (3.4), permanent on-board control position (3.5), load entry / exit points (3.7), working place (3.8), pick and deposit station (3.9), restricted area (3.11), danger area (3.12), satellite vehicle (3.15), powered access cabin (3.20), climb assistance system (3.21), rated speed (3.22), normal operation (3.25), deleted definition 3.22 and renamed following definitions;
- speed limitation (4.9.4) has been updated and been stated more precisely;
- where a powered access cabin is provided, it shall comply with the requirements for control positions (4.9.7.2);
- Detachable ladders may be used up to a maximum height of 3 m (4.9.7);
- safety gear required for lifting carriages, that are designed to carry person(s) (4.4.4.1);

- the ratio of the minimum breaking force to the maximum static force for all types of suspension elements to the lifting of persons has been reduced from 10 to 8 (4.4.5.1);
- requirements for additional person(s) on the lifting carriage has been stated more precisely (4.9.2.2);
- ladder along the mast shall be fitted with a guided type of fall arresters according with EN 353-1:2014+A1:2017 and anchor points at the transition points (4.9.3);
- prevention against load falling into adjacent automatically operated aisles: Safety level (PLr) is not more depending on the frequency of access to the aisle (4.10.7.3);
- physical safety backstops shall be dimensioned according to the loads that occur (4.10.7);
- information on the planned dismantling of the installation is required in information for use (6.8).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This document is a type C standard as stated in EN ISO 12100:2010.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulars, accident prevention organizations, market surveillance etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises).

The above-mentioned stakeholder groups have been given possibility to participate at the drafting process of this document.

The machinery concerned and the extent to which hazards, hazardous situations and hazardous events are covered are indicated in the Scope of this standard.

When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards, for machines that have been designed and built according to the requirements of this type-C standard.

While producing this standard, it was assumed that:

- a) only competent persons operate the machine;
- b) components without specific requirements are:
 - 1) designed in accordance with the usual engineering practice and calculation codes, including all failure modes;
 - 2) of suitable mechanical and electrical construction;
 - 3) made of materials with adequate strength and of suitable quality;
- c) harmful materials, such as asbestos are not used as part of the machine;
- d) components are kept in good repair and working order, so that the required characteristics remain despite wear;
- e) by design of the load bearing elements, safe operation of the machine is ensured for loading ranging from zero to 100 % of the rated possibilities;
- f) discussions have taken place between the user and the supplier concerning particular conditions for the use and places of use of the machinery;
- g) working area is adequately lit;
- h) places of installation allow a safe use of the machine.

1 Scope

This document is applicable to all types of Storage and Retrieval (S/R) machines, restricted to the rails on which they travel within and outside the aisles for the storage and retrieval of unit loads and/or long goods such as bar materials and/or for order picking or similar duties. These machines embody lifting means along a mast and may include lateral handling facilities. Also included is the transfer equipment used to change between aisles. Control of machines may range from manual to fully automatic.

S/R-machine-related satellite vehicles according to definition 3.15 are included as a load-handling-device (LHD).

References in this standard to racking, buildings and systems only apply where it is necessary to assess the hazards and risks at their interfaces with S/R machines.

This document deals with all significant hazards relevant to rail dependent storage and retrieval equipment, when they are used under the conditions intended by the manufacturer including reasonably foreseeable misuse (see Annex F "List of significant hazards").

This document is applicable to machines and equipment that are manufactured after the date of issue of this document. A transition period of 12 months is proposed.

Figures of examples of machines and transfer equipment to which this standard applies are shown in Annex A.

Safety requirements and/or measures in this standard apply to equipment used under indoor conditions. However, additional risk assessments and safety measures need to be considered for uses in severe conditions, e.g. extremely high temperatures, loads, the nature of which could lead to a dangerous situation (e.g. especially brittle loads, explosives), earthquake effects and also contact with foodstuff.

This document also deals with the technical requirements for electromagnetic compatibility (EMC).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 81-50:2020, *Safety rules for the construction and installation of lifts — Examinations and tests — Part 50: Design rules, calculations, examinations and tests of lift components*

EN 341:2011, *Personal fall protection equipment — Descender devices for rescue*

EN 353-1:2014+A1:2017, *Personal fall protection equipment — Guided type fall arresters including an anchor line — Part 1: Guided type fall arresters including a rigid anchor line*

EN 358:2018, *Personal protective equipment for work positioning and prevention of falls from a height — Belts and lanyards for work positioning or restraint*

EN 361:2002, *Personal protective equipment against falls from a height — Full body harnesses*

EN 363:2018, *Personal fall protection equipment — Personal fall protection systems*

EN 614-1:2006+A1:2009, *Safety of machinery — Ergonomic design principles — Part 1: Terminology and general principles*

EN 795:2012, *Personal fall protection equipment — Anchor devices*

EN 894-1:1997+A1:2008, *Safety of machinery — Ergonomics requirements for the design of displays and control actuators — Part 1: General principles for human interactions with displays and control actuators*

- EN 894-2:1997+A1:2008, *Safety of machinery — Ergonomics requirements for the design of displays and control actuators — Part 2: Displays*
- EN 894-3:2000+A1:2008, *Safety of machinery — Ergonomics requirements for the design of displays and control actuators — Part 3: Control actuators*
- EN 12385-4:2002+A1:2008, *Steel wire ropes — Safety — Part 4: Stranded ropes for general lifting applications*
- EN 13501-1:2018, *Fire classification of construction products and building elements — Part 1: Classification using data from reaction to fire tests*
- EN 14449:2005, *Glass in building — Laminated glass and laminated safety glass — Product standard*
- EN 60204-32:2008, *Safety of machinery — Electrical equipment of machines — Part 32: Requirements for hoisting machines (IEC 60204-32:2008)*
- EN IEC 61000-6-2:2019, *Electromagnetic compatibility (EMC) — Part 6-2: Generic standards — Immunity for industrial environments (IEC 61000-6-2:2016)*
- EN 61496-1:2013, *Safety of machinery — Electro-sensitive protective equipment — Part 1: General requirements and tests*
- EN ISO 4413:2010, *Hydraulic fluid power — General rules and safety requirements for systems and their components (ISO 4413:2010)*
- EN ISO 4871:2009, *Acoustics — Declaration and verification of noise emission values of machinery and equipment (ISO 4871:1996)*
- EN ISO 7731:2008, *Ergonomics — Danger signals for public and work areas — Auditory danger signals (ISO 7731:2003)*
- EN ISO 11201:2010, *Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions in an essentially free field over a reflecting plane with negligible environmental corrections (ISO 11201:2010)*
- EN ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction (ISO 12100:2010)*
- EN ISO 13849-1:2015, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design (ISO 13849-1:2015)*
- EN ISO 13850:2015, *Safety of machinery — Emergency stop function — Principles for design (ISO 13850:2015)*
- EN ISO 13851:2019, *Safety of machinery — Two-hand control devices — Principles for design and selection (ISO 13851:2019)*
- EN ISO 13855:2010, *Safety of machinery — Positioning of safeguards with respect to the approach speeds of parts of the human body (ISO 13855:2010)*
- EN ISO 13856-1:2013, *Safety of machinery — Pressure-sensitive protective devices — Part 1: General principles for design and testing of pressure-sensitive mats and pressure-sensitive floors (ISO 13856-1:2013)*
- EN ISO 13857:2019, *Safety of machinery — Safety distances to prevent hazard zones being reached by upper and lower limbs (ISO 13857:2019)*

EN ISO 14119:2013, *Safety of machinery — Interlocking devices associated with guards — Principles for design and selection (ISO 14119:2013)*

EN ISO 14120:2015, *Safety of machinery — Guards — General requirements for the design and construction of fixed and movable guards (ISO 14120:2015)*

EN ISO 14122-1:2016, *Safety of machinery — Permanent means of access to machinery — Part 1: Choice of fixed means and general requirements of access (ISO 14122-1:2016)*

EN ISO 14122-2:2016, *Safety of machinery — Permanent means of access to machinery — Part 2: Working platforms and walkways (ISO 14122-2:2016)*

EN ISO 14122-3:2016, *Safety of machinery — Permanent means of access to machinery — Part 3: Stairs, stepladders and guard-rails (ISO 14122-3:2016)*

EN ISO 14122-4:2016, *Safety of machinery — Permanent means of access to machinery — Part 4: Fixed ladders (ISO 14122-4:2016)*

ISO 16625:2013, *Cranes and hoists — Selection of wire ropes, drums and sheaves*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 12100:2010 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

control position

every place, from where the machine can be controlled, including external control position (3.2), emergency control position (3.3) and on-board control position (3.4)

3.2

external control position

control position placed outside of the operational area of the S/R machine, from where the movements of the machine can be controlled

3.3

emergency control position

position on the machine or inside the danger area of the machine, from where the machine can be controlled in case of fault clearing (emergency) or maintenance works

3.4

on-board control position

protected position on the machine, from where the movements of the machine can be controlled (includes permanent on-board-control position as defined in 3.5)

3.5

permanent on-board control position

protected position on the machine, from where the movements of the machine can be controlled, intended to be used by an on-board operator in the normal operation

Note 1 to entry: Permanent on-board control is fitted e.g. for on-board picking.