
**Mechanical vibration — Vibration of
rotating machinery equipped with
active magnetic bearings —**

**Part 5:
Touch-down bearings**

*Vibrations mécaniques — Vibrations de machines rotatives équipées
de paliers magnétiques actifs —*

Partie 5: Paliers d'arrêt



This document is a preview generated by ELS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 General structure and components	2
5 Functional targets	4
5.1 General	4
5.2 Design life	6
5.3 Clearance requirements	6
5.4 Life-cycle requirements	6
6 Touch-down bearing design considerations	7
6.1 General	7
6.2 Trigger events	7
6.2.1 Overload due to abnormal process conditions	7
6.2.2 AMB control instability	8
6.2.3 Loss of power	9
6.2.4 Failure in the AMB system	10
6.2.5 Misoperation	10
6.3 Transportation duty	10
6.3.1 General	10
6.3.2 AMBs without permanent magnets	11
6.3.3 AMBs with permanent magnets	11
6.4 Failure modes	12
6.4.1 General	12
6.4.2 Rolling element failure modes	12
6.4.3 Sliding bearing failure modes	13
6.5 Environmental factors	13
6.5.1 General	13
6.5.2 Corrosion resistance	13
6.5.3 Erosion resistance, particulate contamination	14
6.5.4 Liquid contamination	14
6.5.5 Operating temperature	14
6.5.6 Available cooling flow	14
6.6 Rotordynamic modelling considerations	14
6.6.1 General	14
6.6.2 Rotor and housing modelling requirements	14
6.6.3 Touch-down bearing soft mount design considerations	16
6.6.4 Touch-down bearing clearance design considerations	16
6.6.5 Friction between the rotor and touch-down bearing design considerations	16
6.7 Contact classification/severity	17
6.7.1 Contact duration	17
6.7.2 Types of motion	17
6.8 Control actions following touch-down bearing contact	19
6.8.1 General	19
6.8.2 AMB controller action	19
6.8.3 Plant/variable-frequency drive control actions	19
7 Design and design verification	19
7.1 General	19
7.2 Design process details	20
7.3 Documentation	30
8 Condition monitoring and damage estimation methods	30
8.1 General	30

8.2	Event detection and data capture	30
8.2.1	Contact detection.....	30
8.2.2	Contact event.....	30
8.3	Inspection	31
8.3.1	General.....	31
8.3.2	Common techniques in non-intrusive inspection.....	31
8.3.3	Intrusive inspection.....	32
8.4	Damage estimation.....	34
8.4.1	Event data.....	34
8.4.2	Inspection-based estimation.....	35
8.4.3	Criteria for further operation.....	36
9	Maintenance and life cycle factors	37
9.1	General.....	37
9.2	Inspection plan	37
9.2.1	General.....	37
9.2.2	Minimum intervention cycle.....	37
9.3	Interventions.....	37
9.3.1	Routine checks.....	37
9.3.2	Predicted excessive damage accumulation	38
9.3.3	Contamination.....	39
9.4	Maintenance actions.....	39
9.4.1	General.....	39
9.4.2	Touch-down-bearing refurbishment.....	39
9.4.3	Touch-down bearing replacement.....	40
9.5	Life-cycle factors.....	41
9.5.1	General.....	41
9.5.2	Spare part management.....	41
9.5.3	Decommissioning, recycling and disposal.....	42
9.5.4	Obsolescence management	42
	Bibliography	43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 2, *Measurement and evaluation of mechanical vibration and shock as applied to machines, vehicles and structures*.

A list of all parts in the ISO 14839 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Mechanical vibration — Vibration of rotating machinery equipped with active magnetic bearings —

Part 5: Touch-down bearings

1 Scope

This document gives guidelines for identifying:

- a) The typical architectures of touch-down bearing systems to show which components are likely to comprise such systems and which functions these components provide;

NOTE Touch-down bearings are also known as “backup bearings”, “auxiliary bearings”, “catcher bearings” or “landing bearings”. Within this document, the term “touch-down bearings” is used exclusively as defined in ISO 14839-1.
- b) The functional requirements for touch-down bearing systems so that clear performance targets can be set;
- c) Elements to be considered in the design of the dynamic system such that rotordynamic performance can be optimized, both for touch-down bearings and active magnetic bearings (AMBs);
- d) The environmental factors that have significant impact on touch-down bearing system performance allowing optimization of overall machine design;
- e) The AMB operational conditions that can give rise to contact within the touch-down bearing system so that such events can be considered as part of an overall machine design. It also considers failure modes within the AMB system that can give rise to a contact event. This ensures that the specification of the touch-down bearings covers all operational requirements;
- f) The most commonly encountered touch-down bearing failure modes and typical mechanisms for managing these events;
- g) Typical elements of a design process for touch-down bearing systems including the specification of load requirements, the sizing process, the analytical and simulation methods employed for design validation;
- h) The parameters to be taken into account when designing a touch-down bearing system acceptance test programme including the test conditions to be specified and the associated instrumentation to be used to ensure successful test execution;
- i) The condition monitoring and inspection methods that allow the status of in-service touch-down bearings to be evaluated and when necessary identifying the corrective actions to be taken;
- j) The factors to be considered when designing the maintenance regime for a touch-down bearing system including the actions to be taken after specified events have occurred together with any actions to be performed on a regular basis;
- k) The factors to be considered regarding other life cycle topics (e.g. obsolescence management, de-commissioning and disposal).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*

ISO 14839-1, *Mechanical vibration — Vibration of rotating machinery equipped with active magnetic bearings — Part 1: Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041 and ISO 14839-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 General structure and components

Rotating machinery equipped with AMBs is typically also equipped with touch-down bearings. These touch-down bearings are intended to support the rotor when the AMB system is not activated or during a failure or overload of the AMB system. In these instances, the touch-down bearings are required to support the rotor until either levitation is recovered or the rotor is brought to zero rotational speed without damaging to other parts of the machine.

During normal operation of the machinery, the touch-down bearings have a clearance with the rotor and consequently do not apply force. The clearance at the touch-down bearings is typically the closest clearance within the rotating machine. This ensures in the event of a problem with the AMB, when the rotor moves away from its normal “centred” operating position, the first item to make contact between the rotor and stator is the touch-down bearing. Such an event occurring during rotation is referred to as a “touch-down event”, “landing event”, “contact event” or “drop event”. Such events have historically been categorized by some vendors as either “hard” landings, where a full de-levitation from high speed occurs or “soft” landings where either a partial de-levitation or a momentary contact occurs.

Touch-down bearings are required to constrain rotor movement in the degrees of freedom normally constrained by the AMB system. In the case of a rotor with two radial AMBs and one axial AMB, the touch-down bearings are required to constrain the associated five axes of movement. This is typically achieved by using:

- a) two radial touch-down bearings with a separate axial touch-down bearing;
- b) two radial touch-down bearings, each with a single acting thrust face; or
- c) one radial touch-down bearing with a combined radial/axial touch-down bearing.

Touch-down bearings use a range of technologies, such as:

- d) stator mounted rolling element bearings;
- e) rotor mounted rolling element bearings;
- f) dry lubricated plain bushings;
- g) dry lubricated pad construction;
- h) foil bearings;