

---

---

**Water quality — Nickel-59 and  
nickel-63 —**

**Part 1:  
Test method using liquid scintillation  
counting**

*Qualité de l'eau — Nickel 59 et Nickel 63 —*

*Partie 1: Méthode d'essai par comptage des scintillations en milieu  
liquide*



This document is a preview generated by ELS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 General symbols and nickel-59 and nickel-63 specific symbols.....</b>	<b>2</b>
<b>5 Principle.....</b>	<b>4</b>
<b>6 Reagents.....</b>	<b>4</b>
6.1 Standard solutions.....	5
6.1.1 Nickel-59 and $^{63}\text{Ni}$ standards.....	5
6.1.2 Stable nickel standards.....	5
6.2 Chemical quenching agent.....	5
6.3 Colour quenching agent.....	5
6.4 Holdback carrier.....	5
6.5 Water.....	5
6.6 Specific reagents for chemical separation.....	5
<b>7 Equipment.....</b>	<b>6</b>
7.1 Laboratory equipment for direct evaporation.....	6
7.2 Liquid scintillation vials.....	6
7.3 Measurement equipment: Liquid scintillation counter.....	6
<b>8 Sampling.....</b>	<b>6</b>
<b>9 Liquid scintillation set up and calibration.....</b>	<b>7</b>
9.1 Window setting.....	7
9.2 Background.....	7
9.3 Calibration.....	7
<b>10 Procedure.....</b>	<b>9</b>
10.1 Preliminary.....	9
10.1.1 Stable nickel content.....	9
10.1.2 Iron and nickel separation.....	9
10.2 Liquid scintillation source preparation.....	9
<b>11 Quality control.....</b>	<b>10</b>
<b>12 Expression of results.....</b>	<b>10</b>
12.1 Nickel-59 measurements.....	10
12.1.1 Nickel recovery.....	10
12.1.2 Activity calculation.....	10
12.2 Nickel-63 measurements.....	11
12.3 Uncertainties and characteristic limits.....	11
12.3.1 Nickel recovery.....	11
12.3.2 Nickel-59 measurements.....	11
12.3.3 Nickel-63 measurements.....	13
12.4 Limits of the coverage interval.....	15
12.4.1 Limits of the probabilistically symmetric coverage interval.....	15
12.4.2 Shortest coverage interval.....	16
<b>13 Test report.....</b>	<b>16</b>
<b>Annex A (normative) Isolation and purification of nickel.....</b>	<b>18</b>
<b>Bibliography.....</b>	<b>20</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 147, *Water quality*, Subcommittee SC 3, *Radioactivity measurements*.

A list of all the parts in the ISO 23655 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

Radioactivity from several naturally-occurring and anthropogenic sources is present throughout the environment. Thus, water bodies (e.g. surface waters, ground waters, sea waters) can contain radionuclides of natural, human-made or both origins:

- natural radionuclides, including  $^{40}\text{K}$ ,  $^3\text{H}$ ,  $^{14}\text{C}$ , and those originating from the thorium and uranium decay series, in particular  $^{226}\text{Ra}$ ,  $^{228}\text{Ra}$ ,  $^{234}\text{U}$ ,  $^{238}\text{U}$ ,  $^{210}\text{Po}$  and  $^{210}\text{Pb}$  can be found in water for natural reasons (e.g. desorption from the soil and washoff by rain water) or can be released from technological processes involving naturally occurring radioactive materials (e.g. the mining and processing of mineral sands or phosphate fertilizers production and use);
- human-made radionuclides such as transuranium elements (americium, plutonium, neptunium, curium),  $^3\text{H}$ ,  $^{14}\text{C}$ ,  $^{90}\text{Sr}$ , and gamma emitting radionuclides can also be found in natural waters. Small quantities of these radionuclides are discharged from nuclear fuel cycle facilities into the environment as a result of authorized routine releases. Some of these radionuclides used for medical and industrial applications are also released into the environment after use. Anthropogenic radionuclides are also found in waters as a result of past fallout contaminations resulting from the explosion in the atmosphere of nuclear devices and accidents such as those that occurred in Chernobyl and Fukushima.

Radionuclide activity concentration in water bodies can vary according to local geological characteristics and climatic conditions and can be locally and temporally enhanced by releases from nuclear installation during planned, existing and emergency exposure situations<sup>[1]</sup>. Drinking-water can thus contain radionuclides at activity concentrations which can present a risk to human health.

The radionuclides present in liquid effluents are usually controlled before being discharged into the environment<sup>[2]</sup> and water bodies. Drinking waters are monitored for their radioactivity as recommended by the World Health Organization (WHO)<sup>[3]</sup> so that proper actions can be taken to ensure that there is no adverse health effect to the public. Following these international recommendations, national regulations usually specify radionuclide authorized concentration limits for liquid effluent discharged to the environment and radionuclide guidance levels for waterbodies and drinking waters for planned, existing, and emergency exposure situations. Compliance with these limits can be assessed using measurement results with their associated uncertainties as specified by ISO/IEC Guide 98-3<sup>[4]</sup> and ISO 5667-20<sup>[5]</sup>.

Depending on the exposure situation, there are different limits and guideline levels (GLs) that would result in an action to reduce health risk. As an example, during a planned or existing situation, the WHO GL for drinking water is  $1\,000\text{ Bq}\cdot\text{l}^{-1}$  for Ni activity concentration.

NOTE 1 The GL is the activity concentration with an intake of  $2\text{ l}\cdot\text{d}^{-1}$  of drinking water for one year that results in an effective dose of  $0,1\text{ mSv}\cdot\text{a}^{-1}$  for members of the public. This is an effective dose that represents a very low level of risk and which is not expected to give rise to any detectable adverse health effects<sup>[3]</sup>.

In the event of a nuclear emergency, the WHO Codex GLs<sup>[6]</sup> mentioned that the activity concentration might not be greater than  $10\,000\text{ Bq}\cdot\text{l}^{-1}$  for Ni.

NOTE 2 The Codex GLs apply to radionuclides contained in foods destined for human consumption and traded internationally, which have been contaminated following a nuclear or radiological emergency. These GLs apply to food after reconstitution or as prepared for consumption, i.e. not to dried or concentrated foods, and are based on an intervention exemption level of  $1\text{ mSv}$  in a year for members of the public (infant and adult)<sup>[6]</sup>.

Thus, the test method can be adapted so that the characteristic limits, decision threshold, detection limit and uncertainties ensure that the radionuclide activity concentrations test results can be verified to be below the guidance levels required by a national authority for either planned/existing situations or for an emergency situation<sup>[7],[8]</sup>.

Usually, the test methods can be adjusted to measure the activity concentration of the radionuclide(s) in either wastewaters before storage or in liquid effluents before being discharged to the environment.

The test results will enable the plant/installation operator to verify that, before their discharge, wastewaters/liquid effluent radioactive activity concentrations do not exceed authorized limits.

The test method(s) described in this document can be used during planned, existing and emergency exposure situations as well as for wastewaters and liquid effluents with specific modifications that can increase the overall uncertainty, detection limit and threshold.

The test method(s) can be used for water samples after proper sampling, sample handling and test sample preparation (see the relevant part of ISO 5667 series).

This document has been developed to support the need of test laboratories carrying out these measurements, that are sometimes required by national authorities, as they can need to obtain a specific accreditation for radionuclide measurement in drinking water samples.

This document is one of a set of International Standards on test methods dealing with the measurement of the activity concentration of radionuclides in water samples.

# Water quality — Nickel-59 and nickel-63 —

## Part 1:

## Test method using liquid scintillation counting

**WARNING** — Persons using this document should be familiar with normal laboratory practice. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices.

**IMPORTANT** — It is absolutely essential that tests conducted according to this document be carried out by suitably trained staff.

### 1 Scope

This document specifies the determination of nickel-59 and nickel-63 ( $^{59}\text{Ni}$  and  $^{63}\text{Ni}$ ) activity concentration in samples of all types of water using liquid scintillation counting (LSC). Using currently available liquid scintillation counters, this test method can measure  $^{59}\text{Ni}$  activity concentrations of  $50 \text{ mBq}\cdot\text{l}^{-1}$  and  $^{63}\text{Ni}$  activity concentrations of  $20 \text{ mBq}\cdot\text{l}^{-1}$  with a counting time of 200 min and a sample volume of 1,5 l.

**NOTE** These performance indicators are wholly dependent on the measurement regimes in individual laboratories; in particular, the detection limits for  $^{59}\text{Ni}$  are entirely dependent on the levels of  $^{63}\text{Ni}$  that can be present.

The range of application depends on the amount of dissolved material in the water and on the performance characteristics of the measurement equipment (background count rate and detection efficiency).

It is the laboratory's responsibility to ensure the suitability of this test method for the water samples tested.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

ISO 5667-1, *Water quality — Sampling — Part 1: Guidance on the design of sampling programmes and sampling techniques*

ISO 5667-3, *Water quality — Sampling — Part 3: Preservation and handling of water samples*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

ISO 80000-10, *Quantities and units — Part 10: Atomic and nuclear physics*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 80000-10 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>