



Edition 1.0 2023-02

INTERNATIONAL STANDARD

Hybrid communication cables -

Part 3: Outdoor hybrid cables – Sectional specification





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



Edition 1.0 2023-02

INTERNATIONAL STANDARD

Hybrid communication cables – Part 3: Outdoor hybrid cables – Sectional specification

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.120.20 ISBN 978-2-8322-6397-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| FO | REWORE |) | 3 | | | |
|---------------------|--|--|----|--|--|--|
| 1 Scope5 | | | | | | |
| 2 | Normati | Normative references5 | | | | |
| 3 | Terms, | erms, definitions, symbols and abbreviated terms7 | | | | |
| 4 | Design and construction | | | | | |
| 5 | Rated values and characteristics | | | | | |
| 6 | | | | | | |
| | 5.1 General | | | | | |
| | | otical requirements for cabled optical fibre | | | | |
| | | ectrical and transmission requirements for cabled electrical element | | | | |
| | 6.3.1 | Coaxial element | | | | |
| | 6.3.2 | Pair/quad element | | | | |
| | 6.3.3 | Current carrying element | | | | |
| | 6.3.4 | Crosstalk between elements | | | | |
| | 6.4 M | echanical requirements of hybrid cable | 11 | | | |
| | 6.4.1 | Tensile | | | | |
| | 6.4.2 | Crush | 11 | | | |
| | 6.4.3 | Impact | 12 | | | |
| | 6.4.4 | Repeated bending | 12 | | | |
| | 6.4.5 | Cold bend | | | | |
| | 6.4.6 | Torsion | 12 | | | |
| | 6.4.7 | Bend | 13 | | | |
| | 6.4.8 | Abrasion resistance of cable sheaths | | | | |
| | 6.4.9 | Abrasion resistance of cable markings | 13 | | | |
| | 6.4.10 | Tensile strength, and elongation at break of sheath | | | | |
| | 6.4.11 | Other mechanical requirements | | | | |
| | | nvironmental requirements of hybrid cable | | | | |
| | 6.5.1 | Temperature cycling | | | | |
| | 6.5.2 | Water penetration | | | | |
| | 6.5.3 | Compound flow | | | | |
| _ | 6.5.4 | UV resistance test | | | | |
| 7 | | | 14 | | | |
| 8 Quality assurance | | assurance | 14 | | | |
| | | | | | | |
| Та | Table 1 – Requirements of optical element | | | | | |
| Та | Table 2 – Requirements of coaxial element | | | | | |
| Та | Table 3 – Requirements of pair/quad element10 | | | | | |
| Та | Table 4 – Requirements of current carrying element11 | | | | | |
| | | | | | | |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HYBRID COMMUNICATION CABLES -

Part 3: Outdoor hybrid cables - Sectional specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62807-3 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

The text of this International Standard is based on the following documents:

| Draft | Report on voting |
|---------------|------------------|
| 46C/1243/FDIS | 46C/1250/RVD |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62807 series, published under the general title *Hybrid telecommunication cables*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

"is a preview developed by the

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

HYBRID COMMUNICATION CABLES -

Part 3: Outdoor hybrid cables - Sectional specification

1 Scope

This part of IEC 62807 is a sectional specification for outdoor hybrid communication cables intended to be used externally in various applications. It specifies terms, definitions, symbols and abbreviated terms, the design and construction, rated values and characteristics, performance requirements and test methods, packaging and quality assurance.

Hybrid cables are designed for networks and customer premises cabling that transmit data, telecommunication, instrumentation, control and signalling services over optical fibres and/or broadband data over coaxial element, wire/pair/quad element and can have the option of supplying electrical current to a remote equipment.

In the IEC 62807 series, the current carrying elements are used only to supply power to the equipment within the communication network. They are not used for electricity distribution or transmission, nor for power supply to domestic appliances. The specific uses are defined in the relevant specification.

The relationship between each of the MICE classifications in ISO/IEC 11801-1, performance requirements and test methods of hybrid cables being proposed in a specific application are fully considered and aligned.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-461, International Electrotechnical Vocabulary (IEV) – Part 461: Electric cables

IEC 60050-731, International Electrotechnical Vocabulary (IEV) - Part 731: Optical fibre communication

IEC 60227 (all parts), Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V

IEC 60227-1, Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V – Part 1: General requirements

IEC 60228, Conductors of insulated cables

IEC 60502-1, Power cables with extruded insulation and their accessories for rated voltages from 1 kV (Um = 1.2 kV) up to 30 kV (Um = 36 kV) – Part 1: Cables for rated voltages of 1 kV (Um = 1.2 kV) and 3 kV (Um = 3.6 kV)

IEC 60793-1-40, Optical fibres – Part 1-40: Attenuation measurement methods

IEC 60793-1-44, Optical fibres – Part 1-44: Measurement methods and test procedures – Cut-off wavelength

IEC 60793-1-46, Optical fibres – Part 1-46: Measurement methods and test procedures – Monitoring of changes in optical transmittance

IEC 60793-1-48, Optical fibres – Part 1-48: Measurement methods and test procedures – Polarization mode dispersion

IEC 60794-1-1, Optical fibre cables – Part 1-1: Generic specification – General

IEC 60794-1-21, Optical fibre cables – Part 1-21: Generic specification – Basic optical cable test procedures – Mechanical test methods

IEC 60794-1-22, Optical fibre cables – Part 1-22: Generic specification – Basic optical cable test procedures – Environmental test methods

IEC 60794-3, Optical fibre cables – Part 3: Outdoor optical fibre cables – Sectional specification

IEC 60811-501, Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds

IEC 61156 (all parts), Multicore and symmetrical pair/quad cables for digital communications

IEC 61156-1, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

IEC 61196 (all parts), Coaxial communication cables

IEC 61196-1, Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements

IEC 61196-1-102, Coaxial communication cables – Part 1-102: Electrical test methods – Test for insulation resistance of cable dielectric

IEC 61196-1-105, Coaxial communication cables – Part 1-105: Electrical test methods – Test for withstand voltage of cable dielectric

IEC 61196-1-108, Coaxial communication cables – Part 1-108: Electrical test methods – Test for characteristic impedance, phase and group delay, electrical length and propagation velocity

IEC 61196-1-112, Coaxial communication cables – Part 1-112: Electrical test methods – Test for return loss (uniformity of impedance)

IEC 61196-1-113, Coaxial communication cables – Part 1-113: Electrical test methods – Test for attenuation constant

IEC 61196-1-122, Coaxial communication cables – Part 1-122: Electrical test methods – Test for cross-talk between coaxial cables

IEC 61196-1-201, Coaxial communication cables – Part 1-201: Environmental test methods – Test for cold bend performance of cable

IEC TR 61931, Fibre optic – Terminology

IEC 62153-4-3, Metallic communication cable test methods – Part 4-3: Electromagnetic Compatibility (EMC) – Surface transfer impedance – Triaxial method

IEC 62153-4-4, Metallic communication cable test methods – Part 4-4: Electromagnetic compatibility (EMC) – Test method for measuring of the screening attenuation as up to and above 3 GHz, triaxial method

IEC 62153-4-9, Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method

IEC 62807-1, Hybrid telecommunication cables - Part 1: Generic specification

IEC 62821 (all parts), Electric cables – Halogen-free, low smoke, thermoplastic insulated and sheathed cables of rated voltages up to and including 450/750 V

IEC 62821-1, Electric cables – Halogen-free, low smoke, thermoplastic insulated and sheathed cables of rated voltages up to and including 450/750 V – Part 1: General requirements

IEC 63294, Test methods for electric cables with rated voltages up to and including 450/750 V

ISO/IEC 11801-1, Information technology – Generic cabling for customer premises – Part 1: General requirements

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms, definitions, symbols and abbreviated terms given in IEC 60050-461, IEC 60050-731, IEC 62807-1, IEC 60794-1-1, IEC 61156-1, IEC 61196-1, IEC 60227-1, IEC 62821-1, IEC 60502-1 and IEC TR 61931 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1

hybrid cable

cable that is composed of at least one optical fibre element and one metallic element such as a coaxial element, wire/pair/quad element or other current carrying elements

3.2

rated voltage

in a cable, reference voltage for which the cable is designed

Note 1 to entry: The rated voltage in an alternating current system is expressed by the combination of two values U_0/U_c expressed in volts, where

- a) U_0 is the RMS value between any insulated phase conductor and the "earth" (metal covering of the cable or the surrounding medium);
- b) U is the RMS value between two phase conductors of a multicore cable or of a system of a single core cable.

In an alternating current system, the rated voltage of a cable or cord shall be at least equal to the nominal voltage of the system for which it is intended. This condition applies to the values of both U_0 and U.