INTERNATIONAL STANDARD

ISO 11819-1

Second edition 2023-02

Acoustics — Measurement of the influence of road surfaces on traffic noise —

Part 1: Statistical pass-by method

Acoustique — Mesurage de l'influence des revêtements de chaussées sur le bruit émis par la circulation —

Partie 1: Méthode statistique au passage



Reference number ISO 11819-1:2023(E)



© ISO 2023

tation, no part of 'including plot' 'om either'. All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents				
Fore	word		v	
Intro	oductio	n	vii	
1	Scope	e	1	
2	Norm	native references	1	
3	Term	is and definitions	2	
	3.1 3.2 3.3 3.4 3.5 3.6 3.7	Types of noise Measurement method Road speed categories Vehicle categories Measured noise quantities Road surface terms applicable in this method Backing board terms	2 2 3 3	
4	Symb	ools and abbreviated terms	4	
5	Meas	ruring principle	5	
6	6.1 6.2 6.3	Instruments for acoustical measurements 6.1.1 General 6.1.2 Verification Instruments for vehicle speed measurements 6.2.1 General 6.2.2 Verification Instruments for temperature measurements 6.3.1 General 6.3.2 Verification	5 5 6 6 6	
7	Tost	sites		
,	7.1 7.2 7.3 7.4 7.5	Selection of measuring site		
8	Traff	ic conditions	10	
	8.1 8.2 8.3 8.4	Vehicle classification Selection of vehicles for measurement Minimum number of vehicles Road speed categories	10 10 11 12	
9	Meas 9.1	uring procedure		
	9.1 9.2 9.3 9.4 9.5 9.6	Microphone position Calibrations Sound level measurement Frequency spectrum measurement Speed measurement Temperature measurement	13 14 14 14	
10	Mete 10.1	orological conditions Wind		
	10.1 10.2 10.3	Temperature Recommendations on road surface moisture	14	
11	Back	ground noise	15	
12	Norm	nalization of data	15	

ISO 11819-1:2023(E)

	12.1	Compensating for the effect of the additional (higher) microphone position	15
	12.2	Combining vehicle categories H2 and H3+ into a common heavy vehicle category H	
	12.3		16
	12.4		16
	12.5	Noise versus speed – normalization of frequency spectra for vehicles in categories	10
	12.6	P and H Determination of SPB sound level at reference speeds	
	12.7	Useful speed range for the speed normalization	
	12.8	Correction of sound levels according to temperature	18
13		urement uncertainty	
14		rted data	
	14.1 14.2	General information Information relating to the location and appearance of the test site	
	14.2	Information relating to the type and construction of the tested road surface	21 21
	14.4	Information relating to the condition of the tested surface and environmental factors	
	14.5	Road speed category and vehicle information	
	14.6	Measured and calculated sound level and speed data	21
	14.7	Others	22
Anne	ex A (no	rmative) Vehicle categories	23
Anne	ex B (inf	formative) Determination of the statistical pass-by index (SPBI)	27
Anne	ex C (inf	Formative) The backing board variant	29
Anne	ex D (in:	formative) Adding 95 % confidence intervals	34
Anne	ex E (inf	Formative) Validity and stability of the method	35
Anne	ex F (inf	formative) Reference road surface	36
Anne	ex G (inf	formative) Monitoring the stability of sound levels of vehicle fleets	38
Anne	ex H (in	formative) Uncertainty	40
Anne	ex I (inf	ormative) Example of test report	43
Bibli	ograph	y	47
			5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*, in collaboration with ISO Technical Committee TC 227, *Road materials*, in accordance with the agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition of ISO 11819-1:1997 and ISO/PAS 11819-4:2013, which have been technically revised.

The main changes are as follows:

- ISO/PAS 11819-4 has now been integrated as Annex C;
- the backing board method makes possible a wider application of the method, where the old version would not meet the acoustical free field conditions;
- changes to nomenclature for vehicle categories in <u>3.1</u>, including the introduction of a 'generic' vehicle category and the introduction of a minimum gross vehicle weight (8 t) for dual-axle heavy vehicles;
- changes to some key symbols and abbreviations in Clause 4;
- using a generic speed exponent for heavy vehicles instead of calculating a speed exponent from each measurement;
- using a correction to 2-axle medium vehicles for correcting them to a level typical of 3-axle heavy vehicles;
- more liberal requirement regarding the number of heavy vehicles to measure;
- an additional microphone position (at the height of 3,0 m) can be used in cases where reflecting objects could influence the results.

The objective of the changes and supplements is to make SPB measurements more practical while maintaining or reducing uncertainties.

ISO 11819-1:2023(E)

A list of all parts in the ISO 11819 series can be found on the ISO website.

rin the L.

or questions, mg of these bod. Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The emission of road traffic noise greatly depends on road surface characteristics, notably on texture and porosity; the latter due to the flow resistivity of the air voids. Both these characteristics influence the generation of tyre/road noise and, in addition, the porosity can influence the emission of sound, particularly when the emission takes place close to the surface. Power unit noise, which is usually generated at a greater height above the road surface than tyre/road noise, can also be affected during emission by the porosity characteristics of the road surface. These effects lead to differences in sound levels, associated with a given traffic flow and composition, from different road surfaces of up to 15 dB, which can have a substantial impact on the environmental acoustic quality alongside a road.

It is therefore important to be able to measure this influence by a standardized method and to arrive at a quantitative ranking of road surfaces with respect to traffic noise. This document offers such a method, the objective of which is to satisfy a need expressed by road planners, road administrators, contractors, manufacturers of so-called "low-noise surfaces" and by other parties concerned with the prediction and control of road traffic noise. SOR DELIGIO DELIGIO DEL CONTROL DEL CONTRO

This document is a previous general ded by tills

Acoustics — Measurement of the influence of road surfaces on traffic noise —

Part 1:

Statistical pass-by method

1 Scope

This document specifies a method of comparing traffic noise on different road surfaces for various compositions of road traffic for the purpose of evaluating different road surface types. Sound levels representing either light or heavy vehicles at selected speeds are assigned to a certain road surface. The method is applicable to traffic travelling at constant speed, i.e. free-flowing conditions at posted speeds of 50 km/h and upwards. For conditions where traffic is not free flowing, such as at junctions and where the traffic is congested, the method is not applicable.

A standard method for comparing the noise characteristics of road surfaces gives road and environment authorities a tool for establishing common practices or limits regarding the use of road surfaces meeting certain noise criteria. However, it is not within the scope of ISO 11819 (all parts) to suggest such criteria.

The statistical pass-by (SPB) method is suitable for use for the following main purposes:

- to classify road surfaces according to their influence on traffic noise (surface classification);
- to assist in verifying conformity of production of road surfaces;
- to evaluate acoustic performance of road surfaces throughout operation relative to new condition;
- to evaluate the influence of different road surfaces on traffic noise at sites irrespective of condition and service time;
- to evaluate acoustic performance of a road surface relative to a reference surface.

Due to practical restrictions, the method cannot be applied at all possible locations. However, the backing board method can allow some locations to be tested that were not previously acceptable.

<u>Clause 5</u> gives a general description of the SPB method.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1996-2, Acoustics — Description, measurement and assessment of environmental noise — Part 2: Determination of sound pressure levels

ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

IEC 60942:2017, *Electroacoustics* — *Sound calibrators*

IEC 61183, Electroacoustics - Random-incidence and diffuse-field calibration of sound level meters

ISO 11819-1:2023(E)

IEC 61260-1, Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications

IEC 61672-1, Electroacoustics — Sound level meters — Part 1: Specifications

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1 Types of noise

3.1.1

vehicle noise

total noise from an individual vehicle, including the two major components of *power unit noise* (3.1.3) and tyre/road noise (3.1.2)

3.1.2

tyre/road noise

noise generated by the tyre/road interaction

3.1.3

power unit noise

noise generated by the vehicle engine, exhaust system, air intake, fans, transmission, etc.

3.1.4

background noise

unwanted noise interfering with the noise that is intended to be measured

3.2 Measurement method

3.2.1

statistical pass-by method

SPB method

measurement procedure designed to evaluate vehicle and traffic noise generated on different sections of road surface under specific traffic conditions

Note 1 to entry: The measurements are taken from a great number of vehicles operating normally on the road. Results obtained using this procedure are normalized to standard speeds according to the category or type of road being considered.

3.3 Road speed categories

NOTE Three categories of roads are defined with respect to the range of speeds at which the traffic flows and usually associated with certain areas (urban, suburban, rural, etc.).

3.3.1

"low" speed road

road category where traffic operates at an average speed of 45 km/h to 64 km/h

3.3.2

"medium" speed road

road category where traffic operates at an average speed of 65 km/h to 99 km/h

Note 1 to entry: These conditions are mostly found in suburban areas or on rural highways.