INTERNATIONAL STANDARD

ISO 18123

Second edition 2023-03

Solid biofuels — Determination of volatile matter

Biocombustibles solides – Détermination des matières volatiles



Reference number ISO 18123:2023(E)



© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Fore	word	iv
Intro	oduction	v
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Principle	
5	Apparatus5.1Furnace5.2Thermocouples and temperature calibration5.3Crucible5.4Crucible stand5.5Balance5.6Desiccator and desiccant	2 3 3 4 5
6	Sample preparation 6.1 General 6.2 Sample size 6.3 Sample conditioning	
7	Procedure 7.1 General 7.2 Conditioning of crucibles 7.3 Charging of crucibles 7.4 Volatilization of test portion	
8	Calculation	7
9 10	Performance characteristics 9.1 Repeatability 9.2 Reproducibility Test report	
	iography	
		25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 238, *Solid biofuels*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 335, *Solid biofuels*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 18123:2015), which has been technically revised.

The main changes are as follows:

- ISO 21945 added to <u>Clause 2</u>;
- specification that the entire procedure shall be done in duplicate;
- EN standards replaced by ISO documents;
- minor editorial corrections.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

Volatile matter is determined as the loss in mass, less that due to moisture, when a solid biofuel is heated out of contact with air under standardised conditions. The test is empirical and, in order to ensure reproducible results, it is essential that the rate of heating, the final temperature and the overall duration of the test are carefully controlled. It is also essential to exclude air from the solid biofuel during heating to prevent oxidation. The fit of the crucible lid is therefore critical. The moisture i, eral. setion c. content of the general analysis sample is determined at the same time as the volatile matter so that the appropriate correction can be made.

this document is a preview demendence of the document is a preview demendence of the document of the document

Solid biofuels — Determination of volatile matter

1 Scope

This document specifies the requirements and method used to determine the volatile matter of solid biofuels. It is intended for persons and organisations that manufacture, plan, sell, erect or use machinery, equipment, tools and entire plants related to solid biofuels, and for all persons and organisations involved in producing, purchasing, selling and utilizing solid biofuels.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14780, Solid biofuels — Sample preparation

ISO 16559, Solid biofuels — Vocabulary

ISO 18134-3, Solid biofuels — Determination of moisture content — Oven dry method — Part 3: Moisture in general analysis sample

ISO 18135, Solid Biofuels — Sampling

ISO 21945, Solid biofuels — Simplified sampling method for small scale applications

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16559 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

4 **Principle**

A portion of the general analysis sample is heated mostly out of contact with air at 900 °C \pm 10 °C for 7 min. The furnace is normally not equipped with a vacuum; however, there is a partial vacuum created during heating to a degree depending on air influx during charging of the test portion into the chamber and the air trapped in the crucible before the lid is put on. The percentage of volatile matter is calculated from the loss in mass of the test portion after deducting the loss in mass due to moisture.

Automatic equipment may be used when the method is validated with biomass reference samples of an adequate biomass type. The automatic equipment shall fulfil all the requirements given in <u>Clauses 5</u> to <u>8</u> regarding sample size, atmosphere, temperatures and weighing accuracy.

5 Apparatus

The usual laboratory apparatus and, in particular, the following shall be used.