

---

---

**Photography — Electronic still-picture  
imaging — Noise measurements**

*Photographie — Imagerie des prises de vue électroniques —  
Mesurages du bruit*



This document is a preview generated by EUS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b>	<b>v</b>
<b>Introduction</b>	<b>vi</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Test conditions</b>	<b>3</b>
4.1 General	3
4.2 Illumination	4
4.2.1 Characteristics	4
4.2.2 Daylight illumination	4
4.2.3 Tungsten illumination	4
4.2.4 Uniformity of illumination and reflection test chart illumination geometry	4
4.2.5 Light source amplitude variations	4
4.3 Temperature and relative humidity	4
4.4 White balance	5
4.5 Infrared (IR) blocking filter	5
4.6 Photosite integration time	5
4.7 Compression	5
<b>5 Noise measurement procedures</b>	<b>5</b>
5.1 General	5
5.2 Measurement of a DSC using a test chart	5
5.2.1 General	5
5.2.2 OECF measurement	5
5.2.3 Adjustment of illumination	6
5.2.4 Test chart	6
5.2.5 Non-uniformity and image structure spatial components	6
5.2.6 Camera lens focus	6
5.3 Measurement of a DSC having manual exposure control	7
5.3.1 General	7
5.3.2 OECF measurement	7
5.3.3 Adjustment of illumination	8
5.3.4 Test densities	8
5.3.5 Diffuser setting	8
5.3.6 Camera lens focus	8
5.4 Measurement of a DSC having a removable lens	9
5.4.1 General	9
5.4.2 OECF measurement	9
5.4.3 Adjustment of illumination	9
5.4.4 Test densities	9
<b>6 Calculation of metrics</b>	<b>10</b>
6.1 General	10
6.2 Noise	10
6.2.1 General	10
6.2.2 Determining the noise for luminance measurements	11
6.2.3 Determining the noise for exposure measurements	12
6.3 Signal-to-noise ratios — large area	12
6.3.1 General	12
6.3.2 Determining the reference luminance and luminance value for calculating signal-to-noise ratio	12
6.3.3 Determining the signal-to-total noise ratio	13
6.3.4 Determining the temporal signal-to-noise ratio	14
6.3.5 Determining the fixed pattern signal-to-noise ratio	14

6.3.6	Determining the exposure values and the signal-to-noise ratios for exposure measurements.....	15
6.4	DSC dynamic range.....	15
6.4.1	General.....	15
6.4.2	Determining the DSC dynamic range for luminance measurements.....	15
6.4.3	Determining the DSC dynamic range for exposure measurements.....	17
7	<b>Presentation of results</b> .....	<b>17</b>
7.1	General.....	17
7.2	Signal-to-noise ratios.....	17
7.3	DSC dynamic range.....	17
	<b>Annex A (normative) Noise component analysis</b> .....	<b>18</b>
	<b>Annex B (normative) Visual noise measurements</b> .....	<b>24</b>
	<b>Annex C (normative) Removing low frequency variations from the image signals</b> .....	<b>34</b>
	<b>Annex D (informative) Procedure for determining signal-to-noise ratio</b> .....	<b>35</b>
	<b>Annex E (informative) Practical viewing conditions for various output media</b> .....	<b>37</b>
	<b>Annex F (informative) Introduction of perceptually uniform mapping of visual noise to noisiness JND</b> .....	<b>38</b>
	<b>Bibliography</b> .....	<b>41</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 42, *Photography*.

This fourth edition cancels and replaces the third edition (ISO 15739:2017), which has been technically revised.

The main changes are as follows:

- several terms and definitions have been modified, added, and deleted (see [Clause 3](#));
- calculation procedures of camera noise, signal-to-noise ratios, and DSC dynamic range have been revised for measurement accuracy (see [Clause 6](#));
- presentation of results has been specified expressly (see [Clause 7](#));
- description of noise component analysis has been revised to be more detailed (see [Annex A](#));
- measurement method of visual noise has been revised to model the human visual system more closely (see [Annex B](#));
- method for removing low frequency variations from the image signals has been revised and changed from informative to normative processing (see [Annex C](#));
- description of procedure for determining signal-to-noise ratio has been revised (see [Annex D](#));
- introduction of perceptually uniform mapping of visual noise to noisiness JND has been added (see [Annex F](#)).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

Noise is an important attribute of electronic still-picture imaging. If noticeable levels of noise exist in the images captured by a camera, then detail textures of objects are lost in reproduction and the visibility of the images is degraded. Therefore, measurement methods for noise are very important and are needed to provide important information relevant to evaluating image fidelity and the visibility of noise in captured images. Measurement methods are also important for assessing camera performance relative to these image quality factors.

The primary sources of noise in captured images are photon shot noise, dark current shot noise, analogue processing readout noise of image sensors, and quantization noise of A/D converters. This type of noise source adds spatially random noise to captured still images, whose spatial pattern differs from frame to frame. The other type of noise source includes dark current pattern noise, row/column pattern noise, and photo response non-uniformity of image sensors. This type of noise source also introduces spatially random noise in captured images; however, its spatial pattern does not change under the same shooting conditions.

The noise level introduced by these sources in output images is highly dependent on shooting conditions, such as the camera exposure time, aperture value, and ISO sensitivity. Camera operating temperature is also an influential factor. Some camera processing, such as contrast amplification and noise reduction, heavily influence the noise spectrum, in addition to the noise level itself.

The image quality metrics described in this document are determined from the measurement of spatially distributed noise in the output still image that is viewed by an observer. The metrics include the effect of the internal camera processing on the spectrum and level of the noise.

When observers view output images, several factors affect how they perceive noise in images, in addition to the noise level itself. Observers view noise differently depending on the apparent tone of the area being viewed, the luminance and colour channels where noise exists, the noise spectrum, and the viewing conditions.

This document specifies methods for measuring noise and related metrics of digital still cameras accounting for these influential factors. Measurement conditions are specified to minimize the influence of disturbance factors, to ensure that temporal and spatial statistical property changes are negligible, and to provide a good estimate of the noise level.

The main body of this document specifies methods for measuring input-referred noise, signal-to-noise ratios, and DSC dynamic range. Noise is determined as an estimate of the perceived noise computed using root mean square values measured in image signals linearized from the camera output signals. The two types of spatially random noise, temporal and fixed pattern, are determined using a noise component analysis applied to multiple captured images, the details of which are provided in [Annex A](#).

[Annex B](#) describes a procedure for measuring the visual noise (an output-referred noise metric) using a human visual model that aims to predict the perceived quality of the image. The model weights spectral components of the noise and takes into account the noise spectrum, viewing conditions, and the perceived difference between luminance and colour channels. The metric has been shown to provide a high level of correlation with human perception of noise in images.

Low frequency variations may be introduced in the captured image due to lens shading and non-uniform test chart illumination. Since these variations can influence the noise measurement a method for removing low frequency variations from the image is provided in [Annex C](#).

[Annex D](#) provides a recommended step-by-step procedure for determining the signal-to-noise ratio.

[Annex E](#) describes recommendations for practical viewing conditions for various output media.

[Annex F](#) introduces perceptually uniform mapping of visual noise to noisiness JND.

# Photography — Electronic still-picture imaging — Noise measurements

## 1 Scope

This document specifies methods for measuring and reporting the noise versus signal level and dynamic range of digital still cameras. It applies to both monochrome and colour electronic digital still cameras.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 7589:2002, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 12232:2019, *Photography — Digital still cameras — Determination of exposure index, ISO speed ratings, standard output sensitivity, and recommended exposure index*

ISO 14524, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

ITU-R BT.709-6, *Parameter values for the HDTV Standards for production and International programme exchange*

IEC 61966-2-1, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB*

IEC 61966-2-1/Amd.1:2003, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB — Amendment 1*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### camera opto-electronic conversion function

#### camera OECF

relationship between the input scene log luminances and the output pixel values for an opto-electronic digital capture system

Note 1 to entry: The unit of luminance ( $L$ ) is  $\text{cd}/\text{m}^2$ . Log luminance is dimensionless, expressed as  $\log_{10} (L/L_0)$ , where  $L_0 = 1 \text{ cd}/\text{m}^2$ .