
**Information technology — Digitally
recorded media for information
interchange and storage — Quality
discrimination method for optical
disks and operating method of
storage systems for long-term data
preservation**

This document is a preview generated by EUS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Quality of optical disk	4
4.1 Types and quality indicators of optical disk (CD, DVD and BD)	4
4.2 Lifetime estimation of optical disks	4
5 Recordable optical disk and drive used for long-term data preservation	5
5.1 General	5
5.2 Recordable optical disk used for long-term data preservation	5
5.3 Drive used for long-term data preservation	5
5.4 Combination of recordable optical disk and drive	5
6 Quality discrimination method for recordable optical disk	5
6.1 General	5
6.2 Test method	5
6.2.1 Preparation for test	5
6.2.2 Test parameters	5
6.2.3 Recording method of optical disk for test	6
6.2.4 Playback evaluation drive	6
6.3 Quality classification by data error testing	6
7 Quality test of recordable optical disk and operation of long-term storage systems	7
7.1 General	7
7.2 Initial quality test	7
7.3 Periodic quality test	8
8 Quality test of read-only optical disk and operation of long-term storage systems	10
8.1 General	10
8.2 Initial quality test	10
8.2.1 Preparation for test	10
8.2.2 Test parameters	10
8.2.3 Playback evaluation drive	10
8.2.4 Test operation	10
8.3 Periodic quality test	11
9 Handling and storage of optical disks	12
Annex A (normative) Defect management on BD recordable disk	13
Bibliography	15

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digitally Recorded Media for Information Interchange and Storage*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

In the digital information society, there is no secure means for storing and accumulating rapidly growing digital information safely and on a permanent basis. There is therefore a concern that the world will face a critical situation and significant problem in the near future. Within this context, optical disks are increasingly being considered as a solution for archiving storage media with high capacity because of their unique features (such as low cost, high compatibility and low energy consumption) and more specifically, their data storage capability without power consumption.

On the other hand, the data storage performance of an optical disk often depends on the initial recording quality and storage environment conditions. Therefore, when an optical disk is used for long-term data storage, it is desirable to check its estimated lifetime and initial recording quality by using a combination of a good quality optical disk and a good quality recording drive.

For this reason, this document specifies quality discrimination criteria using the initial quality of recordable optical disks as an index. It also specifies a quality judgement method for storage systems for long-term data preservation, including the consistency of the recordable optical disks and recording drives to ensure the quality of recorded digital data. In this document, recordable (write-once) optical disks are adopted as long-term storage media to ensure the security of the stored digital data when giving greater importance to evidence, because physical overwriting and deletion by erroneous or intentional operation can be prevented.

This document is also applicable to read-only optical disks such as CD-ROM, DVD-ROM and BD-ROM, specifying the quality judgement method for long-term data preservation.

This document enables users to build data storage systems that use recordable and/or read-only optical disks for long-term data preservation. Optical disks with sufficient quality can be confirmed based on the results of the initial quality test. Through the periodic quality test described in this document, the possibility of data restoration from the optical disk can be continuously monitored. Using this document, manufacturers will be able to supply recordable and read-only optical disks incorporated with suitable recording and playback drives for building data storage systems for long-term data preservation.

In the future, it will be possible to build data storage systems using optical disks for storing and accumulating important digital information safely and on a permanent basis, for consumer use and professional use. The safe and secure progress of the digital information society towards greater sophistication can be expected.

Information technology — Digitally recorded media for information interchange and storage — Quality discrimination method for optical disks and operating method of storage systems for long-term data preservation

1 Scope

This document specifies a quality discrimination method for optical disks and the operating method of storage systems for long-term digital data preservation using optical disks and optical disk drives (hereinafter referred to as "drives").

It is applicable to recordable (write-once) optical disks which can prevent physical overwriting and deletion by erroneous or intentional operation in contexts where greater importance is given to evidence. It is also applicable to read-only (ROM) optical disks.

This document specifies:

- combinations of recordable optical disks and drives used for long-term data preservation;
- quality discrimination criteria for recordable optical disks and the operation method of long-term storage systems;
- a quality test for read-only optical disks and the operation method of long-term storage systems;
- quality discrimination criteria for BD recordable disks when adopting defect management.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10149, *Information technology — Data interchange on read-only 120 mm optical data disks (CD-ROM)*

ISO/IEC 12862, *Information technology — 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD recordable disk for dual layer (DVD-R for DL)*

ISO/IEC 16448, *Information technology — 120 mm DVD — Read-only disk*

ISO/IEC 16449, *Information technology — 80 mm DVD — Read-only disk*

ISO/IEC 16963, *Information technology — Digitally recorded media for information interchange and storage — Test method for the estimation of lifetime of optical disks for long-term data storage*

ISO/IEC 17344, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R format — Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 16X)*

ISO/IEC 23912, *Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R)*

ISO/IEC 25434, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R DL format — Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed up to 16X)*

ISO/IEC 30190, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk*

ISO/IEC 30191, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes single sided disk and 200,0 Gbytes double sided disk) and Quadruple Layer (128,0 Gbytes single sided disk) BD Recordable disk*

ECMA-394, *Recordable Compact Disk Systems CD-R Multi-Speed*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

maximum C1 error

Max C1

maximum number of C1 errors per second averaged over any 10 s in one of the relevant areas on a CD, measured at the input of error correction decoder under the standard data transfer rate

Note 1 to entry: See ISO/IEC 10149, ISO/IEC 16963, and ECMA 394.

3.2

maximum PI SUM 8

Max PI SUM 8

maximum parity of inner code (PI) error count at any consecutive 8 *error correction code* (3.7) blocks in one of the relevant areas on a DVD, measured at the first pass of the decoder before correction

Note 1 to entry: See ISO/IEC 12862, ISO/IEC 16448, ISO/IEC 16449, ISO/IEC 17344, ISO/IEC 23912, and ISO/IEC 25434.

3.3

maximum random symbol error rate

Max RSER

maximum value of random symbol error rate in one of the relevant areas on a BD excluding burst errors of 40 bytes or more, measured at the input of error-correction decoder

Note 1 to entry: See ISO/IEC 30190, and ISO/IEC 30191.

Note 2 to entry: Maximum random symbol error rate shall be measured by averaging over any N consecutive *long distance code* (3.8) blocks to reduce the impact of burst errors, with the condition that all blocks are recorded in a continuously written sequence, in a discontinuously written sequence excluding disk defects. In this document, the number of N shall be 10 000, and when *defect management* (3.17) is applied, the number of N shall be 10 000 at maximum.

3.4

maximum burst error

Max BE

maximum sum of the lengths of burst errors with length greater than or equal to 40 bytes in one recording-unit block in one of the relevant areas on a BD

Note 1 to entry: See ISO/IEC 30190 and ISO/IEC 30191.

Note 2 to entry: The number of burst errors is not covered in this document.