
**Telecommunications and
information exchange between
systems — Recursive inter-network
architecture —**

**Part 7:
Flow allocator**

*Télécommunications et échange d'information entre systèmes —
Architecture récursive inter-réseaux —*

Partie 7: Allocateur de débit



This document is a preview generated by EUS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Overview of the flow allocator.....	2
4.1 Narrative description of the service.....	2
4.2 Narrative description of the task.....	2
5 Service definition.....	2
6 Detailed specification of the task.....	2
6.1 Common elements.....	2
6.1.1 Directory forwarding table.....	2
6.1.2 Flow object.....	2
6.2 Specification.....	4
6.2.1 General.....	4
6.2.2 Behaviour of a flow allocator.....	4
6.2.3 Behaviour of a flow allocator instance.....	5
6.2.4 Events.....	8
6.3 Description of the policies.....	10
6.3.1 AllocateNotifyPolicy.....	10
6.3.2 AllocateRetryPolicy.....	10
6.3.3 NewFlowRequestPolicy.....	10
6.3.4 SeqRollOverPolicy.....	10

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6 *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC 4396 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

This document defines the sequencing of the interactions of the flow allocator (FA). It is not, strictly speaking, a protocol specification. The protocol used in this document is the common distributed application protocol (CDAP). This document uses the objects required to create a flow between two processes and bind their endpoints to the applications that requested the flow.

The flow allocator is responsible for creating and managing an instance of interprocess communication (IPC), i.e. a flow. The IPC-API communicates requests from the application to the distributed IPC facility (DIF). An Allocate-Request causes an instance of the flow allocator to be created. The flow allocator-instance (FAI) determines what policies will be utilized to provide the characteristics requested in the Allocate. It is important that how these characteristics are communicated by the application is decoupled from the selection of policies. This gives the DIF important flexibility in using different policies, but also allows new policies to be incorporated. The FAI creates the error and flow control protocol (EFCP) instance for the requested flow before sending the CDAP Create Flow Request to find the destination application and determine whether the requestor has access to it.

A create request is sent with the source and destination application names, quality of service information, and policy choices, as well as the necessary access control information. Using the name space management (NSM) function, the FAI searches the IPC process (IPCP) in the DIF that resides on the processing system that has access to the requested application. This exchange accomplishes three functions:

- follows the search rules using the NSM function to find the address of an IPC-Process with access to the destination application;
- determines whether the requesting application process has access to the requested application process and whether or not the destination IPC-Process can support the requested communication;
- instantiates the requested application process, if necessary, and allocate a FAI and port-id in the destination IPCP.

The create response will return an indication of success or failure. If successful, destination address and connection-id information will also be returned along with suggested policy choices. This gives the IPC-Processes sufficient information to then bind the port-ids to an EFCP-instance, i.e. a connection, so that data transfer may proceed.

Telecommunications and information exchange between systems — Recursive inter-network architecture —

Part 7: Flow allocator

1 Scope

This document provides the flow allocator (FA) specification. It includes an overview of the flow allocator, its service definition, and its specification.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4396-1, *Telecommunications and information exchange between systems – Recursive Inter-Network Architecture – Part 1: Reference Model*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4396-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 directory forwarding table

table that maintains a set of entries that map application naming information to interprocess communication (IPC) process addresses which belong to the IPC Processes, where the requested application can be found or has information about where to search next

3.2 error and flow control protocol instance EFCP instance

instantiation of EFCP for managing a single connection

3.3 Quality of Service-cube-id QoS-cube-id

identifier unambiguous within this distributed IPC facility (DIF) that identifies a QoS-hypercube

Note 1 to entry: As QoS-cubes are created they are sequentially enumerated. QoS-cube-id is an element of Data Transfer PCI that may be used to classify protocol-data-units (PDUs).