### INTERNATIONAL STANDARD

ISO/IEC 15426-2

Third edition 2023-12

# Information technology — Automatic identification and data capture techniques — Bar code verifier conformance specification —

#### Part 2:

#### **Two-dimensional symbols**

Technologies de l'information — Techniques automatiques d'identification et de capture des données — Spécifications de conformité des vérificateurs de codes à barres —

Partie 2: Symboles bi-dimensionnels





© ISO/IEC 2023

tation no part of "including phore" "om either?" All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

	vord duction	iv
	duction	
1		v
	Scope	1
2	Normative references	
3	Terms and definitions	
	Symbols	
4		
5	Conformance	
6	Functional requirements 6.1 General requirements 6.2 Reflectance calibration 6.3 Mandatory functions 6.3.1 Verifiers for multi-row bar code symbols 6.3.2 Verifiers for two-dimensional matrix symbols	2 
	6.4 Optional functions	3
8	General constructional and operational requirements 7.1 Installation, operation and maintenance 7.2 Power supply 7.3 Temperature 7.3.1 Operating temperature range 7.3.2 Storage temperature range 7.4 Humidity 7.5 Ambient light immunity  Test requirements 8.1 Test methods 8.1.1 General 8.1.2 Selection of equipment for testing 8.1.3 Scanning parameters 8.1.4 Test measurements 8.2 Test environment 8.3 Primary reference test symbols 8.4 Test report	4 4 4 4 4 5 5 5 5 5 5 6
9	Declaration and labelling	6
10	Equipment specification	7
Anne	x A (normative) Primary reference test symbols	8
Anne	x B (normative) Verification requirements for primary reference test symb	ools13
Biblio	ography	14

#### Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a> or <a href="www.iso.org/directives">www.iso.org/directives<

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <a href="https://patents.iec.ch">www.iso.org/patents</a> and <a href="https://patents.iec.ch">https://patents.iec.ch</a>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>. In the IEC, see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>. In the IEC, see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This third edition cancels and replaces the second edition (ISO/IEC 15426-2:2015), which has been technically revised.

The main changes are as follows:

- tolerances for certain parameters have been clarified;
- fixed pattern damage test symbol for Aztec code has been added.

A list of all parts in the ISO/IEC 15426 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a> and <a href="https://www.iso.org/members.html">www.iso.org/members.html</a

#### Introduction

The technology of bar coding is based on the recognition of patterns encoded, in bars and spaces or in a matrix of modules of defined dimensions, according to rules defining the translation of characters into such patterns, known as the symbology specification. Symbology specifications can be categorised into linear symbols, on the one hand, and two-dimensional symbols on the other; the latter can in turn be subdivided into «multi-row bar codes» sometimes referred to as "stacked bar codes", and "two-dimensional matrix codes".

Multi-row bar codes are constructed graphically as a series of rows of symbol characters, representing data and overhead components, placed in a defined vertical arrangement to form a (normally) rectangular symbol, which contains a single data message. Each row of the symbol has the characteristics of a linear bar code symbol and can be read by linear symbol scanning techniques.

Two-dimensional matrix symbols are usually rectangular arrangements of modules placed at the intersections of a grid of two (sometimes more) axes; the coordinates of each module need to be known in order to determine its significance, and the symbol must therefore be analysed two-dimensionally before it can be decoded.

Unless the context requires otherwise, the term "symbol" in this document can refer to either type of symbology.

The symbol, as a machine-readable data carrier, must be produced in such a way as to be reliably decoded at the point of use, if it is to fulfil its basic objective. Standard methodologies have been developed for measuring and assessing the quality of symbols for process control and quality assurance purposes during symbol production as well as afterwards.

Manufacturers of bar code equipment, the producers of bar code symbols and the users of bar code technology require publicly available standard conformance specifications for measuring equipment applying these methodologies, to ensure the accuracy and consistency of the performance of this equipment.

This document is intended to be similar in technical content (mutatis mutandis) to the linear bar code verifier conformance standard, ISO/IEC 15426-1, on which this document has been based. This document should be read in conjunction with the symbology specification applicable to the bar code symbol being tested, which provides symbology-specific detail necessary for its application.

This document is a previous general ded by tills

## Information technology — Automatic identification and data capture techniques — Bar code verifier conformance specification —

#### Part 2:

#### **Two-dimensional symbols**

#### 1 Scope

This document specifies the test methods for representative samples of the equipment and the minimum accuracy criteria applicable to verifiers using the methodologies of ISO/IEC 15415 for multi-row bar code symbols and two-dimensional matrix symbologies. This document also specifies reference calibration standards for verifier conformance.

NOTE ISO/IEC 15426-1 applies to verifiers for linear bar code symbols.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 15415, Information technology — Automatic identification and data capture techniques — Bar code symbol print quality test specification — Two-dimensional symbols

ISO/IEC 15416, Automatic identification and data capture techniques — Bar code print quality test specification — Linear symbols

ISO/IEC 19762, Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 15415, ISO/IEC 19762 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>

#### 3.1

#### primary reference test symbol

bar code symbol intended for the testing of the accuracy of bar code verifiers and manufactured to close tolerances, much higher than bar code verifiers to be tested, by methods traceable to national standards