

Eurocode 6:
Design of masonry structures
Part 3: Simplified calculation methods for
unreinforced masonry structures
Estonian National Annex

Eurokoodeks 6:
Kivikonstruktsioonide projekteerimine
Osa 3: Armeerimata kivikonstruktsioonide
lihtsustatud arvutus
Eesti standardi rahvuslik lisa

FOREWORD

This document:

- is the Estonian National Annex to the European Standard EN 1996-3:2006 „Eurocode 6: Design of masonry structures – Part 3: Simplified calculation methods for unreinforced masonry structures“. It includes Estonian Nationally Determined Parameters (NDP) and procedures and it must be used together with EN 1996-3 for structural design of buildings and civil engineering works built in Estonia,
- was ratified with an order of Estonian Centre for Standardisation dated 27.02.2009 nr 34,
- is endorsed with the notification published in the March 2009 issue of the official bulletin of the Estonian Centre for Standardisation.

The National Annex was prepared by Väino Voltri. This document has been approved by Technical Committee EVS/TK 13 „Ehituskonstruktsioonide projekteerimine“.

The proposition to prepare a National Annex was made by EVS/TK 13, it was coordinated by the Estonian Centre for Standardisation.

ICS 91.010.30 Technical aspects; 91.080.30 Masonry
Price group D

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact the Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone: 605 5050; e-mail: info@evs.ee

CONTENTS

NA.2.3	Verification by the partial factor method	4
NA.4.1	General	5
NA.4.2.1.1	General conditions.....	5
NA.4.2.2.3	Capacity reduction factor	6
NA.D.1	Characteristic compressive strength	7
NA.D.2	Characteristic flexural strength.....	7
NA.D.3	Characteristic initial shear strength	7