SAAGIKORISTUSMASINAD Rohusöödakoristid Osa 3: Katsemeetodid

Equipment for harvesting Forage harvesters Part 3: Test methods

EESTI STANDARDIKESKUS ESTONIAN CENTRE FOR STANDARDISATION

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-ISO 8909-3:2001 "Saagikoristusmasinad. Rohusöödakoristid. Osa 3: Katsemeetodid" sisaldab rahvusvahelise standardi ISO 8909-3:1994 "Equipment for harvesting - Forage harvesters - Part 3: Test methods" ingliskeelset teksti.

Standardi avaldamise korraldas Eesti Standardikeskus.

Standard EVS-ISO 8909-3:2001 on kinnitatud Eesti Standardikeskuse 05.11,2001 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teataja 2001. aasta detsembrikuu numbrs.

Standard on kättesaadav Eest andardikeskusest. This Estonian Standard EVS-ISO 8909-3:2001 consists of the identical English text of the International Standard ISO 8909-3:1994 "Equipment for harvesting -Forage harvesters - Part 3: Test methods".

Estonian standard is published by the Estonian Centre for Standardisation.

This standard is ratified with the order of Estonian Centre for Standardisation dated 05.11.2001 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

The standard is available from Estonian Centre for Standardisation.

Käsitlusala

Standardi ISO 8909 käesolev osa täptustab katsemeetodid rohusöödakoristi töötamise ja suutlikkuse hindamiseks, hõlmates masinad, mis koristavad saagi laus- või reas-niitmisega (-lõikamisega) või koguvad eelnevalt mahalõigatud saagi.

See kehtib aktiivnugadega rohusöödakoristitele, mis hekseldavad saagi ja toimetavad selle punkrisse, ris. The server of the option of the server konteinerisse, eraldi veokile või haagisele. Need koristid võivad olla traktorile paigaldatavad, traktoriga veetavad (haake- ja poolripp-) või liikurmasinad.

ICS 65.060.50 Koristusseadmed

Standardite reprodutseerimis- ja levitamisõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse poolt antud kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:

Aru 10 Tallinn 10317 Eesti; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

Right to reproduce and distribute belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:

Aru str 10 Tallinn 10317 Estonia; www.evs.ee; Phone: 605 5050; E-mail: info@evs.ee

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the international Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8909-3 was prepared by Technical Committee ISO/TC 23, Tractors and machinery for agriculture and forestry, Subcommittee SC 7, Equipment for harvesting and conservation

ISO 8909 consists of the following parts, under the general title Frage harvesters:

- Part 1: Vocabulary
- Part 2: Specification of characteristics and performance
- Part 3: Test methods

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Forage harvesters —

Part 3:

Test methods

1 Scope

This part of ISO 8909 specifies test methods for evaluations of forage harvester function and performance, covering forage harvesters which cut the crop directly at full width or from spaced-apart plant rows, or which pick up precut crop.

It applies to forage harvesters with driven knives for chopping and which deliver the chopped crop into a container or a separate vehicle or trailer. The harvesters may be tractor-mounted, trailed or self-propelled.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 8909. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 8909 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 500:1991, Agricultural tractors — Rear-mounted power take-off — Types 1, 2 and 3.

ISO 730-1:1990, Agricultural wheeled tractors — Rear-mounted three-point linkage — Part 1: Categories 1, 2 and 3.

ISO 730-2:1979, Agricultural wheeled tractors — Three-point linkage — Part 2: Category 1 N (Narrow hitch).

ISO 730-3:1982, Agricultural wheeled tractors — Three-point linkage — Part 3: Category 4.

ISO 789-3:1993, Agricultural tractors — Test procedures — Part 3: Turning and clearance diameters.

3600:1981, Tractors and machinery for agriculture and forestry — Operator manuals and technical publications — Presentation.

ISO 3767 1991, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Symbols for operator controls and other displays — Part 1: Common symbols.

ISO 3767-2:1991, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Symbols for operator controls and other displays — Part 2: Symbols for agricultural tractors and machinery.

ISO 3965:1990, Agricultural wheeled tractors — Maximum speeds — Method of determination.

ISO 4254-1:1989, Tractors and machinery for agriculture and forestry — Technical means for ensuring safety — Part 1: General.

ISO 5007:1990, Agricultural wheeled tractors — Operator's seat — Laboratory measurement of transmitted vibration.

- ISO 5008:1979, Agricultural wheeled tractors and field machinery Measurement of whole-body vibration of the operator.
- ISO 5131:1982, Acoustics Tractors and machinery for agriculture and forestry Measurement of noise at the operator's position Survey method.
- ISO 5675:1992, Agricultural tractors and machinery General purpose quick-action hydraulic couplers.
- ISO 5697:1982, Agricultural and forestry vehicles Determination of braking performance.
- ISO 5715:1983, Equipment for harvesting Dimensional compatibility of forage harvesting machinery.
- ISO 5718-1:1989, Harvesting equipment Flat blades for rotary mowers Specifications Part 1: Type A flat blades.
- ISO 5718-2:1991, Harvesting equipment Flat blades for rotary mowers Part 2: Specifications for type B flat blades.
- ISO 6097:1989, Tractors and self-properted machines for agriculture Performance of heating and ventilation systems in closed cabs Teamethod.
- ISO 6489-1:1991, Agricultural vehicles Mechanical connections on towing vehicles Part 1: Hook type.
- ISO 6489-2:1980, Agricultural vehicles Mechanical connections on towing vehicles Part 2: Clevis type Dimensions.
- ISO 8909-1:1994, Forage harvesters Part 1: Vocabulary.
- ISO 8909-2:1994, Forage harvesters Part 2: Specification of characteristics and performance.

3 Definitions

For the purposes of this part of ISO 8909, the definitions given in ISO 8909-1 and the following definitions apply.

- **3.1 test machine:** Machine whose performance is being assessed.
- **3.2 reference machine:** Machine of known performance required to be used alongside the test machine.
- 3.3 test series: All the events and data comprising several test runs in one crop and set of conditions.

- **3.4 catch:** Mass of the material collected from the harvester during a test run, in kilograms.
- **3.5 capacity**: Continuous output (mass) on a wet and dry basis of chopped crop from the harvester per unit of time. The capacity is expressed in tonnes per hour.
- **3.6 power requirement:** Time-averaged total power, in kilowatts, required to operate the harvester during a test run at rated operating speed, excluding the power for propulsion.
- **3.7 no-load power requirement**: Time-averaged total power, in kilowatts, required to operate the harvester at the rated speed when stationary and with the attachments to be tested engaged.
- **3.8 specific energy requirement:** Total harvester energy required per unit of crop mass on a wet and dry basis. It is expressed in kilowatt hours per tonne.
- **3.9 theoretical length of cut:** Length of cut, in millimetres, calculated from the number of knives and the speeds and effective dimensions of all relevant components.
- 2.10 length of cut analyser: Apparatus for dividing a typical sample of the chopped forage harvested by the machine into particle length groups, to enable the percentage of cumulative undersize by mass to be determined from each group.
 - 3.11 length of cut distribution graph: Logarithmic normal propebility graph of percent cumulative undersize mass versus mean particle length data from the length of cut analysis for each sample. (See annex B.)
 - 3.12 geometric mean length of cut: Particle length, in millimetres, calculated from the analysis data or taken from the length of cut distribution graph at the 50 % level of cumulative undersized mass. It denotes the fineness of chopped crop and is the most appropriate dimension for comparison with the theoretical length of cut.
 - 3.13 geometric standard deviation of length of cut: Particle length taken from the length of cut distribution graph at the 84 % level of cumulative undersized mass divided by the mean length at the 50 % level of cumulative undersized mass; alternatively, it may be calculated mathematically from the analysis data. The geometric length of cut standard deviation is an index of the uniformity of cut.