# INTERNATIONAL STANDARD

ISO/IEC 11584

First edition 1996-03-01

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode multi-rate bearer services — Service description, functional capabilities and information flows

Technologies de l'information — Télécommunications et échange d'information entre systèmes — Réseau privé avec intégration de services — Services porteurs multidébits en mode circuit — Description du service, capacités fonctionnelles et débit d'informations



# ISO/IEC 11584:1996(E)

# **Contents**

Foreword Introduction		iii
		iv
Section 1: General		
1	Scope	1
2	Conformance	1
3	Normative References	1
4	Definition	2
Sectio	n 2: Service Description, Stage 1	
5	Circuit-mode multi-rate unrestricted 8 kHz structured bearer service	3
5.1.	Description	3
5.2	Network capability for charging	3
5.3	Static Description. Service Attributes	3
5.3.1	Dominant information transfer attributes	3
5.3.2	Secondary information transfer attributes	3
5.3.3	Access attributes	4
6	Procedures for multi-rate bearer service within a PISN	4
6.1	Provision of services	4
6.2	Normal Procedures 0	4
6.2.1	Call establishment at the callinguser	4
6.2.2	Call establishment at the called <b>use</b> r	5
6.2.3	Terminating the call service (call refease)	5
6.3	Exceptional procedures/unsuccessful_outcome	5
7	Interworking	6
7.1	Interworking requirements	6
7.2	Interactions with supplementary services	6
8	Dynamic Description	7
Sectio	on 3: Functional capabilities and information flows, Stage 2	9
	<sup>O</sup>	
	Q.	
	б,	
	<b>U</b>	

© ISO/IEC 1996 All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

http:// doited.parting.off.com/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integration/integr

iii

#### ISO/IEC 11584:1996(E)

## Introduction

This International Standard is one of a series of ISO standards describing the service specification functional model and information flows applicable to Private Integrated Services Network. The series uses the ISDN concepts as developed by ITU-T (formerly CCITT) and is also within the framework of standards for Open Systems Interconnection as defined by ISO.

This particular International Standard defines the service specification for circuit mode multi-rate bearer service.

The circuit-mode multivate bearer services for Private Integrated Services Network (PISN), specified in this International Standard complement, and are compatible with the corresponding services for public ISDN as specified by ITU-T (formeth CCITT). Specifications of the equivalence of the circuit-mode multi-rate bearer services. specified by ITU-T (formety CCITT). Specifications of the equivalent services are to be found in Rec. I.220,

iv

Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit-mode multi-rate bearer services - Service description, functional capabilities and information flows

# Section 1: General

This International Standard specifies service description and control aspects of the multi-rate circuit-mode basic services which may be supported by Private Integrated Services Network (PISN).

One of the purposes of the stage 1 and stage 2 specifications is to guide and constrain the work on signalling protocols at stage 3. Therefore, this International Standard is concerned mainly with the control aspects of services.

A stage 3 standard shall be in conformance with this International Standard, if the signalling protocols and equipment behavior specified in the stage 3 standard are capable of being used in a PISN which supports any or all of the basic services specified in this International Standard.

This International Standard encompasses Circuit-Mode Multi-rate Unrestricted 8 kHz Structured Bearer Service.

Negotiation of services at call establishment time, interworking using channel aggregation (Nx64kbit/s) and change of service during a call are outside the scope of this International Standard.

## 2 Conformance

1

Scope

In order to conform to this International Standard, a stage 3 standard shall specify signalling protocols and equipment behavior that are capable of being used in a PISN which supports the bearer service specified in this International Standard. This means that to claim conformance a Stage 3 standard is required to be adequate for the support of those aspects of stage 1 (section 2) and stage 2 (section 3) which are relevant to the interface or equipment to which the Stage 3 standard applies.

#### 3 Normative References

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.