

INTERNATIONAL STANDARD

ISO/IEC
14251

First edition
1995-08-01

Information technology — Data interchange on 12,7 mm 36-track magnetic tape cartridges

*Technologies de l'information — Échange de données sur cartouches de
bande magnétique de 12,7 mm, 36 pistes*



Reference number
ISO/IEC 14251:1995(E)

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
3 References	2
4 Definitions	2
4.1 algorithm	2
4.2 algorithmically Processed Data	2
4.3 Beginning of Tape (BOT)	2
4.4 byte	2
4.5 Cyclic Redundancy Check (CRC) character	2
4.6 Data Records	2
4.6.1 Processed Data Record (PDR)	2
4.6.2 Host Data Record	2
4.6.3 Logical Data Record (LDR)	2
4.6.4 User Data Record (UDR)	2
4.7 End of Tape (EOT)	2
4.8 Error correcting code (ECC)	2
4.9 flux transition position	2
4.10 flux transition spacing	2
4.11 Frame	2
4.12 logical backwards	2
4.13 logical forwards	2
4.14 magnetic tape	2
4.15 Master Standard Reference tape	2
4.16 packet	3
4.17 pad byte	3
4.18 physical backward	3
4.19 physical forward	3
4.20 physical recording density	3

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.21	Processed Data	3
4.22	Secondary Standard Reference tape	3
4.23	Standard Reference Amplitude (SRA)	3
4.24	Standard Reference Current	3
4.25	Tape Reference Edge	3
4.26	Test Recording Current	3
4.27	track	3
4.28	Typical Field	3
4.29	transformation	3
4.30	Wrap	3
4.31	Half-Wrap	3
5	Conventions and notations	3
5.1	Representation of numbers	3
5.2	Names	3
5.3	Acronyms	4
6	Environment and safety	4
6.1	Cartridge/tape testing environment	4
6.2	Cartridge operating environment	4
6.3	Cartridge storage environment	4
6.4	Safety requirements	5
6.4.1	Safeness	5
6.4.2	Flammability	5
6.5	Transportation	5
Section 2	- Characteristics of the tapes	5
7	Characteristics of the tapes	5
7.1	Material	5
7.2	Tape length	5
7.3	Tape width	5
7.4	Tape discontinuity	5
7.5	Total thickness of tape	5
7.6	Base material thickness	5
7.7	Longitudinal curvature	6
7.7.1	CST tape	6
7.7.2	ECCST tape	6
7.8	Out-of-plane distortions	6
7.9	Cupping	6
7.10	Dynamic frictional characteristics	6
7.10.1	Frictional drag between the recording surface and the back surface	6
7.10.2	Frictional drag between the tape recording surface and ferrite after environmental cycling	6
7.11	Coating adhesion	7
7.12	Flexural rigidity	8
7.13	Electrical resistance of coated surfaces	8
7.14	Tape durability	9
7.15	Inhibitor tape	9
7.16	Tape abrasivity	9
7.17	Accelerated life test	9
7.18	Data integrity test	9
7.18.1	Requirement	9

7.18.2 Procedure	9
7.19 Pre-recording condition	10
7.20 Magnetic recording characteristics	10
7.20.1 Typical field	10
7.20.2 Signal amplitude	10
7.20.3 Resolution	10
7.20.4 Overwrite	11
7.20.5 Narrow-band signal-to-noise ratio (NB-SNR)	11
7.21 Tape quality	11
7.21.1 Missing pulses	12
7.21.2 Missing pulse zones	12
7.21.3 Coincident Missing Pulse Zones	12
Section 3 - Cartridge	12
8 Dimensional and mechanical characteristics of the cartridge	12
8.1 Overall dimensions	13
8.2 Write-inhibit mechanism	13
8.3 Label area(s) of the rear side	14
8.3.1 Implementation of a single label area	14
8.3.2 Implementation for two label areas	14
8.4 Label area of the top side	14
8.5 Case opening	14
8.6 Locating notches	15
8.7 Locating areas	15
8.8 Inside configuration of the case around the case opening	15
8.9 Other external dimensions of the case	15
8.10 Central window	16
8.11 Stacking ribs	16
8.12 Recessed area	16
8.13 Flexibility of the case	16
8.13.1 Requirements	16
8.13.2 Procedure	17
8.14 Tape reel	17
8.14.1 Locking mechanism	17
8.14.2 Axis of rotation of the reel	17
8.14.3 Metallic insert	17
8.14.4 Toothed rim	17
8.14.5 Hub of the reel	18
8.14.6 Relative positions	18
8.14.7 Characteristics of the toothed rim	18
8.15 Leader block	19
8.16 Attachment of the tape to the leader block	19
8.17 Latching mechanism	20
8.18 Tape wind	20
8.19 Wind tension	20
8.20 Circumference of the tape reel	20
8.21 Moment of inertia	20
8.22 Cartridge case colours	21
Section 4 - Recording method and formats	30

9 Method of recording	30
9.1 Physical recording density	30
9.2 Bit cell length	30
9.3 Average bit cell length	30
9.3.1 Long-term average bit cell length	30
9.3.2 Short-term average bit cell length	30
9.4 Rate of change of the short-term average bit cell length	30
9.5 Bit cell peak position	30
9.6 Bit shift	31
9.7 Total character skew	31
9.8 Read signal amplitude	31
9.9 Coincident missing pulse zones	31
10 Track format	31
10.1 Number of tracks	31
10.2 Track positions	31
10.3 Track width	32
10.4 Azimuth	32
10.5 Track identification	32
11 Packet format	33
11.1 Packets	33
11.2 Packet ID	34
11.3 UDR	35
11.4 Packet trailer	35
11.4.1 Packet trailer when data has been processed	35
11.4.2 Packet trailer when the data has not been processed	35
12 Data block format	35
12.1 Data part	35
12.1.1 Packet bytes	36
12.1.2 Count field bytes	36
12.1.3 Block ID bytes	36
12.2 Allocation of the bytes of the data block to frames	36
12.2.1 Prefix frames	37
12.2.2 Data frames	37
12.2.3 Residual frame 1	38
12.2.4 Residual frame 2	39
12.2.5 Suffix frames	40
12.3 Error correction code (ECC)	40
12.4 Recording of 8-bit bytes on the tape	41
12.5 Recorded data block	41
12.5.1 Preamble	42
12.5.2 Beginning of data mark (BDM)	42
12.5.3 Resync control frame	42
12.5.4 End of data mark (EDM)	42
12.5.5 Postamble	42
12.6 Maximum data density	43
13 Tape format	43

13.1 Zones	43
13.2 Density ID mark	43
13.3 VOLID mark	44
13.4 ID separator mark	45
13.5 Interblock gap	45
13.6 Erase gap	46
13.6.1 Normal erase gap	46
13.6.2 Extended erase gap	46
13.7 Tape mark	46
13.8 Wrap marks	46
13.9 Mark merge	47
13.9.1 IBG followed by a tape mark	47
13.9.2 Tape mark followed by an IBG	47
13.9.3 IBG followed by a erase gap	48
13.9.4 Erase gap followed by an IBG	48
13.9.5 IBG followed by a Wrap Mark	48
13.9.6 Wrap mark followed by an IBG	48
13.9.7 IBG followed by a VOLID mark ONE or ZERO	48
13.9.8 VOLID mark ONE or ZERO followed by an IBG	48
13.9.9 Summary of the relationship between interblock gaps, erase gaps, tape marks, and wrap marks	49
13.10 End of Data Block	49
13.11 Recording Area	50
Annexes	
A - Tape abrasivity measurement procedure	52
B - Pre-recording condition	55
C - Representation of 8-bit bytes by 9-bit patterns	56
D - Measurement of bit shift	59
E - Implementation of a CRC	61
F - Calculation of a physical position indicator	62
G - Media Type Label	63
H - Recommendations for transportation	67
J - Inhibitor cartridge	68
K - Recommendations on tape durability	69
L - Summary of data flow	70
M - Accelerated life test	71

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 14251 was prepared by the European Computer Manufacturers Association (as Standard ECMA-196) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to G form an integral part of this International Standard. Annexes H to M are for information only.

Introduction

The following International Standards specify data interchange on 12,7 mm wide magnetic tape cartridges:

ISO/IEC 9661: 1994, *Information technology - Data interchange on 12,7 mm wide magnetic tape cartridges - 18 tracks, 1 491 bytes per millimetre*

ISO/IEC 11559: 1993, *Information technology - Data interchange on 12,7 mm wide 18-track magnetic tape cartridges - Extended format*

ISO/IEC 13421: 1993, *Information technology - Data interchange on 12,7 mm, 48-track magnetic tape cartridges - DLT 1 format*

ISO/IEC 13962: 1995, *Information technology - Data interchange on 12,7 mm, 112-track magnetic tape cartridges - DLT 2 format*

This International Standard is related to further developments of cartridges containing 12,7 mm magnetic tape. It incorporates most of the requirements of ISO/IEC 11559, together with extensions and modifications which specify the additional features that allow higher capacities to be achieved.

Two types of cartridge are defined within this International Standard. For one of the types, the requirements for the case and the tape are identical with those in ISO/IEC 11559. The second type conforms to different requirements which are defined in this International Standard. This International Standard also specifies a recording method and format for use with either type.

It is not intended that this International Standard replaces ISO/IEC 11559. Existing cartridges which conform to ISO/IEC 11559 will continue to do so and will not conform to all the requirements of this International Standard. Drives which write and read according to this International Standard may have the ability to accept and read cartridges conforming to ISO/IEC 9661 or ISO/IEC 11559.

Information technology - Data interchange on 12,7 mm 36-track magnetic tape cartridges

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of 12,7 mm wide, 36-track magnetic tape cartridges to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, the format and the recording method, thus allowing, together with International Standard ISO 1001 or equivalent, full data interchange by means of such magnetic tape cartridges.

This International Standard specifies two types of cartridge which, for the purposes of this International Standard, are referred to as Cartridge System Tape (CST) and Extended Capacity Cartridge System Tape (ECCST), and contain tape of different thicknesses and lengths.

CST cartridges have a nominal uncompressed capacity of approximately 400 Mbytes.

ECCST cartridges have a nominal uncompressed capacity of approximately 800 Mbytes.

This International Standard specifies extensions and modifications to the recorded format that is described in International Standard ISO/IEC 11559.

These extensions and modifications

- increase the number of tracks recorded on the tape from 18 to 36. Actual recordings will be made 18 tracks at a time requiring two complete passes of the tape, one from the beginning of tape to the end of tape and the other from the end of tape to the beginning of tape;
- specify a different method of defining the ECC characters used to detect and correct errors when the data is read from the tape.

2 Conformance

2.1 Magnetic tape cartridge

A magnetic tape cartridge is in conformance with this International Standard if:

- the cartridge meets all the requirements of clauses 6 to 8 for either one of the two types of magnetic tape cartridge;
- the recording on the tape meets the requirements of clauses 9 to 13;
- for each recorded packet the algorithm used for processing the data therein, if Processed Data has been recorded, is defined and the identification is included in Byte 13 of the Packet ID of this packet (see 11.2). This identification shall conform to ISO/IEC 11576.

2.2 Generating system

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all the recordings that it makes on a tape meet the mandatory requirements of this International Standard. A claim of conformance shall state which types of magnetic tape cartridges it is capable of recording, whether or not one, or more, registered algorithms are implemented and, if so, the registered identifiers of all implemented algorithms. It shall also state whether it is capable of generating the optional VOLID Mark information.

2.3 Receiving system

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard and specifies which of the two types of magnetic tape cartridges it is capable of reading. In particular it shall

- be able to retrieve data from individual packets within the extended blocks;
- be able to recognize that the data has been processed, to identify the algorithm(s) used, restore the data to its original form or to indicate to the host that it cannot do so;

A claim of conformance shall state whether or not one, or more, registered algorithm(s) is (are) implemented and, if so, the registered identifier(s) of all implemented algorithms. It shall also state whether it is capable of using the optional VOLID Mark information.