

Characterization of waste - Leaching behaviour test -
Influence of pH on leaching with initial acid/base
addition

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 14429:2015 sisaldab Euroopa standardi EN 14429:2015 ingliskeelset teksti.	This Estonian standard EVS-EN 14429:2015 consists of the English text of the European standard EN 14429:2015.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 25.03.2015.	Date of Availability of the European standard is 25.03.2015.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 13.030.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Characterization of waste - Leaching behaviour test - Influence
of pH on leaching with initial acid/base addition

Caractérisation des déchets - Essais de comportement à la
lixiviation - Influence du pH sur la lixiviation avec ajout initial
d'acide/base

Charakterisierung von Abfällen - Untersuchung des
Elutionsverhaltens - Einfluss des pH-Wertes auf die Elution
unter vorheriger Säure/Base-Zugabe

This European Standard was approved by CEN on 26 December 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	4
Introduction	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviations	8
5 Principle	9
6 Reagents	9
7 Equipment	10
7.1 General.....	10
7.2 Laboratory equipment.....	10
8 Sample preparation	11
8.1 Laboratory sample.....	11
8.2 Preparation of the test sample	11
8.3 Determination of dry residue.....	11
8.4 Preparation of the test portion	12
9 Procedure	12
9.1 Contact time	12
9.2 pH range	12
9.3 Leaching test.....	13
9.3.1 General.....	13
9.3.2 Preparation of leachant.....	13
9.3.3 Leaching procedure	14
9.4 Natural pH.....	15
10 Eluate treatment, storage and analysis	16
11 Blank test.....	16
12 Performance characteristics	16
13 Test report	17
Annex A (informative) Example of a data sheet	19
Annex B (informative) Operation and uses of the test — Influence of pH on the leaching behaviour.....	20
B.1 Clarification of the two modes of operation of the test: influence of pH on the leaching behaviour.....	20
B.2 Expression of results	22
B.3 Scope and limits of the application field of the test.....	22
B.3.1 Remarks on the use of pH dependence test results to assess the effects of ageing	22
B.3.2 Examples of test result use and considerations on scope	23
B.4 Example: Identification of the sensitivity of leaching to pH over the environmentally relevant pH range.....	24
Annex C (informative) Preliminary determination of the acid/base consumption	25
C.1 General.....	25

C.2	Titration procedure to estimate the ANC and the BNC	25
C.2.1	Reagents and laboratory devices	25
C.2.2	Test portion	25
C.2.3	Procedure	25
C.2.4	Expression of results	27
C.3	Arbitrary division of the maximum acid/base consumption for the extreme pH values	27
C.3.1	General	27
C.3.2	Reagents and laboratory devices	27
C.3.3	Test portion	27
C.3.4	Procedure	27
C.3.5	Expression of results	28
Annex D	(informative) Examples of acid and base neutralization capacities for waste, soil, sediment and construction materials.....	30
D.1	Examples of acid and base neutralization capacities	30
D.2	Use of acid and base neutralization capacity data	32
Annex E	(informative) Repeatability and reproducibility data.....	33
E.1	Materials used in the interlaboratory comparison study	33
E.2	Interlaboratory comparison results	33
Bibliography		51

Foreword

This document (EN 14429:2015) has been prepared by Technical Committee CEN/TC 292 "Characterization of waste", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2015, and conflicting national standards shall be withdrawn at the latest by September 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 14429:2005.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

The following significant technical changes have been implemented in this new edition of the text:

- the status of the document has been changed from a CEN/TS into a European Standard;
- performance data has been added (see Annex E).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This document has been developed primarily to support the requirements for leaching behaviour testing within EU and EFTA countries.

This document specifies a test method to determine the influence of pH on the leachability of inorganic constituents from waste materials.

For the complete characterization of the leaching behaviour of waste under specified conditions the application of other test methods is required (see EN 12920).

Anyone dealing with waste and sludge analysis should be aware of the typical risks of that kind of material irrespective of the parameter to be determined. Waste and sludge samples can contain hazardous (e.g. toxic, reactive, flammable, infectious) substances, which can be liable to biological and/or chemical reaction.

Consequently these samples should be handled with special care. Gases which can be produced by microbiological or chemical activity are potentially flammable and will pressurize sealed bottles. Bursting bottles are likely to result in hazardous shrapnel, dust and/or aerosol. National regulations will be followed with respect to all hazards associated with this method.

In the different European countries, tests have been developed to characterize and assess the constituents which can be leached from waste materials. The release of soluble constituents upon contact with water is regarded as one of the main mechanism of release which results in a potential risk to the environment during life-cycle of waste materials (disposal or re-use scenario). The intent of these tests is to identify the leaching properties of waste materials. The complexity of the leaching process makes simplifications necessary. Not all of the relevant aspects of leaching behaviour can be addressed in one single standard.

Procedures to characterize the behaviour of waste materials can generally be divided into three steps, using different tests in relation to the objective. The following test hierarchy is taken from the Landfill Directive ¹⁾ and the Decision on Annex II of this Directive ²⁾ for disposal of waste.

- a) Basic characterization constitutes a full characterization of the waste by gathering all the necessary information for a safe management of the waste in the short and long term. Basic characterization may provide information on the waste (type and origin, composition, consistency, leachability, etc.), information for understanding the behaviour of waste in the considered management scenario, comparison of waste properties against limit values, and detection of key variables (critical parameters as liquid/solid (L/S) ratios, leachant composition, factors controlling leachability such as pH, redox potential, complexing capacity and physical parameters) for compliance testing and options for simplification of compliance testing. Characterization may deliver ratios between test results from basic characterization and results from simplified test procedures as well as information on a suitable frequency for compliance testing. In addition to the leaching behaviour, the composition of the waste should be known or determined by testing. The tests used for basic characterization should always include those to be used for compliance testing.
- b) Compliance testing is used to demonstrate that the sample of today fits the population of samples tested before by basic characterization and through that, is used to carry out compliance with regulatory limit values. The compliance test should therefore always be part of the basic characterization program. The compliance test focuses on key variables and leaching behaviour identified by basic characterization tests. Parts of basic characterization tests can also be used for compliance purposes.

1) Council Directive 1999/31/EC of 26 April 1999 on the landfill of waste.

2) Council Decision 2003/33/EC of 19 December 2002.

- c) On-site verification tests are used as a rapid check to confirm that the waste is the same as that which has been subjected to characterization or compliance tests. On-site verification tests are not necessarily leaching tests.

The test procedure described in this document is a basic characterization test and falls in category a).

In this European Standard leaching is carried out at different pH values as a result of the reaction between pre-selected amounts of acid or base and test portions of the waste material. Size reduction is performed to facilitate approaching equilibrium.

This test is different from the "pH dependence test with continuous pH control" (pH static test, see EN 14997) in which the pH is controlled at pre-selected values over the entire testing period by continuous measurement and automatic addition of acid or base. The test is aiming at approaching equilibrium at the end of the procedure.

NOTE In Annex B specific uses of both the pH dependence test with initial acid/ base addition and the pH dependence test with continuous pH control are indicated.

1 Scope

This European Standard specifies a method for the determination of the influence of pH on the leachability of inorganic constituents from a waste material. The equilibrium condition as defined in the standard is established by addition of pre-determined amounts of acid or base to reach desired end pH values. This test method produces eluates, which are subsequently characterized physically and chemically.

This European Standard is a parameter specific test as specified in EN 12920. The application of this test method alone is not sufficient for the determination of the detailed leaching behaviour of a waste under specified conditions.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14346:2006, *Characterization of waste — Calculation of dry matter by determination of dry residue or water content*

EN 14899, *Characterization of waste — Sampling of waste materials — Framework for the preparation and application of a Sampling Plan*

EN 15002, *Characterization of waste — Preparation of test portions from the laboratory sample*

EN 16192, *Characterization of waste — Analysis of eluates*

EN ISO 3696, *Water for analytical laboratory use — Specification and test methods (ISO 3696)*

EN ISO 5667-3, *Water quality — Sampling — Part 3: Preservation and handling of water samples (ISO 5667-3)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

dry residue

W_{dr}

remaining mass fraction of a sample after a drying process at 105 °C

[SOURCE: EN 14346:2006]

3.2

eluate

solution obtained by a leaching test

3.3

equilibrium

condition achieved when the pH deviation during a checking period at the last 4 h of the test is below 0,3 pH unit