
**Intelligent transport systems — Traffic
and travel information messages via
traffic message coding —**

**Part 1:
Coding protocol for Radio Data System —
Traffic Message Channel (RDS-TMC)
using ALERT-C**

*Systèmes intelligents de transport — Informations sur le trafic et le
tourisme via le codage de messages sur le trafic —*

*Partie 1: Protocole de codage pour le système de radiodiffusion de
données (RDS) — Canal de messages d'informations sur le trafic
(RDS-TMC) avec ALERT-C*



This document is a preview generated by PVIS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vii
1 Scope	1
1.1 General scope	1
1.2 Content	1
1.3 Message management	2
1.4 Transmission	2
1.5 Event list	2
2 Normative references	2
3 Terms, definitions and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Abbreviated terms	5
4 Application	7
4.1 General	7
4.2 Definition of the TMC "travel service"	7
4.3 TMC virtual terminal	8
4.4 Event-oriented end-user information messages	8
4.5 Strategic and tactical information	8
4.6 Geographic relevance	9
4.7 Transmitted message priority	9
4.8 Event List	10
4.9 Future extensions	10
5 Presentation	10
5.1 General	10
5.2 TMC virtual language	10
5.3 Message content	11
5.3.1 General	11
5.3.2 Event Description (11 bits)	11
5.3.3 Primary Location (16 bits)	11
5.3.4 Direction and Extent (4 bits)	12
5.3.5 Duration (3 bits)	13
5.3.6 Diversion Advice (1 bit)	14
5.4 Implicit information	15
5.4.1 Road class and road number	15
5.4.2 Road segment	15
5.4.3 Area, region and country	15
5.4.4 Pre-assigned diversion advice	15
5.4.5 Urgency within the terminal	15
5.4.6 Directionality	15
5.4.7 Duration type	16
5.4.8 Nature	16
5.4.9 Update class	16
5.4.10 Quantifier type	16
5.5 Optional message content	16
5.5.1 General	16
5.5.2 Combination of additional information	17
5.5.3 Control codes (label 1)	18
5.5.4 Length of route affected (label 2)	18
5.5.5 Speed limit (label 3)	18

5.5.6	Additional quantifiers (labels 4 and 5).....	19
5.5.7	Supplementary information (label 6)	19
5.5.8	Start and stop times (labels 7 and 8)	19
5.5.9	Multi-event messages (label 9).....	19
5.5.10	Detailed diversion instructions (label 10)	20
5.5.11	Destinations (label 11).....	20
5.5.12	Precise location reference (label 12)	20
5.5.13	Cross linkage to source of problem (label 13).....	21
5.5.14	Separator (label 14)	22
5.5.15	Other information as defined by sub-labels (label 15).....	22
5.5.16	Reference to telephone services (label 15, sub-label 1-2).....	22
6	Message management	25
6.1	General.....	25
6.2	System messages.....	26
6.2.1	General.....	26
6.2.2	Location table.....	26
6.2.3	Terminal requirements	26
6.2.4	Change of database numbers	27
6.3	Message repetition	27
6.4	Message updating.....	28
6.5	Message deletion.....	28
6.5.1	General.....	28
6.5.2	Message persistence.....	28
6.5.3	Detailed stop-time.....	29
6.5.4	Silent cancellation message.....	29
6.5.5	Null message.....	29
6.6	Message presentation	30
6.7	Out of area referencing	30
6.7.1	Structure of the INTER-ROAD concept.....	30
6.7.2	INTER-ROAD messages.....	31
6.7.3	Updating and cancellation of INTER-ROAD messages	31
7	Transmission.....	32
7.1	General.....	32
7.2	Format of type 8A groups	32
7.3	Immediate repetition.....	32
7.4	Single-group user messages.....	33
7.5	System messages.....	34
7.5.1	General.....	34
7.5.2	System information	34
7.5.3	Tuning information	38
7.6	Multi-group messages.....	40
7.6.1	First group	40
7.6.2	Subsequent groups	41
7.7	Summary of X-bit usage in RDS-TMC type 8A groups	43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 204, *Intelligent transport systems*.

This second edition cancels and replaces the first edition (ISO 14819-1:2003), which has been technically revised.

ISO 14819 consists of the following parts, under the general title *Intelligent transport systems — Traffic and travel information messages via traffic message coding*:

- *Part 1: Coding protocol for Radio Data System — Traffic Message Channel (RDS-TMC) using ALERT-C*
- *Part 2: Event and information codes for Radio Data System — Traffic Message Channel (RDS-TMC) using ALERT-C*
- *Part 3: Location referencing for Radio Data System — Traffic Message Channel (RDS-TMC) using ALERT-C*
- *Part 6: Encryption and conditional access for the Radio Data System — Traffic Message Channel ALERT C coding*

Compared to previous releases, this version includes the following additions:

- Precise location referencing
- Tendencies of Traffic Queue Lengths (TTQL)
- Coding of parking POIs
- Coding of interrupted roads

- Coding of other isolated POIs (except parking POIs)
- Coding of parallel roads
- Version identification of TMC location tables
- Location Table Exchange Format
- North American Safety Events in TMC
- Explicit Location Table Country Code transmission in TMC
- Guidelines for Service Providers and Terminal Manufacturers for Implementation of explicit Location Table Country Code transmission
- Coding of link roads
- GB-English - List of Quantifiers
- Additional Event Codes identified by Germany
- Additional TMC Events from Danish proposal
- Additional TMC Supplementary Information: Unconfirmed Report
- RDS-TMC delivery of IVR Telephone Number
- Coding of link roads

Introduction

Traffic and traveller information (TTI) may be disseminated through a number of services and means of communication to the end user, including static displays (e.g. Variable Message Signs), broadcast audio to car radios, broadcast data services to in-vehicle equipment (e.g. installed navigation system) and to nomadic device terminals (e.g. portable navigation device).

For all such services, the data to be disseminated and the message structure involved in the various interfaces require clear definition and standard formats, in order to allow competitive products to operate with any received data.

This part of ISO 14819 describes the data specification for TTI messages, together with their network layer and their service layer, which shall be conveyed by the RDS-TMC feature, specified in IEC 62106 (Second edition - 2009).

The TTI information chain, from event to end-user is quite complex and the TISA (the Traveller Information Services Association) value chain shown in Figure 1 helps to understand the key components:



Figure 1 — The Traveller Information Services Association TTI value chain

A number of entities (e.g. companies, businesses) take part in one or more activities to complete the activities shown in the value chain. Two, in particular are described, for improved understanding:

Service Provider: An organisation that constructs a data service, by gathering data, processing data and supplying the data service. A Service Provider then negotiates for the use of the necessary data bandwidth with a Broadcaster and/or Transmission Operator. A Service Provider is responsible for the "quality" of the content to his customers and must provide suitable customer support.

Broadcaster: A traditionally incorporated organisation responsible for a continuous strand of audio programmes and their quality. A broadcaster may also be responsible for overall co-ordination of "broadcast transmissions" (often a Broadcaster is the licensee of a national regulator). A Broadcaster may also be a Service Provider.

TTI services for travellers, using spoken radio reports and in-vision reports occupy broadcast air-time and whilst valuable to some, they are considered less useful by others. Furthermore, only some are useful for travellers on the move. Due to the widespread adoption of the Radio Data System, in VHF/FM broadcasting on Band II there is the possibility of transmitting coded TTI messages digitally and "silently" using the RDS-TMC feature, which avoids the interruption of planned programmes. This TTI delivery method has a number of advantages: TTI messages can be decoded into the language of the end user, regardless of location, more messages can be made available and planned broadcast programme interruption is avoided, so make delivery of TTI messages more timely and topical.

The ALERT-C protocol defined in this part of ISO 14819 supports a data broadcasting service for travellers, providing information about many kinds of traffic and travel events. Messages include traffic incident information relating to national and regional routes and some urban roads and other information required by a traveller, such as roadworks and weather information.

This part of ISO 14819 is based on the ALERT-C traffic message coding protocol, which was a product of DRIVE Project V1029, "RDS Advice and Problem Location for European Road Traffic". The RDS-ALERT project aimed to define standards for RDS-TMC, working in conjunction with the European Broadcasting Union (EBU) and the European Conference of Ministers of Transport (ECMT).

The international standard has been implemented in many countries worldwide and, as a result of very extensive implementation experience, it has matured with many changes from the earliest version of the ALERT-C proposal of 1990. At that time CEN TC 278 Sub-working group (SWG) 4.1 developed the coding protocol, herein and the event list described in ISO 14819-2; meanwhile CEN TC 278 SWG 7.3 developed the location referencing method which is described in ISO 14819-3. Subsequently the TMC Forum was responsible for collecting specific additions and improvements intended for inclusion in this part of ISO 14819. Latterly, the Traveller Information Services Association (TISA) took over all responsibility (including TMC Forum legacy) for maintenance of this part of ISO 14819, which now includes an up to date set of industry supported enhancements to RDS-TMC.

The RDS system is fully described in IEC 62106 (Second edition, 2009) and it contains the 'hooks' to RDS-TMC, detailed in this part of ISO 14819. It employs a group structured data protocol. It uses type 3A groups defined to carry Open Data Application (ODA) identification and service and network layer information. This enables signalling of the TMC feature in other data groups. It uses type 8A groups defined to carry RDS-TMC messages and location information, together with TMC service tuning information.

Broadly, two types of RDS-TMC services are required: one that is, in effect, free of charge at the point of use by an end user and thus uses un-encrypted data, and one that is paid-for using encrypted data. The conditional access capability was developed by the TMC Forum and is described in ISO 14819-6.

Intelligent transport systems — Traffic and travel information messages via traffic message coding —

Part 1: Coding protocol for Radio Data System — Traffic Message Channel (RDS-TMC) using ALERT-C

1 Scope

1.1 General scope

The ALERT-C protocol is designed to provide mostly event-oriented road end-user information messages. Many "hooks" have been left for future development and a few status-orientated road end-user information messages were included.

1.2 Content

The presentation section of the ALERT-C protocol specifies messages that may be presented to the user in accordance with the general requirements set out above. It defines the message structure and content, and its presentation to the end-user.

RDS-TMC messages are language-independent, and can be presented in the language of the user's choice. The ALERT-C protocol utilises a standardised Event List (ISO 14819-2) of event messages with their code values, which also includes general traffic problems and weather situations.

ALERT-C defines two categories of information within messages: basic and optional items. In principle, basic information is present in all messages. Optional information can be added to messages where necessary.

Standard RDS-TMC user messages provide the following five basic items of explicit, broadcast information:

1. **Event description**, giving details of road event situations, general traffic problems and weather situations (e.g. congestion caused by accident) and where appropriate its severity (e.g. resulting queue length).
2. **Location**, indicating the area, road segment or point location where the source of the problem is situated.
3. **Direction and Extent**, identifying the adjacent segments or specific point locations also affected by the incident, and where appropriate the direction of traffic affected.
4. **Duration**, giving an indication of how long the problem is expected to last.
5. **Diversion advice**, showing whether or not end-users are recommended to find and follow an alternative route.

Optional information can be added to any message using one or more additional RDS data groups. This optional addition can give greater detail or can deal with unusual situations. Any number of additional fields can in principle be added to each basic message, subject only to a maximum message length of five RDS data groups.

1.3 Message management

The message management component deals with the message management functions of RDS-TMC. The ALERT-C protocol distinguishes between user messages and system messages. User messages are those potentially made known to the end-user, as defined in the presentation section. System messages are of use only to the RDS-TMC terminal, for message management purposes.

1.4 Transmission

The transmission component conveys the messages over-air. The ALERT-C protocol, which RDS-TMC uses, retains the fundamental approach of earlier work, which aims to code most messages entirely within a single RDS group.

RDS-TMC information comprises both 'system information' and 'user messages'. System information relates to the particular TMC service, and details the parameters that the terminal needs to be able to find identify and decode the TMC information. System information is transmitted in type 3A groups and in type 8A groups.

User messages contain the details of the traffic events; these may use one or more type 8A groups. Most messages may be transmitted using a single type 8A group, however messages with more detail (e.g. diversion advice) may use up to a total of five, type 8A groups.

1.5 Event list

The ALERT-C Event List contains all event descriptions. It is described in ISO 14819-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4217:2008, *Codes for the representation of currencies and funds*

ISO 8601:2004, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO 14819-2, *Intelligent transport systems — Traffic and travel information messages via traffic message coding — Part 2: Event and information codes for Radio Data System — Traffic Message Channel (RDS-TMC) using ALERT-C*

ISO 14819-3, *Intelligent transport systems — Traffic and travel information messages via traffic message coding — Part 3: Location referencing for Radio Data System — Traffic message Channel (RDS-TMC) using ALERT-C*

IEC 62106:2009, *Specification of the radio data system (RDS) for VHF/FM sound broadcasting in the frequency range from 87.5 to 108.0 MHz*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.