INTERNATIONAL STANDARD

ISO 4000-2

Fifth edition 2013-12-15

Passenger car tyres and rims —

Part 2: **Rims**

Pneumatiques et jantes pour voitures particulières — Partie 2: Jantes





vroduced or utilized c to internet or an ' or ISO's memb All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Content	S	Page
Foreword		iv
1 Scop	oe	1
2 Norn	native references	1
3 Term	ns and definitions	1
4 Desig	gnation and marking	1
5 5° ta 5.1 5.2 5.3	Rim flanges Rim contours Rim diameter and hump circumference	
	e holes. General	
© ISO 2013 – A	All rights reserved	iii

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 31, Tyres, rims and valves, Subcommittee SC 3, *Passenger car tyres and rims.*

This fifth edition cancels and replaces the fourth edition (ISO 4000-2:2007), which has been technically revised.

ISO 4000 consists of the following parts, under the general title *Passenger car tyres and rims*: .SS

- Part 1: Tyres (metric series)
- Part 2: Rims

Passenger car tyres and rims —

Part 2: **Rims**

1 Scope

This part of ISO 4000 specifies the designation, contour and dimensions of 5° tapered (drop-centre) rims primarily intended for passenger cars.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3911, Wheels and rims for pneumatic tyres — Vocabulary, designation and marking

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3911 apply.

4 Designation and marking

The rim shall be designated by its nominal rim-diameter code, nominal rim-width code and rim flange type (e.g. 15×6 J or $13 \times 5,50$ B).

5 5° tapered (drop-centre) rims

5.1 Rim flanges

Recommended rim flange contours are given in $\underline{\text{Table 1}}$ for the nominal rim diameter codes.

-80-7-7-5